

Index

Note: Page numbers followed by “*f*” and “*t*” refer to figures and tables, respectively.

A

- Access and mobility management function (AMF), 40–41, 115–117, 143, 243, 806
- Access network (AN), 1, 112–140
 - bearers and identifiers, 124–132
 - radio bearers and packet data unit sessions, 124–129
 - radio network identifiers, 129–132
- entities and interfaces, 112–123
 - E1 control-plane functions and procedures, 121–122
 - F1 control-plane/user-plane functions and procedures, 119–121
 - NG control-plane/user-plane functions and procedures, 122–123
 - Xn control-plane/user-plane functions and procedures, 117–118
 - user-plane and control-plane protocol stacks, 132–140
- Access network discovery and selection function (ANDSF), 845
- Access point name (APN), 124–125, 803–804
- Access security management entity (ASME), 185
- Access stratum (AS), 10, 60–62, 199–200
 - security, 187
- Access-network-initiated paging, 166
- Acoustic filter technologies, 735–736
- Active antenna systems (AASs), 574, 655
- Active self-interference cancellation techniques, 377
- Additional maximum power reduction (A-MPR), 676, 696
- Adjacent channel interference ratio (ACIR), 683–685
- Adjacent channel leakage ratio (ACLR), 668–671, 682, 697
- Adjacent channel selectivity (ACS), 673–674, 683–685, 690
- Advanced driver assistance systems (ADAS), 15–16
- Aerial vehicle control, 37–38
- Aggregated maximum bit rate (AMBR), 172–173
- Aggregation level (AL), 764
- Allocation and retention priority (ARP), 146–147, 182
- Almost blank subframes (ABS), 874, 907–909
- AMF Name, 130
- Analog beamforming (ABF), 564–573, 738
- Analog front-end (AFE), 714–715
 - design considerations, 719–723
- Analog to digital converter (ADC), 321–322, 704, 706, 783
- Angle of arrival (AoA), 287
- Angle of departure (AoD), 295–296
- Angular spread (AS), 291, 295–296
- Antenna
 - antenna-port virtualization, 575
 - aperture, 737
 - arrays, 311, 737
 - bearing, 307
 - calibration, 743
 - configurations, 733
 - connectors, 741
 - design considerations, 726–727
 - panels, 307
 - port, 392
- Aperiodic CSI trigger state subselection, 206
- Aperiodic SRS, 604, 886
- Application functions (AFs), 109
- Application protocol identity (AP ID), 131–132
- Arbitration interframe space (AIFS), 862–864
- Area traffic capacity, 41
- Area-specific SIB, 240–241
- Asynchronous HARQ protocol, 214, 897
- Asynchronous LBT, 907
- Atmospheric effects, 300–301
- Authentication, 185, 751
- Authentication, authorization, and accounting (AAA), 12
- Authentication and key agreement (AKA), 144–145
- Authentication credential repository and processing function (ARPF), 188
- Authentication server function (AUSF), 143
- Automated driving-related services, 796–797

Automatic gain control (AGC), 721
 Automatic neighbor relation
 scheme (ANR scheme),
 50–51
 Automatic repeat request (ARQ),
 68–72, 197–198
 error control mechanism,
 539–542
 Autonomous uplink (AUL),
 868–869
 Average mutual information,
 367–368
 Average power tracking (APT), 724
 Average spectral efficiency, 39
 Averaging window, 178, 184

B

Backhaul (BH), 48, 84–85, 90
 Backoff indicator (BI), 205
 Balian–Low theorem, 338–339
 Bandwidth adaptation (BA),
 394–395
 Bandwidth part (BWP), 379–380,
 393–396
 inactivity timer, 169–170
 Base graph, 530
 Base station transceiver RF
 conducted and radiated BS
 transmitter/receiver
 characteristics, 671–691
 requirements, 665–671
 Baseband modems, 719
 Baseband signal processing,
 62–63
 Baseband unit (BBU), 7, 67–68
 Basic service set (BSS), 859
 Beam
 reporting, 511–512
 steering, 743
 sweeping, 510
 tracking, 743
 Beam management (BM),
 411–412, 509–515
 Beam-level mobility, 253, 260
 Beamforming, 567, 846
 Beamforming unit (BFU), 739
 Belief propagation (BP), 359–360
 algorithm, 531
 decoder, 515–516, 518

Bhattacharyya parameter, 516,
 518–519
 Binary phase shift keying (BPSK),
 535, 772
 Bipolar junction transistor (BJT), 66
 Bit error rates (BERs), 76,
 515–516
 Blank-subframe, 907–909
 Block interlaced frequency
 division multiple access
 (B-IFDMA), 888–890
 Blockage, 296–298
 Blocking, 689–690
 Bluetooth, 55–58, 747, 848
 Bragg diffraction, 291–292
 Break-before-make mode, 109
 Broadcast channel (BCH), 138,
 202
 Broadcast control channel
 (BCCH), 137–138
 Broadcast multicast service center
 (BM-SC), 803–804
 Buffer status report (BSR), 208
 Bulk acoustic wave (BAW),
 735–736
 filter, 736–737
 Business support system (BSS),
 15–16
 Butler matrix, 739

C

Camping on cell, 246
 Candidate waveforms, 335–350
 CAPEX, 21
 Carrier aggregation (CA), 53–54,
 280–283
 scenarios, 881–882
 Carrier frequency offsets (CFOs),
 326–328, 777
 Carrier sense multiple access with
 collision avoidance
 (CSMA/CA), 857
 Carrier sensing adaptive
 transmission (CSAT),
 879–880
 Carrier Wi-Fi, 56–57
 Cauchy distribution, 329–330
 CBG flush indicator (CBGFI),
 492–493
 CBG transmit indicator (CBGTI),
 492–493
 Cell
 cell-level mobility, 259–260
 cell-specific reference signals,
 415
 cell-specific SIB, 240–241
 densification, 300
 range extension, 52–53
 reselection, 165, 248
 search and random-access
 procedure, 777–780
 selection, 265–266, 897
 virtualization, 59
 Cell global ID (CGID), 50–51
 Cell Radio Network Temporary
 Identifier (C-RNTI), 130,
 202
 Cell-defining SSBs (CD-SSBs),
 247
 Cell-specific reference signals
 (CRS), 699, 757–758
 Cellular IoT (CIoT), 750–751
 Cellular network, 350
 Cellular V2X (C-V2X), 789, 841
 Central network controller, 65
 Central offices (COs), 56–57
 Central unit (CU), 26–27, 60–62
 Central unit of logical gNB (gNB-
 CU), 26–27, 119
 gNB-CU-CP, 121–122
 UE F1AP ID, 120, 132
 Centralized C-RAN architectural
 concept, 30
 Centralized-RAN architecture (C-
 RAN architecture), 28–30,
 57
 high-capacity cloud-RAN, 15
 Channel busy ratio (CBR), 836
 Channel coding, 515–539
 low density parity check coding
 principles, 529–531
 modulation schemes and
 modulation coding scheme
 determination, 535–539
 NR low density parity check
 coding, 532–534
 NR polar coding, 523–528
 polar coding principles,
 516–523

- Channel hardening, 305, 583
- Channel impulse response, 310
- Channel matrix, 556
- Channel measurement (CM), 431
- Channel models, 287–313
- Channel occupancy (CO), 905
- Channel polarization, 517–518
- Channel quality indicator (CQI), 457
- Channel raster, 382
- Channel realizations, 307–309
- Channel reservation, 901
- Channel state information (CSI), 411–412, 571, 847
 - measurement and reporting, 496–509
- Channel state information
 - reference signals (CSI-RS), 425–431, 450, 888
 - CSI-RS-based intrafrequency measurement, 273
- Channel state information signal-to-interference-plus-noise ratio (CSI-SINR), 508–509
- Channel state information-received signal strength indicator (CSI-RSSI), 508
- Channel state information-reference signal received power (CSI-RSRP), 431, 507–508
- Channel state information-reference signal received quality (CSI-RSRQ), 508
- Check node (CND), 529–530
- Ciphering, 187, 229–233
- Circulant matrix, 530
- Circulator, 374–375
- Citizen Broadband Radio Service (CBRS), 851–853
- Classic eigen-beamforming scheme, 567
- Clear channel assessment (CCA), 857
- Clear-to-send-to-self message (CTS-to-self message), 858–859
- Closed access mode, 52–53
- Cloud infrastructures, 13
- Cloud-based application, 794–795
- Cloud-based radio access, 17–18
- Cloud-radio access network (C-RAN), 7–10, 56–98
 - architectural aspects, 57–62
 - backhaul transport options, 86–98
 - with distributed RRHs, 54–55
- Coarse/dense wavelength division multiplexing (CWDM/DWDM), 7–10
- Cochannel dual polarization (CCDP), 96–97
- Code block concatenation process, 490–491
- Code block group (CBG), 461
 - CBG-based retransmissions, 214–215
- Code construction algorithms, 517
- Codebooks, 360–361
 - codebook-based precoding, 638–640
 - determination algorithms, 550
 - resolution, 502–503
 - subset restriction concept, 641
- Coding-based NOMA schemes, 368–369
- Coherence
 - bandwidth, 293–294
 - distance, 296
 - time, 295
- Collapsed gNB deployment, 26
- Co-located LWA scenario, 891–892
- Commercial Mobile Alert System (CMAS), 239
- Common control channel (CCCH), 137–138, 204–205
- Common phase error (CPE), 416, 423–424
- Common Public Radio Interface Forum (CPRI Forum), 7, 32–33, 74
 - transport, 75
- Common resource block (CRB), 381–382
- Complementary metal-oxide semiconductor process (CMOS process), 714, 717
- Component carrier (CC), 53–54
- Conducted BS transmitter/receiver characteristics, 671–691
- Conducted UE transmitter/receiver characteristics, 694–699
- Configured grant Type 1, 212–213, 405–406
- Configured scheduling RNTI (CS-RNTI), 405
- Connected mode procedures, 251–253
- Connection density, 41–42, 54
- Connection management states, 243
 - CM-IDLE and CM-CONNECTED states, 243
- Constellation rotation, 328–329
- Container technology, 13–14
- Content caching, 6, 79
- Contention window (CW), 857
- Contention-based performance, 404–405
- Contention-based random-access, 778–779
- Context-aware communication, 80
- Control channels (CCH), 137, 800
 - PBCH, 432–439
 - PDCCH, 439–477
 - in uplink physical layer, 605–631
 - physical random-access channel, 617–631
 - PUCCH, 605–617
- Control elements (CEs), 203
- Control plane entity (CP entity), 6, 26
- Control resource set (CORESET), 416–417, 441–443, 446–448
- Control-and user-plane separation (CUPS), 28–29, 33–35, 141
- Control-plane
 - CIoT EPS optimization, 750–752
 - CU-CP entity, 26–27
 - handover procedures, 260–263
 - latency, 43–44
 - protocols, 113–114, 129–130, 808–809
 - stacks, 149–152
- Conventional open-loop beamforming, 585

- Cooperative C-RAN architectural concept, 30
 - Cooperative radio transmission, 30
 - Coordinated multipoint (CoMP), 28–29, 49
 - transmission and reception feature, 54–55
 - Core network (CN), 1, 141–152, 243
 - architecture, 17–18
 - assistance information, 249
 - CN-initiated paging, 166
 - CN-level interworking, 158–161
 - control-plane protocol stacks, 149–152
 - entities and interfaces, 142–146
 - protocol data unit sessions and 5GC identifiers, 146–149
 - user-plane protocol stacks, 152
 - Counter DAI (cDAI), 550
 - Coupling loss, 47
 - Coverage, 47
 - Crest factor reduction (CFR), 347–348
 - Cross-carrier scheduling, 53–54, 281
 - Cross-polarization discrimination (XPD), 291–292
 - Cross-polarization interference cancelation (XPIC), 96–97, 291–292
 - Cross-polarized signal components, 291–292
 - CSI-RS resource indicator (CRI), 498
 - Cumulative adjacent channel leakage ratio (CACLR), 685–686
 - Cumulative distribution function (CDF), 39–40, 321–322, 755
 - Customer-facing service (CFS), 104–105
- D**
- Data converters, 711
 - Data network (DN), 143
 - name, 149
 - Data plane development kit (DPDK), 13–14
 - Data radio bearers (DRBs), 115, 124, 197
 - Decoding
 - algorithms for LDPC codes, 531
 - process, 522
 - Decoupling of RAT and core network, 141
 - Dedicated control channel (DCCH), 137–138, 217
 - Dedicated EPS bearer, 146–147
 - Dedicated short-range communication (DSRC), 789
 - Dedicated traffic channel (DTCH), 137–138, 217
 - Deep learning models, 80
 - Default EPS bearer, 146–147
 - Default QoS rule, 177–178
 - Delay, 293–294
 - spread, 291–295
 - Demodulation reference signals (DM-RS), 415, 417–423, 592–597, 772, 814, 829–830
 - for PUCCH, 596–597
 - for PUSCH, 593–596
 - Demodulator, 521
 - Dense Urban-eMBB test environment, 39, 44–45, 48, 307–309
 - Densification of wireless networks, 55–56
 - Deployment models, 853–856
 - Deployment scenarios, 158–164
 - Extreme Long Distance deployment scenario, 49
 - Destination layer-2 ID, 839
 - Device energy efficiency, 46
 - Device-to-device (D2D), 80
 - communications, 22
 - D2D-based positioning techniques, 55–58
 - mode, 792
 - technology, 791
 - Device-to-network mode, 792
 - DFT-spread OFDM (DFT-S-OFDM), 346–347, 353
 - basics and transmission characteristics, 330–335
 - QPSK waveform, 323–325
 - subcarrier mapping in, 331–332
 - Diameter, 34–35
 - Diffuse scattering, 291–292
 - Digital beamforming (DBF), 564–573, 738–739
 - Digital down-conversion (DDC), 708
 - Digital precoding, 571
 - Digital predistortion (DPD), 683, 725
 - Digital subscriber line (DSL), 48–49, 91
 - Digital-to-analog converter (DAC), 704
 - Direct frame number (DFN), 835–836
 - Direct RF sampling transceivers, 704–716
 - Nyquist zones and sampling of wideband signals, 708–711
 - receiver design, 714–716
 - transmitter design, 712–714
 - Direct-conversion RF DAC technology, 713–714
 - Direction-of-arrival beamforming, 567
 - Disaggregated gNB deployment, 26–27
 - Disaggregation, 26–28
 - Discontinuous reception (DRX), 43, 138, 169, 171, 200, 206, 255–258
 - Discovery reference signals (DRS), 868
 - Distributed antenna system (DAS), 55–57
 - Distributed coordination function (DCF), 857, 859–862
 - Distributed CRC polar code (D-CRC polar code), 523
 - Distributed interframe space (DIFS), 857
 - Distributed unit (DU), 26–27, 30–32, 36
 - Distributed unit of logical gNB (gNB-DU), 26–27, 119, 121
 - ID, 132
 - UE F1AP ID, 132

Diverse user interactions, 14–15
dl-UL-TransmissionPeriodicity
 parameter, 389
 Doherty amplifier, 725
 Domain name system (DNS), 36,
 105–106
 Doppler frequency component,
 310
 Doppler power spectrum, 296
 Doppler shift, 311, 589
 Doppler spread, 292–293, 295
 angular spread, 295–296
 Double-symbol DM-RS, 420
 Downlink (DL), 51–52, 197
 assignment, 212
 beamforming, 450
 channel-dependent scheduling,
 211
 MIMO schemes, 551–590
 analog, digital, and hybrid
 beamforming, 564–573
 capacity of MIMO channels,
 552–558
 FD-MIMO, 573–582
 large-scale MIMO systems,
 582–586
 NR multi-antenna
 transmission schemes,
 586–590
 SU-MIMO techniques,
 558–564
 multiple access, 757
 scanning and synchronization
 + broadcast channel
 acquisition, 43
 scheduler, 210–211
 transmission, 871–873
 Downlink assignment index
 (DAI), 460
 Downlink control information
 (DCI), 207–208, 420,
 763–764, 822
 format, 457–465
 Downlink physical layer, 412.
See also Uplink physical
 layer
 beam management, 509–515
 channel coding and modulation
 schemes, 515–539
 control channels, 432–477

CSI measurement and reporting,
 496–509
 hybrid ARQ operation and
 protocols, 539–550
 PDSCH, 487–496
 reference signals, 413–432
 synchronization signals,
 477–487
 Downlink pilot time slot (DwPTS),
 895–896
 Downlink shared channel (DL-
 SCH), 138, 200
 DRS measurement timing
 configuration (DMTC), 897
 Dual connectivity (DC), 127–128,
 199–200
 duplication, 225–226
 schemes, 153–158
 Dual registration approach, 161
 Dual-connectivity, 728
 Dual-polarized antenna, 376–377
 array, 588
 Duplex schemes, 369–379
 frequency and time division
 duplex schemes, 369–371
 full-duplex schemes, 373–379
 half-duplex and flexible-duplex
 schemes, 371–373
 Duplication activation/deactivation
 for MAC CE, 205–206
 DwPTS. *See* Downlink pilot time
 slot (DwPTS)
 Dynamic 3D beamforming, 574
 Dynamic blockage, 296–297
 Dynamic frequency selection
 (DFS), 845, 870–871
 Dynamic scheduling, 475–477,
 636–637, 820
 Dynamic spectrum sharing rules,
 851

E

E-mode pHEMT device, 734
 E-URAN random access bearer
 (ERAB), 124, 146–147
 E-UTRAN cell global identifier
 (ECGI), 804–805
 E1 application protocol (E1AP),
 121–122

E1 control-plane functions and
 procedures, 121–122
 Earthquake and Tsunami Warning
 System (ETWS), 238
 eCPRI, 32–33, 63. *See also*
 Common Public Radio
 Interface Forum (CPRI
 Forum)
 characteristics, 77
 specification, 78–81
 transport, 76–77
 eCPRI radio equipment
 (eRE), 78
 eCPRI radio equipment control
 (eREC), 78
 Edge computing, 109
 Edge proximity services, 80
 Effective number of bits (ENOB),
 704–706
 Eigen-beamforming, 567
 Eigenvector transform, 580–581
 Electromagnetic shielding,
 376–377
 Element management (EM),
 19–20
 Element management systems
 (EMSs), 15–16
 Elementary procedures (EPs), 120
 Elementary signal estimator (ESE),
 357–358
 Elevation spread of departure
 (ESD), 578–579
 Embedded wafer-level-ball grid
 array package (eWLB grid
 array package), 718
 Emergency response service,
 13–14
 Emission mask, 683
 Energy detection threshold (ED
 threshold), 871–873
 Energy efficiency (EE), 30, 46, 52
 Energy per resource element
 (EPRE), 500–501
 Enhanced distributed channel
 access (EDCA), 862–864
 Enhanced ICIC (eICIC), 53
 Enhanced LAA (eLAA),
 867–868
 Enhanced licensed-assisted access,
 897–898

- Enhanced MIMO schemes, 67
- Enhanced mobile broadband (eMBB), 13–14, 20, 54, 515–516
- Enhanced multimedia broadcast multicast service (eMBMS), 68
- Enhanced subscriber/device privacy, 840
- Envelope tracking (ET), 348–350, 724
- Environmental sensing capability (ESC), 852–853
- EPS connection management (ECM), 164–165
- EPS mobility management (EMM), 164–165
- Equivalent isotropic radiated power (EIRP), 668, 671–672, 846
- Equivalent isotropic sensitivity (EIS), 668, 672–673
- Error vector magnitude (EVM), 325–326, 673, 680–681, 784
- ETSI Industry Specification Group (ISG), 99
- ETWS. *See* Earthquake and Tsunami Warning System (ETWS)
- Euclidean norm of square matrix, 568–569
- European Conference of Postal and Telecommunications Administrations (CEPT), 656–657
- European Telecommunications Standards Institute (ETSI), 19
- Evolved packet core (EPC), 11, 26
control-and user-plane
separation of EPC nodes, 33–35
- Evolved packet system (EPS), 51, 750–751
AKA procedure, 185
bearer, 124, 172
- Evolved Universal Terrestrial Radio Access (E-UTRA), 224–225
- Evolved Universal Terrestrial Radio Access-NR-DC (EN-DC), 113–114, 154, 224–225, 697–699
- Evolved V2X (eV2X), 792–795
- Extended discontinuous reception (eDRX), 747, 781
- Extensible authentication protocol (EAP), 840
- Extreme Long Distance deployment scenario, 49
- ## F
- F1 application protocol (F1AP), 119
- F1 control-plane/user-plane functions and procedures, 119–121
- Far-field (Fraunhofer) region, 667
- Fast hopping sounding reference signal, 733
- Faster than Nyquist (FTN), 344–346
- Favorable propagation, 582–585
- FD-SOI technology, 718
- Feed-back precoding matrix selection techniques, 571
- Femtocells, 3–4, 46–47, 55–56, 91
- Fifth generation network (5G network), 1, 13–18, 81, 728, 850–851
cellular systems, 303–304
deployment scenarios, 158–164
design principles and prominent network topologies, 3–111
cloud-radio access network and virtual-radio access network, 56–98
heterogeneous and ultra-dense networks, 46–56
MEC, 98–109
network and service requirements, 10–11
network sharing, 109–111
network slicing, 37–46
NFV, 12–26
separation of control and user planes, 26–36
- dual connectivity and multi-connectivity schemes, 153–158
- future outlook, 78–83
- GUTI, 148–149
- IMT-2020 standardization activities, 62–66
- ITU-R standardization activities, 62–66
- KPIs, architectural, system, and service requirements, 36–62
high-level architectural requirements, 50–53
performance metrics, 38–48
service requirements, 54–62
system performance requirements, 53–54
test environments, 48–50
- long-term evolution—new radio interworking, 158–164
- mmWave fixed wireless applications, 76–78
- network aspects of mobility and power management, 164–171
- network slices accommodating different use cases, 18
- QoS
flows, 126–127
framework, 172–184
model, 177
- RAN architecture, 28–29
- reference architectures, 111–152
access network, 112–140
core network, 141–152
security, 185–191, 839
spectrum and regulations, 70–78
system and service requirements, 16–18
- 3GPP 5G standardization activities, 66–70
- use cases, 21–25
categories, 15
and deployment scenarios, 18–36
- Fifth percentile user spectral efficiency, 39–40

Figure of merit (FoM), 722–723
 Filter bank multicarrier (FBMC), 337–340
 Filtered-orthogonal frequency division multiplexing (F-OFDM), 336–337
 First Fresnel ellipsoid, 288
 Five-point beam test, 743
 5G core network (5GC network), 1, 26
 identifiers, 146–149
 5G QoS identifier (5QI), 175–177, 180–181
 Fixed frame period (FFP), 883
 Flexible-duplex scheme, 371–373
 Flip chip method, 718
 ForCES, 35
 Forward error correction (FEC), 539–542
 Forwarding and control element separation, 28
 Fractional-T/E carrier, 91
 Frame structure
 NB-IoT, 757
 and numerology, 383–391
 type 3, 886–887
 Frame timing synchronization, 821
 Frame-based equipment (FBE), 883
 Free-space conditions, 288
 Free-space path loss, 287–288
 Frequency
 bands, 303–304
 error, 589
 frequency-selective fading effects, 294–295
 frequency-selective resource allocation, 586
 hopping, 771–772
 flag, 459
 synchronization, 89–90
 Frequency division duplex (FDD), 49–50, 314, 369–371, 826–827
 Frequency division duplex/time division duplex (FDD/TDD), 49
 Frequency domain, 391–392
 equalization, 332

 resource allocation in, 400–403
 PRB bundling, 403
 Zadoff-Chu sequence, 830–831
 Frequency range (FR), 287
 Fresnel zone, 288
 Frobenius norm, 321–322
 Fronthaul bandwidth, 73–74
 Fronthaul latency, 73–74
 Fronthaul transport options, 62–86
 Fronthaul-I (NGFI-I), 84–85
 Fronthaul-II (NGFI-II), 84–85
 Full-dimension MIMO (FD-MIMO), 67–68, 573–582
 Full-duplex schemes, 373–379
 Full-functional base station, 47
 Fully depleted/partially depleted silicon on insulator (RF-SOI/FD-SOI), 718
 Fully-qualified domain name (FQDN), 130
 Functional splits, 68
 options, 62–86

G

Gabor system, 338–339
 Gabor's theory of communication, 314–315
 Gallium arsenide (GaAs), 716–717
 E-mode pHEMT technology, 734, 736–737
 GaAs-based devices, 734–735
 mHEMT technology, 735
 Gap interval, 765–767
 Gateway core network approach (GWCN approach), 109
 General authorized access (GAA), 851
 Generalized frequency division multiplexing (GFDM), 343–344
 Generator matrix, 519, 529–530
 Generic PA, 348–350
 Generic public subscription identifier (GPSI), 149
 Geometry-induced blockage, 296–297
 Gigabit passive optical network, 91–94

Global gNB ID, 130
 Global ITS spectrum, 801–802
 Global navigation satellite system (GNSS), 55–58, 89–90, 797–798
 Global positioning system (GPS), 89–90
 Global synchronization channel number (GSCN), 383
 gNB, 28
 entity, 115
 scheduler, 210, 213–214
 UE context, 120–121
 UE NG application protocol ID, 131
 gNB Identifier (gNB ID), 130
 Gold sequence, 421, 427
 GPRS tunneling protocol, 117–118, 152
 Grant-based performance, 404–405
 Grant-free/semi-persistent scheduling, 403–407
 Group-common PDCCH (GC-PDCCH), 439
 Guaranteed bit rate (GBR), 51–52, 172–173
 Guaranteed flow bit rate (GFBR), 175–176
 Guard subcarriers, 320
 Guard-band, 754
 mode, 755

H

Half-duplex FDD (H-FDD), 371–372
 Half-duplex scheme, 371–373
 Handover, 258–274
 interruption time, 47–48
 Handover Command message, 252
 Handover Complete message, 252
 Hardware virtualization, 13
 Header compression, 222–223
 function, 226–229
 Heterogeneous networks, 46–56
 Heterojunction bipolar transistor (HBT), 66, 716–717

- HetNet
 - architecture, 91
 - deployments, 52–53
 - topology, 90
 - High-electron-mobility transistor (HEMT), 734–735
 - High-level architectural
 - requirements for 5G, 50–53
 - High-level language for SDN
 - applications, 30–31
 - High-power UE (HPUE), 730
 - High-spatial-resolution CSI, 503, 505–506
 - Higher accuracy positioning, 55–58
 - Hilbert–Schmidt norm, 321–322
 - Home eNB concept (HeNB concept), 52–53
 - Home subscriber server (HSS), 185
 - Hotelling transform, 580–581
 - Hotspot 2.0, 56–57
 - Hybrid automatic repeat request (HARQ), 763–764, 796–797, 847, 902–903
 - entity, 135
 - functionality in MAC sublayer, 213–214
 - HARQ-ACKs, 214
 - operation and protocols
 - semi-static/dynamic codebook
 - hybrid ARQ-ACK
 - multiplexing, 548–550
 - UE processing times, HARQ protocol and timing, 542–548
 - principles, 539–542
 - protocols, 411
 - retransmissions, 44–45
 - time, 43
 - and scheduling, 775–776
 - synchronous uplink, 903
 - timing, 64
 - Hybrid beamforming (HBF), 564–573, 739
 - Hybrid coordination function (HCF), 862–864
 - Hybrid fiber-coaxial cable (HFC cable), 91–94
 - Hybrid NOMA, 364–365
 - Hyper frame number (HFN), 229–230, 757
 - Hypervisor, 13–14
- I**
- Idle mode procedures, 246–248
 - IDLE state, 43–44
 - IEC 61907 2009 standard, 58–59
 - IEEE 1588v2 precision timing protocol, 89–90
 - IEEE 1914 working group, 32–33
 - IEEE 1914.1 Next-Generation Fronthaul Interface, 82–83
 - IEEE 1914.3 Radio-Over-Ethernet Transport, 81
 - IEEE 802.11 operation principles, 846–847, 857–865
 - IEEE P1914.1 standard, 32
 - IEEE P1914.3 standard, 32
 - IKE protocol, 145
 - IKEv2 protocol, 145
 - Imperfect IQ mixer, 377–378
 - In-band, 754
 - emissions, 696
 - mode, 755
 - In-channel selectivity (ICS), 677, 690
 - In-device coexistence (IDC), 796
 - interference, 910
 - In-phase and quadrature (I/Q)
 - data message type, 78–80
 - digital radio samples, 62–63
 - Inactive mode procedures, 248–251
 - Inactive RNTI (I-RNTI), 130
 - INACTIVE state, 43
 - Inactivity-timer, 171
 - Incremental redundancy HARQ
 - scheme (IR HARQ scheme), 540–542
 - Indoor hotspot (InH), 287
 - Indoor hotspot-eMBB test
 - environment, 39, 44–45, 48, 307–309
 - Industrial, scientific, and medical (ISM bands), 846
 - radio communications in, 848
 - Industrial automation, 53
 - Information and Communication Technologies (ICT), 83
 - Information element (IE), 882–883
 - Information-centric networking (ICN), 66–67, 141
 - Infrastructure layer, 43–44
 - Integrated LNAs, 732
 - Integrated passive devices (IPDs), 76–78
 - Integrity
 - check, 187
 - protection functions, 229–233
 - Intelligent transport systems (ITS), 60–62, 791
 - Intended number of paging attempts, 269
 - Inter-gNB handover procedure, 259–260
 - Inter-RAT handover process, 59–60
 - Inter-RF bandwidth gap, 690–691
 - Intercell coordination function, 54–55
 - Intercell interference cancelation (ICIC), 53, 907
 - Interdigital transducers (IDTs), 736–737
 - Interference management, 55
 - Interference measurement (IM), 416
 - Interference mitigation techniques, 72–73
 - Intermodulation products, 348–350
 - Internal-group identifier, 149
 - International Mobile Equipment Identity (IMEI), 129–130
 - International Mobile Subscriber Identity (IMSI), 129–130, 148–149, 781–782
 - International Mobile Telecommunications
 - (IMT), 20–21, 82–83, 656–657
 - International Mobile Telecommunications–2020 (IMT-2020), 62–66
 - test environment mapping, 49
 - 3D channel model, 307–309

International Telecommunication
Union (ITU), 18
ITU-T, 66–67

International Telecommunication
Union Radio-
Communication Sector
(ITU-R), 18, 62–66
LoS path loss model, 301
Study Group 5, 63–64

Internet Engineering Task Force
(IETF), 66–67, 222–223

Internet of Things (IoT), 11,
13–14, 24, 62, 82, 101,
167, 747, 840, 856. *See also*
Narrowband IoT (NB-IoT)
general aspects and use cases,
749–750
implementation and deployment
considerations, 783–785
layer 2/3 aspects, 775–783
network architecture and
protocol aspects, 750–756
physical layer aspects, 757–775

Internet protocol (IP), 12,
750–751, 804–805

Internet Engineering Task Force
(IETF), 67

Inter-node radio resource
aggregation, 153

Inter-node synchronization, 910

Interspersed ROHC feedback,
232–233

Inter-symbol interference (ISI),
292–293

Inter-vendor interoperability, 81

Intra-AMF/UPF handover in NR,
260–263

Intra-band non-contiguous carrier
aggregation, 664

IP multimedia subsystem (IMS),
124–125

IPsec protocol, 145

IPsec security association (IPsec
SA), 145

J

JavaScript Object Notation
(JSON), 26–27

JESD204B/C model, 707–708

K

Karhunen–Loève theorem,
580–581

KASME, 185

Key performance indicators
(KPIs), 36–62, 85–86

Kronecker model, 312
product correlation model,
580–581

L

Large antenna arrays, 564
design and implementation,
737–744

array calibration, 740

Large-scale MIMO systems,
16–17, 411–412,
577–578, 582–586

Layer 2/3 aspects

IoT, 775–783
cell search and random-access
procedure, 777–780

hybrid automatic repeat
request and scheduling,
775–776

paging and mobility,
781–783

physical, logical, and
transport channels,
776–777

PSM, 780–781

V2X communications, 831–841

Layer indication (LI), 498

License-assisted access (LAA),
845, 854–855, 867–877

deployment scenarios, 854–855

Licensed frequency bands, 846

Licensed spectrum, 846

Light detection and ranging
(LIDAR), 790

Limited-buffer rate matching
(LBRM), 490–491

Line-of-sight (LoS), 60–62, 288

microwave link, 96–97

microwave systems, 94–96

path loss probability, 301–303

probability, 302

propagation model, 44–45

Linear equalizer, 332

Linear MMSE (LMMSE),
357–358
receiver, 561

Link adaptation in uplink physical
layer, 643–651

Link-to-system mapping, 44–45

Listen-before-talk (LBT), 845,
877, 887

Load-based equipment (LBE), 883

Local oscillator (LO), 712

Local radio resource allocation
strategies, 55

Location/positioning service,
55–58

Log likelihood ratios (LLRs),
489–490

Logarithmic encoding algorithms, 64

Logical channel groups (LCGs),
202

Logical channel ID (LCID), 203,
808–809

Logical channels, 137–138,
201–202, 776–777

prioritization procedure, 208

Long-PUCCH, 608

Long-term evolution (LTE), 11,
66–67, 657–659, 791

co-deployment scenarios, 30
control mechanisms, 69–70

deployment scenarios, 26

eNB, 900–901

LTE-advanced base stations, 93

LTE-Advanced Pro, 66–67

LTE-based cellular radio access
technology, 747

LTE-based LAA, 845, 874–875

LTE/NR

operation, 906–907

V2X security, 838–841

LTE–new radio interworking,
158–164

networks, 23–24

and new radio solutions for
operation in unlicensed
spectrum, 865–890

LAA, 867–877

LTE-U and MulteFire,
879–881

LTE-Wi-Fi aggregation,
877–879

- Long-term evolution (LTE)
 (Continued)
 new radio-unlicensed,
 881–890
 Rel-8, 53
 Rel-9, 52–53
 Rel-10, 53
 Rel-11, 54–55
 Rel-15, 870
 3GPP LTE, 747
 X2 interface, 48–49
- Low-complexity baseband
 decoding process, 783
- Low-density parity check
 (LDPC), 411
 coding principles, 515–516,
 529–531
- Low-density spreading (LDS),
 359–360
- Low-latency communications, 20
- Low-noise amplifier (LNA),
 686–687
- Low-power wide-area (LPWA), 747
- Low-voltage differential-swing
 (LVDS), 707–708
- LTE unlicensed Forum (LTE-U
 Forum), 845, 879–881
- LTE-Wi-Fi aggregation (LWA),
 845, 865–867, 877–879
- LTE-Wi-Fi aggregation adaptation
 protocol (LWAAP), 892
- LTE-Wi-Fi radio-level integration
 with IP security tunnel
 (LWIP), 865–867
- M**
- Machine learning (ML), 79, 750
- Macro-eNB, 53
- Macro-TRPs, 48
- Macrocells, 3–4, 46–47, 91, 94
 network coverage, 70
- Macro-extension access node, 47
- Macroscopic fading, 289
- Make-before-break mode, 109
- Management and orchestration
 (MANO), 1–2, 15–16, 23
 of NFVI, 25–26
- Management reference points
 (Mm), 103, 107
- Massive IoT, 747, 749–750
- Massive machine type
 communications (mMTC),
 6, 13–14, 20, 747
- Massive MTC slice, 36
- Master cell group (MCG),
 127–128, 202
 bearer, 156
 in multi-RAT dual connectivity
 scheme, 153–154
 split bearer, 156
- Master gNB (MgNB), 128, 153
 UE XnAP ID, 132
- Master information block (MIB),
 200, 412
 message, 433–434
- Master node (MN), 154, 277
- Matched filter, 357–358
- Maximum bit rate (MBR),
 172–173, 177–178
- Maximum coupling loss (MCL),
 47, 748–749
- Maximum flow bit rate (MFBR),
 175–176
- Maximum length sequences
 (M-sequences), 478–479
- Maximum power reduction
 (MPR), 695–696
- Maximum sensitivity degradation
 (MSD), 697–699
- Maximum-a-posteriori estimate
 (MAP estimate), 361–363
- Mean path loss, 289
- Measurement gap length (MGL),
 701
- Measurement gap repetition period
 (MGRP), 701
- Measurement model, 270–274
- Medium access control (MAC),
 39–40, 195–196,
 198–199, 771–772,
 808–809, 858–859
 PDU, 204–205, 208–209
 sublayer, 133–135, 137,
 201–215, 285
- Memoryless SISO channel, 553
- Message authentication codes,
 230–231
- Message passing algorithm (MPA),
 354
- Metro ANs, 83–84
- Metro cell, 91
- Micro TRPs, 48
- Microcells, 46–47
- Microelectromechanical systems
 (MEMS), 735–736
- Microscopic fading, 289–290
- Min-sum algorithm, 531
- Minimum mean square error
 (MMSE), 331, 561
- Mission-critical IoT, 747,
 749–750
 service, 33–34
 slice, 36
- mmWave bands, 25, 74, 83
 channels, 299
 implementation and operation
 analog front-end design
 considerations, 719–723
 antenna design considerations,
 726–727
 power consumption
 considerations, 723–726
 semiconductor technologies,
 716–719
 large antenna array design and
 implementation in,
 737–744
- Mobile backhaul, 89–90
- Mobile broadband, 21
 slice, 20
- Mobile edge (ME), 103
 host-level management,
 104–105
 orchestrator, 105–106
 platform, 105
 reference architecture,
 106–107
 system-level management,
 104–105
- Mobile edge computing (MEC), 3,
 79–80, 98–109
 architectural aspects, 101–109
 host, 102
 orchestrator, 103–104
 platform manager, 103–104
 reference points, 103
 services, 30–32
 and deployment scenarios,
 99–101

- Mobile networks, 33–34, 80–81, 111–112
 - Mobile video optimization (MVO), 35
 - Mobile-originated data, 767–768
 - Mobility, 44, 781–783
 - function, 114
 - load balancing, 51–52
 - management, 52–53, 258–274
 - network aspects of, 164–171
 - pattern, 166–167
 - robustness optimization, 51–52
 - Mobility management entity (MME), 750–751, 805
 - Modification period, 240
 - Modified Bessel function, 290
 - Modularized functional design, 1–2
 - Modulation coding scheme (MCS), 416, 515–539, 718, 808
 - determination, 535–539
 - Molecular oxygen absorption, 300
 - Monolithic microwave integrated circuit (MMIC), 716–717
 - Monte Carlo simulation, 368
 - MSISDN, 149
 - MU-MIMO, 358–359, 396–397, 502, 505–506
 - precoded MU-MIMO system, 569–570
 - schemes, 551–552, 559–560
 - MulteFire, 879–881
 - Multi-RAT
 - coexistence, 59–60
 - systems, 14–15
 - Multi-antenna
 - systems, 577–578
 - transmission, 846
 - Multicarrier NOMA, 364–365
 - Multi-cluster PUSCH transmission, 897–898
 - Multi-connectivity, 18
 - schemes, 153–158
 - Multi-layer networks, 14–15
 - Multi-layer SU-MIMO schemes, 559
 - Multimedia broadcast/multicast service, 54–55
 - Multimedia messaging, 22
 - Multimedia priority service (MPS), 59–60
 - Multi-mode devices, 14–15
 - Multi-operator core network approach (MOCN approach), 109
 - Multi-panel MIMO, 411–412
 - Multipath
 - fading, 287
 - multipath-intensity function, 296
 - propagation, 287
 - Multiple access (MA), 323–325
 - schemes, 350–369
 - non-orthogonal multiple-access schemes, 353–369
 - OFDMA, 351–352
 - SC-FDMA, 353
 - Multiple access channel (MAC), 412
 - Multiple input and multiple output (MIMO), 59
 - channels, 552–553
 - systems, 291–292
 - Multiple SCeLLs, 874–875
 - Multiple-entry PHR MAC CE, 207–208
 - Multiple-input–single-output (MISO), 552–553
 - Multi-pole filters, 76–78
 - Multi-port CSI-RS, 426–427
 - Multi-radio dual connectivity (MR-DC), 154, 254, 277–280
 - Multi-user shared access (MUSA), 350
 - Mutual information, 556
- N**
- N2 interface, 151
 - N26 interface, 159–161
 - Narrowband control channel
 - element (NCCE), 763–764
 - Narrowband IoT (NB-IoT), 747
 - protocol stack, 755
 - uplink transmission, 755
 - Narrowband master information block (MIB-NB), 760
 - Narrowband physical broadcast channel (NPBCH), 760–762
 - Narrowband physical cell identity (NB-PCID), 758–760
 - Narrowband physical downlink control channel (NPDCCH), 763–767
 - Narrowband physical downlink shared channel (NPDSCH), 763–764, 767–769
 - Narrowband physical random-access channel (NPRACH), 769–772, 777
 - Narrowband physical uplink shared channel (NPUSCH), 765, 772–775
 - Narrowband primary synchronization signal (NPSS), 757–758
 - Narrowband reference signal (NRS), 760
 - Narrowband secondary synchronization signal (NSSS), 757–760
 - Narrowband system information block type 1 (SIB1-NB), 761
 - NAS mobility and session management (NAS-MM and SM), 149–150
 - NEA algorithms, 128-bit, 229–230
 - Neighbor cell list (NCL), 248
 - Network
 - energy efficiency, 46
 - identifiers, 274–276
 - infrastructure, 79–80
 - management layer, 43–44
 - network-based communication, 802
 - networked VLC, 82
 - operators, 14
 - scalability, 36–37
 - service
 - behavior, 19
 - chaining, 37–38
 - sharing, 52, 109–111
 - stability, 16
 - status
 - collection process, 30–31
 - synchronization process, 30–31
 - synchronization, 49
 - technical domains, 82
 - technology, 749–750

- Network access identifier (NAI), 148
- Network allocation vector (NAV), 858–859
- Network architecture, 750–752
 - modes of operation, 752–755
 - and protocol aspects, 891–895
 - reference architecture, 802–807
 - sidelink and radio access protocols, 807–811
- Network exposure function (NEF), 144
- Network function repository function (NRF), 144
- Network function virtualization (NFV), 1, 12–26, 34–37
 - architectural aspects, 16–19
 - challenges, 14–16
 - functional aspects, 19–22
 - legacy support and interworking aspects, 24–26
 - operational aspects, 22–24
- Network function virtualization-management and orchestration (NFV-MANO), 22
 - architectural framework, 22
 - functional blocks, 20
- Network functions (NFs), 2
- Network management systems (NMSs), 15
- Network signaling (NS), 676
- Network slice instances (NSIs), 38–40, 46, 82
- Network slice management (NSM), 43–44
- Network slice selection function (NSSF), 40–41
- Network slice template (NST), 43
- Network slice/slicing, 1–2, 6, 33–34, 37–46, 52, 85, 111–112, 191
 - blueprint, 38–39
 - layer, 43–44
 - SDN, 36–37
- Network-as-a-service (NaaS), 34
- Network-controlled mobility, 259–265
 - control-plane handover procedures, 260–263
 - user-plane handover procedures, 263–265
- Network-controlled power management, 168–171
- Neutral host network access mode, 881
- New 5G NR spectrum, 731
- New gNB UE XnAP ID, 132
- New radio (NR), 74, 655, 747, 790
 - BS transceiver RF characteristics and requirements, 665–691
 - direct radio frequency sampling transceivers, 704–716
 - interface, 14–15
 - large antenna array design and implementation, 737–744
 - mmWave transceiver and antenna design considerations, 734–737
 - multi-antenna transmission schemes, 586–590
 - polar coding, 523–528
 - radio parameters and spectrum, 656–664
 - RRM specifications, 699–704
 - sub-6 GHz transceiver and antenna design considerations, 727–733
 - systems, 846
 - transmission interval, 387
 - UE, 454
 - transceiver RF characteristics and requirements, 691–699
 - V2X network slicing, 806
- New radio absolute radio frequency channel number (NR-ARFCN), 382
- New radio access
 - carrier aggregation, 280–283
 - discontinuous reception and power-saving schemes, 255–258
- layer 2
 - functions, 195–235
 - services, 201–235
- layer 3
 - functions, 195–201, 236–255
 - services, 236–255
- mobility management, handover, and user equipment measurements, 258–274
- multi-radio dual connectivity, 277–280
- physical layer aspects
 - channel models and propagation characteristics, 287–313
 - downlink physical layer functions and procedures, 412–590
 - duplex schemes, 369–379
 - frame structure and numerology, 383–391
 - multiple-access schemes, 350–369
 - operating frequency bands, 379–383
 - time-frequency resources, 391–407
 - uplink physical layer functions and procedures, 591–651
 - waveforms, 314–350
- random-access procedure, 276
- user equipment and network identifiers, 274–276
- New radio low density parity check coding (NR LDPC coding), 532–534
- New radio-unlicensed study (NR-U study), 855–856, 881–890
- Next-generation (NG)
 - control-plane/user-plane functions and procedures, 122–123
 - networks, 29–30
 - NG-interface management functions, 115
 - V2X communication, 798–799
- Next-generation application protocol (NGAP), 122–123
- Next-generation control-plane interface (NG-C), 122–123

- Next-generation fronthaul interface (NGFI), 30, 60–62
 - deployment scenarios, 85–86
 - NGFI-compliant transport network, 85
 - Next-generation radio access network (NG-RAN), 42, 111, 199–200
 - architecture, 112–114
 - gNB functions, 119
 - termination, 113–114
 - Next-generation user-plane interface (NG-U interface), 123
 - NFV infrastructure (NFVI), 17–18, 20–21
 - NFV orchestrator (NFVO), 18–19
 - NFV to VIM interface (Nf–Vi), 17
 - NFVI points-of-presence (NFVI-PoPs), 18–19
 - NH chaining count (NCC), 187
 - NIA algorithms, 128-bit, 230–231
 - Nominal channel bandwidth (NCB), 856
 - Non-3GPP interworking function (N3IWF), 145–146
 - Non-3GPP wireless access technologies, 748
 - Non-co-located LWA scenario, 891–892
 - Non-IP PDU session support, 141
 - Non-line-of-sight (NLoS), 91, 791
 - path loss modeling, 301–302
 - propagation model, 44–45
 - Non-RAN-assisted techniques, 55–58
 - Non-access stratum (NAS), 60–62, 195–196
 - Non-centralized RAN architecture, 28
 - Non-codebook-based precoding, 639–640
 - Non-guaranteed bit rate (Non-GBR), 838
 - Non-orthogonal multiple-access schemes (NOMA schemes), 350, 353–369
 - Non-safety-related services, 796–797
 - Non-self-blocking region, 297
 - Non-slot-based scheduling, 545–547
 - Non-standalone mode (NSA mode), 26
 - Non-zero power-CSI-RS (NZP-CSI-RS), 430–431
 - North-bound interface, 28
 - NR cell global identifier (NCGI), 130, 247
 - NR cell identity (NCI), 130, 275
 - nrofDownlinkSlots* parameter, 389
 - nrofDownlinkSymbols* parameter, 390
 - nrofUplinkSlots* parameter, 390
 - nrofUplinkSymbols* parameter, 390
 - Numerology, 383–391
 - Nyquist zones, 708–711
- O**
- Offset QAM (OQAM), 338–339
 - Old gNB UE XnAP ID, 132
 - On-chip passive devices, 716–717
 - On-duration, 171
 - Open access mode, 52–53
 - Open Network Operating System, 27–28
 - Open Networking Foundation (ONF), 26–28
 - Open system interconnection (OSI), 133
 - Open vSwitch, 13–14
 - Open-loop power control, 644–645
 - OpenDaylight, 27–28
 - OpenFlow, 29–31, 35
 - controller, 31–32
 - flow table entries, 32
 - logical switch, 32–33
 - protocol, 26–28
 - switch, 32
 - OpenStack software, 17, 21
 - Operating band, 382
 - Operating band unwanted emissions (OBUEs), 677, 683
 - Operating frequency bands, 379–383
 - channel and transmission
 - bandwidth configuration, 381
 - maximum transmission bandwidth configuration, 381
 - Operation and maintenance (OAM), 85–86
 - Operations support system (OSS), 15–16, 106
 - Operator-controlled side-link operation (D2D operation), 51
 - OPEX, 21
 - Optical fiber, 28, 56–57, 76–78
 - Optical transport network (OTN), 28–29, 60–63
 - Optimal selection criterion, 568–569
 - Optimistic mode (O mode), 227
 - Orthogonal frequency division multiple access (OFDMA), 350–352
 - Orthogonal frequency division multiplexing (OFDM), 64, 249–251, 285, 315–316, 383–384, 412, 814
 - basics and transmission characteristics, 315–330
 - carrier frequency offset, 326–328
 - cyclic prefix, 316–320
 - EVM, 325–326
 - PAPR, 321–325
 - phase noise, 328–330
 - pre-and postprocessing signal-to-noise ratio, 321
 - DFT-S-OFDM, 330–335
 - OFDM-based LTE air-interface, 16
 - OFDM-based technologies, 656
 - signal generation and reception, 319
 - waveforms, 411, 655, 859
 - Orthogonality, 419–420
 - Oscillators, 328
 - OTA sensitivity direction declaration (OSDD), 671–672

Out-of-band (OOB), 659
 blocking, 689–690
 emissions, 314, 665, 681, 697
 Over-the-air (OTA), 672
 tests, 741–742
 Oxygen absorption, 298–301

P

Packaging processes, 718
 Packet data convergence protocol (PDCP), 68, 195–197, 808–809
 ciphering and integrity protection functions, 229–233
 header compression function, 226–229
 PDU formats, 232
 services and functions, 222–226
 sublayer, 222–233
 Packet data network (PDN), 34, 803–804
 Packet data unit sessions, 124–129
 Packet delay budget (PDB), 146–147, 183, 808–809
 Packet delay variation, 66–67
 Packet error rate (PER), 183
 Packet filter set, 178
 Packet flow description (PFD), 36
 Packet gateway (PGW), 28–29
 Packet optical transport, 89
 Packet-forwarding control protocol (PFCP), 35
 Paging, 268–270
 attempt
 count, 269
 information, 269
 function, 114
 and mobility, 781–783
 Paging channel (PCH), 138, 202
 Paging control channel (PCCH), 137
 Paging frame (PF), 249–251, 781–782
 Paging occasions (POs), 249–251, 781–782
 Paging transmission window (PTW), 781–782
 Paging-RNTI (P-RNTI), 764–765
 Paired spectrum, 372
 Passive optical network (PON), 60–63
 Passive scanning, 864
 Path loss
 with and without shadowing for scenarios, 303
 models, 287–292
 Payload header compression, 222–223
 Peak data rate, 38
 Peak-to-average power ratio (PAPR), 321–325, 772
 Pedestrian UE (P-UE), 837–838
 Peer-to-peer communication, 831–832
 Percent bandwidth, 730
 Performance metrics for 5G, 38–48
 Periodic registration update timer, 249
 Periodic SRS, 604
 Permanent equipment identifier (PEI), 148–149
 Phase error, 328–329, 740–741
 Phase noise, 328–330
 Phase synchronization, 66–67, 89–90
 Phase tracking reference signals (PT-RS), 415–416, 423–425
 in uplink physical layer, 597–600
 Phase-locked loop (PLL), 96–97, 719
 Physical broadcast channel (PBCH), 383–384, 412, 432–439
 Physical cell identity (PCI), 50–51, 278–279, 903–904
 Physical channels, 776–777
 Physical control format indicator channel (PCFICH), 757–758
 Physical downlink control channel (PDCCH), 206, 255–256, 415, 439–477, 757–758, 822–823
 common and UE-specific search spaces, 465–475
 DCI formats, 457–465
 dynamic and semi-persistent scheduling, 475–477
 monitoring occasion, 241
 REG-to-CCE mapping options and REG composition, 447
 structure and physical layer processing of, 441–453
 UE group-common signaling, 453–457
 Physical downlink shared channel (PDSCH), 206, 416, 487–496
 bit-level interleaving for 256QAM modulation, 491
 CBG-based retransmissions, 492
 code word to layer mapping for spatial multiplexing, 494
 mapping to VRBs and from VRBs to PRBs, 495
 physical layer processing of, 488
 rate-matching and code block concatenation processes, 490
 usage of NR LDPC base graphs, 488
 Physical layer, 137–138, 285
 aspects, 895–901
 IoT
 frame structure, 757
 NPBCH, 761–762
 NPDCCH, 763–767
 NPDSCH, 767–769
 NPRACH, 769–772
 NPSS, 757–758
 NPUSCH, 772–775
 NRS, 760
 NSSS, 758–760
 V2X communications, 811–831
 C-V2X frame structure and resource allocation schemes, 815
 calculation of average RSSI of candidate resource, 818
 LTE V2X modes, 813, 818
 mode 4 UE autonomous sensing and resource selection, 819
 scheduling transmission resources for direct communication, 812

- sensing and resource reservation for collision avoidance, 820
- sidelink physical channels, 823–829
- sidelink physical resources and resource pool, 821–823
- sidelink physical signals, 829–831
- Physical layer convergence protocol (PLCP), 864
- Physical medium dependent sublayer (PMD sublayer), 864
- Physical random-access channel (PRACH), 239–240, 617–631
 - four-step random-access procedure, 627–628
- NR PRACH preamble
 - structures, 621
- preamble
 - formats, 617
 - transmission, 648–649
- random-access procedure, 629
- structure of NR PRACH
 - opportunities, 619
- two-step random-access procedure, 628–631
- Physical resource block (PRB), 391–393, 752–753
 - bundling, 403
 - minimum and maximum number of resource blocks/ transmission bandwidths, 393
- Physical sidelink broadcast channel (PSBCH), 817, 828–829
- Physical sidelink control channel (PSCCH), 825–827
- Physical sidelink discovery channel (PSDCH), 815–816, 828
- Physical sidelink shared channel (PSSCH), 823–825
- Physical uplink control channel (PUCCH), 207, 461, 605–617
 - DM-RSs for, 596–597
 - format 0 structure and physical processing, 608–609
 - format 1 structure and physical processing, 609–611
 - format 2 structure and physical processing, 611–614
 - formats 3 and 4 structure and physical processing, 614–617
 - short-PUCCH time-frequency structure, 615
 - spatial relation activation/deactivation, 207
- Physical uplink shared channel (PUSCH), 213, 420, 631–638, 823, 868–869
 - DM-RSs for, 593–596
 - $\pi/2$ -BPSK, 535
- Picocells, 3–4, 46–47, 91
- Pilot-based channel estimation, 414–415
- Ping-pong effect, 59
- Platooning, 793
- PLCP protocol data unit (PPDU), 864
- Point coordination function (PCF), 859–862
- Point-to-multipoint mmWave wireless backhaul (PMP mmWave wireless backhaul), 76–78
- Point-to-point
 - microwave backhaul link, 94–96
 - topologies, 83–84
- Poisson summation formula, 709
- Polar code/coding, 441
 - generator matrix, 528
 - principles, 516–523
- Polar decoder, 521
- Polar encoding, 517
- Polar reliability sequence, 525–526
- Polarization diversity techniques, 291–292
- Policy control, 59–60
- Policy control function (PCF), 144, 178
- Portability/interoperability, 14–15
- Postprocessing signal-to-noise ratio, 321
- Power
 - combination techniques, 725
 - consumption considerations, 723–726
 - control, 678
 - schemes, 411, 586, 644–645
 - of uplink NOMA, 366
 - in uplink physical layer, 643–651
 - delay profile, 304
 - network aspects of power management, 164–171
 - power-domain non-orthogonal multiple access, 363–366
 - power-saving schemes, 255–258
- Power amplifier (PA), 305, 679–680, 683, 713–714, 784
- Power headroom (PH), 207–208
- Power headroom report (PHR), 207–208
- Power spectral density (PSD), 329, 845
- Power-added efficiency (PAE), 723–725
- Power-save mode (PSM), 780–781
- Pre-processing signal-to-noise ratio, 321
- Preamble, 858–859
- Precision time protocol (PTP), 66
- Precoding, 346–347
 - matrix, 502–503, 635, 639–640
 - precoded OFDMA, 352
 - scheme, 568–569
- Precoding matrix indicator (PMI), 411–412, 551
- Precoding resource block group (PRG), 403
- Preemption, 453–454
- Primary and secondary
 - synchronization signals (PSS/SSS), 383–384, 897
- Primary cell (PCell), 207–208, 853–854
- Primary logical channel, 225
- Primary second cell (PSCell), 236

Primary sidelink synchronization signal (PSSS), 830–831

Primary synchronization signal (PSS), 415, 479

time-frequency structure, 480

Principal component analysis (PCA), 580–581

Priority, 59–60

Priority access license (PAL), 851–852

Proactive caching, 79

Probability distribution function (PDF), 289–290

Propagation

- characteristics, 287–313
- effects of wireless channel, 304

Proportional fairness (PF), 365

ProSe per-packet priority (PPPP), 808–810

Protocol, 133

- network architecture and protocol aspects, 750–756, 802–807
- stacks, 132–133
- structure, 755–756

Protocol data units (PDUs), 10, 68–72, 195–196, 808–809, 858–859

sessions, 115, 125–127, 141, 146–149, 152, 167

Pseudo-random sequence, 594–595, 771–772

PSSCH reference signal received power (PSSCH-RSRP), 817

Public key infrastructure (PKI), 839–841

Public land mobile network (PLMN), 41, 200, 803–804

- access mode, 881

Pulse amplitude modulation (PAM), 337–338

Q

QoS class identifier (QCI), 838

QoS flow identifier (QFI), 126–127, 197

Quadrature amplitude modulation (QAM), 94, 315–316

16QAM, 535, 814

64QAM, 535

256QAM, 535

Quadrature I/Q DAC, 721–722

Quadrature phase shift keying (QPSK), 94, 535, 760, 814

Quality of experience (QoE), 50–53

Quality of service (QoS), 3, 18–19, 59–60, 197, 749–750, 796, 809–810, 853–854, 862–864, 910

flow, 133–135, 175, 177, 180

framework, 172–184

- in NR, 175

parameters in LTE, 174

profile, 175

rule, 177–178

- precedence value, 178

Quasi-co-location (QCL), 429–430, 450, 502

Quasi-cyclic LDPC codes (QC LDPC codes), 530

R

Radiated BS transmitter/receiver characteristics, 671–691

Radiated interface boundary (RIB), 665, 668

Radiated power, 743

Radiated UE transmitter/receiver characteristics, 694–699

Radiating near-field (Fresnel) region, 667

Radio

- access
- NFV, 19–20
- protocols, 807–811
- bearers, 124–129
- communication system, 369
- distribution network, 665
- radio-related parameters, 658–659
- resources in UDN, 55
- waves, 296–297

Radio access network (RAN), 7, 86–88

- architecture
- centralized RAN architecture, 28–29
- co-sited RAN deployment scenarios, 29
- non-centralized RAN architecture, 28
- scenarios, 26
- shared RAN deployment scenarios, 29
- radio access network-level, 158–161
- RAN-assisted techniques, 55–58
- slicing, 36

Radio access network area ID (RAI), 270

Radio access network-based notification area (RNA), 200

Radio equipment (RE), 75

Radio equipment control (REC), 75

Radio equipment group (REG), 441

Radio frequency (RF), 655, 783

- DAC, 712
- PA, 734
- spectrum, 845

Radio link control (RLC), 68–72, 195–198, 808–809

- high-level architecture of RLC sublayer, 215

PDUs, 198–199, 219

RLC-AM and RLC-UM entity models, 218

RLC-AM operation, 221

- sublayer, 133–135, 138–139, 215–222

Radio link failure (RLF), 199–200, 509–510, 782–783

Radio network identifiers, 129–132

Radio network temporary identifiers (RNTIs), 130, 202, 764–765, 827

Radio protocol architecture, 891–892

Radio resource control (RRC), 11, 26–27, 195–196, 199–200, 751, 809–810

- characteristics, 244

- connection establishment/
reconfiguration + HARQ
retransmissions, 44
- functions in standalone and non-
standalone NR operation,
237
- PDU, 154–155
- RRC_CONNECTED*, 200,
245–246, 252
- RRC_IDLE*, 200, 245, 250
- RRC_INACTIVE*, 200, 245,
248–250
- signaling, 476–477
- sublayer, 236–238
- Radio resource management
(RRM), 36, 262–263
- centralized PDCP with
centralized RRM in
separate platforms, 38
- centralized PDCP-U with local,
37
- functions, 119
- specifications, 699–704
- Radio-over-Ethernet (RoE), 63, 81
encapsulation, 82
- Random access channel(s)
(RACH), 138, 202,
511–512, 765
- Random access-RNTI (RA-RNTI),
764–765
- Random-access
preamble sequence, 625
- procedure, 43–44, 276,
395–396, 769–770,
777–780
- Random-access preamble ID
(RAPID), 205, 208–209
- Random-access response (RAR),
205, 763–764
- Rank indication (RI), 498, 502,
551
- Rate matching, 490–491
- Reactive near-field region,
666–667
- Real-time
cloud infrastructure, 30
- control data message type,
78–80
- multi-user gaming, 22
- Received signal power, 287–288
- Received signal strength indicator
(RSSI), 507
- Receiver
intermodulation, 690–691
- sensitivity, 743
- spurious emissions power, 691
- Reception resource pools, 822
- Reciprocity-based schemes, 571
- Recommended bit rate, 207
- Redistribution layer (RDL), 718
- Redundancy version (RV), 459
- Reed–Muller codes, 519,
611–612
- Reference architecture
for MBMS for LTE-Uu-based
V2X communication via
MB2, 803
- V2X communications,
802–807
- Reference points, 142–146
- Reference points interfacing with
external entities (Mx), 103,
107–108
- Reference points related to ME
platform functionality
(Mp), 103, 106
- Reference signal received power
(RSRP (dBm)), 905
- Reference signal received quality
(RSRQ (dB)), 905
- Reference signals (RSs), 411–432
- CSI-RS, 425–431
- DM-RS, 417–423
- downlink RSs and
corresponding overhead,
417
- PT-RS, 423–425
- TRS, 431–432
- in uplink physical layer
DM-RSs, 592–597
- phase-tracking reference
signals, 597–600
- SRS, 601–605
- Reference-point representation of
architecture, 146
- Reflective mapping, 176
- Reflective QoS, 184
- flow to DRB mapping, 235
- Reflective QoS attribute (RQA),
175–176, 182
- Reflective QoS indication (RQI),
235
- Registration management (RM),
243
- Registration with anchor gNB +
HARQ retransmissions, 44
- Rel-13 LAA functionality, 868
- Rel-15
deployment, 728
- NR, 510
- Rel-16 NOMA, 358–359
- Reliability, 45, 58–59
- communication service
availability and, 60
- Reliable mode (R mode), 227
- Remaining minimum SI (RMSI),
120–121, 238–239,
432–434
- Remote
control, 794
- driving, 794–795
- Remote radio heads (RRHs), 4–5,
15, 57, 67–68
- Remote radio unit (RRU), 4–5, 57
- Representational state transfer
(REST), 26–27
- application programming
interface, 26–27
- Request to send frame (RTS
frame), 864–865
- Resource
allocation, 396–403, 586
- in frequency domain,
400–403
- for grant-free/semi-persistent
scheduling, 403–407
- in time domain, 397–400
- type 0, 400–401
- isolation, 42–43
- layer, 38–39
- Resource block group (RBG),
400–402
- Resource blocks (RBs), 752–753,
813
- Resource element (RE), 421, 441
- Resource indication value (RIV),
402
- Resource spread multiple access
(RSMA), 355
- Resource unit (RU), 763–764

- Retransmissions, 544
 - retransmission-timer, 171
 - Rician fading, 289–290
 - Ring network topologies, 83–84
 - Road-side unit (RSU), 60–62, 790–791
 - implementation options, 807
 - Roaming/non-roaming network
 - architecture for LTE-based V2X communication, 803
 - Robust Header Compression (ROHC), 197, 808–809
 - compression/decompression of RTP/UDP/IP headers, 226
 - compressor, 227
 - state machines, 228
 - Root mean square delay spread (RMS delay spread), 290
 - Round-trip latency, 74
 - RSSI measurement time
 - configuration (RMTC), 905
 - Rule update process, 30–31
 - Rural macro-cell (RMa), 287
 - Rural-eMBB test environments, 39, 44–45, 48–49, 307–309
- S**
- Safety-related services, 796–797
 - Sampling of wideband signals, 708–711
 - Satellite
 - backhaul, 97
 - networks, 71
 - SAW filters, 735–736
 - Scheduling assignment period, 822–823
 - Scheduling request (SR), 203, 606
 - Scrambling-based non-orthogonal multiple-access schemes, 366–369
 - Seamless mobility, 36–37
 - Second order (SO), 227
 - Secondary cell (SCell), 202, 853–854
 - activation/deactivation, 206, 282
 - Secondary cell group (SCG), 127–128, 202
 - bearer, 156
 - counter, 187
 - in multi-RAT dual connectivity scheme, 153–154
 - split bearer, 156
 - Secondary gNB (SgNB), 128, 153–154
 - UE XnAP ID, 132
 - Secondary node (SN), 154, 277
 - Secondary synchronization signal (SSS), 415, 479–481
 - Secondary synchronization signal
 - RS received quality (SS-RSRQ), 507
 - Security, 16, 62
 - edge protection proxy, 146
 - framework, 185–191
 - Security anchor function (SEAF), 143, 188–189, 840
 - Security context management (SCM), 143
 - Security context management function (SCMF), 188
 - Security policy control function (SPCF), 188
 - Segmentation offset (SO), 217–219
 - Selection window, 819
 - Selective content caching, 57
 - Self-blocking region, 297–298
 - Self-configuration of SON, 50–51
 - Self-driving cars, 101
 - Self-healing of SON, 52
 - Self-interference, 374–376
 - cancellation performance, 378–379
 - Self-optimization of SON, 51–52
 - Self-organizing networks (SON), 50–52
 - framework, 50
 - Self-scheduling, 281
 - Semiconductor technologies, 738–739
 - for mmWave operation, 716–719
 - Semi-persistent (SP)
 - CSI-RS/CSI-IM resource set activation/deactivation, 206
 - SP-SRS activation/deactivation, 207
 - SRS, 604
 - zero power CSI-RS resource set activation/deactivation, 207
 - Semi-persistent scheduling (SPS), 211, 405, 465, 475–477, 809–810, 820
 - SL-SPS-V-RNTI, 826
 - Semi-static/dynamic codebook
 - HARQ-ACK multiplexing, 548–550
 - Sensor network, 20
 - Sequence number (SN), 227–229, 232–233
 - Serializer/de-serializer (SERDES), 707–708
 - Server/cloud-based big data analytics, 750
 - Service, 133
 - area restriction, 24, 166–167
 - continuity and reliability, 58–59
 - service-centric design, 141
 - 5G network architecture, 10
 - service-guaranteed network slicing, 80–81
 - Service access points (SAPs), 30, 133–135, 831–832
 - Service capability exposure function (SCEF), 751–752
 - Service channels (SCHs), 800
 - Service data adaptation protocol (SDAP), 126–127, 195–197
 - high-level SDAP sublayer functional architecture, 234
 - PDU formats, 235
 - sublayer, 133–135, 233–235
 - Service data flow (SDF), 117, 129–130, 173
 - aggregate level, 172–173
 - bearer, 172
 - level, 172–173
 - template precedence value, 178
 - Service data units (SDUs), 40, 68–72, 195–196
 - Service function chaining (SFC), 37–38
 - Service instance layer, 38–39
 - Service requirements for 5G, 54–62

-
- Serving gateway (SGW), 28–29
 - Session and service continuity mode (SSC mode), 108
 - Session management function (SMF), 112, 117, 178, 806
 - SFN and frame timing difference (SFTD), 701–702, 705
 - Shannon's theorem, 556
 - Shared RAN deployment scenarios, 29
 - Shared spectrum, 847–853
 - Short-PUCCH, 608
 - Short-range communication technologies, 848
 - Sidelink
 - communication, 807, 822
 - control period, 822–823
 - design, 795
 - direct communication resource pool, 822–823
 - discovery, 810–811
 - operating bands, 796
 - physical channels
 - physical SL-BCH, 828–829
 - physical SL-DCH, 828
 - PSCCH, 825–827
 - PSSCH, 823–825
 - physical resources and resource pool, 821–823
 - physical signals
 - DM-RSs, 829–830
 - synchronization signals, 830–831
 - and radio access protocols, 807–811
 - timing alignment, 821
 - transmission modes, 829–830
 - Sidelink broadcast channel (SL-BCH), 809–810
 - Sidelink broadcast control channel (SBCCH), 807, 832
 - Sidelink control information (SCI), 808
 - Sidelink discovery reference signal received power (SD-RSRP), 817
 - Sidelink ID (SID), 830–831
 - Sidelink radio network temporary identifier (SL-RNTI), 826
 - Sidelink reference signal received power (S-RSRP), 817
 - Sidelink reference signal strength indicator (S-RSSI), 817
 - Sidelink shared channel (SL-SCH), 823
 - Sidelink synchronization signals (SLSS), 830–831
 - Sidelink traffic channel (STCH), 808–809, 832
 - Signal-to-interference-plus-noise ratio (SINR), 44–45, 846
 - Signal-to-noise ratio (SNR), 64, 769
 - degradation, 328–329
 - Signal-to-noise-plus-distortion (SINAD), 704–706
 - Signaling radio bearers (SRBs), 124, 197–198, 751–752
 - Signaling transmission, 767–768
 - Silicon
 - RFIC technology, 83, 719
 - wafer level technology, 718
 - Silicon germanium (SiGe), 717
 - Single-carrier frequency division multiple access (SC-FDMA), 323–325, 353, 757, 813
 - Single-entry PHR MAC CE, 207
 - Single-input–multiple-output channel (SIMO channel), 552–553
 - Single-input–single-output channel (SISO channel), 552–553
 - Single-link channel model, 307–309
 - Single-network slice selection assistance information (S-NSSAI), 41, 130
 - Single-node 4G BBU to separated CU/DU architecture, 30–32
 - Single-tone frequency hopping, 769–770
 - Single-user MIMO techniques (SU-MIMO techniques), 558–564
 - Singular value decomposition theorem (SVD theorem), 555
 - Slice differentiator (SD), 41
 - Slice/service type (SST), 41
 - Slicing-agnostic transport, 85–87
 - Slicing-aware transport mode, 86–87
 - Sliding window width (SWW), 229
 - Slot format indication (SFI), 387–390, 439
 - Slot-based scheduling, 210
 - Small cells, 15, 46–47, 57
 - backhaul options for, 48
 - enhancements, 49–50
 - nodes, 47–48
 - supporting CA bands, 49
 - Smart devices, 78–79
 - Smart grid service, 13–14
 - SMARTER, 66
 - Social networking, 22
 - Software-defined networks (SDN), 1, 13, 18, 26–36
 - for air-interface flexibility, 19–20
 - applications, 26–27
 - architecture
 - APIs, 28
 - aspects, 29–36
 - controller, 27–28
 - framework and main components, 30
 - networking devices, 28
 - Sounding reference signal (SRS), 460, 601–605, 733
 - SRS-RSRP, 509
 - Source layer-2 ID, 838
 - South-bound interface, 28
 - Space-selective fading, 296
 - Spaced-frequency correlation function, 293–294, 296
 - Spaced-time correlation function, 295–296, 327–328
 - Sparse code multiple access (SCMA), 350, 359–363
 - Spatial correlation, 312
 - Spatial multiplexing, 96–97
 - Spatial RX processing, 424
 - Spatial-resolution CSI, 502

- Special cell (SpCell), 202, 396
- Spectrum
- allocation, 800–802
 - regional-specific ITS, 801
 - flexibility, 655
 - harmonization, 74–76
 - and regulations for 5G network, 70–78
 - candidate spectrum for 5G network, 75
 - mapping of RF components and technologies to spectrum bands, 77
- Spectrum access system (SAS), 852–853
- Spectrum emissions mask (SEM), 681–682, 697
- Spherical unit vectors, 310
- Split bearer
- via MCG, 127–128
 - in multi-RAT dual connectivity, 153–154
 - via SCG, 128
- Spreading-based non-orthogonal multiple-access schemes, 366–369
- Spurious emissions, 697
- Spurious free dynamic range (SFDR), 706
- Spurs, 348–350
- SRS resource indication (SRI), 631
- SSB-based RRM measurement
- time configuration (SMTC), 506, 700–702
- Stand-alone deployment (SA deployment), 26
- Standalone mode, 754
- Standard-resolution CSI, 502–503
- State transitions, 241–253
- Static 3D beamforming, 574
- Static context (SC), 228
- Stream control transmission protocol (SCTP), 118
- Study Group 5 (SG 5), 802
- Sub-6 GHz
- large antenna array design and implementation in, 737–744
 - spectrum, 73
 - transceiver and antenna design considerations, 727–733
- Subband filtering, 336–337
- Subcarrier mapping in DFT-S-OFDM, 331–332
- Subcarrier spacings (SCSs), 657–658
- Sub-network
- blueprint, 39–40
 - instance, 38–39
- Subscribed session-AMBR, 182
- Subscriber identity module (SIM), 190–191
- Subscription permanent identifier (SUPI), 148–149, 840
- Successive cancelation (SC), 516
- decoder, 517–518, 521
- Successive cancelation list (SCL), 517
- with CRC decoder, 518
- Successive interference
- cancellation (SIC), 353–354
- Supplementary downlink (SDL), 379, 656
- Supplementary uplink (SUL), 379, 393–394, 459, 656–657
- Survival time, 58–59
- Switch(es), 12, 737
- Switching point synchronization, 372
- Sxa interface, 35
- Sxb interface, 35
- Sxc interface, 35
- Synchronization, 897
- raster, 383, 486
- Synchronization signal block (SSB), 481–487
- beam sweeping and correspondence to transmission, 485
 - SSB-based inter-frequency measurement, 273
 - SSB-based intra-frequency measurement, 273
 - structure and timing of SS/PBCH block transmission, 483
- Synchronization signals (SS), 477–487, 830–831
- PSS, 479
- SS-RSRP, 506
- SS-SINR, 508
- SSS, 479–481
- Synchronous Ethernet (SyncE), 74, 89–90
- Synchronous LBT, 907
- System frame number (SFN), 757
- System information (SI), 197–198, 200, 238–241
- provisioning, 239
 - SI-windows, 240–241
- System information blocks (SIBs), 200, 238–239
- SIB18, 808
- SystemInformationBlockType18*, 833
 - SystemInformationBlockType19*, 833
 - SystemInformationBlockType21*, 833
- System performance requirements for 5G, 53–55
- System-in-package technology, 66
- System-level analysis, 800
- Systematic polar encoding, 517
- ## T
- t-Reassembly* timer, 220–221
- t-StatusProhibit* timer, 221–222
- Tactile Internet, 3, 30–32
- Tail-biting convolutional code (TBCC), 760, 828
- Tanner graphs, 529–530
- Taylor series, 375–376
- Technology-neutral channel
- access, 656–657
- Temp ID, 42
- Temporary C-RNTI, 130
- Terrestrial beacon systems (TBS), 55–58
- Test environment(s), 307–309
- for 5G, 48–50
- Third-generation partnership project (3GPP), 1–3, 16, 18, 56, 81, 656, 747, 790, 845, 871, 895–896, 907
- fifth generation standardization activities, 66–70

- LTE, 59–60, 845
 - NR, 74, 383–384, 393–394, 532, 847
 - frame structure, 385
 - polar encoding, 523
 - Rel-15, 66
 - Rel-16, 66
 - systems, 36–37
 - 3D channel model, 303–304, 309–310
 - Three-dimension (3D)
 - base station antenna model, 305–306
 - beamforming, 574
 - channel model parameters and model generation procedure, 313–314
 - channel models, 285–286, 303–313
 - MIMO channel model and parameters, 307–309
 - multi-site tele-presence, 22
 - 3GPP 5G radio access network (NG-RAN), 10–11
 - Through encapsulate via technology (TEV technology), 718
 - Through silicon via technology (TSV technology), 718
 - Time division duplex scheme (TDD scheme), 40, 89, 314, 369–373, 390, 826
 - Time resource pattern (TRP), 825
 - Time-division multiplexing (TDM), 880–881
 - Time-Sensitive Networking (TSN), 65–66
 - Time/timing
 - advance command, 206
 - domain
 - resource allocation in, 397–400
 - resource assignment field, 400
 - error, 66–67
 - and frequency synchronization, 830–831
 - time-critical applications, 749–750
 - time-frequency resources
 - bandwidth part, 393–396
 - for grant-free/semi-persistent scheduling, 403–407
 - physical resource blocks, 391–393
 - resource allocation, 396–403
 - time-variant impulse response matrix, 309–310
 - time-varying fading, 292–293
 - time–frequency
 - synchronization, 777–778
 - Timer, 228
 - Timestamp (TS), 227–228
 - Timing advance group (TAG), 206
 - Timing advance group identity (TAG ID), 206
 - Total downlink assignment index (tDAI), 550
 - Total radiated power (TRP), 668
 - Tracking area identity (TAI), 111, 130, 270, 275
 - Tracking area update (TAU), 780–781
 - Tracking areas (TAs), 110
 - Tracking reference signals (TRSs), 416, 431–432
 - Traditional cellular
 - communications systems, 845
 - Traffic
 - channels, 137
 - density, 54
 - safety, 13–14
 - Traffic control center (TCC), 60–62
 - Traffic detection function (TDF), 33–35
 - Traffic flow templates (TFTs), 172
 - Transceiver array boundary (TAB), 665
 - Transceiver calibration, 743
 - Transceiver-unit virtualization (TXRU virtualization), 575
 - Transit frequency, 717
 - Transmission configuration indication (TCI), 449
 - Transmission control protocol (TCP), 13, 217
 - Transmission modes (TMs), 897
 - Transmission resource pools, 822
 - Transmission time interval (TTI), 42–43, 201–202, 902–903
 - Transmission/reception points (TRPs), 39
 - Transmit power control (TPC), 459, 848–850
 - Transmit signal of FTN, 344–345
 - Transmit/receive antenna system, 376–377
 - Transmitted precoding matrix indicator (TPMI), 635
 - Transmitter leakage, 374
 - Transmitter transient period, 671–672
 - Transparent mode (TM), 138–139, 197–198
 - Transport block size (TBS), 763–764
 - Transport blocks (TBs), 434–435, 439, 813
 - Transport channels, 137–138, 201–202, 776–777
 - Transport format selection, 201–202
 - Travel time index (TTI), 796–797
 - Two-dimension (2D)
 - antenna array, 311
 - channel models, 285–286, 303–313
 - sampling theorem, 414–415
 - Two-dimensional electron gas (2DEG), 734–735
 - Type A multi-carrier access procedure, 900–901
 - Type B multi-carrier access procedure, 901
 - Type I CSI. *See* Standard-resolution CSI
 - Type I multi-panel CSI, 503–505
 - Type I single-panel CSI, 503–505
 - Type II CSI, 411–412, 642
- U**
- Ultra-dense networks (UDN), 19–20, 46–56
 - Ultra-high-resolution video streaming, 22
 - Ultra-low-cost technologies, 83
 - Ultra-reliable communications, 20

- Ultra-reliable low-latency communication (URLLC), 3, 13–14, 794
 - Unacknowledged mode (UM), 138–139, 197–198, 808–809
 - Unidirectional mode (U mode), 227
 - Unified authentication framework, 51
 - Unified data management (UDM), 144–145
 - Unified data repository (UDR), 144–145
 - Universal filtered multicarrier (UFMC), 340–342
 - Universal subscriber identity module (USIM), 806–807
 - Unlicensed bands, 880–881
 - Unlicensed spectrum, 845, 847–853
 - implementation and deployment considerations, 906–910
 - layer 2/3 aspects, 902–906
 - LTE and new radio solutions for operation in, 865–890
 - network architecture and protocol aspects, 891–895
 - physical layer aspects, 895–901
 - Unmanned aerial vehicle remote control (UAV remote control), 53
 - Unstructured data storage network function (UDSF), 144
 - Unstructured payloads, 141
 - Uplink (UL), 51–52, 197
 - coverage in cellular system, 47
 - grant, 212–213
 - scheduler, 210–211
 - synchronization, 44
 - traffic channel, 396
 - transmissions, 868–869
 - Uplink control information (UCI), 605–606, 772
 - Uplink MIMO schemes, 638–643
 - codebook-based uplink transmission vs. non-codebook-based uplink transmission, 638–643
 - Uplink physical layer, 591
 - control channels, 605–631
 - link adaptation and power control, 643–651
 - physical-layer processing for UL-SCH, 591
 - PUSCH, 631–638
 - reference signals, 592–605
 - uplink MIMO schemes, 638–643
 - Uplink shared channels (UL-SCH), 138, 202, 774–775
 - Urban Macro-mMTC test environment, 49, 307–309
 - Urban Macro-URLLC test environment, 45, 49, 307–309
 - Urban macrocell (UMa), 287
 - Urban microcell (UMi), 287
 - Use cases, 853–856
 - User application, 106
 - User datagram protocol (UDP), 35
 - User equipment (UE), 10, 47–48, 52, 110, 173, 198–200, 274–276, 656–657, 748, 791, 809–810
 - capability, 253–255
 - conducted and radiated UE transmitter/receiver characteristics, 694–699
 - contention resolution identity, 206
 - context
 - management function, 114
 - modification, 120–121
 - release command message, 248–249
 - release request, 120–121
 - setup, 120–121
 - group-common signaling, 453–457
 - identity index value, 249
 - measurements, 258–274
 - mobility command, 120–121
 - mobility state, 268
 - power class, 695
 - processing times with HARQ protocol and timing, 542–548
 - radio frequency requirements, 691–694
 - in RRC_IDLE, 248
 - state transitions, 268
 - states, 241–253
 - temporary identifier, 115
 - UE-specific PDCCH, 441
 - UE-specific search spaces, 465–475
 - user equipment-based mobility, 265–268
 - wakeup time, 43
 - User experienced data rate, 40
 - User service descriptions (USDs), 803–804
 - User-plane (UP), 6
 - CIoT EPS optimization, 750–751
 - CU-UP entity, 26–27
 - entity, 26
 - function separation, 51–52
 - handover procedures, 263–265
 - integrity protection, 224–225
 - latency, 42–43
 - protocols, 6, 113–114, 129–130, 808–809
 - User-plane functions (UPFs), 2, 112, 117, 248–249
 - Uu enhancements for advanced V2X use cases, 795
 - Uu-based sidelink resource allocation/configuration, 795
- ## V
- V2X application server, 790–791, 803–805
 - Variable gain amplifier (VGA), 96–97
 - Variable nodes (VND), 529–530
 - Vehicle-to-Everything communications (V2X communications), 789
 - implementation and deployment considerations, 841–842
 - layer 2/3 aspects, 831–841
 - network architecture and protocol aspects, 802–811
 - physical layer aspects, 811–831
 - services, 60–62
 - spectrum allocation, 800–802
 - use cases, 790–799

Vehicle-to-infrastructure (V2I), 790–791
 Vehicle-to-network (V2N), 789
 Vehicle-to-pedestrian (V2P), 790–791
 Vehicle-to-vehicle (V2V), 790–791
 Very small aperture terminals (VSAT), 97–98
 Virtual infrastructure manager (VIM), 17, 20–21, 106
 Virtual machines (VMs), 13–14, 34–36
 Virtual medium sensing mechanism, 858–859
 Virtual network functions (VNFs), 17, 19, 34
 descriptor, 23
 manager, 20
 Virtual RAN architectures, 15
 Virtual reality services (VR services), 24, 53
 Virtual resource blocks, 393
 Virtual switch (vSwitch), 13–14
 Virtual-radio access network, 56–98
 architectural aspects, 57–62
 backhaul transport options, 86–98
 Virtual/augmented reality (VR/AR), 22, 53, 78–79
 Virtualization layer, 20
 Visible light communication (VLC), 81
 VNF to NFVI interface (Vn–Nf), 17
 Voice over IP (VoIP), 57, 216
 Voice services slice, 35
 Volterra series, 375–376

W

Wafer fabrication technologies, 76–78
 Wave-guiding effect, 291
 Waveforms, 314–350
 candidates, 335–350
 OFDM basics and transmission characteristics, 315–330
 Wavelength-division multiplexing (WDM), 7–10, 60–62
 Welch Bound Equality (WBE), 366–367
 Welch bounds, 356–357
 White Rabbit technology, 74
 Wi-Fi, 845, 848
 communication module, 864
 mobility set, 894
 networks, 51
 Wide area base stations, 676–677
 Wideband signal sampling, 708–711
 Window-based least significant bit (*W_LSB*), 229
 Windowing, 345–346
 Wired backhaul physical media, 91
 Wireless
 backhaul, 90–91
 channels
 blockage, 296–298
 characteristics of, 287–303
 delay spread, 292–295
 Doppler spread, 295
 line-of-sight path loss probability, 301–303
 oxygen absorption, 298–301
 path loss models, 287–292
 2D and 3D distances in outdoor/indoor environments
 communication technologies, 556, 747, 848
 infrastructure, 82

self-backhauling, 55
 services, 72–73
 systems, 857
 WLAN, 55–58
 Working Party 5A (WP 5A), 802
 Working Party 5D (WP 5D), 63–64
 World Radiocommunication Conference (WRC), 20, 850–851
 WRC-15, 801–802
 WRC-19, 802

X

Xn application protocol (Xn-AP), 118
 Xn control-plane/user-plane functions and procedures, 117–118
 Xw control-plane interface (*Xw-C*), 893–894
 Xw user-plane interface (*Xw-U* interface), 893
 Xw–AP protocol, 893–894

Z

Zadoff–Chu sequence (ZC sequence), 592, 602, 620, 757–758
 Zenith angle spread of departure (ZSD), 301–302
 Zenith AoA (ZoA), 301–302
 Zero-forcing (ZF)
 equalization, 332
 precoding, 568–569
 Zero-intermediate-frequency (ZIF), 712
 Zero-tail DFT-S-OFDM (ZT DFT-S-OFDM), 346–347
 ZigBee, 747, 848