231501173

Ex1a: Text Generation using N-gram Language model

Learning Objective:
Implement an N-Gram–based predictive text model using bigram and trigram probability distributions. This helps to understand how contextual probability influences next-word prediction.

Steps:

1. Initialize the environment by installing and importing the Natural Language Toolkit (nltk). Download the ***Brown Corpus*** (for text data) and the ***Universal Tagset*** (for simplified Part-of-Speech tags).
2. Extract raw sentences from the Brown Corpus using brown.sents().
3. ***Tokenization:*** Convert all words to lowercase and flatten the nested list into a single list of tokens to verify the total volume of training data.
4. Build an N-Gram Model for Bigram and Trigram.
5. Predict Next Word and display Top-5 Suggestions
6. Test Bigram & Trigram Prediction on certain words.

Program:

```
import nltk
from nltk.corpus import brown, stopwords
from nltk.util import ngrams
from collections import defaultdict, Counter
import string
nltk.download('brown')
sentences = brown.sents()

processed = []
for sent in sentences:

    sent = ['<s>'] + [w.lower() for w in sent if w.isalpha()] + ['</s>']
    processed.append(sent)

bigram_counts = defaultdict(Counter)
trigram_counts = defaultdict(Counter)

forsent in processed:
    forw1, w2 in ngrams(sent, 2):
        bigram_counts[w1][w2] += 1

     forw1, w2, w3 in ngrams(sent, 3):
       trigram_counts[(w1, w2)][w3] += 1
```

```
defpredict_bigram_candidates(context, top_k=5):
    words = context.lower().split()

    iflen(words) != 2:
        return "Bigram input must contain exactly 2 words"
```

```
    last_word = words[1]

    iflast_word not in bigram_counts:
        return "No prediction found"
    return bigram_counts[last_word].most_common(top_k)
defpredict_trigram_candidates(context, top_k=5):
    words = context.lower().split()

    iflen(words) != 3:
        return "Trigram input must contain exactly 3 words"

    key= (words[1], words[2])

    ifkey not in trigram_counts:
        return "No prediction found"

    return trigram_counts[key].most_common(top_k)

choice= input("Enter model (bigram/trigram): ").strip().lower()

ifchoice == "bigram":
    text= input("Enter 2-word context: ")
    results = predict_bigram_candidates(text)

elifchoice == "trigram":
    text= input("Enter 3-word context: ")
    results = predict_trigram_candidates(text)

e lse:
    print("Invalid choice")
    results = []

print("\nSuitable next words with counts:")
ifisinstance(results, str):
    print(results)
e lse:
    forword, count in results:
        print(f"{word} → {count}"
```

Output:

```
[nltk_data] Downloading package brown to /root/nltk_data...
[nltk_data]   Package brown is already up-to-date!
True
```

```
Enter model (bigram/trigram): bigram
Enter 2-word context: the word

Suitable next words with counts:
of → 36
</s> → 25
or → 17
for → 11
that → 9
```

RESULT:

Thus the implementation of predictive text system using n-gram has been executed successfully.

231501173

Ex1b: Hidden Markov Model (HMM) based Predictive Text System

Learning Objective:
To implement a predictive text system using Hidden Markov Model (HMM), enabling students to understand contextual probability, POS transitions, and next-word prediction using the Brown Corpus.

Steps:

1. Initialize the environment by installing and importing the Natural Language Toolkit (nltk). Download the Brown Corpus (for text data) and the Universal Tagset (for simplified Part-of-Speech tags).
2. Extract raw sentences from the Brown Corpus using brown.sents().
3. Tokenization: Convert all words to lowercase and flatten the nested list into a single list of tokens to verify the total volume of training data.
4. Load the tagged version of the corpus (brown.tagged_sents) which provides the "Hidden States" (POS tags) linked to the "Observations" (words).
5. Train the HMM Model. Use the HiddenMarkovModelTrainer to perform Supervised Learning. Calculate the internal parameters of the HMM: Initial State Probabilities, Transition Probabilities, Emission Probabilities
6. Build POS Transition Probabilities
7. Build Emission Probabilities
8. Define Prediction Function
9. Test the Model
10. Verify POS prediction on certain words.

Program:

```
import nltk
from nltk.corpus import brown, stopwords
from nltk.util import ngrams
from collections import defaultdict, Counter
import string
nltk.download('brown')
nltk.download('universal_tagset')
nltk.download('stopwords')

STOPWORDS = set(stopwords.words('english'))
tagged_sentences = brown.tagged_sents(tagset='universal')
transition = defaultdict(Counter)
emission = defaultdict(Counter)
for sent in tagged_sentences:

    prev_tag = '<s>'
    for word, tag in sent:
        word = word.lower()
        if not word.isalpha():
            continue
        if word in STOPWORDS:
            continue
        transition[prev_tag][tag] += 1
        emission[tag][word] += 1
```

```
        prev_tag = tag
defpredict_hmm_candidates(previous_word, top_k=5):
    previous_word = previous_word.lower()
    possible_tags = []
    fortaginemission:
        ifprevious_word in emission[tag]:
            possible_tags.append(tag)
    ifnotpossible_tags:
        return"No prediction found"
    word_scores = Counter()
    fortaginpossible_tags:
        total_trans = sum(transition[tag].values())
        iftotal_trans == 0:
            continue
        fornext_tag, t_count in transition[tag].items():
            t_prob = t_count / total_trans
            total_emis = sum(emission[next_tag].values())
            iftotal_emis == 0:
                continue
            forword, e_count in emission[next_tag].items():
                e_prob = e_count / total_emis
                word_scores[word] += t_prob * e_prob

    ifnotword_scores:
        return"No prediction found"

    returnword_scores.most_common(top_k)
previous_word = input("Enter previous word (HMM): ").strip().lower()
results=predict_hmm_candidates(previous_word)
print("\nHMM Suitable Next Words (Ranked):")
ifisinstance(results, str):
    print(results)
e lse:
    forword,score in results:
        print(f"{word} → score: {score:.6f}")
```

Output:

```
[nltk_data] Downloading package brown to /root/nltk_data...
[nltk_data]   Unzipping corpora/brown.zip.
[nltk_data] Downloading package universal_tagset to /root/nltk_data...
[nltk_data]   Unzipping taggers/universal_tagset.zip.
[nltk_data] Downloading package stopwords to /root/nltk_data...
[nltk_data]   Unzipping corpora/stopwords.zip.
```

```
Enter previous word (HMM): hello

HMM Suitable Next Words (Ranked):
half → score: 0.014665
well → score: 0.009987
oh → score: 0.007302
would → score: 0.005735
one → score: 0.005058
```

RESULT:

Thus the implementation of a HMM model based on text prediction system has been executed successfully