ASP.NET Core Web API Project File

ASP.NET Core Web API Project File

In ASP.NET Core, the project file used to organize and compile a cross-platform .NET Core application is called a project file. It contains a list of dependencies, configurations, and instructions on how to compile the application. The project file is typically named "MyProject.csproj" and is used by the .NET Core command-line interface (CLI) and Visual Studio to build and manage the project.

What is a Project File in ASP.NET Core Web API?

In ASP.NET Core, the project file (usually ending in .csproj) is a text-based file that contains all the metadata of the application's dependencies, configurations, and instructions on how to compile the application. The project file is used by the .NET Core command-line interface (CLI) and Visual Studio to manage the project. The .NET Framework project files the .NET Core project file is simpler, cleaner, and more streamlined.

The project file contains information about the following:

- **Dependencies**: This lists the external libraries and packages that the application depends on.
- **Configurations**: This defines the build settings, such as the target framework, output directory, and build options.
- **Build Instructions**: This specifies the commands and tasks that are executed during the build process, such as compiling source code, copying files, and generating output files.
- **Metadata**: This includes information about the project, such as the project name, version, and author.

The project file uses a custom syntax called MSBuild, which is a flexible and extensible build system that allows developers to define complex build processes and customize the build process to meet their specific requirements. The project file can be edited using any text editor or integrated development environment (IDE) that supports MSBuild syntax, such as Visual Studio or Visual Studio Code.

What is a Project File in ASP.NET Core Web API?

The project file, also known as the .csproj file, is a text-based file that contains all the metadata of the application's dependencies, configurations, and instructions on how to compile the application. The project file is used by the .NET Core command-line interface (CLI) and Visual Studio to manage the project. The .NET Framework project files the .NET Core project file is simpler, cleaner, and more streamlined.

The project file contains information about the following:

- **Dependencies**: This lists the external libraries and packages that the application depends on.
- **Configurations**: This defines the build settings, such as the target framework, output directory, and build options.
- **Build Instructions**: This specifies the commands and tasks that are executed during the build process, such as compiling source code, copying files, and generating output files.
- **Metadata**: This includes information about the project, such as the project name, version, and author.

The project file uses a custom syntax called MSBuild, which is a flexible and extensible build system that allows developers to define complex build processes and customize the build process to meet their specific requirements. The project file can be edited using any text editor or integrated development environment (IDE) that supports MSBuild syntax, such as Visual Studio or Visual Studio Code.

The typical Web API project file includes the following:

- **Target Framework**: This specifies the target framework for the application, such as .NET Core 3.1 or .NET 5.0.
- **Dependencies**: This lists the external libraries and packages that the application depends on, such as ASP.NET Core MVC, Entity Framework Core, and Newtonsoft.Json.
- **Build Configurations**: This defines the build settings, such as the output directory, the build configuration (Debug or Release), and the target platform.
- **Build Instructions**: This specifies the commands and tasks that are executed during the build process, such as compiling source code, copying files, and generating output files.
- **Metadata**: This includes information about the project, such as the project name, version, and author.

The project file uses a custom syntax called MSBuild, which is a flexible and extensible build system that allows developers to define complex build processes and customize the build process to meet their specific requirements. The project file can be edited using any text editor or integrated development environment (IDE) that supports MSBuild syntax, such as Visual Studio or Visual Studio Code.

How to Edit a Project File in ASP.NET Core Web API?

ASP.NET Core Web API project file is a text-based file that contains all the metadata of the application's dependencies, configurations, and instructions on how to compile the application. To edit the project file in ASP.NET Core Web API, you can use any text editor or integrated development environment (IDE) that supports MSBuild syntax, such as Visual Studio or Visual Studio Code. Here is a step-by-step guide on how to edit the project file in ASP.NET Core Web API:

1. Open the project file: To edit the project file, you need to open it in your text editor or IDE. The project file is typically named "MyProject.csproj" and is located in the root directory of the project.
2. Add dependencies: To add a new dependency to the project file, you need to add a new PackageReference element to the project file. For example, to add the Newtonsoft.Json package, you can add the following line:
```
<PackageReference Include="Newtonsoft.Json" Version="13.0.1" />
```
3. Modify build configurations: To modify the build configurations, you can add or modify the PropertyGroup elements in the project file. For example, to set the output directory to "bin/Release", you can add the following line:
```
<OutputPath>bin\Release\</OutputPath>
```
4. Add build instructions: To add a new build instruction, you can add a new Target element to the project file. For example, to add a custom build instruction that copies a file to the output directory, you can add the following line:
```
<Target Name="CopyFile" AfterTargets="Build">
  <Copy SourceFiles="$(MyFolder)\myfile.txt" DestinationFolder="$(OutputPath)" />
</Target>
```
5. Save the project file: After you have made your changes, save the project file.
6. Rebuild the project: After you have edited the project file, you need to rebuild the project for the changes to take effect. You can rebuild the project using the command line interface (CLI) or Visual Studio.

Overall, editing the project file in ASP.NET Core Web API requires a basic understanding of the project file syntax and the build process. By following the steps outlined above, you can edit the project file to add dependencies, modify build configurations, and add build instructions to customize the build process to meet your specific requirements.

Why Does the Project File Track Extensions?

- **Automatic Compilation**: Keeping the project file synchronized with the actual file structure of your application ensures automatic compilation. Files should be included in the project file so the compiler knows about them.
- **Build Inclusion**: Changes to files inside the folder are considered in related commands related to their type.
- **Content Management**: The project file can specify how certain file types should be handled during the build process.
- **Cross-platform compatibility**: Different operating systems (Windows, Linux, macOS) may have different file extensions. The project file helps manage these differences.

When you create a new project in ASP.NET Core, your project file, **MyApp.csproj**, is created in the root directory of your project. This file contains all the metadata and instructions needed to build and manage your project. The project file uses a custom syntax called MSBuild, which is a flexible and extensible build system that allows developers to define complex build processes and customize the build process to meet their specific requirements. The project file can be edited using any text editor or integrated development environment (IDE) that supports MSBuild syntax, such as Visual Studio or Visual Studio Code.

Once you click on the **Edit Project File**, the Project file will open in the Visual Studio editor as shown in the image below.

```
<Project Sdk="Microsoft.NET.Sdk.Web">

  <PropertyGroup>
    <TargetFramework>net6.0</TargetFramework>
    <Nullable>enable</Nullable>
    <ImplicitUsings>enable</ImplicitUsings>
  </PropertyGroup>

  <ItemGroup>
    <PackageReference Include="Swashbuckle.AspNetCore" Version="6.2.3" />
  </ItemGroup>

</Project>
```

Key Components of the Project File in ASP.NET Core

In ASP.NET Core, the project file contains various elements that define the application's behavior. Each section has a specific purpose in managing the project. Here's a breakdown of the key components:

Project Sdk="Microsoft.NET.Sdk.Web"

The SDK attribute in **Project Sdk="Microsoft.NET.Sdk.Web"** tells the project set up in ASP.NET Core applications. The Microsoft.NET.Sdk.Web SDK is the most common one, ideal for building web projects with everything required to build and run ASP.NET Core applications.

- Includes the libraries and tasks for ASP.NET Core applications.
- Provides support for **Web APIs, MVC applications, and Razor Pages**.
- Automatically includes common dependencies like **Kestrel, Middleware, and Routing**.
- If you need a different SDK, you can specify it, such as Microsoft.NET.Sdk (for console apps).

<PropertyGroup> Section

The <PropertyGroup> element stores project-level properties that affect compilation, build settings, and runtime behavior. Related Properties Inside <PropertyGroup> Framework and Runtime Configuration (e.g., Target Framework)

Common elements inside PropertyGroup:

- **Target Framework**: <TargetFramework>net6.0</TargetFramework>
  - Indicates that the project is built against **.NET 6.0**.
  - Determines which APIs and features are available for compilation (provided by .NET).
  - Sometimes multiple values can be specified, such as:
```
<TargetFrameworks>net6.0;net7.0</TargetFrameworks>
```
- **Nullable Reference Types**: <Nullable>enable</Nullable>
  - Enables nullable reference types for better null safety in the codebase.
  - The compiler generates warnings when nullable values may potentially be null.
  - Options: enable, disable, warnings, and safeto.
- **Implicit Namespaces**: <ImplicitUsings>enable</ImplicitUsings>
  - Automatically imports common namespaces (e.g., System.Linq, Microsoft.AspNetCore.Http).
  - Reduces boilerplate code by avoiding manual using statements.
  - Helps keep code **cleaner and more readable**.

<ItemGroup> Section

The <ItemGroup> element is used to define collections of items such as dependencies, references, or even files. It's the primary mechanism for managing NuGet packages and project references.

PackageReference - <PackageReference Include="Newtonsoft.Json" Version="13.0.1" />

- Adds a NuGet package dependency to the project.
- The Include attribute specifies the package name (Newtonsoft.Json).
- The Version attribute specifies the exact version to use.
- Once added, the package will appear in the **Dependencies** → **Packages** in Visual Studio.
- If the package is installed, the project will recognize it and load the necessary DLLs at runtime.

Other uses of ItemGroup:

- Managing project references when linking multiple projects together.
- Including **Content or Resx** files, linkers, freezes in the project structure.

Actions:

- The **Project SDK** tells Visual Studio what kind of project you are building.
- The **PropertyGroup** defines how the project compiles and behaves during build and runtime.
- The **ItemGroup** manages dependencies, project references, and other resources.

Adding Packages in ASP.NET Core

ASP.NET Core follows a **modular approach**, which means that, unlike the .NET Framework, it does not come preloaded with a large number of dependencies. Instead, you add only the most essential components required for an application, keeping it lightweight. This approach aids in OS-wide processing flexibility, leverage for MS-specialized, or administrative problems—and ensures security and efficiency. The primary tool for managing packages is the **Install-Package** command.

What you add a package to your ASP.NET Core project, two things happen simultaneously:

- A dependency gets added to the project file (.csproj) — Packages restore when Visual Studio opens.
- Visual Studio downloads the package and adds it to the cache project file, ensuring that the package is restored automatically when needed.

How to Add a Package Using Nuget Package Manager

Visual Studio provides a graphical tool called **NuGet Package Manager**, which makes it easy to add external libraries.

Steps to add a package:

1. Open Visual Studio.
2. Go to **Tools** → **NuGet Package Manager** → **Manage NuGet Packages for Solution...**
3. In the **Browse** tab, search for the package name (e.g., Newtonsoft.Json).
4. Select the package and click **Install**.
5. Visual Studio automatically updates the project file and restores the package.

Whenever we add a new package to our dependencies, Nuget Package Manager is also added to the equivalent project file. This ensures that the dependency is aware of our project. Whenever we add our packages, these packages are their dependencies, packages will be stored here:

```
C:\Users\yourusername\.nuget\packages
```

Packages Consumed
Newtonsoft.Json
13.0.1
Microsoft.AspNetCore.Mvc.Core
2.1.1
Microsoft.AspNetCore.Mvc.Formatters.Json
2.1.1
Microsoft.AspNetCore.Mvc.Razor.Extensions
2.1.1
Microsoft.AspNetCore.Razor.Language
2.1.1
Microsoft.CodeAnalysis.Razor
2.1.1
Microsoft.Extensions.Caching.Memory
2.1.1
Microsoft.Extensions.Configuration.Abstractions
2.1.1
Microsoft.Extensions.Configuration.Binder
2.1.1
Microsoft.Extensions.DependencyInjection.Abstractions
2.1.1
Microsoft.Extensions.Diagnostics.Abstractions
2.1.1
Microsoft.Extensions.Hosting.Abstractions
2.1.1
Microsoft.Extensions.Logging.Abstractions
2.1.1
Microsoft.Extensions.Logging.Debug
2.1.1
Microsoft.Extensions.Logging.EventSource
2.1.1
Microsoft.Extensions.Logging.Console
2.1.1
Microsoft.Extensions.Logging.EventLog
2.1.1
Microsoft.Extensions.Logging.TraceSource
2.1.1
Microsoft.Extensions.Logging.Abstractions
2.1.1
Microsoft.Extensions.Logging.Configuration
2.1.1
Microsoft.Extensions.Logging.Filter
2.1.1
Microsoft.Extensions.Options.ConfigurationExtensions
2.1.1
Microsoft.Extensions.Options
2.1.1
Microsoft.Extensions.Primitives
2.1.1
System.Diagnostics.DiagnosticSource
4.5.1
System.Text.Encodings.Web
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources.Strings
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources.Strings.resx
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources.Strings.resx.Generated
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources.Strings.resx.Generated.cs
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources.Strings.resx.Generated.cs.cs
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources.Strings.resx.Generated.cs.cs.cs
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources.Strings.resx.Generated.cs.cs.cs.cs
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources.Strings.resx.Generated.cs.cs.cs.cs.cs
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources.Strings.resx.Generated.cs.cs.cs.cs.cs.cs
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources.Strings.resx.Generated.cs.cs.cs.cs.cs.cs.cs
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources.Strings.resx.Generated.cs.cs.cs.cs.cs.cs.cs.cs
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources.Strings.resx.Generated.cs.cs.cs.cs.cs.cs.cs.cs.cs
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources.Strings.resx.Generated.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources.Strings.resx.Generated.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources.Strings.resx.Generated.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources.Strings.resx.Generated.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources.Strings.resx.Generated.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources.Strings.resx.Generated.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources.Strings.resx.Generated.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources.Strings.resx.Generated.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources.Strings.resx.Generated.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources.Strings.resx.Generated.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources.Strings.resx.Generated.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources.Strings.resx.Generated.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources.Strings.resx.Generated.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources.Strings.resx.Generated.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources.Strings.resx.Generated.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources.Strings.resx.Generated.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources.Strings.resx.Generated.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources.Strings.resx.Generated.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources.Strings.resx.Generated.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources.Strings.resx.Generated.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources.Strings.resx.Generated.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources.Strings.resx.Generated.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources.Strings.resx.Generated.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources.Strings.resx.Generated.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources.Strings.resx.Generated.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources.Strings.resx.Generated.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources.Strings.resx.Generated.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources.Strings.resx.Generated.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources.Strings.resx.Generated.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources.Strings.resx.Generated.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources.Strings.resx.Generated.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources.Strings.resx.Generated.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources.Strings.resx.Generated.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources.Strings.resx.Generated.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs.cs
4.5.1
System.Text.Encodings.Web.Sources.Generators.SourceGenerator.Sources.Resources.Strings.resx.Generated.cs