StyleARZ — Team Guide

GitHub	https://github.com/Thingkers/styleARZ
Live site	https://stylearz.com
cPanel	https://stylearz.com:2083/
Stack	React 18, Vite, Express · Node.js 18+

1. Get the code & run locally

Requires Node.js 18+ (`node -v`).

```
git clone https://github.com/Thingkers/styleARZ.git
cd styleARZ
npm install
cp .env.example .env
npm run dev
```

Open **http://127.0.0.1:5173** (API on port 4000; Vite proxies `/api`).

Role	Email	Login
Customer	farhan@stylearz.com	style123
Admin	admin@stylearz.com	style123

Reset local DB: `npm run seed:reset` · Stop: `Ctrl+C`

2. Day-to-day git

```
git pull origin main
npm run dev
# edit files under client/ or server/
git add -A
git commit -m "Why you changed it"
git push origin main
```

3. Project layout

```
styleARZ/
├── client/           React (Vite) storefront
├── server/           Express API + seed data
│   └── public/       Built frontend (after npm run build)
├── app.js            Production entry (cPanel startup)
├── scripts/deploy-ssh.sh
├── deploy/GUIDE.md   Full hosting guide in repo
├── credentials.example.json
└── .env.example
```

4. Hosting access

Item	Value
cPanel	https://stylearz.com:2083/
cPanel user	stylvrey
SSH host	premium115.web-hosting.com
SSH port	21098 (not 22)
SSH user	stylvrey
App directory	/home/stylvrey/stylearz
Startup file	app.js

SSH (once per teammate)

1. Log in to cPanel → **SSH Access** → **Manage SSH Keys**
2. Import/generate a key → **Authorize** the public key
3. Keep the private key locally (e.g. `~/.ssh/stylearz_deploy`)
4. Test:

```
ssh -p 21098 -i ~/.ssh/stylearz_deploy stylvrey@premium115.web-hosting.com
```

Node.js app in cPanel (already set up — verify if needed)

Field	Value
Node version	18.x or 20.x
Mode	Production
Application root	stylearz
Application URL	stylearz.com
Startup file	app.js
Env	NODE_ENV=production · JWT_SECRET

> **CloudLinux:** Do not create a real `node_modules` folder in the app root. Use cPanel **Run NPM Install** only. The panel manages a symlink into a virtual env.

5. Deploy after code changes

```
cp credentials.example.json credentials.json
# fill credentials.json (cPanel, SSH key path, JWT_SECRET)

bash scripts/deploy-ssh.sh
```

Then cPanel → **Setup Node.js App** → **Restart** (and **Run NPM Install** only if `package.json` changed).

6. Checklist

- □ Clone repo + `npm install` + `npm run dev`
- □ Open http://127.0.0.1:5173 and log in with demo accounts
- □ SSH key authorized; test connection on port 21098
- □ Local `credentials.json` filled
- □ After deploy: Restart Node app; check https://stylearz.com

---