

GetChallengesTest Class

ISTEST

Apex Code

```
@isTest
private class GetChallengesTest {
    @isTest
    static void testGetChallenges_NoInput() {
        // Arrange
        List<GetChallenges.ChallengeQueryInput> inputs = new
List<GetChallenges.ChallengeQueryInput>();

        // Act
        List<GetChallenges.ChallengeResultWrapper> results =
GetChallenges.getChallenges(inputs);

        // Assert
        System.assertEquals(1, results.size());
        System.assertEquals('No input provided', results[0].message);
        System.assertEquals(0, results[0].challenges.size());
    }

    @isTest
    static void testGetChallenges_NoResults() {
        // Arrange
        GetChallenges.ChallengeQueryInput input = new
GetChallenges.ChallengeQueryInput();
        input.status = 'NonExistentStatus';
        List<GetChallenges.ChallengeQueryInput> inputs = new
List<GetChallenges.ChallengeQueryInput>{ input };

        // Act
        List<GetChallenges.ChallengeResultWrapper> results =
GetChallenges.getChallenges(inputs);

        // Assert
        System.assertEquals(1, results.size());
        System.assertEquals('No challenges found', results[0].message);
        System.assertEquals(0, results[0].challenges.size());
    }

    @isTest
    static void testGetChallenges_WithResults() {
        // Arrange
        Challenge__c challenge = new Challenge__c(
            Name = 'Test Challenge',
            Status__c = 'Draft',
            Participants__c = 'John Doe'
```

```

    );
    insert challenge;

    GetChallenges.ChallengeQueryInput input = new
GetChallenges.ChallengeQueryInput();
    input.status = 'Draft';
    input.participantName = 'John';
    List<GetChallenges.ChallengeQueryInput> inputs = new
List<GetChallenges.ChallengeQueryInput>{ input };

    // Act
    List<GetChallenges.ChallengeResultWrapper> results =
GetChallenges.getChallenges(inputs);

    // Assert
    System.assertEquals(1, results.size());
    System.assertEquals('Challenges retrieved successfully', results[0].message);
    System.assertEquals(1, results[0].challenges.size());
    System.assertEquals('Test Challenge', results[0].challenges[0].Name);
}

@Test
static void testGetChallenges_FilterOnParticipants() {
    // Arrange
    Challenge__c challenge1 = new Challenge__c(
        Name = 'Challenge 1',
        Status__c = 'Draft',
        Participants__c = 'John Doe, Jane Smith'
    );
    Challenge__c challenge2 = new Challenge__c(
        Name = 'Challenge 2',
        Status__c = 'Draft',
        Participants__c = 'Alice Smith, Bob Brown'
    );
    insert new List<Challenge__c>{ challenge1, challenge2 };

    GetChallenges.ChallengeQueryInput input = new
GetChallenges.ChallengeQueryInput();
    input.participantName = 'john';
    List<GetChallenges.ChallengeQueryInput> inputs = new
List<GetChallenges.ChallengeQueryInput>{ input };

    // Act
    List<GetChallenges.ChallengeResultWrapper> results =
GetChallenges.getChallenges(inputs);

    // Assert
    System.assertEquals(1, results.size());
    System.assertEquals('Challenges retrieved successfully', results[0].message);
    System.assertEquals(1, results[0].challenges.size());
    System.assertEquals('Challenge 1', results[0].challenges[0].Name);
}

```

```
}  
}
```

Methods

testGetChallenges_NoInput()

ISTEST

Signature

```
private static void testGetChallenges_NoInput()
```

Return Type

void

testGetChallenges_NoResults()

ISTEST

Signature

```
private static void testGetChallenges_NoResults()
```

Return Type

void

testGetChallenges_WithResults()

ISTEST

Signature

```
private static void testGetChallenges_WithResults()
```

Return Type

void

testGetChallenges_FilterOnParticipants()

ISTEST

Signature

```
private static void testGetChallenges_FilterOnParticipants()
```

Return Type

void