

SendSlackToChannel Class

Apex Code

```
public with sharing class SendSlackToChannel {
    private static final String SLACK_API_URL =
'https://slack.com/api/chat.postMessage?unfurl_links=true';

    public class Input {
        @InvocableVariable(
            label='Channel ID'
            description='Slack Channel ID (e.g. C01XXXXXXX) or Slack User ID (e.g.
U01XXXXXXX)'
        )
        public String channelId;

        @InvocableVariable(label='Message Text' description='Text of the message to send
to the Slack channel or DM')
        public String messageText;

        @InvocableVariable(
            label='agentName'
            description='The name of the agent (used to fetch the bot token in the custom
metadata type)'
        )
        public String agentName;

        @InvocableVariable(label='User set slack Bot Token' description='Optional bot
token (xoxb-...)' )
        public String userSlackBotToken;
    }

    public class Output {
        @InvocableVariable(label='Output Message' description='Result message from Slack
API')
        public String message;

        public Output(String message) {
            this.message = message;
        }
    }

    @InvocableMethod(
        label='Send Slack Message to Channel or DMs'
        description='Sends a simple message to a Slack channel or DM'
    )
    public static List<Output> postMessage(List<Input> requests) {
        List<Output> outputs = new List<Output>();

        for (Input request : requests) {
```

```

        String messageEscaped = request.messageText.replaceAll("'", "");
        // Prepare the payload
        String payload = '{"channel":"" + request.channelId + "', "text":"' +
messageEscaped + '"}';
        SlackHelper.ReturnToken returnedToken =
SlackHelper.getBotToken(request.agentName, request.userSlackBotToken);

        if (String.isBlank(returnedToken.token)) {
            outputs.add(new Output('No valid Slack bot token provided'));
            return outputs;
        }

        SlackHelper.ReturnSlackCallout slackCallout = SlackHelper.SlackApiCallout(
            SLACK_API_URL,
            'POST',
            returnedToken.token,
            payload
        );
        outputs.add(new Output(slackCallout.message));
    }

    // Return the list of sent messages
    return outputs;
}
}

```

Fields

SLACK_API_URL

Signature

```
private static final SLACK_API_URL
```

Type

String

Methods

postMessage(requests)

INVOCABLEMETHOD

Signature

```
public static List<Output> postMessage(List<Input> requests)
```

Parameters

Name	Type	Description
requests	List<Input>	

Return Type

List<Output>

Classes

Input Class

Fields

channelId

OTHER

SIGNATURE

```
public channelId
```

TYPE

String

messageText

INVOCABLEVARIABLE

SIGNATURE

```
public messageText
```

TYPE

String

agentName

OTHER

SIGNATURE

```
public agentName
```

TYPE

String

userSlackBotToken

OTHER

SIGNATURE

```
public userSlackBotToken
```

TYPE

String

Output Class

Fields

message

INVOCABLEVARIABLE

SIGNATURE

public message

TYPE

String

Constructors

Output(message)

SIGNATURE

public Output(String message)

PARAMETERS

Name	Type	Description
message	String	