

SlackCreateChannel Class

Apex Code

```
public with sharing class SlackCreateChannel {
    private static final String SLACK_API_URL =
'https://slack.com/api/conversations.create';

    @InvocableMethod(label='Create Slack Channel' description='Creates a new Slack
channel')
    public static List<Output> createChannel(List<Input> requests) {
        List<Output> outputs = new List<Output>();

        for (Input request : requests) {
            Output output = new Output();
            String payload = '{"name":"' + request.channelName + '", "is_private":"' +
request.isPrivate + '}'';

            SlackHelper.ReturnToken returned_token =
SlackHelper.getBotToken(request.agentName, request.userSlackBotToken);
            SlackHelper.ReturnSlackCallout slackCallout = SlackHelper.SlackApiCallout(
                SLACK_API_URL,
                'POST',
                returned_token.token,
                payload
            );

            output.message = slackCallout.message;
            outputs.add(output);
        }

        return outputs;
    }

    public class Input {
        @InvocableVariable(label='Channel Name' description='Name of the Slack channel
to create (lowercase, no spaces)')
        public String channelName;

        @InvocableVariable(label='Is Private' description='Whether the channel should be
private')
        public Boolean isPrivate;

        @InvocableVariable(
            label='Agent Name'
            description='The name of the agent (used to fetch the bot token in the custom
metadata type)'
        )
        public String agentName;
    }
}
```

```
    @InvocableVariable(label='User Set Slack Bot Token' description='Optional bot
token (xoxb-...)')
    public String userSlackBotToken;
}

public class Output {
    @InvocableVariable(label='Output Message')
    public String message;
}
}
```

Fields

SLACK_API_URL

Signature

```
private static final SLACK_API_URL
```

Type

String

Methods

createChannel(requests)

INVOCABLEMETHOD

Signature

```
public static List<Output> createChannel(List<Input> requests)
```

Parameters

Name	Type	Description
requests	List<Input>	

Return Type

List<Output>

Classes

Input Class

Fields

channelName

OTHER

SIGNATURE

```
public channelName
```

TYPE

String

isPrivate

INVOCABLEVARIABLE

SIGNATURE

```
public isPrivate
```

TYPE

Boolean

agentName

OTHER

SIGNATURE

```
public agentName
```

TYPE

String

userSlackBotToken

OTHER

SIGNATURE

```
public userSlackBotToken
```

TYPE

String

Output Class

Fields

message

INVOCABLEVARIABLE

SIGNATURE

```
public message
```

TYPE

String