

UserHelper Class

Apex Code

```
public with sharing class UserHelper {  
    public static List<User> queryUsersByName(String name) {  
        String likeName = '%' + name + '%';  
        return [  
            SELECT Id, FirstName, LastName, Name, Email, UserRoleId, UserRole.Name,  
Manager.Name, ManagerId, Department  
            FROM User  
            WHERE Name LIKE :likeName  
        ];  
    }  
  
    public static List<User> queryUsersByRole(String roleIdentifier) {  
        if (String.isBlank(roleIdentifier)) {  
            return new List<User>();  
        }  
        String likeRoleIdentifier = '%' + roleIdentifier + '%';  
  
        return [  
            SELECT Id, FirstName, LastName, Name, Email, UserRoleId, UserRole.Name,  
Manager.Name, ManagerId, Department  
            FROM User  
            WHERE UserRole.Name LIKE :likeRoleIdentifier OR UserRoleId = :roleIdentifier  
        ];  
    }  
  
    public static List<String> extractIdentifiersFromText(String inputText) {  
        if (String.isBlank(inputText)) {  
            return new List<String>();  
        }  
  
        // Extract the substring between '[' and ']'  
        Integer startIndex = inputText.indexOf('[');  
        Integer endIndex = inputText.indexOf(']');  
        if (startIndex == -1 || endIndex == -1 || startIndex >= endIndex) {  
            return new List<String>();  
        }  
  
        String identifiersText = inputText.substring(startIndex + 1, endIndex);  
        // Split by comma and trim whitespace and quote characters  
        List<String> identifiers = new List<String>();  
        for (String identifier : identifiersText.split(',')) {  
            identifiers.add(identifier.trim().replace('"', '').replace('\'', ''));  
        }  
  
        return identifiers;  
    }  
}
```

```

public static List<User> queryUsersByIdentifiers(List<String> identifiers) {
    if (identifiers.isEmpty()) {
        return new List<User>();
    }

    // Build dynamic WHERE clause for partial matches
    List<User> users = new List<User>();
    String baseQuery = 'SELECT Id, FirstName, LastName, Name, Email, UserRoleId,
    UserRole.Name, Manager.Name, ManagerId, Department FROM User WHERE ';
    List<String> conditions = new List<String>();

    for (String identifier : identifiers) {
        String likeIdentifier = '%' + String.escapeSingleQuotes(identifier) + '%';
        conditions.add('(Name LIKE \'' + likeIdentifier + '\'' OR UserRole.Name LIKE
        \'' + likeIdentifier + '\')');
    }

    String finalQuery = baseQuery + String.join(conditions, ' OR ');

    // Execute the dynamic query
    users = Database.query(finalQuery);

    return users;
}

public static Set<Id> getUserIdsByNamesAndIds(List<Id> userIds, List<String>
userNames) {
    // Validate inputs
    if ((userIds == null || userIds.isEmpty()) && (userNames == null ||
userNames.isEmpty())) {
        return new Set<Id>();
    }

    // Query users based on IDs or names using a single query with OR
    List<User> users = [
        SELECT Id, Name
        FROM User
        WHERE Id IN :userIds OR Name IN :userNames
    ];

    // Collect and return user IDs
    Set<Id> queriedUserIds = new Set<Id>();
    for (User user : users) {
        queriedUserIds.add(user.Id);
    }
    return queriedUserIds;
}

public static Map<Id, List<String>> getCustomPermissionsForUsers(List<Id> userIds,
List<String> userNames) {
    // Use the new helper method to get user IDs

```

```

Set<Id> queriedUserIds = getUserIdsByNamesAndIds(userIds, userNames);

if (queriedUserIds.isEmpty()) {
    return new Map<Id, List<String>>();
}

// Step 2: Get all Permission Sets assigned to the users
Map<Id, Set<Id>> userToPermissionSetIds = new Map<Id, Set<Id>>();
for (PermissionSetAssignment psa : [
    SELECT AssigneeId, PermissionSetId
    FROM PermissionSetAssignment
    WHERE AssigneeId IN :queriedUserIds
]) {
    if (!userToPermissionSetIds.containsKey(psa.AssigneeId)) {
        userToPermissionSetIds.put(psa.AssigneeId, new Set<Id>());
    }
    userToPermissionSetIds.get(psa.AssigneeId).add(psa.PermissionSetId);
}

// Step 3: Flatten all Permission Set IDs
Set<Id> allPermissionSetIds = new Set<Id>();
for (Set<Id> permissionSetIds : userToPermissionSetIds.values()) {
    allPermissionSetIds.addAll(permissionSetIds);
}

// Step 4: Get all Custom Permissions accessible via these Permission Sets
Map<Id, List<String>> permissionSetToCustomPermissions = new Map<Id,
List<String>>();
for (CustomPermission cp : [
    SELECT DeveloperName, Id
    FROM CustomPermission
    WHERE
        Id IN (
            SELECT SetupEntityId
            FROM SetupEntityAccess
            WHERE ParentId IN :allPermissionSetIds AND SetupEntityType =
'CustomPermission'
        )
]) {
    if (!permissionSetToCustomPermissions.containsKey(cp.Id)) {
        permissionSetToCustomPermissions.put(cp.Id, new List<String>());
    }
    permissionSetToCustomPermissions.get(cp.Id).add(cp.DeveloperName);
}

// Step 5: Map custom permissions back to users
Map<Id, List<String>> userToCustomPermissions = new Map<Id, List<String>>();
for (Id userId : userToPermissionSetIds.keySet()) {
    List<String> userPermissions = new List<String>();
    for (Id permissionSetId : userToPermissionSetIds.get(userId)) {
        if (permissionSetToCustomPermissions.containsKey(permissionSetId)) {

```

```
userPermissions.addAll(permissionSetToCustomPermissions.get(permissionSetId));
    }
}
userToCustomPermissions.put(userId, userPermissions);
}

    return userToCustomPermissions;
}
}
```

Methods

queryUsersByName(name)

Signature

```
public static List<User> queryUsersByName(String name)
```

Parameters

Name	Type	Description
name	String	

Return Type

List<User>

queryUsersByRole(roleIdentifier)

Signature

```
public static List<User> queryUsersByRole(String roleIdentifier)
```

Parameters

Name	Type	Description
roleIdentifier	String	

Return Type

List<User>

extractIdentifiersFromText(inputText)

Signature

```
public static List<String> extractIdentifiersFromText(String inputText)
```

Parameters

Name	Type	Description
inputText	String	

Return Type

List<String>

queryUsersByIdentifiers(identifiers)

Signature

```
public static List<User> queryUsersByIdentifiers(List<String> identifiers)
```

Parameters

Name	Type	Description
identifiers	List<String>	

Return Type

List<User>

getUserIdsByNamesAndIds(userIds, userNames)

Signature

```
public static Set<Id> getUserIdsByNamesAndIds(List<Id> userIds, List<String> userNames)
```

Parameters

Name	Type	Description
userIds	List<Id>	
userNames	List<String>	

Return Type

Set<Id>

getCustomPermissionsForUsers(userIds, userNames)

Signature

```
public static Map<Id, List<String>> getCustomPermissionsForUsers(List<Id> userIds, List<String> userNames)
```

Parameters

Name	Type	Description
userIds	List<Id>	
userNames	List<String>	

Return Type

Map<Id,List<String>>