

GetMembersOfSlackChannel Class

Apex Code

```
public with sharing class GetMembersOfSlackChannel {
    private static final String SLACK_API_URL =
'https://slack.com/api/conversations.members';

    public class Input {
        @InvocableVariable(required=true description='Slack Channel ID (CXXXXXXX)')
        public String channelId;

        @InvocableVariable(
            label='Agent Name'
            description='The name of the agent (used to fetch the bot token in the custom
metadata type)'
        )
        public String agentName;

        @InvocableVariable(label='User set Slack Bot Token' description='Optional bot
token (xoxb-...)')
        public String userSlackBotToken;
    }

    public class Output {
        @InvocableVariable(description='Result message')
        public String message;

        @InvocableVariable(description='List of Slack User IDs')
        public List<String> slackUserIds;

        public Output(String message, List<String> slackUserIds) {
            this.message = message;
            this.slackUserIds = slackUserIds;
        }
    }

    @InvocableMethod(
        label='Get Members of Slack Channel'
        description='Retrieve Slack user IDs of a Slack Channel given a Channel ID
(CXXXXXXX)'
    )
    public static List<Output> getMembersOfSlackChannel(List<Input> inputList) {
        List<Output> results = new List<Output>();

        if (inputList == null || inputList.isEmpty()) {
            results.add(new Output('No input provided', new List<String>()));
            return results;
        }
    }
}
```

```

// Process only the first element of the input list
Input input = inputList[0];

// Validate the input
if (String.isBlank(input.channelId)) {
    results.add(new Output('Invalid channel ID provided', new List<String>()));
    return results;
}

// Fetch the bot token
SlackHelper.ReturnToken returnedToken = SlackHelper.getBotToken(input.agentName,
input.userSlackBotToken);

if (String.isBlank(returnedToken.token)) {
    results.add(new Output('No valid Slack bot token provided', new List<String>
()));
    return results;
}

// Prepare the API endpoint with the channel ID
String endpoint = SLACK_API_URL + '?channel=' + input.channelId;

// Call the Slack API
SlackHelper.ReturnSlackCallout slackCallout = SlackHelper.SlackApiCallout(
    endpoint,
    'GET',
    returnedToken.token,
    null
);

if (slackCallout.status == 'success') {
    // Parse the response
    Map<String, Object> response = (Map<String, Object>)
JSON.deserializeUntyped(slackCallout.res.getBody());

    if (response.get('ok') == true) {
        // Ensure proper casting of the 'members' field
        Object membersObj = response.get('members');
        if (membersObj instanceof List<Object>) {
            List<Object> membersList = (List<Object>) membersObj;
            List<String> members = new List<String>();
            for (Object member : membersList) {
                members.add((String) member);
            }
            results.add(new Output('Successfully retrieved members', members));
        } else {
            results.add(new Output('Unexpected response format for members', new
List<String>()));
        }
    } else {
        results.add(new Output('Failed to retrieve members: ' +
response.get('error'), new List<String>()));
    }
}

```

```
    }  
    } else {  
        results.add(new Output('Slack API callout failed: ' + slackCallout.message,  
new List<String>()));  
    }  
  
    return results;  
    }  
}
```

Fields

SLACK_API_URL

Signature

```
private static final SLACK_API_URL
```

Type

String

Methods

getMembersOfSlackChannel(inputList)

OTHER

Signature

```
public static List<Output> getMembersOfSlackChannel(List<Input> inputList)
```

Parameters

Name	Type	Description
inputList	List<Input>	

Return Type

List<Output>

Classes

Input Class

Fields

channelId

OTHER

SIGNATURE

```
public channelId
```

TYPE

String

agentName

OTHER

SIGNATURE

```
public agentName
```

TYPE

String

userSlackBotToken

OTHER

SIGNATURE

```
public userSlackBotToken
```

TYPE

String

Output Class**Fields**

message

INVOCABLEVARIABLE

SIGNATURE

```
public message
```

TYPE

String

slackUserIds

INVOCABLEVARIABLE

SIGNATURE

```
public slackUserIds
```

TYPE

List<String>

Constructors

Output(message, slackUserIds)

SIGNATURE

```
public Output(String message, List<String> slackUserIds)
```

PARAMETERS

Name	Type	Description
message	String	
slackUserIds	List<String>	