

GetOpportunities Class

Apex Code

```
public with sharing class GetOpportunities {  
    public class Input {  
        @InvocableVariable(description='Text field specifying Opportunity Name')  
        public String name;  
        @InvocableVariable(description='Text field specifying the Opportunity Owner Name')  
        public String owner;  
        @InvocableVariable(description='Lookup field to User specifying the Opportunity Owner Id')  
        public String ownerId;  
        @InvocableVariable(description='Date field at the date of the opportunity has been closed')  
        public Date closeDate;  
        @InvocableVariable(  
            description='Picklist list specifying the opportunity type\nValues: \nExisting Customer - Upgrade\nExisting Customer - Replacement\nExisting Customer - Downgrade\nNew Customer'  
        )  
        public String type;  
        @InvocableVariable(  
            description='Picklist list specifying the opportunity stage\nValues in the order of progression:\nProspecting\nQualification\nNeeds Analysis\nValue Proposition\nId. Decision Makers\nPerception Analysis\nProposal/Price Quote\nNegotiation/Review\nClosed Won\nClosed Lost'  
        )  
        public String stage;  
        @InvocableVariable(description='Boolean specifying Is Opportunity Closed')  
        public Boolean isClosed;  
        @InvocableVariable(description='Boolean specifying Is Opportunity Won')  
        public Boolean isWon;  
        @InvocableVariable(description='Date input for the start date for searching in a range of Close Date')  
        public Date closeDateStart;  
        @InvocableVariable(description='Date input for the end date for searching in a range of Close Date')  
        public Date closeDateEnd;  
    }  
  
    public class Output {  
        @InvocableVariable(description='List of Opportunity Objects')  
        public List<Opportunity> opportunities;  
        @InvocableVariable(description='Result message')  
        public String message;  
  
        public Output(List<Opportunity> opportunities, String message) {  
            this.opportunities = opportunities;  
        }  
    }  
}
```

```

        this.message = message;
    }
}

@InvocableMethod(
    label='Get Opportunities'
    description='- If the users asks for opportunities with a close date between a range of dates, filled the fields CloseDateStart and CloseDateEnd. CloseDateStart must be inferior to CloseDateEnd\n- if the users asks for opportunities created or modified at a specific date or between a range of dates, explain that you can\'t answer\n- If the user asks for Closed opportunities search with IsClosed equals true\n- If the user asks for Open opportunities search with IsClosed equals false\n- If the user asks for Lost opportunities search with IsWon equals false\n- If the user asks for Won opportunities search with IsWon equals true\n- An opportunity is considered as Advanced if the stage is Value Proposition or on the next stages'
)
public static List<Output> getOpportunities(List<Input> inputList) {
    List<Output> results = new List<Output>();
    if (inputList == null || inputList.isEmpty()) {
        results.add(new Output(new List<Opportunity>(), 'No input provided'));
        return results;
    }

    Input queryInput = inputList[0];
    List<Opportunity> opportunities = OpportunityHelper.queryOpportunities(
        queryInput.name,
        queryInput.owner,
        queryInput.ownerId,
        queryInput.closeDate,
        queryInput.closeDateStart,
        queryInput.closeDateEnd,
        queryInput.type,
        queryInput.stage,
        queryInput.isClosed,
        queryInput.isWon
    );

    if (opportunities.isEmpty()) {
        results.add(new Output(new List<Opportunity>(), 'No opportunities found'));
    } else {
        results.add(new Output(opportunities, 'Opportunities retrieved successfully'));
    }

    return results;
}
}

```

Methods

getOpportunities(inputList)

INVOCABLEMETHOD

Signature

```
public static List<Output> getOpportunities(List<Input> inputList)
```

Parameters

Name	Type	Description
inputList	List<Input>	

Return Type

List<Output>

Classes

Input Class

Fields

name

INVOCABLEVARIABLE

SIGNATURE

```
public name
```

TYPE

String

owner

INVOCABLEVARIABLE

SIGNATURE

```
public owner
```

TYPE

String

ownerId

INVOCABLEVARIABLE

SIGNATURE

```
public ownerId
```

TYPE

String

closeDate

INVOCABLEVARIABLE

SIGNATURE

```
public closeDate
```

TYPE

Date

type

INVOCABLEVARIABLE

SIGNATURE

```
public type
```

TYPE

String

stage

INVOCABLEVARIABLE

SIGNATURE

```
public stage
```

TYPE

String

isClosed

INVOCABLEVARIABLE

SIGNATURE

```
public isClosed
```

TYPE

Boolean

isWon

INVOCABLEVARIABLE

SIGNATURE

```
public isWon
```

TYPE

Boolean

closeDateStart

INVOCABLEVARIABLE

SIGNATURE

```
public closeDateStart
```

TYPE

Date

closeDateEnd

INVOCABLEVARIABLE

SIGNATURE

```
public closeDateEnd
```

TYPE

Date

Output Class

Fields

opportunities

INVOCABLEVARIABLE

SIGNATURE

```
public opportunities
```

TYPE

List<Opportunity>

message

INVOCABLEVARIABLE

SIGNATURE

```
public message
```

TYPE

String

Constructors

Output(opportunities, message)

SIGNATURE

```
public Output(List<Opportunity> opportunities, String message)
```

PARAMETERS

Name	Type	Description
opportunities	List<Opportunity>	
message	String	