

ListSlackPublicChannels Class

Apex Code

```
public with sharing class ListSlackPublicChannels {
    private static final String SLACK_API_URL =
'https://slack.com/api/conversations.list?exclude_archived=true&limit=1000';

    // Input of the invocable method : name of the agent to fetch Slack bot token from
    custom metadata and Slack bot token. One of them is required
    public class Input {
        @InvocableVariable(
            label='agentName'
            description='The name of the agent (used to fetch the bot token in the custom
metadata type)'
        )
        public String agentName;

        @InvocableVariable(label='User set slack Bot Token' description='Optional bot
token (xoxb-...)' )
        public String userSlackBotToken;
    }

    // Output of the invocable method : List of channels and action message
    public class Output {
        @InvocableVariable
        public List<ChannelInfo> channelInfoList;

        @InvocableVariable(label='Result Message')
        public String message;

        public Output() {
            this.message = '';
            this.channelInfoList = new List<ChannelInfo>();
        }

        public Output(String message, List<ChannelInfo> channelInfoList) {
            this.message = message;
            this.channelInfoList = channelInfoList;
        }
    }

    public class ChannelInfo {
        public String id;
        public String name;
    }

    // Slack API response model
    private class SlackResponse {
        public Boolean ok;
    }
}
```

```

    public List<SlackChannel> channels;
}

// Slack Channel model used for deserialization
private class SlackChannel {
    public String id;
    public String name;
}

// This method will be called from the AgentForce custom action to fetch the list
of public channels
@InvocableMethod(label='List public Slack channels' description='Returns the names
and IDs of public Slack channels')
public static List<Output> getSlackChannels(List<Input> configs) {
    List<Output> outputs = new List<Output>();

    // Loop through the list of requests
    for (Input config : configs) {
        Output output = new Output();
        output.channelInfoList = new List<ChannelInfo>();

        // Auth
        SlackHelper.ReturnToken returnedToken =
SlackHelper.getBotToken(config.agentName, config.userSlackBotToken);
        if (String.isBlank(returnedToken.token)) {
            output.message = 'No valid Slack bot token provided';
            outputs.add(output);
            return outputs;
        }

        // Get the public channels
        SlackHelper.ReturnSlackCallout slackCallout = SlackHelper.SlackApiCallout(
            SLACK_API_URL,
            'GET',
            returnedToken.token,
            null
        );
        output.message = slackCallout.message;
        // Handle the response
        if (slackCallout.status == 'success') {
            SlackResponse slackRes = (SlackResponse)
JSON.deserialize(slackCallout.res.getBody(), SlackResponse.class);

            // Check if the response is valid and parse the channels
            if (slackRes.ok && slackRes.channels != null) {
                for (SlackChannel ch : slackRes.channels) {
                    ChannelInfo info = new ChannelInfo();
                    info.id = ch.id;
                    info.name = ch.name;
                    output.channelInfoList.add(info);
                    output.message = 'Fetched ' + output.channelInfoList.size() + '
channels';
                }
            }
        }
    }
    return outputs;
}

```

```
        }
    } else {
        output.message =
            'Failed to fetch channels: ' +
            (slackRes.ok ? 'No channels found' : 'Invalid response' +
            slackCallout.res.getBody());
        outputs.add(output);
        return outputs;
    }
}

// Add the Output to the list of Outputs
outputs.add(Output);
}

// Return the list of Outputs
return outputs;
}
}
```

Fields

SLACK_API_URL

Signature

```
private static final SLACK_API_URL
```

Type

String

Methods

getSlackChannels(configs)

INVOCABLEMETHOD

Signature

```
public static List<Output> getSlackChannels(List<Input> configs)
```

Parameters

Name	Type	Description
configs	List<Input>	

Return Type

List<Output>

Classes

Input Class

Fields

agentName

OTHER

SIGNATURE

```
public agentName
```

TYPE

String

userSlackBotToken

OTHER

SIGNATURE

```
public userSlackBotToken
```

TYPE

String

Output Class

Fields

channelInfoList

INVOCABLEVARIABLE

SIGNATURE

```
public channelInfoList
```

TYPE

List<ChannelInfo>

message

INVOCABLEVARIABLE

SIGNATURE

```
public message
```

TYPE

String

Constructors

Output()

SIGNATURE

```
public Output()
```

Output(message, channelInfoList)

SIGNATURE

```
public Output(String message, List<ChannelInfo> channelInfoList)
```

PARAMETERS

Name	Type	Description
message	String	
channelInfoList	List<ChannelInfo>	

ChannelInfo Class

Fields

id

SIGNATURE

```
public id
```

TYPE

String

name

SIGNATURE

```
public name
```

TYPE

String

SlackResponse Class

Fields

ok

SIGNATURE

```
public ok
```

TYPE

Boolean

channels

SIGNATURE

public channels

TYPE

List<SlackChannel>

SlackChannel Class

Fields

id

SIGNATURE

public id

TYPE

String

name

SIGNATURE

public name

TYPE

String