POLITECNICO
MILANO 1863

Wave Equation FEM Solver

Discretization Choices, Dissipation/Dispersion, and Numerical Results

Qiansong Li Chengxi Rao Chenyu Ye Zhenyu Zhao

March 4, 2026

Outline

1. Problem and Model
2. Numerical Methods
3. Implementation and Experiments
4. Numerical Results
5. Conclusions

Project Goal and PDE

Goal: build and analyze a 2D FEM solver for the scalar wave equation, and discuss time/space discretization choices in terms of **accuracy, dissipation, and dispersion**.

Initial-Boundary Value Problem

$$\begin{cases} u_{tt} - \Delta u = f, & (x,t) \in \Omega \times (0,T), \\ u = g, & (x,t) \in \partial\Omega \times (0,T), \\ u(x,0) = u_0(x), \quad u_t(x,0) = v_0(x), & x \in \Omega. \end{cases}$$

- Benchmark in code: eigenmode manufactured solution on unit square.
- Additional case: driven boundary to study physical energy injection.
- Implementation: deal.II + simplex meshes.

Weak Form and Space Semi-Discretization

For homogeneous Dirichlet BC, with $V = H_0^1(\Omega)$:

$$(u_{tt}, v) + a(u, v) = (f, v), \quad a(u, v) = \int_\Omega \nabla u \cdot \nabla v \, dx.$$

Choose FEM space $V_h = \text{span}\{\phi_i\}_{i=1}^N$, $u_h = \sum_j U_j(t)\phi_j$.

Matrix ODE System

$$M\ddot{\mathbf{U}}(t) + K\mathbf{U}(t) = \mathbf{F}(t),$$

$$M_{ij} = \int_\Omega \phi_i \phi_j \, dx, \qquad K_{ij} = \int_\Omega \nabla\phi_i \cdot \nabla\phi_j \, dx.$$

- This is the common starting point for all tested time integrators.
- Mass treatment (consistent/lumped) changes both cost and dynamics.

Non-homogeneous Dirichlet BC Handling

For $u = g(x,t)$ on $\partial\Omega$, introduce a lifting:

$$u(x,t) = w(x,t) + \ell(x,t), \qquad \ell|_{\partial\Omega} = g, \quad w|_{\partial\Omega} = 0.$$

Then for all $v \in H_0^1(\Omega)$:

$$(w_{tt}, v) + a(w, v) = (f, v) - (\ell_{tt}, v) - a(\ell, v).$$

After FEM discretization, split interior/boundary DoFs:

$$\begin{bmatrix} M_{II} & M_{IB} \\ M_{BI} & M_{BB} \end{bmatrix} \begin{bmatrix} \ddot{\mathbf{U}}_I \\ \ddot{\mathbf{g}}_B \end{bmatrix} + \begin{bmatrix} K_{II} & K_{IB} \\ K_{BI} & K_{BB} \end{bmatrix} \begin{bmatrix} \mathbf{U}_I \\ \mathbf{g}_B \end{bmatrix} = \begin{bmatrix} \mathbf{F}_I \\ \mathbf{F}_B \end{bmatrix}.$$

Hence the interior equation to advance is

$$M_{II}\ddot{\mathbf{U}}_I + K_{II}\mathbf{U}_I = \mathbf{F}_I - M_{IB}\ddot{\mathbf{g}}_B - K_{IB}\mathbf{g}_B.$$

The boundary trace $\mathbf{U}_B(t) = \mathbf{g}_B(t)$ is prescribed data.

Central Difference Method

Discretize acceleration:

$$\ddot{\mathbf{U}}^n \approx \frac{\mathbf{U}^{n+1} - 2\mathbf{U}^n + \mathbf{U}^{n-1}}{\Delta t^2},$$

giving

$$\mathbf{U}^{n+1} = 2\mathbf{U}^n - \mathbf{U}^{n-1} - \Delta t^2 M^{-1} K \mathbf{U}^n.$$

- Explicit update when M^{-1} is cheap (best with lumped mass).
- CFL-type stability condition:

$$\Delta t \leq \frac{2}{\sqrt{\lambda_{\max}(M^{-1}K)}}.$$

- In stable range: low dissipation, but phase error accumulates (numerical dispersion).

Newmark-β Method

Kinematic update:

$$\mathbf{U}^{n+1} = \mathbf{U}^n + \Delta t\, \mathbf{V}^n + \Delta t^2 \left(\tfrac{1}{2} - \beta\right) \mathbf{A}^n + \beta \Delta t^2 \mathbf{A}^{n+1},$$

$$\mathbf{V}^{n+1} = \mathbf{V}^n + \Delta t (1-\gamma) \mathbf{A}^n + \gamma \Delta t\, \mathbf{A}^{n+1}.$$

Using $M\mathbf{A}^{n+1} + K\mathbf{U}^{n+1} = \mathbf{F}^{n+1}$:

$$\left(M + \beta \Delta t^2 K\right) \mathbf{U}^{n+1} = M\mathbf{U}^\star + \beta \Delta t^2 \mathbf{F}^{n+1}.$$

- One sparse linear solve per step (implicit).
- Used in project: $(\beta, \gamma) = (1/4, 1/2)$.
- Central difference can be viewed as a special explicit member of the Newmark family.

Mass Matrix Choices and Four Combinations

Consistent mass

$$M_{ij} = \int_\Omega \phi_i \phi_j \, dx$$

- Galerkin-consistent
- Sparse but non-diagonal
- More expensive in explicit-like updates

Lumped mass

$$M_{ii}^{\text{lump}} = \sum_j M_{ij}$$

- Diagonal approximation
- Very cheap inverse
- Practical choice for explicit wave runs

Compared combinations: central difference + lumped/consistent, Newmark + lumped/consistent.

Implementation Architecture

- `src/Wave2D.cpp`: mesh reading, assembly, BC treatment, time stepping, diagnostics, VTU/CSV output.
- `src/main.cpp`: CLI interface for mesh, Δt, T, time scheme, mass type, FE degree, etc.
- `scripts/run_experiments.sh`: batch experiments.
- Plot scripts: `plot_convergence.py`, `plot_energy_comparison.py`, `plot_error_comparison.py`, `dispersion_analysis.py`.

Typical workflow

build $\rightarrow$ run batch cases $\rightarrow$ generate CSV/VTU $\rightarrow$ produce report figures.

Experiment Matrix and Metrics

- **Spatial refinement:** vary h with small fixed Δt.
- **Temporal refinement:** vary Δt on fine fixed mesh.
- **Scheme/mass comparison:** same $h, \Delta t$, different methods.
- **Supplements:** Newmark parameter study, driven boundary, explicit CFL scan.

Monitored outputs

- Error: L^2, H^1 vs time and at final time.
- Discrete energy:

$$E(t) = \frac{1}{2}\,\mathbf{v}^T M \mathbf{v} + \frac{1}{2}\,\mathbf{u}^T K \mathbf{u}.$$

- Runtime statistics (mean/std/median).

Spatial Convergence



- Error decreases monotonically under mesh refinement.
- For smooth eigenmode benchmark, trend is close to expected second-order behavior in L^2 with P1 elements.

Temporal Convergence



- Reducing Δt lowers time error until a spatial-error floor appears.
- Setup used here: Newmark ($h = 0.05,\ P2,$ consistent).
- This is consistent with

$$\|u - u_h\| \lesssim C_1 h^{p+1} + C_2 \Delta t^2.$$

Dispersion Diagnostic



- The ratio $\omega_h^d/\omega_{\text{exact}}$ departs from 1 at large normalized wavenumber.
- This means short waves travel with the wrong phase speed, producing accumulated phase error over long integrations.

Dissipation Diagnostic (Amplification Factor)





- For central difference and Newmark $(\beta, \gamma) = (1/4, 1/2)$, curves stay close to $|G| = 1$ in the stable range.
- Hence the dominant numerical effect is dispersion rather than strong artificial damping.

Energy Comparison (Same $h, \Delta t$)



- Central difference schemes show oscillatory energy errors.
- Newmark-consistent preserves energy almost exactly.
- Mass lumping slightly changes the energy behavior.

These results are consistent with our earlier conclusion that dispersion is the dominant numerical effect, while dissipation remains weak.

Runtime Comparison

Method + Mass	mean [s]	std [s]	median [s]	rel.
central diff. + lumped	0.0154	0.0184	0.0083	1.00x
central diff. + consistent	0.0523	0.0051	0.0548	6.59x
Newmark + lumped	0.0466	0.0095	0.0431	5.19x
Newmark + consistent	0.0530	0.0075	0.0543	6.53x

- Fastest: central difference + lumped mass.
- Consistent mass increases cost due to repeated sparse solves.
- Newmark variants are costlier because of implicit linear solve each step.