

Depth-first search

COMS20010 2020, Video 4-2

John Lapinskas, University of Bristol

Path-finding

One of the most basic problems in graph theory: Given a graph G and two vertices $x, y \in V(G)$, is there a path from x to y ?

Path-finding

One of the most basic problems in graph theory: Given a graph G and two vertices $x, y \in V(G)$, is there a path from x to y ?

E.g. can an enemy attack the base without breaking down a wall?



Path-finding

One of the most basic problems in graph theory: Given a graph G and two vertices $x, y \in V(G)$, is there a path from x to y ?

E.g. can an enemy attack the base without breaking down a wall?



Often we want to know the **shortest** path from x to y — see next video!

Component-finding

In fact, it's better to ask for something more.

Input: A graph G and a vertex $x \in V(G)$.


Output: A list of all vertices in the component of G containing x .

Component-finding

In fact, it's better to ask for something more.

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .




Input: v_1

Component-finding

In fact, it's better to ask for something more.

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .



Input: v_1


Output: $[v_1, v_2, v_3, v_5, v_6, v_7, v_9, v_{10}, v_{11}, v_{12}]$

Component-finding

In fact, it's better to ask for something more.

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .




Input: v_6

Component-finding

In fact, it's better to ask for something more.

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .



Input: v_6


Output: $[v_1, v_2, v_3, v_5, v_6, v_7, v_9, v_{10}, v_{11}, v_{12}]$

Component-finding

In fact, it's better to ask for something more.

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .




Component-finding

In fact, it's better to ask for something more.

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .



Input: v_4


Output: $[v_4, v_8]$

Component-finding

In fact, it's better to ask for something more.

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .



Input: v_4

Output: $[v_4, v_8]$


In other words, we check whether there is a path from x to y for **all** y . Turns out the worst-case running time is the same either way!

Depth-first search: The idea

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .

Idea: Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



Input: G, v_1


Output:

Depth-first search: The idea

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .

Idea: Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



Input: G, v_1


Output: $[v_1$

Depth-first search: The idea

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .

Idea: Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



Input: G, v_1


Output: $[v_1$

Depth-first search: The idea

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .

Idea: Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



Input: G, v_1


Output: $[v_1, v_5]$

Depth-first search: The idea

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .

Idea: Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



Input: G, v_1


Output: $[v_1, v_5]$

Depth-first search: The idea

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .

Idea: Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



Input: G, v_1


Output: $[v_1, v_5, v_9]$

Depth-first search: The idea

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .

Idea: Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



Input: G, v_1


Output: $[v_1, v_5, v_9]$

Depth-first search: The idea

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .

Idea: Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



Input: G, v_1


Output: $[v_1, v_5, v_9, v_{10}]$

Depth-first search: The idea

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .

Idea: Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



Input: G, v_1


Output: $[v_1, v_5, v_9, v_{10}]$

Depth-first search: The idea

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .

Idea: Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



Input: G, v_1


Output: $[v_1, v_5, v_9, v_{10}, v_{11}]$

Depth-first search: The idea

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .

Idea: Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



Input: G, v_1


Output: $[v_1, v_5, v_9, v_{10}, v_{11}]$

Depth-first search: The idea

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .

Idea: Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



Input: G, v_1


Output: $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}]$

Depth-first search: The idea

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .

Idea: Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



Input: G, v_1


Output: $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}]$

Depth-first search: The idea

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .

Idea: Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



Input: G, v_1


Output: $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}]$

Depth-first search: The idea

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .

Idea: Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



Input: G, v_1


Output: $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6]$

Depth-first search: The idea

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .

Idea: Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



Input: G, v_1


Output: $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6]$

Depth-first search: The idea

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .

Idea: Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



Input: G, v_1


Output: $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6]$

Depth-first search: The idea

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .

Idea: Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



Input: G, v_1


Output: $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6]$

Depth-first search: The idea

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .

Idea: Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



Input: G, v_1


Output: $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6]$

Depth-first search: The idea

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .

Idea: Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



Input: G, v_1


Output: $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6, v_7]$

Depth-first search: The idea

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .

Idea: Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



Input: G, v_1


Output: $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6, v_7]$

Depth-first search: The idea

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .

Idea: Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



Input: G, v_1


Output: $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6, v_7, v_3]$

Depth-first search: The idea

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .

Idea: Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



Input: G, v_1


Output: $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6, v_7, v_3]$

Depth-first search: The idea

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .

Idea: Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



Input: G, v_1


Output: $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6, v_7, v_3, v_2]$

Depth-first search: The idea

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .

Idea: Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



Input: G, v_1


Output: $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6, v_7, v_3, v_2]$

Depth-first search: The idea

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .

Idea: Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



Input: G, v_1


Output: $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6, v_7, v_3, v_2]$

Depth-first search: The idea

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .

Idea: Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



Input: G, v_1


Output: $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6, v_7, v_3, v_2]$

Depth-first search: The idea

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .

Idea: Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



Input: G, v_1


Output: $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6, v_7, v_3, v_2]$

Depth-first search: The idea

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .

Idea: Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



Input: G, v_1


Output: $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6, v_7, v_3, v_2]$

Depth-first search: The idea

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .

Idea: Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



Input: G, v_1


Output: $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6, v_7, v_3, v_2]$

Depth-first search: The idea

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .

Idea: Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



Input: G, v_1


Output: $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6, v_7, v_3, v_2]$

Depth-first search: The idea

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .

Idea: Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



Input: G, v_1


Output: $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6, v_7, v_3, v_2]$

Depth-first search: The idea

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .

Idea: Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



Input: G, v_1


Output: $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6, v_7, v_3, v_2]$

Depth-first search: The idea

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .

Idea: Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



Input: G, v_1


Output: $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6, v_7, v_3, v_2]$

Depth-first search: The idea

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .

Idea: Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



Input: G, v_1


Output: $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6, v_7, v_3, v_2]$

Depth-first search: The idea

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .

Idea: Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



Input: G, v_1


Output: $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6, v_7, v_3, v_2]$

Depth-first search: The idea

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .

Idea: Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



Input: G, v_1


Output: $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6, v_7, v_3, v_2]$

Depth-first search: The idea

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .

Idea: Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



Input: G, v_1


Output: $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6, v_7, v_3, v_2]$

Depth-first search: The idea

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .

Idea: Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



Input: G, v_1


Output: $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6, v_7, v_3, v_2]$

Depth-first search: The idea

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .

Idea: Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



Input: G, v_1


Output: $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6, v_7, v_3, v_2]$

Depth-first search: The idea

Input: A graph G and a vertex $x \in V(G)$.

Output: A list of all vertices in the component of G containing x .

Idea: Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.




Input: G, v_1

Output: $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6, v_7, v_3, v_2]$

The slick way to implement this is to use recursion.

Pseudocode and example



Input: v_1


Algorithm: DFS

Input : Graph $G = (V, E)$, vertex $v \in V$.

Output : List of vertices in v 's component.

- 1 Number the vertices of G as v_1, \dots, v_n .
- 2 Let $\text{explored}[i] \leftarrow 0$ for all $i \in [n]$.
- 3 **Procedure** $\text{helper}(v_i)$
 - 4 **if** $\text{explored}[i] = 0$ **then**
 - 5 Set $\text{explored}[i] \leftarrow 1$.
 - 6 **for** v_j *adjacent to* v_i **do**
 - 7 **if** $\text{explored}[j] = 0$ **then**
 - 8 Call $\text{helper}(v_j)$.
 - 9 Call $\text{helper}(v)$.
 - 10 Return $[v_i : \text{explored}[i] = 1]$ (in some order).

Pseudocode and example



Input: v_1


Algorithm: DFS

Input : Graph $G = (V, E)$, vertex $v \in V$.

Output : List of vertices in v 's component.

- 1 Number the vertices of G as v_1, \dots, v_n .
 - 2 Let $\text{explored}[i] \leftarrow 0$ for all $i \in [n]$.
 - 3 **Procedure** $\text{helper}(v_i)$
 - 4 **if** $\text{explored}[i] = 0$ **then**
 - 5 Set $\text{explored}[i] \leftarrow 1$.
 - 6 **for** v_j adjacent to v_i **do**
 - 7 **if** $\text{explored}[j] = 0$ **then**
 - 8 Call $\text{helper}(v_j)$.
 - 9 Call $\text{helper}(v)$.
 - 10 Return $[v_i : \text{explored}[i] = 1]$ (in some order).
-

Pseudocode and example



Input: v_1

Algorithm: DFS

Input : Graph $G = (V, E)$, vertex $v \in V$.

Output : List of vertices in v 's component.

- 1 Number the vertices of G as v_1, \dots, v_n .
- 2 Let $\text{explored}[i] \leftarrow 0$ for all $i \in [n]$.

3 Procedure helper(v_i)

- ```

4 if explored[j] = 0 then
5 Set explored[j] ← 1.
6 for v_j adjacent to v_i do
7 if explored[j] = 0 then
8 Call helper(v_j).


```

- ```

9 Call helper( $v$ ).
10 Return  $[v_i : \text{explored}[i] = 1]$  (in some order).

```


Pseudocode and example



Input: v_1


Algorithm: DFS

Input : Graph $G = (V, E)$, vertex $v \in V$.

Output : List of vertices in v 's component.

- 1 Number the vertices of G as v_1, \dots, v_n .
- 2 Let $\text{explored}[i] \leftarrow 0$ for all $i \in [n]$.
- 3 **Procedure** $\text{helper}(v_i)$
 - 4 **if** $\text{explored}[i] = 0$ **then**
 - 5 Set $\text{explored}[i] \leftarrow 1$.
 - 6 **for** v_j adjacent to v_i **do**
 - 7 **if** $\text{explored}[j] = 0$ **then**
 - 8 Call $\text{helper}(v_j)$.
 - 9 Call $\text{helper}(v)$.
 - 10 Return $[v_i : \text{explored}[i] = 1]$ (in some order).

Pseudocode and example



Input: v_1


Algorithm: DFS

Input : Graph $G = (V, E)$, vertex $v \in V$.

Output : List of vertices in v 's component.

- 1 Number the vertices of G as v_1, \dots, v_n .
- 2 Let $\text{explored}[i] \leftarrow 0$ for all $i \in [n]$.
- 3 **Procedure** $\text{helper}(v_i)$
 - 4 **if** $\text{explored}[i] = 0$ **then**
 - 5 Set $\text{explored}[i] \leftarrow 1$.
 - 6 **for** v_j adjacent to v_i **do**
 - 7 **if** $\text{explored}[j] = 0$ **then**
 - 8 Call $\text{helper}(v_j)$.
 - 9 Call $\text{helper}(v)$.
 - 10 Return $[v_i : \text{explored}[i] = 1]$ (in some order).

Pseudocode and example



Input: v_1


Algorithm: DFS

Input : Graph $G = (V, E)$, vertex $v \in V$.

Output : List of vertices in v 's component.

- 1 Number the vertices of G as v_1, \dots, v_n .
 - 2 Let $\text{explored}[i] \leftarrow 0$ for all $i \in [n]$.
 - 3 **Procedure** $\text{helper}(v_i)$
 - 4 **if** $\text{explored}[i] = 0$ **then**
 - 5 Set $\text{explored}[i] \leftarrow 1$.
 - 6 **for** v_j adjacent to v_i **do**
 - 7 **if** $\text{explored}[j] = 0$ **then**
 - 8 Call $\text{helper}(v_j)$.
 - 9 Call $\text{helper}(v)$.
 - 10 Return $[v_i : \text{explored}[i] = 1]$ (in some order).
-

Pseudocode and example



Input: v_1


Algorithm: DFS

Input : Graph $G = (V, E)$, vertex $v \in V$.

Output : List of vertices in v 's component.

- 1 Number the vertices of G as v_1, \dots, v_n .
 - 2 Let $\text{explored}[i] \leftarrow 0$ for all $i \in [n]$.
 - 3 **Procedure** $\text{helper}(v_i)$
 - 4 **if** $\text{explored}[i] = 0$ **then**
 - 5 Set $\text{explored}[i] \leftarrow 1$.
 - 6 **for** v_j adjacent to v_i **do**
 - 7 **if** $\text{explored}[j] = 0$ **then**
 - 8 Call $\text{helper}(v_j)$.
 - 9 Call $\text{helper}(v)$.
 - 10 Return $[v_i : \text{explored}[i] = 1]$ (in some order).
-

Pseudocode and example



Input: v_1


Algorithm: DFS

Input : Graph $G = (V, E)$, vertex $v \in V$.

Output : List of vertices in v 's component.

- 1 Number the vertices of G as v_1, \dots, v_n .
 - 2 Let $\text{explored}[i] \leftarrow 0$ for all $i \in [n]$.
 - 3 **Procedure** $\text{helper}(v_i)$
 - 4 **if** $\text{explored}[i] = 0$ **then**
 - 5 Set $\text{explored}[i] \leftarrow 1$.
 - 6 **for** v_j adjacent to v_i **do**
 - 7 **if** $\text{explored}[j] = 0$ **then**
 - 8 Call $\text{helper}(v_j)$.
 - 9 Call $\text{helper}(v)$.
 - 10 Return $[v_i : \text{explored}[i] = 1]$ (in some order).
-

Pseudocode and example




Algorithm: DFS

Input : Graph $G = (V, E)$, vertex $v \in V$.

Output : List of vertices in v 's component.

- 1 Number the vertices of G as v_1, \dots, v_n .
 - 2 Let $\text{explored}[i] \leftarrow 0$ for all $i \in [n]$.
 - 3 **Procedure** $\text{helper}(v_i)$
 - 4 **if** $\text{explored}[i] = 0$ **then**
 - 5 Set $\text{explored}[i] \leftarrow 1$.
 - 6 **for** v_j adjacent to v_i **do**
 - 7 **if** $\text{explored}[j] = 0$ **then**
 - 8 Call $\text{helper}(v_j)$.
 - 9 Call $\text{helper}(v)$.
 - 10 Return $[v_i : \text{explored}[i] = 1]$ (in some order).
-

Pseudocode and example



Input: v_1


Algorithm: DFS

Input : Graph $G = (V, E)$, vertex $v \in V$.

Output : List of vertices in v 's component.

- 1 Number the vertices of G as v_1, \dots, v_n .
- 2 Let $\text{explored}[i] \leftarrow 0$ for all $i \in [n]$.
- 3 **Procedure** $\text{helper}(v_i)$
 - 4 **if** $\text{explored}[i] = 0$ **then**
 - 5 Set $\text{explored}[i] \leftarrow 1$.
 - 6 **for** v_j *adjacent to* v_i **do**
 - 7 **if** $\text{explored}[j] = 0$ **then**
 - 8 Call $\text{helper}(v_j)$.
 - 9 Call $\text{helper}(v)$.
 - 10 Return $[v_i : \text{explored}[i] = 1]$ (in some order).

Pseudocode and example



Input: v_1


Algorithm: DFS

Input : Graph $G = (V, E)$, vertex $v \in V$.

Output : List of vertices in v 's component.

- 1 Number the vertices of G as v_1, \dots, v_n .
 - 2 Let $\text{explored}[i] \leftarrow 0$ for all $i \in [n]$.
 - 3 **Procedure** $\text{helper}(v_i)$
 - 4 **if** $\text{explored}[i] = 0$ **then**
 - 5 Set $\text{explored}[i] \leftarrow 1$.
 - 6 **for** v_j adjacent to v_i **do**
 - 7 **if** $\text{explored}[j] = 0$ **then**
 - 8 Call $\text{helper}(v_j)$.
 - 9 Call $\text{helper}(v)$.
 - 10 Return $[v_i : \text{explored}[i] = 1]$ (in some order).
-

Pseudocode and example



Input: v_1


Algorithm: DFS

Input : Graph $G = (V, E)$, vertex $v \in V$.

Output : List of vertices in v 's component.

- 1 Number the vertices of G as v_1, \dots, v_n .
 - 2 Let $\text{explored}[i] \leftarrow 0$ for all $i \in [n]$.
 - 3 **Procedure** $\text{helper}(v_i)$
 - 4 **if** $\text{explored}[i] = 0$ **then**
 - 5 Set $\text{explored}[i] \leftarrow 1$.
 - 6 **for** v_j adjacent to v_i **do**
 - 7 **if** $\text{explored}[j] = 0$ **then**
 - 8 Call $\text{helper}(v_j)$.
 - 9 Call $\text{helper}(v)$.
 - 10 Return $[v_i : \text{explored}[i] = 1]$ (in some order).
-

Pseudocode and example



Input: v_1


Algorithm: DFS

Input : Graph $G = (V, E)$, vertex $v \in V$.

Output : List of vertices in v 's component.

- 1 Number the vertices of G as v_1, \dots, v_n .
- 2 Let $\text{explored}[i] \leftarrow 0$ for all $i \in [n]$.
- 3 **Procedure** $\text{helper}(v_i)$
 - 4 **if** $\text{explored}[i] = 0$ **then**
 - 5 Set $\text{explored}[i] \leftarrow 1$.
 - 6 **for** v_j adjacent to v_i **do**
 - 7 **if** $\text{explored}[j] = 0$ **then**
 - 8 Call $\text{helper}(v_j)$.
 - 9 Call $\text{helper}(v)$.
 - 10 Return $[v_i : \text{explored}[i] = 1]$ (in some order).

Pseudocode and example



Input: v_1


Algorithm: DFS

Input : Graph $G = (V, E)$, vertex $v \in V$.

Output : List of vertices in v 's component.

- 1 Number the vertices of G as v_1, \dots, v_n .
- 2 Let $\text{explored}[i] \leftarrow 0$ for all $i \in [n]$.
- 3 **Procedure** $\text{helper}(v_i)$
 - 4 **if** $\text{explored}[i] = 0$ **then**
 - 5 Set $\text{explored}[i] \leftarrow 1$.
 - 6 **for** v_j adjacent to v_i **do**
 - 7 **if** $\text{explored}[j] = 0$ **then**
 - 8 Call $\text{helper}(v_j)$.
 - 9 Call $\text{helper}(v)$.
 - 10 Return $[v_i : \text{explored}[i] = 1]$ (in some order).

Pseudocode and example



Input: v_1


Algorithm: DFS

Input : Graph $G = (V, E)$, vertex $v \in V$.

Output : List of vertices in v 's component.

- 1 Number the vertices of G as v_1, \dots, v_n .
 - 2 Let $\text{explored}[i] \leftarrow 0$ for all $i \in [n]$.
 - 3 **Procedure** $\text{helper}(v_i)$
 - 4 **if** $\text{explored}[i] = 0$ **then**
 - 5 Set $\text{explored}[i] \leftarrow 1$.
 - 6 **for** v_j adjacent to v_i **do**
 - 7 **if** $\text{explored}[j] = 0$ **then**
 - 8 Call $\text{helper}(v_j)$.
 - 9 Call $\text{helper}(v)$.
 - 10 Return $[v_i : \text{explored}[i] = 1]$ (in some order).
-

Pseudocode and example



Input: v_1


Algorithm: DFS

Input : Graph $G = (V, E)$, vertex $v \in V$.

Output : List of vertices in v 's component.

- 1 Number the vertices of G as v_1, \dots, v_n .
- 2 Let $\text{explored}[i] \leftarrow 0$ for all $i \in [n]$.
- 3 **Procedure** $\text{helper}(v_i)$
 - 4 **if** $\text{explored}[i] = 0$ **then**
 - 5 Set $\text{explored}[i] \leftarrow 1$.
 - 6 **for** v_j adjacent to v_i **do**
 - 7 **if** $\text{explored}[j] = 0$ **then**
 - 8 Call $\text{helper}(v_j)$.
 - 9 Call $\text{helper}(v)$.
 - 10 Return $[v_i : \text{explored}[i] = 1]$ (in some order).

Pseudocode and example



Input: v_1


Algorithm: DFS

Input : Graph $G = (V, E)$, vertex $v \in V$.

Output : List of vertices in v 's component.

- 1 Number the vertices of G as v_1, \dots, v_n .
- 2 Let $\text{explored}[i] \leftarrow 0$ for all $i \in [n]$.
- 3 **Procedure** $\text{helper}(v_i)$
 - 4 **if** $\text{explored}[i] = 0$ **then**
 - 5 Set $\text{explored}[i] \leftarrow 1$.
 - 6 **for** v_j adjacent to v_i **do**
 - 7 **if** $\text{explored}[j] = 0$ **then**
 - 8 Call $\text{helper}(v_j)$.
 - 9 Call $\text{helper}(v)$.
 - 10 Return $[v_i : \text{explored}[i] = 1]$ (in some order).

Pseudocode and example



Input: v_1


Algorithm: DFS

Input : Graph $G = (V, E)$, vertex $v \in V$.

Output : List of vertices in v 's component.

- 1 Number the vertices of G as v_1, \dots, v_n .
- 2 Let $\text{explored}[i] \leftarrow 0$ for all $i \in [n]$.
- 3 **Procedure** $\text{helper}(v_i)$
 - 4 **if** $\text{explored}[i] = 0$ **then**
 - 5 Set $\text{explored}[i] \leftarrow 1$.
 - 6 **for** v_j adjacent to v_i **do**
 - 7 **if** $\text{explored}[j] = 0$ **then**
 - 8 Call $\text{helper}(v_j)$.
 - 9 Call $\text{helper}(v)$.
 - 10 Return $[v_i : \text{explored}[i] = 1]$ (in some order).

Pseudocode and example



Input: v_1


Algorithm: DFS

Input : Graph $G = (V, E)$, vertex $v \in V$.

Output : List of vertices in v 's component.

- 1 Number the vertices of G as v_1, \dots, v_n .
- 2 Let $\text{explored}[i] \leftarrow 0$ for all $i \in [n]$.
- 3 **Procedure** $\text{helper}(v_i)$
 - 4 **if** $\text{explored}[i] = 0$ **then**
 - 5 Set $\text{explored}[i] \leftarrow 1$.
 - 6 **for** v_j adjacent to v_i **do**
 - 7 **if** $\text{explored}[j] = 0$ **then**
 - 8 Call $\text{helper}(v_j)$.
 - 9 Call $\text{helper}(v)$.
 - 10 Return $[v_i : \text{explored}[i] = 1]$ (in some order).

Pseudocode and example



Input: v_1


Algorithm: DFS

Input : Graph $G = (V, E)$, vertex $v \in V$.

Output : List of vertices in v 's component.

- 1 Number the vertices of G as v_1, \dots, v_n .
 - 2 Let $\text{explored}[i] \leftarrow 0$ for all $i \in [n]$.
 - 3 **Procedure** $\text{helper}(v_i)$
 - 4 **if** $\text{explored}[i] = 0$ **then**
 - 5 Set $\text{explored}[i] \leftarrow 1$.
 - 6 **for** v_j adjacent to v_i **do**
 - 7 **if** $\text{explored}[j] = 0$ **then**
 - 8 Call $\text{helper}(v_j)$.
 - 9 Call $\text{helper}(v)$.
 - 10 Return $[v_i : \text{explored}[i] = 1]$ (in some order).
-

Pseudocode and example



Input: v_1


Algorithm: DFS

Input : Graph $G = (V, E)$, vertex $v \in V$.

Output : List of vertices in v 's component.

- 1 Number the vertices of G as v_1, \dots, v_n .
 - 2 Let $\text{explored}[i] \leftarrow 0$ for all $i \in [n]$.
 - 3 **Procedure** $\text{helper}(v_i)$
 - 4 **if** $\text{explored}[i] = 0$ **then**
 - 5 Set $\text{explored}[i] \leftarrow 1$.
 - 6 **for** v_j adjacent to v_i **do**
 - 7 **if** $\text{explored}[j] = 0$ **then**
 - 8 Call $\text{helper}(v_j)$.
 - 9 Call $\text{helper}(v)$.
 - 10 Return $[v_i : \text{explored}[i] = 1]$ (in some order).
-

Pseudocode and example




Algorithm: DFS

Input : Graph $G = (V, E)$, vertex $v \in V$.

Output : List of vertices in v 's component.

- 1 Number the vertices of G as v_1, \dots, v_n .
- 2 Let $\text{explored}[i] \leftarrow 0$ for all $i \in [n]$.
- 3 **Procedure** $\text{helper}(v_i)$
 - 4 **if** $\text{explored}[i] = 0$ **then**
 - 5 Set $\text{explored}[i] \leftarrow 1$.
 - 6 **for** v_j adjacent to v_i **do**
 - 7 **if** $\text{explored}[j] = 0$ **then**
 - 8 Call $\text{helper}(v_j)$.
 - 9 Call $\text{helper}(v)$.
 - 10 Return $[v_i : \text{explored}[i] = 1]$ (in some order).

Pseudocode and example




Algorithm: DFS

Input : Graph $G = (V, E)$, vertex $v \in V$.

Output : List of vertices in v 's component.

- 1 Number the vertices of G as v_1, \dots, v_n .
 - 2 Let $\text{explored}[i] \leftarrow 0$ for all $i \in [n]$.
 - 3 **Procedure** $\text{helper}(v_i)$
 - 4 **if** $\text{explored}[i] = 0$ **then**
 - 5 Set $\text{explored}[i] \leftarrow 1$.
 - 6 **for** v_j adjacent to v_i **do**
 - 7 **if** $\text{explored}[j] = 0$ **then**
 - 8 Call $\text{helper}(v_j)$.
 - 9 Call $\text{helper}(v)$.
 - 10 Return $[v_i : \text{explored}[i] = 1]$ (in some order).
-

Pseudocode and example



Algorithm: DFS

Input : Graph $G = (V, E)$, vertex $v \in V$.

Output : List of vertices in v 's component.

- 1 Number the vertices of G as v_1, \dots, v_n .
- 2 Let $\text{explored}[i] \leftarrow 0$ for all $i \in [n]$.

3 Procedure $\text{helper}(v_i)$

- ```

4 if explored[j] = 0 then
5 Set explored[j] ← 1.
6 for v_j adjacent to v_i do
7 if explored[j] = 0 then
8 Call helper(v_j).


```

- ```

9 Call helper( $v$ ).
10 Return  $[v_i : \text{explored}[i] = 1]$  (in some order).

```

Pseudocode and example




Algorithm: DFS

Input : Graph $G = (V, E)$, vertex $v \in V$.

Output : List of vertices in v 's component.

- 1 Number the vertices of G as v_1, \dots, v_n .
- 2 Let $\text{explored}[i] \leftarrow 0$ for all $i \in [n]$.
- 3 **Procedure** $\text{helper}(v_i)$
 - 4 **if** $\text{explored}[i] = 0$ **then**
 - 5 Set $\text{explored}[i] \leftarrow 1$.
 - 6 **for** v_j adjacent to v_i **do**
 - 7 **if** $\text{explored}[j] = 0$ **then**
 - 8 Call $\text{helper}(v_j)$.
 - 9 Call $\text{helper}(v)$.
 - 10 Return $[v_i : \text{explored}[i] = 1]$ (in some order).

Pseudocode and example




Algorithm: DFS

Input : Graph $G = (V, E)$, vertex $v \in V$.

Output : List of vertices in v 's component.

- 1 Number the vertices of G as v_1, \dots, v_n .
 - 2 Let $\text{explored}[i] \leftarrow 0$ for all $i \in [n]$.
 - 3 **Procedure** $\text{helper}(v_i)$
 - 4 **if** $\text{explored}[i] = 0$ **then**
 - 5 Set $\text{explored}[i] \leftarrow 1$.
 - 6 **for** v_j adjacent to v_i **do**
 - 7 **if** $\text{explored}[j] = 0$ **then**
 - 8 Call $\text{helper}(v_j)$.
 - 9 Call $\text{helper}(v)$.
 - 10 Return $[v_i : \text{explored}[i] = 1]$ (in some order).
-

Pseudocode and example




Algorithm: DFS

Input : Graph $G = (V, E)$, vertex $v \in V$.

Output : List of vertices in v 's component.

- 1 Number the vertices of G as v_1, \dots, v_n .
- 2 Let $\text{explored}[i] \leftarrow 0$ for all $i \in [n]$.
- 3 **Procedure** $\text{helper}(v_i)$
 - 4 **if** $\text{explored}[i] = 0$ **then**
 - 5 Set $\text{explored}[i] \leftarrow 1$.
 - 6 **for** v_j adjacent to v_i **do**
 - 7 **if** $\text{explored}[j] = 0$ **then**
 - 8 Call $\text{helper}(v_j)$.
 - 9 Call $\text{helper}(v)$.
 - 10 Return $[v_i : \text{explored}[i] = 1]$ (in some order).

Pseudocode and example



Input: v_1


Algorithm: DFS

Input : Graph $G = (V, E)$, vertex $v \in V$.

Output : List of vertices in v 's component.

- 1 Number the vertices of G as v_1, \dots, v_n .
- 2 Let $\text{explored}[i] \leftarrow 0$ for all $i \in [n]$.
- 3 **Procedure** $\text{helper}(v_i)$
 - 4 **if** $\text{explored}[i] = 0$ **then**
 - 5 Set $\text{explored}[i] \leftarrow 1$.
 - 6 **for** v_j adjacent to v_i **do**
 - 7 **if** $\text{explored}[j] = 0$ **then**
 - 8 Call $\text{helper}(v_j)$.
 - 9 Call $\text{helper}(v)$.
 - 10 Return $[v_i : \text{explored}[i] = 1]$ (in some order).

Pseudocode and example




Algorithm: DFS

Input : Graph $G = (V, E)$, vertex $v \in V$.

Output : List of vertices in v 's component.

- 1 Number the vertices of G as v_1, \dots, v_n .
 - 2 Let $\text{explored}[i] \leftarrow 0$ for all $i \in [n]$.
 - 3 **Procedure** $\text{helper}(v_i)$
 - 4 **if** $\text{explored}[i] = 0$ **then**
 - 5 Set $\text{explored}[i] \leftarrow 1$.
 - 6 **for** v_j adjacent to v_i **do**
 - 7 **if** $\text{explored}[j] = 0$ **then**
 - 8 Call $\text{helper}(v_j)$.
 - 9 Call $\text{helper}(v)$.
 - 10 Return $[v_i : \text{explored}[i] = 1]$ (in some order).
-

Pseudocode and example



Input: v_1


Algorithm: DFS

Input : Graph $G = (V, E)$, vertex $v \in V$.

Output : List of vertices in v 's component.

- 1 Number the vertices of G as v_1, \dots, v_n .
 - 2 Let $\text{explored}[i] \leftarrow 0$ for all $i \in [n]$.
 - 3 **Procedure** $\text{helper}(v_i)$
 - 4 **if** $\text{explored}[i] = 0$ **then**
 - 5 Set $\text{explored}[i] \leftarrow 1$.
 - 6 **for** v_j adjacent to v_i **do**
 - 7 **if** $\text{explored}[j] = 0$ **then**
 - 8 Call $\text{helper}(v_j)$.
 - 9 Call $\text{helper}(v)$.
 - 10 Return $[v_i : \text{explored}[i] = 1]$ (in some order).
-

Pseudocode and example



Input: V_1

Algorithm: DFS

Input : Graph $G = (V, E)$, vertex $v \in V$.

Output : List of vertices in v 's component.

1 Number the vertices of G as v_1, \dots, v_n .

2 Let $\text{explored}[i] \leftarrow 0$ for all $i \in [n]$.

3 Procedure helper(v_i)

```

4 |   if explored[i] = 0 then

```

5	Set $\text{explored}[i] \leftarrow 1$.
---	---

6	for v_j <i>adjacent to</i> v_i do
---	---

7	if explored[j] = 0 then
---	-------------------------

8				Call helper(v_i).
---	--	--	--	-----------------------


```

9 Call helper( $v$ ).

```

10 Return $[v_i: \text{explored}[i] = 1]$ (in some order).

Pseudocode and example




Algorithm: DFS

Input : Graph $G = (V, E)$, vertex $v \in V$.

Output : List of vertices in v 's component.

- 1 Number the vertices of G as v_1, \dots, v_n .
- 2 Let $\text{explored}[i] \leftarrow 0$ for all $i \in [n]$.
- 3 **Procedure** $\text{helper}(v_i)$
 - 4 **if** $\text{explored}[i] = 0$ **then**
 - 5 Set $\text{explored}[i] \leftarrow 1$.
 - 6 **for** v_j adjacent to v_i **do**
 - 7 **if** $\text{explored}[j] = 0$ **then**
 - 8 Call $\text{helper}(v_j)$.
 - 9 Call $\text{helper}(v)$.
 - 10 Return $[v_i : \text{explored}[i] = 1]$ (in some order).

Pseudocode and example




Algorithm: DFS

Input : Graph $G = (V, E)$, vertex $v \in V$.

Output : List of vertices in v 's component.

- 1 Number the vertices of G as v_1, \dots, v_n .
- 2 Let $\text{explored}[i] \leftarrow 0$ for all $i \in [n]$.
- 3 **Procedure** $\text{helper}(v_i)$
 - 4 **if** $\text{explored}[i] = 0$ **then**
 - 5 Set $\text{explored}[i] \leftarrow 1$.
 - 6 **for** v_j adjacent to v_i **do**
 - 7 **if** $\text{explored}[j] = 0$ **then**
 - 8 Call $\text{helper}(v_j)$.
 - 9 Call $\text{helper}(v)$.
 - 10 Return $[v_i : \text{explored}[i] = 1]$ (in some order).

Pseudocode and example



Input: v_1


Algorithm: DFS

Input : Graph $G = (V, E)$, vertex $v \in V$.

Output : List of vertices in v 's component.

- 1 Number the vertices of G as v_1, \dots, v_n .
 - 2 Let $\text{explored}[i] \leftarrow 0$ for all $i \in [n]$.
 - 3 **Procedure** $\text{helper}(v_i)$
 - 4 **if** $\text{explored}[i] = 0$ **then**
 - 5 Set $\text{explored}[i] \leftarrow 1$.
 - 6 **for** v_j adjacent to v_i **do**
 - 7 **if** $\text{explored}[j] = 0$ **then**
 - 8 Call $\text{helper}(v_j)$.
 - 9 Call $\text{helper}(v)$.
 - 10 Return $[v_i : \text{explored}[i] = 1]$ (in some order).
-

Pseudocode and example



Input: v_1


Algorithm: DFS

Input : Graph $G = (V, E)$, vertex $v \in V$.

Output : List of vertices in v 's component.

- 1 Number the vertices of G as v_1, \dots, v_n .
- 2 Let $\text{explored}[i] \leftarrow 0$ for all $i \in [n]$.
- 3 **Procedure** $\text{helper}(v_i)$
 - 4 **if** $\text{explored}[i] = 0$ **then**
 - 5 Set $\text{explored}[i] \leftarrow 1$.
 - 6 **for** v_j adjacent to v_i **do**
 - 7 **if** $\text{explored}[j] = 0$ **then**
 - 8 Call $\text{helper}(v_j)$.
 - 9 Call $\text{helper}(v)$.
 - 10 Return $[v_i : \text{explored}[i] = 1]$ (in some order).

Pseudocode and example




Algorithm: DFS

Input : Graph $G = (V, E)$, vertex $v \in V$.

Output : List of vertices in v 's component.

- 1 Number the vertices of G as v_1, \dots, v_n .
 - 2 Let $\text{explored}[i] \leftarrow 0$ for all $i \in [n]$.
 - 3 **Procedure** $\text{helper}(v_i)$
 - 4 **if** $\text{explored}[i] = 0$ **then**
 - 5 Set $\text{explored}[i] \leftarrow 1$.
 - 6 **for** v_j adjacent to v_i **do**
 - 7 **if** $\text{explored}[j] = 0$ **then**
 - 8 Call $\text{helper}(v_j)$.
 - 9 Call $\text{helper}(v)$.
 - 10 Return $[v_i : \text{explored}[i] = 1]$ (in some order).
-

Pseudocode and example



Input: v_1


Algorithm: DFS

Input : Graph $G = (V, E)$, vertex $v \in V$.

Output : List of vertices in v 's component.

- 1 Number the vertices of G as v_1, \dots, v_n .
 - 2 Let $\text{explored}[i] \leftarrow 0$ for all $i \in [n]$.
 - 3 **Procedure** $\text{helper}(v_i)$
 - 4 **if** $\text{explored}[i] = 0$ **then**
 - 5 Set $\text{explored}[i] \leftarrow 1$.
 - 6 **for** v_j *adjacent to* v_i **do**
 - 7 **if** $\text{explored}[j] = 0$ **then**
 - 8 Call $\text{helper}(v_j)$.
 - 9 Call $\text{helper}(v)$.
 - 10 Return $[v_i : \text{explored}[i] = 1]$ (in some order).
-

Pseudocode and example



Input: v_1


Algorithm: DFS

Input : Graph $G = (V, E)$, vertex $v \in V$.

Output : List of vertices in v 's component.

- 1 Number the vertices of G as v_1, \dots, v_n .
 - 2 Let $\text{explored}[i] \leftarrow 0$ for all $i \in [n]$.
 - 3 **Procedure** $\text{helper}(v_i)$
 - 4 **if** $\text{explored}[i] = 0$ **then**
 - 5 Set $\text{explored}[i] \leftarrow 1$.
 - 6 **for** v_j adjacent to v_i **do**
 - 7 **if** $\text{explored}[j] = 0$ **then**
 - 8 Call $\text{helper}(v_j)$.
 - 9 Call $\text{helper}(v)$.
 - 10 Return $[v_i : \text{explored}[i] = 1]$ (in some order).
-

Pseudocode and example




Algorithm: DFS

Input : Graph $G = (V, E)$, vertex $v \in V$.

Output : List of vertices in v 's component.

- 1 Number the vertices of G as v_1, \dots, v_n .
 - 2 Let $\text{explored}[i] \leftarrow 0$ for all $i \in [n]$.
 - 3 **Procedure** $\text{helper}(v_i)$
 - 4 **if** $\text{explored}[i] = 0$ **then**
 - 5 Set $\text{explored}[i] \leftarrow 1$.
 - 6 **for** v_j adjacent to v_i **do**
 - 7 **if** $\text{explored}[j] = 0$ **then**
 - 8 Call $\text{helper}(v_j)$.
 - 9 Call $\text{helper}(v)$.
 - 10 Return $[v_i : \text{explored}[i] = 1]$ (in some order).
-

Pseudocode and example



Input: v_1

Algorithm: DFS

Input : Graph $G = (V, E)$, vertex $v \in V$.


Output : List of vertices in v 's component.

- 1 Number the vertices of G as v_1, \dots, v_n .
 - 2 Let $\text{explored}[i] \leftarrow 0$ for all $i \in [n]$.
 - 3 **Procedure** $\text{helper}(v_i)$
 - 4 **if** $\text{explored}[i] = 0$ **then**
 - 5 Set $\text{explored}[i] \leftarrow 1$.
 - 6 **for** v_j *adjacent to* v_i **do**
 - 7 **if** $\text{explored}[j] = 0$ **then**
 - 8 Call $\text{helper}(v_j)$.
 - 9 Call $\text{helper}(v)$.
 - 10 Return $[v_i : \text{explored}[i] = 1]$ (in some order).
-


We assume G is in adjacency list form.

Time analysis: In total there are $\sum_{v \in V} d(v) = O(|E|)$ calls to helper (each vertex only runs lines 5–7 once), and there is $O(1)$ time between calls. So the running time is $O(|V| + |E|)$.

Correctness I: Output is contained in v 's component C




Correctness I: Output is contained in v 's component C



Invariant: “When helper is called, if $\text{explored}[i] = 1$ then $v_i \in V(C)$.”


Correctness I: Output is contained in v 's component C



Invariant: “When `helper` is called, if `explored[i] = 1` then $v_i \in V(C)$.”

Proof by induction. Vacuously true for initial call and second call. ✓

Correctness I: Output is contained in v 's component C




Invariant: “When `helper` is called, if `explored[i] = 1` then $v_i \in V(C)$.”

Proof by induction. Vacuously true for initial call and second call. ✓

Suppose it holds at the start of some call `helper(v_j)` from `helper(v_i)`.
If v_j is already explored, we’re done.

Correctness I: Output is contained in v 's component C




Invariant: “When `helper` is called, if `explored[i] = 1` then $v_i \in V(C)$.”

Proof by induction. Vacuously true for initial call and second call. ✓

Suppose it holds at the start of some call `helper(v_j)` from `helper(v_i)`.
If v_j is already explored, we're done.

Correctness I: Output is contained in v 's component C




Invariant: “When `helper` is called, if `explored[i] = 1` then $v_i \in V(C)$.”

Proof by induction. Vacuously true for initial call and second call. ✓

Suppose it holds at the start of some call `helper(v_j)` from `helper(v_i)`.
If v_j is already explored, we’re done.

Correctness I: Output is contained in v 's component C




Invariant: “When `helper` is called, if `explored[i] = 1` then $v_i \in V(C)$.”

Proof by induction. Vacuously true for initial call and second call. ✓

Suppose it holds at the start of some call `helper(v_j)` from `helper(v_i)`.
If v_j is already explored, we're done. If not, we must show $v_j \in V(C)$.

Correctness I: Output is contained in v 's component C




Invariant: “When helper is called, if $\text{explored}[i] = 1$ then $v_i \in V(C)$.”

Proof by induction. Vacuously true for initial call and second call. ✓

Suppose it holds at the start of some call $\text{helper}(v_j)$ from $\text{helper}(v_i)$. If v_j is already explored, we're done. If not, we must show $v_j \in V(C)$.

Correctness I: Output is contained in v 's component C




Invariant: “When `helper` is called, if `explored[i] = 1` then $v_i \in V(C)$.”

Proof by induction. Vacuously true for initial call and second call. ✓

Suppose it holds at the start of some call `helper(v_j)` from `helper(v_i)`. If v_j is already explored, we’re done. If not, we must show $v_j \in V(C)$.

Since we called from `helper(v_i)`, $\{v_i, v_j\} \in E$ and v_i is explored.

Correctness I: Output is contained in v 's component C



Invariant: “When `helper` is called, if `explored[i] = 1` then $v_i \in V(C)$.”


Proof by induction. Vacuously true for initial call and second call. ✓

Suppose it holds at the start of some call `helper(v_j)` from `helper(v_i)`.
If v_j is already explored, we’re done. If not, we must show $v_j \in V(C)$.

Since we called from `helper(v_i)`, $\{v_i, v_j\} \in E$ and v_i is explored.


By induction there is a path P from v to v_i . Then Pv_iv_j is a walk from v to v_j , which contains a path, so $v_j \in V(C)$. □

Correctness II: Output contains v 's component C




Let $w \in V(C)$. Then there is a path $P = x_1 \dots x_t$ from v to w .

Correctness II: Output contains v 's component C



Let $w \in V(C)$. Then there is a path $P = x_1 \dots x_t$ from v to w .

Correctness II: Output contains v 's component C




Let $w \in V(C)$. Then there is a path $P = x_1 \dots x_t$ from v to w .

Claim: Every vertex in P is explored.

Proof by induction: We prove x_1, \dots, x_i are explored for all $i \leq t$.

x_1 is explored.

Correctness II: Output contains v 's component C



Let $w \in V(C)$. Then there is a path $P = x_1 \dots x_t$ from v to w .


Claim: Every vertex in P is explored.

Proof by induction: We prove x_1, \dots, x_i are explored for all $i \leq t$.

x_1 is explored.



Correctness II: Output contains v 's component C



Let $w \in V(C)$. Then there is a path $P = x_1 \dots x_t$ from v to w .


Claim: Every vertex in P is explored.

Proof by induction: We prove x_1, \dots, x_i are explored for all $i \leq t$.

x_1 is explored. ✓

If x_i is explored, then $\text{helper}(x_{i+1})$ will be called from $\text{helper}(x_i)$, so x_{i+1} will also be explored (either then or earlier).

Correctness II: Output contains v 's component C



Let $w \in V(C)$. Then there is a path $P = x_1 \dots x_t$ from v to w .


Claim: Every vertex in P is explored.

Proof by induction: We prove x_1, \dots, x_i are explored for all $i \leq t$.

x_1 is explored. ✓

If x_i is explored, then $\text{helper}(x_{i+1})$ will be called from $\text{helper}(x_i)$, so x_{i+1} will also be explored (either then or earlier).

Correctness II: Output contains v 's component C



Let $w \in V(C)$. Then there is a path $P = x_1 \dots x_t$ from v to w .

Claim: Every vertex in P is explored.

Proof by induction: We prove x_1, \dots, x_i are explored for all $i \leq t$.

x_1 is explored.


✓

If x_i is explored, then $\text{helper}(x_{i+1})$ will be called from $\text{helper}(x_i)$, so x_{i+1} will also be explored (either then or earlier).

5

Depth-first search trees


Consider the subgraph formed by the edges **traversed** in DFS:



This is an example of a **DFS tree** rooted at v .

Depth-first search trees

Consider the subgraph formed by the edges **traversed** in DFS:



This is an example of a **DFS tree** rooted at v .


Definition: A **DFS tree** T of G is a rooted tree satisfying:

- $V(T)$ is the vertex set of a component of G ;
- If $\{x, y\} \in E(G)$, then x is an ancestor of y in T or vice versa.

Theorem: DFS always gives a DFS tree. (See problem sheet.)

Depth-first search trees

Consider the subgraph formed by the edges **traversed** in DFS:



This is an example of a **DFS tree** rooted at v .

Definition: A **DFS tree** T of G is a rooted tree satisfying:


- $V(T)$ is the vertex set of a component of G ;
- If $\{x, y\} \in E(G)$, then x is an ancestor of y in T or vice versa.

Theorem: DFS always gives a DFS tree. (See problem sheet.)

DFS trees can be independently useful! (See problem sheet.)

Depth-first search trees

Consider the subgraph formed by the edges **traversed** in DFS:



This is an example of a **DFS tree** rooted at v .

Definition: A **DFS tree** T of G is a rooted tree satisfying:

- $V(T)$ is the vertex set of a component of G ;
- If $\{x, y\} \in E(G)$, then x is an ancestor of y in T or vice versa.

Theorem: DFS always gives a DFS tree. (See problem sheet.)

DFS trees can be independently useful! (See problem sheet.)

Depth-first search works for directed graphs too, in exactly the same way. But paths **between** v and w are replaced by paths **from** v **to** w .