




Authentication 1 of 8

What is authentication?

Authentication is the process of letting users signup/signin into websites via **username** / **password** or using SSO (single sign on)

 Acme Inc

"This library has saved me countless hours of work and helped me deliver stunning designs to my clients faster than ever before."

Sofia Davis


Login

Create an account

Enter your email below to create your account

Sign In with Email

OR CONTINUE WITH

 GitHub

By clicking continue, you agree to our [Terms of Service](#) and [Privacy Policy](#).





Authentication 1 of 8

Authentication using jwt + localstorage

Signup

Signin

Auth requests



Authentication using cookies (Part 1)

What are cookies

Cookies in web development are small pieces of data sent from a website and stored on the user's computer by the user's web browser while the user is browsing. They are designed to be a reliable mechanism for websites to remember things (very similar to local storage)

1. **Session Management:** Cookies allow websites to identify users and track their individual session states across multiple pages or visits.
2. **Personalization:** Websites use cookies to personalize content and ads. For instance, cookies might store information about a user's preferences, allowing the site to tailor content or advertisements to those interests.
3. **Tracking:** Cookies can track users across websites, providing insights into browsing behavior. This information can be used for analytics purposes, to improve website functionality, or for advertising targeting.
4. **Security:** Secure cookies can be used to enhance the security of a website by ensuring that the transmission of information is only done over an encrypted connection, helping to prevent unauthorized access to user data.

We will be focussing on point 4

Why not local storage?

(
ε

ways to store data on the client-
nd have different characteristics.

- 1 Cookies are send with every request to the website (by the browser) (you
Authentication 1 of 8 add a header to the fetch call)
this point becomes super important in Next.js, we'll see later why



Ref - <https://github.com/100xdevs-cohort-2/paytm/blob/complete-solution/frontend/src/pages/SendMoney.jsx#L45>

1. Cookies can have an expiry attached to them
2. Cookies can be be restricted to only **https** and to certain **domains**

Authentication with cookies (Part 2)

Signup

Signin

Auth endpoints

cookie header in the browser.

it's automatically set by the browser in every request



Properties of cookies

Types of cookies

1. Persistent – Stay even if u close the window
2. Session – Go away after the window closes
3. **Secure** – Sent only over secure, encrypted connections (HTTPS).

Properties of cookies

- HttpOnly – Can not be accessed by client side scripts
- **SameSite** – Ensures cookies are not send on cross origin requests

1 Strict

vel navigation

3 None

F it Authentication 1 of 8 net/web-security/csrf/bypassing-samesite-restrictions#:~:text=SameSite is a browser security,leaks%2C and some CORS exploits.

- **Domains** – You can also specify what all domains should the cookie be sent from

CSRF attacks

Cross site request forgery attacks were super common because of cookies and hence the **SameSite** attribute was introduced

Let's see a few cases

SameSite: none

SameSite: Strict

But there's a problem –

SameSite: Lax

Example in express (Backend)

1. initialize an empty JS project

```
npm init -v
```

» Authentication 1 of 8

1. Update rootDir and outDir

```
"rootDir": "./src"  
"outDir": "./dist"
```

1. Add required libraries

```
import express from "express";  
import cookieParser from "cookie-parser";  
import cors from "cors";  
import jwt, { JwtPayload } from "jsonwebtoken";  
import path from "path";
```

1. Initialize express app, add middlewares

```
const app = express();  
app.use(cookieParser());  
app.use(express.json());  
app.use(cors({  
  credentials: true,  
  origin: "http://localhost:5173"  
}));
```

1. Add a dummy signin endpoint

```
app.post("/signin", (req, res) => {  
  const email = req.body.email;  
  const password = req.body.password;  
  // do db validations, fetch id of user from db  
  const token = jwt.sign({  
    id: 1  
  }, JWT_SECRET);  
  res.cookie("token", token);  
  res.send("Logged in!");  
});
```

1. Add a protected backend route

```
const token = req.cookies.token;
```

```
const decoded = jwt.verify(token, JWT_SECRET) as JwtPayload;
```

er from the database

Authentication 1 of 8

userId: decoded.id

 $\})$
$$\});$$

1. Add a logout route

```
app.post("/logout", (req, res) => {
```

```
res.cookie("token", "ads");
```

```
res.json({
```

```
message: "Logged out!"
```

 $\})$
$$\});$$

1. Listen on port 3000

```
app.listen(3000);
```

Code - <https://github.com/100xdevs-cohort-2/week-16-auth-1>

Frontend in React

- Initialize an empty react project
- Add a **signin** page

```
import { BACKEND_URL } from './config'
```



```
import axios from "axios"
```

```

Authentication 1 of 8 => {
const [username, setUsername] = useState("")
const [password, setPassword] = useState("")

return <div>
  <input onChange={e => {
    setUsername(e.target.value);
  }} type="text" placeholder="username" />
  <input onChange={e => {
    setPassword(e.target.value);
  }} type="password" placeholder="password" />
  <button onClick={async () => {
    await axios.post(`${BACKEND_URL}/signin`, {
      username,
      password
    }, {
      withCredentials: true,
    });
    alert("you are logged in")
  }}>Submit</button>
</div>
}

```

- Add a **user** page

```

import axios from "axios";
import { useEffect, useState } from "react"
import { BACKEND_URL } from "../config";

export const User = () => {
  const [userData, setUserData] = useState();

  useEffect(() => {
    axios.get(`${BACKEND_URL}/user`, {
      withCredentials: true,
    })
      .then(res => {
        setUserData(res.data);
      })
  })
}

```

```
return <div>
```

```
  <div>{a?.userId}
```

```
  Authentication 1 of 8
```

```
  <button onClick={() => {
```

```
    axios.post(`${BACKEND_URL}/logout`, {}, {
```

```
      withCredentials: true,
```

```
    })
```

```
  }}>Logout</button>
```

```
</div>
```

```
}
```

- Add routing

```
import './App.css'
```

```
import { BrowserRouter, Route, Routes } from "react-router-dom";
```

```
import { Signup } from './components/Signup';
```

```
import { Signin } from './components/Signin';
```

```
import { User } from './components/User';
```

```
function App() {
```

```
  return (
```

```
    <BrowserRouter>
```

```
      <Routes>
```

```
        <Route path={"/signup"} element={<Signup />} />
```

```
        <Route path={"/signin"} element={<Signin />} />
```

```
        <Route path={"/user"} element={<User />} />
```

```
      </Routes>
```

```
    </BrowserRouter>
```

```
  )
```

```
}
```

```
export default App
```

Code - <https://github.com/100xdevs-cohort-2/week-16-auth-1>

Authentication 1 of 8 from express

1. Add an index.html file in src folder of backend

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Login Page</title>
  <script src="https://cdn.jsdelivr.net/npm/axios/dist/axios.min.js"></script>
</head>
<body>

  <input id="username" type="text" placeholder="username" />
  <input id="password" type="password" placeholder="password" />
  <button id="loginButton">Submit</button>
  <button id="logoutButton">Logout</button>
  <div id="userData"></div>

<script>

  document.getElementById('loginButton').addEventListener('click', async () =>
    const username = document.getElementById('username').value;
    const password = document.getElementById('password').value;

    try {
      await axios.post(`/signin`, {
        username,
        password
      });
      alert("You are logged in");
    } catch (error) {
      console.error('Login failed:', error);
      alert("Login failed");
    }
  });

  document.getElementById('logoutButton').addEventListener('click', () => {
    axios.post(`/logout`, {}, {
```

```

        withCredentials: true,
      })
    .then(response => {
      console.log('Logout successful.');
```

Authentication 1 of 8

```

    }).catch(error => {
      console.error('Logout failed:', error);
    });
  });
});

function fetchUserData() {
  axios.get(`/user`, {
    withCredentials: true,
  }).then(response => {
    const userData = response.data;
    displayUserData(userData);
  }).catch(error => {
    console.error('Failed to fetch user data:', error);
  });
}

function displayUserData(userData) {
  const userDataDiv = document.getElementById('userData');
  // Example: Assumes userData contains a 'name' and 'email'. Adapt basec
  userDataDiv.innerHTML = `<p>Your id is: ${userData.userId}</p>`;
}

fetchUserData();
</script>

</body>
</html>

```

1. Add a route that sends this html file

```

app.get("/", (req, res) => {
  res.sendFile(path.join(__dirname, "../src/index.html"))
})

```

1. Remove **credentials** from cors

```

app.use(cors());

```

Link - <https://github.com/100xdevs-conort-2/week-16-auth-1>



Authentication 1 of 8