

LibADMM: A Library of Alternating Direction Method of Multipliers for Compressed Sensing

Version 1.0

Canyi Lu

canyilu@gmail.com

<https://github.com/canyilu/LibADMM>

Department of Electrical and Computer Engineering

National University of Singapore

June, 2016

TABLE 1: Applicability of the LibADMM package

Model	Problem		Function	Description and Reference
Sparse models	$\min_{\mathbf{x}} r(\mathbf{x})$ s.t. $\mathbf{Ax} = \mathbf{b}$	$r(\mathbf{x}) = \ \mathbf{x}\ _1$	l1	ℓ_1 [14]
		$r(\mathbf{x}) = \sum_{g \in \mathcal{G}} \ \mathbf{x}_g\ _2$	group11	Group Lasso [17]
		$r(\mathbf{x}) = \ \mathbf{x}\ _1 + \lambda_2 \ \mathbf{x}\ _2^2$	elasticnet	Elastic net [19]
		$r(\mathbf{x}) = \ \mathbf{x}\ _1 + \lambda_2 \sum_{i=2}^p x_i - x_{i-1} $	fused11	Fused Lasso [15]
		$r(\mathbf{x}) = \ \mathbf{A} \text{Diag}(\mathbf{x})\ _*$	tracelasso	Trace Lasso [12]
		$r(\mathbf{x}) = \frac{1}{2} \ \mathbf{x}\ _{\text{ksp}}^2$	ksupport	k support norm [6]
	$\min_{\mathbf{x}, \mathbf{e}} l(\mathbf{e}) + \lambda r(\mathbf{x})$ s.t. $\mathbf{Ax} + \mathbf{e} = \mathbf{b}$	$l(\mathbf{e}) = \ \mathbf{e}\ _1$ $l(\mathbf{e}) = \frac{1}{2} \ \mathbf{e}\ _2^2$	l1R	Reg. ℓ_1
			group11R	Reg. Group Lasso
			elasticnetR	Reg. Elastic net
			fused11R	Reg. Fused Lasso
			tracelassoR	Reg. Trace Lasso
			ksupportR	Reg. k support norm
Low-rank matrix models	$\min_{\mathbf{L}, \mathbf{S}} \ \mathbf{L}\ _* + \lambda l(\mathbf{S}), \text{ s.t. } \mathbf{X} = \mathbf{L} + \mathbf{S}$		rpca	Robust PCA [2]
	$\min_{\mathbf{X}} \ \mathbf{X}\ _*, \text{ s.t. } \mathcal{P}_{\Omega}(\mathbf{X}) = \mathcal{P}_{\Omega}(\mathbf{M})$		lrnc	Low-rank matrix completion [1]
	$\min_{\mathbf{X}, \mathbf{E}} \ \mathbf{X}\ _* + \lambda l(\mathbf{E}), \text{ s.t. } \mathcal{P}_{\Omega}(\mathbf{X}) + \mathbf{E} = \mathbf{M}$		lrncR	Reg. Low-rank matrix completion
	$\min_{\mathbf{X}, \mathbf{E}} \ \mathbf{X}\ _* + \lambda l(\mathbf{E}), \text{ s.t. } \mathbf{A} = \mathbf{BX} + \mathbf{E}$		lrr	Low-rank representation [8]
	$\min_{\mathbf{Z}, \mathbf{L}, \mathbf{E}} \ \mathbf{Z}\ _* + \ \mathbf{L}\ _* + \lambda l(\mathbf{E})$ s.t. $\mathbf{XZ} + \mathbf{LX} - \mathbf{X} = \mathbf{E}$		latlrr	Latent low-rank representation [9]
	$\min_{\mathbf{X}, \mathbf{E}} \ \mathbf{X}\ _* + \lambda_1 \ \mathbf{X}\ _1 + \lambda_2 l(\mathbf{E})$ s.t. $\mathbf{A} = \mathbf{BX} + \mathbf{E}$		lrslr	Low-rank and sparse representation [18]
	$\min_{\mathbf{L}_i, \mathbf{S}_i} \ \mathbf{L}\ _* + \lambda \sum_{i=1}^m \ \mathbf{S}_i\ _1,$ s.t. $\mathbf{X}_i = \mathbf{L} + \mathbf{S}_i, i = 1, \dots, m, \mathbf{L} \geq 0, \mathbf{L1} = \mathbf{1}$		rmsc	Robust multi-view spectral clustering [16]
	$\min_{\mathbf{Z}_i, \mathbf{E}_i} \sum_{i=1}^K (\ \mathbf{Z}_i\ _* + \lambda l(\mathbf{E}_i)) + \alpha \ \mathbf{Z}\ _{2,1}$ s.t. $\mathbf{X}_i = \mathbf{X}_i \mathbf{Z}_i + \mathbf{E}_i, i = 1, \dots, K$		m1ap	Multi-task low-rank affinity pursuit [4]
	$\min_{\mathbf{L}, \mathbf{S}} \ \mathbf{L}\ _* + \lambda \ \mathbf{C} \circ \mathbf{S}\ _1, \text{ s.t. } \mathbf{A} = \mathbf{L} + \mathbf{S}, 0 \leq \mathbf{L} \leq \mathbf{1}$		igc	Improved graph clustering [3]
	$\min_{\mathbf{P}} \langle \mathbf{P}, \mathbf{L} \rangle + \lambda \ \mathbf{P}\ _1, \text{ s.t. } 0 \preceq \mathbf{P} \preceq \mathbf{I}, \text{Tr}(\mathbf{P}) = k$		sparsesc	Sparse spectral clustering [13]
Low-rank tensor models	$\min_{\mathcal{L}, \mathcal{S}} \sum_{i=1}^k \alpha_i \ \mathcal{L}_{i(i)}\ _* + \ \mathcal{S}\ _1, \text{ s.t. } \mathcal{X} = \mathcal{L} + \mathcal{S}$		trpca_snn	Tensor robust PCA based on sum of nuclear norm [5]
	$\min_{\mathcal{X}} \sum_{i=1}^k \alpha_i \ \mathcal{X}_{i(i)}\ _*, \text{ s.t. } \mathcal{P}_{\Omega}(\mathcal{X}) = \mathcal{P}_{\Omega}(\mathcal{M})$		lrtc_snn	Low-rank tensor completion based on sum of nuclear norm [10]
	$\min_{\mathcal{X}, \mathcal{E}} \sum_{i=1}^k \alpha_i \ \mathcal{X}_{i(i)}\ _* + \lambda l(\mathcal{E})$ s.t. $\mathcal{P}_{\Omega}(\mathcal{X}) + \mathcal{E} = \mathcal{M}$		lrtcR_snn	Reg. low-rank tensor completion based on sum of nuclear norm
	$\min_{\mathcal{L}, \mathcal{S}} \ \mathcal{L}\ _* + \lambda \ \mathcal{S}\ _1, \text{ s.t. } \mathcal{X} = \mathcal{L} + \mathcal{S}$		trpca_tnn	Tensor Robust PCA based on tensor nuclear norm [11]
	$\min_{\mathcal{X}} \ \mathcal{X}\ _*, \text{ s.t. } \mathcal{P}_{\Omega}(\mathcal{X}) = \mathcal{P}_{\Omega}(\mathcal{M})$		lrtc_tnn	Low-rank tensor completion based on tensor nuclear norm [11]
	$\min_{\mathcal{X}, \mathcal{E}} \ \mathcal{X}\ _* + \lambda l(\mathcal{E}), \text{ s.t. } \mathcal{P}_{\Omega}(\mathcal{X}) + \mathcal{E} = \mathcal{M}$		lrtcR_tnn	Reg. low-rank tensor completion based on tensor nuclear norm [11]

REFERENCES

- [1] E. Candès and B. Recht. Exact matrix completion via convex optimization. *Foundations of Computational mathematics*, 9(6):717–772, 2009.
- [2] E. J. Candès, X. D. Li, Y. Ma, and J. Wright. Robust principal component analysis? *Journal of the ACM*, 58(3), 2011.
- [3] Y. Chen, S. Sanghavi, and H. Xu. Improved graph clustering. *IEEE Transactions on Information Theory*, 60(10):6440–6455, 2014.
- [4] B. Cheng, G. Liu, J. Wang, Z. Huang, and S. Yan. Multi-task low-rank affinity pursuit for image segmentation. In *ICCV*, pages 2439–2446. IEEE, 2011.
- [5] D. Goldfarb and Z. Qin. Robust low-rank tensor recovery: Models and algorithms. *SIAM Journal on Matrix Analysis and Applications*, 35(1):225–253, 2014.
- [6] H. Lai, Y. Pan, C. Lu, Y. Tang, and S. Yan. Efficient k-support matrix pursuit. In *ECCV*, 2014.
- [7] Z. Lin, R. Liu, and H. Li. Linearized alternating direction method with parallel splitting and adaptive penalty for separable convex programs in machine learning. *Machine Learning*, 99(2):287–325, 2015.
- [8] G. Liu, Z. Lin, S. Yan, J. Sun, Y. Yu, and Y. Ma. Robust recovery of subspace structures by low-rank representation. *TPAMI*, 2013.
- [9] G. Liu and S. Yan. Latent low-rank representation for subspace segmentation and feature extraction. In *ICCV*, 2011.
- [10] J. Liu, P. Musialski, P. Wonka, and J. Ye. Tensor completion for estimating missing values in visual data. *TPAMI*, 35(1):208–220, 2013.
- [11] C. Lu, J. Feng, Y. Chen, W. Liu, Z. Lin, and S. Y. Yan. Tensor robust principal component analysis: Exact recovery of corrupted low-rank tensors via convex optimization. In *CVPR*. IEEE, 2016.
- [12] C. Lu, J. Feng, Z. Lin, and S. Yan. Correlation adaptive subspace segmentation by trace Lasso. In *ICCV*, 2013.
- [13] C. Lu, S. Yan, and Z. Lin. Convex sparse spectral clustering: Single-view to multi-view. *TIP*, 25(6):2833–2843, 2016.
- [14] R. Tibshirani. Regression shrinkage and selection via the lasso. *Journal of the Royal Statistical Society. Series B (Methodological)*, pages 267–288, 1996.
- [15] R. Tibshirani, M. Saunders, S. Rosset, J. Zhu, and K. Knight. Sparsity and smoothness via the fused lasso. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 67(1):91–108, 2005.

- [16] R. Xia, Y. Pan, L. Du, and J. Yin. Robust multi-view spectral clustering via low-rank and sparse decomposition. In *AAAI*, pages 2149–2155, 2014.
- [17] M. Yuan and Y. Lin. Model selection and estimation in regression with grouped variables. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 68(1):49–67, 2006.
- [18] L. Zhuang, H. Gao, Z. Lin, Y. Ma, X. Zhang, and N. Yu. Non-negative low rank and sparse graph for semi-supervised learning. In *CVPR*, pages 2328–2335. IEEE, 2012.
- [19] H. Zou and T. Hastie. Regularization and variable selection via the elastic net. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 67(2):301–320, 2005.