




# deep generative models

midjourney bot (2023)

# variational autoencoder

In an **autoencoder** the latent variable is not regularized, picking a random latent variable can generate garbage output.

A **variational autoencoder** solves this by mapping the input image to a distribution in the latent space, rather than a single point.




# generative adversarial network (GAN)


The generator learns to generate new data (i.e., fake data) similar to that of the problem domain.

The discriminator learns to identify whether the provided example is fake (comes from a generator ) or real (comes from the actual data domain).

Both the generator and the discriminator are trained together.




# generative adversarial networks






# generative adversarial networks



# generative adversarial networks


<https://this-person-does-not-exist.com/>

.




# conditional GAN

A conditional GAN conditions both the generator and the discriminator so they know which type they are dealing with.



# diffusion model


A diffusion model learns to denoise images blurred with Gaussian noise by learning to reverse the diffusion process.





# diffusion model

A diffusion model learns to denoise images blurred with Gaussian noise by learning to reverse the diffusion process.



# diffusion model


This de-noising process can be guided by an embedding of for instance a text prompt.

A popular approach is to use a Contrastive Language-Image Pretraining (CLIP) model to condition the de-noising.

The CLIP model is trained on image+caption data and learns to compute embeddings that are similar between the image and the caption.


# diffusion model

The CLIP model is trained on image+caption data and learns to compute embeddings that are similar between the image and the caption.



# diffusion model


The CLIP model is trained on image+caption data and learns to compute embeddings that are similar between the image and the caption.






# diffusion model

The CLIP model is trained on image+caption data and learns to compute embeddings that are similar between the image and the caption.




# diffusion model

The idea is to guide the de-noising procedure such the image embedding that is being created from the noise goes into the direction of the text embedding computed by CLIP.



# diffusion model


*RF Diffusion outperforms existing protein design methods across a broad range of problems, including topology-constrained protein monomer design, protein binder design, symmetric oligomer design, enzyme active site scaffolding, and symmetric motif scaffolding for therapeutic and metal-binding protein design.*



<https://www.bakerlab.org/2023/03/30/rf-diffusion-now-free-and-open-source/>

# diffusion model

Here RF Diffusion generates a novel protein that binds to the insulin receptor.



<https://www.bakerlab.org/2023/03/30/rf-diffusion-now-free-and-open-source/>