

A

A

B

B



C

C


D

D

Designator
modFOC-RC-Interface.SchDoc



modFOC-MCU.SchDoc
STM32 MCU and Peripherals



IO-SBUS-TX
IO-SBUS-RX

IO-GPIO-1
IO-GPIO-2
IO-GPIO-3
IO-GPIO-4

AUX-ADC1
AUX-ADC2

SCLK_H
MOSI_H
MISO_H
CS_0
CS_1
CS_2
CS_HRange


IO-UART-TX
IO-UART-RX

IO-SPI-NCS
IO-SPI-SCL
IO-SPI-MISO
IO-SPI-MOSI

IO-I2C-SCL
IO-I2C-SDA

USB-MCU

modFOC-Buck-Supply.SchDoc
Integrated Inductor Buck Supply



modFOC-ESC-Interface.SchDoc
ESC Interface



modFOC Peripheral Interfaces
modFOC-IO.SchDoc



Title **RcMPPT-Top SCC**

Size: A4

Number: 1

Revision: 2.0

Date: 17.03.2022

Time: 20:46:20




Sheet 1 of 7

File: modFOC-Top.SchDoc

RcMPPT
HTL St. Pölten
Thomas Hofmann
*
*



Board Interconnect
RcMPPT-BMS




Title RcMPPT-BMS-Interface		
Size: A4	Number: 8	Revision: 2.0
Date: 17.03.2022	Time: 20:46:20	Sheet 2 of 7
File: modFOC-ESC-Interface.SchDoc		

RcMPPT
HTL St. Pölten
Thomas Hofmann
*
*




5V Buck Regulator
Integrated Inductor

VBat: 3-12S Lipo/Lilon/LiFePo
VPanel: 6-60V



3.3V Linear Regulator



Title RcMPPT-Buck-Supply		
Size: A4	Number: 2	Revision: 2.0
Date: 17.03.2022	Time: 20:46:20	Sheet 3 of 7
File: modFOC-Buck-Supply.SchDoc		

RcMPPT
HTL St. Pölten
Thomas Hofmann
*
*



[illegible]


Place C500 close to D500 for optimal ESD suppression

Title <i>RcMPPT-Debug</i>		
Size: A4	Number: 6	Revision: 2.0
Date: 17.03.2022	Time: 20:46:21	Sheet 4 of 7
File: modFOC-Debug_SchDoc		


RcMPPT
HTL St. Pölten
Thomas Hofmann
*
*

RcMPPT


USB ESD Protection




USB




SPI



UART



I2C



Title **RcMPPT-IO**

Size: **A4**

Number: **5**

Revision: **2.0**

Date: **17.03.2022**

Time: **20:46:21**


Sheet **5** of **7**

File: **modFOC-IO.SchDoc**

RcMPPT
HTL St. Pölten
Thomas Hofmann
*
*


RcMPPT

STM32 MCU



Reset Button

Active low reset of MCU1
(debounce cap to prevent parasitic resets)




External HSE

Analog Supply Filtering

Analog VDD (additional filtering)

Decoupling Capacitors

BOOT Mode



Title **RcMPPT-MCU**

Size: **A4**

Number: **1**

Revision: **2.0**

Date: **17.03.2022**

Time: **20:46:21**





Sheet **6** of **7**



File: **modFOC-MCU.SchDoc**

RcMPPT
HTL St.Pölten
Thomas Hofmann


RcMPPT

GPIO Level Shift






Realistic View




Layer Stack Legend




Material	Layer	Thickness	Dielectric Material	Type	Gerber
Surface Material	Top Overlay			Legend	GTO
Copper	Top Solder	0.01mm	SM-001	Solder Mask	GTS
Prepreg	Top Layer	0.04mm		Signal	GTL
Copper	Mid Layer 1	0.21mm	PP-022	Dielectric	
Core	Mid Layer 2	0.02mm	Core-040	Signal	G1
Copper	Mid Layer 2	0.02mm		Dielectric	G2
Prepreg	Bottom Layer	0.21mm	PP-022	Signal	GBL
Copper	Bottom Solder	0.04mm		Solder Mask	GBS
Surface Material	Bottom Overlay	0.01mm	SM-001	Legend	GBO

Total thickness: 1.61mm


Top Layer (Scale 2:1)



Mid Layer 1 (Scale 2:1)



Mid Layer 2 (Scale 2:1)



Bottom Layer (Scale 2:1)

