

RadiPOP_API

Generated by Doxygen 1.9.2

1 Namespace Index	1
1.1 Packages	1
2 Hierarchical Index	3
2.1 Class Hierarchy	3
3 Class Index	5
3.1 Class List	5
4 File Index	7
4.1 File List	7
5 Namespace Documentation	9
5.1 config Namespace Reference	9
5.2 radipop_gui Namespace Reference	9
5.3 run_app Namespace Reference	9
5.3.1 Function Documentation	10
5.3.1.1 correctPartition()	10
5.3.1.2 drawOnMask()	11
5.3.1.3 extendThresholds()	11
5.3.1.4 getMask()	12
5.3.1.5 highlightOrgan()	12
5.3.1.6 initialize()	13
5.3.1.7 labelOrgan()	13
5.3.1.8 postPickleGetMask()	14
5.3.1.9 saveMasks()	15
5.3.1.10 updateMask()	15
5.3.2 Variable Documentation	15
5.3.2.1 app	16
5.3.2.2 FLASK_PORT	16
5.3.2.3 FLAST_HOST	16
5.3.2.4 host	16
5.3.2.5 patients	16
5.3.2.6 port	16
5.4 segmentation_utils Namespace Reference	16
5.4.1 Function Documentation	17
5.4.1.1 add_sobel_edges()	17
5.4.1.2 draw_region_outlines()	17
5.4.1.3 guess_bounds()	18
5.4.1.4 partition_at_threshold()	18
5.4.1.5 save_partition()	19
6 Class Documentation	21
6.1 BaseConfig Class Reference	21

6.1.1 Member Data Documentation	21
6.1.1.1 SECRET_KEY	21
6.2 DevelopmentConfig Class Reference	21
6.2.1 Member Data Documentation	22
6.2.1.1 DEBUG	22
6.3 ProductionConfig Class Reference	22
6.4 RadiPopGUI Class Reference	22
6.4.1 Detailed Description	24
6.4.2 Constructor & Destructor Documentation	24
6.4.2.1 __init__()	24
6.4.3 Member Function Documentation	24
6.4.3.1 correct_partition()	24
6.4.3.2 create_image_stream()	25
6.4.3.3 draw_on_image()	25
6.4.3.4 extend_labels()	25
6.4.3.5 find_organs()	26
6.4.3.6 highlightOrgan()	27
6.4.3.7 labelMask()	27
6.4.3.8 np_label_array_to_png()	27
6.4.3.9 read_pickle_mask_to_np_label_array()	28
6.4.3.10 readPNG()	28
6.4.3.11 save_masks()	29
6.4.3.12 slice_dim()	29
6.4.3.13 update_mask_upon_slider_change()	29
6.4.4 Member Data Documentation	30
6.4.4.1 last_clicked_x	30
6.4.4.2 last_clicked_y	30
6.4.4.3 LIVER_LABEL	30
6.4.4.4 masks	30
6.4.4.5 pathToSlices	31
6.4.4.6 patient_id	31
6.4.4.7 selected_pixel_value_of_label_mask	31
6.4.4.8 sliceCache	31
6.4.4.9 SPLEEN_LABEL	31
6.5 TestingConfig Class Reference	32
6.5.1 Member Data Documentation	32
6.5.1.1 DEBUG	32
7 File Documentation	33
7.1 /Users/lorenz/Desktop/RadiPOP-standalone/web_app/run_app.py File Reference	33
7.2 /Users/lorenz/Desktop/RadiPOP-standalone/web_app/utility/config.py File Reference	34
7.3 /Users/lorenz/Desktop/RadiPOP-standalone/web_app/utility/radipop_gui.py File Reference	34

7.4 /Users/lorenz/Desktop/RadiPOP-standalone/web_app/utility/segmentation_utils.py File Reference . .	34
Index	37

Chapter 1

Namespace Index

1.1 Packages

Here are the packages with brief descriptions (if available):

config	9
radipop_gui	9
run_app	9
segmentation_utils	16

Chapter 2

Hierarchical Index

2.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

BaseConfig	21
DevelopmentConfig	21
ProductionConfig	22
TestingConfig	32
RadiPopGUI	22

Chapter 3

Class Index

3.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

BaseConfig	21
DevelopmentConfig	21
ProductionConfig	22
RadiPopGUI	
Bridge between the flask server/API and the RadiPOP segmenter:	22
TestingConfig	32

Chapter 4

File Index

4.1 File List

Here is a list of all files with brief descriptions:

/Users/lorenz/Desktop/RadiPOP-standalone/web_app/ run_app.py	33
/Users/lorenz/Desktop/RadiPOP-standalone/web_app/utility/ config.py	34
/Users/lorenz/Desktop/RadiPOP-standalone/web_app/utility/ radipop_gui.py	34
/Users/lorenz/Desktop/RadiPOP-standalone/web_app/utility/ segmentation_utils.py	34

Chapter 5

Namespace Documentation

5.1 config Namespace Reference

Classes

- class [BaseConfig](#)
- class [DevelopmentConfig](#)
- class [ProductionConfig](#)
- class [TestingConfig](#)

5.2 radipop_gui Namespace Reference

Classes

- class [RadiPopGUI](#)

Bridge between the flask server/API and the RadiPOP segmenter:

5.3 run_app Namespace Reference

Functions

- def [correctPartition](#) ()
Reveives index to slice/mask + coordinates--> returns partion corrected mask as PNG to client.
- def [drawOnMask](#) ()
Reveives index to slice/mask + x,y coordinates --> returns drawn on mask as PNG to client.
- def [extendThresholds](#) ()
Reveives index to slice mask + label id --> returns highlighted mask as PNG to client.
- def [getMask](#) ()
Reveives index to slice/mask --> returns mask stored on flask server as PNG to client.
- def [highlightOrgan](#) ()
Reveives index of slice + x,y coordinates --> returns highlighted mask as PNG to client.
- def [initialize](#) ()

- *Receive Paths to ordered slices, caches slices.*
- `def labelOrgan ()`
Reveives index to slice mask + label id --> returns highlighted mask as PNG to client.
- `def postPickleGetMask ()`
Receives path to pickle file --> returns mask as PNG to client.
- `def saveMasks ()`
Reveives path, saves all stored masks as pickle files to path --> returns output path.
- `def updateMask ()`
Receives index of slice + slider values --> returns updated mask as PNG to client.

Variables

- `app = Flask(__name__)`
- `int FLASK_PORT = 4041`
- `string FLASK_HOST = '0.0.0.0'`
- `host`
- `dictionary patients = {}`
Dictionary which will hold for each patientID a RadiPopGUI object.
- `port`

5.3.1 Function Documentation

5.3.1.1 correctPartition()

```
def run_app.correctPartition ( )
```

Reveives index to slice/mask + coordinates--> returns partion corrected mask as PNG to client.

Parameters

<i>patientID</i>	The ID of the patient
<i>index</i>	The index of the slice for which to mask should be updated
<i>coordinates</i>	array of coordinates of the form [x0,y0,x1,y1,...,xn,yn]

Returns

JSON: {mask: byte stream} mask as transparent PNG as byte stream

Note: The coordinates array will be used to generate a line that cuts/divides the segmented organs.

Example handling of return image stream in js:

```
fetch(RadiPOP_states.FLASK_SERVER+"/labelOrgan", {
  method: 'POST',
  headers: { 'Content-Type': 'application/json' },
  body: JSON.stringify(data)
})
```



```
.then(function(response){ return response.json();})
.then(function(data){
bytestring = data["mask"];
img = bytestring.split('\')[1]
```

5.3.1.2 drawOnMask()

```
def run_app.drawOnMask ( )
```

Reveives index to slice/mask + x,y coordinates --> returns drawn on mask as PNG to client.

Parameters

<i>patientID</i>	The ID of the patient
<i>index</i>	The index of the slice for which to mask should be updated
<i>coordinates</i>	array of coordinates of the form [x0,y0,x1,y1,...,xn,yn]

Returns

JSON: {mask: byte stream} mask as transparent PNG as byte stream

Note: The coordinates array will be used to draw a line on the mask.

Example handling of return image stream in js:

```
fetch(RadiPOP_states.FLASK_SERVER+"/labelOrgan", {
  method: 'POST',
  headers: { 'Content-Type': 'application/json' },
  body: JSON.stringify(data)
})
.then(function(response){ return response.json();})
.then(function(data){
bytestring = data["mask"];
img = bytestring.split('\')[1]
```

5.3.1.3 extendThresholds()

```
def run_app.extendThresholds ( )
```

Reveives index to slice mask + label id --> returns highlighted mask as PNG to client.

Parameters

<i>patientID</i>	The ID of the patient
<i>index</i>	The index of the slice for which to mask should be updated
<i>left</i>	Extend labeling up to index-label
<i>right</i>	Extend labeling up to index+label

Returns

JSON: {left_most_idx: idx, right_most_idx: idx}

Note: The left_most_idx and right_most_idx correspond to the indices of the slices up to which the labeling has been extended. After the the function has finished use the function API's function /getMask to update the masks in your GUI. Example in js:

```
for (let index=parseInt(data["left_most_idx"]); index<parseInt(data["right_most_idx"])+1; index++) {
  $.post(FLASK_SERVER+"/getMask", {
    javascript_data: JSON.stringify({patienID: id, index: idx})
  })
}
```

5.3.1.4 getMask()

```
def run_app.getMask ( )
```

Reveives index to slice/mask --> returns mask stored on flask server as PNG to client.

Parameters

<i>patientID</i>	The ID of the patient
<i>index</i>	The index of the slice for which to mask should be updated

Returns

JSON: {mask: byte stream} mask as transparent PNG as byte stream

Example handling of return image stream in js:

```
fetch(RadiPOP_states.FLASK_SERVER+"/labelOrgan", {
  method: 'POST',
  headers: { 'Content-Type': 'application/json' },
  body: JSON.stringify(data)
})
.then(function(response){ return response.json();})
.then(function(data){
  bytestring = data["mask"];
  img = bytestring.split('\n')[1]
```

5.3.1.5 highlightOrgan()

```
def run_app.highlightOrgan ( )
```

Reveives index of slice + x,y coordinates --> returns highlighted mask as PNG to client.

Parameters

<i>patientID</i>	The ID of the patient
<i>index</i>	The index of the slice for which to mask should be updated
<i>x</i>	relative x coordinates ($0 \leq x \leq 1$)
<i>y</i>	relative y coordinates ($0 \leq y \leq 1$)

Returns

JSON: {mask: byte stream} mask as transparent PNG as byte stream

Example handling of return image stream in js:

```
fetch(RadiPOP_states.FLASK_SERVER+"/labelOrgan", {
  method: 'POST',
  headers: { 'Content-Type': 'application/json' },
  body: JSON.stringify(data)
})
.then(function(response){ return response.json(); })
.then(function(data){
  bytestring = data["mask"];
  img = bytestring.split('\')[1]
```

5.3.1.6 initialize()

```
def run_app.initialize ( )
```

Receive Paths to ordered slices, caches slices.

Parameters

<i>patientID</i>	The ID of the patient. Must be unique!
<i>paths</i>	An array with the paths to the slices

Returns

JSON: {message: message}

Note: Paths to slices !!!MUST BE ORDERED!!! 0,1,...,n

5.3.1.7 labelOrgan()

```
def run_app.labelOrgan ( )
```

Reveives index to slice mask + label id --> returns highlighted mask as PNG to client.

Parameters

<i>patientID</i>	The ID of the patient
<i>index</i>	The index of the slice for which to mask should be updated
<i>label</i>	Label of organ (1 for liver, 2 for spleen, 0 nothing, >2 other organ)

Returns

JSON: {mask: byte stream} mask as transparent PNG as byte stream

Example handling of return image stream in js:

```
fetch(RadiPOP_states.FLASK_SERVER+"/labelOrgan", {
  method: 'POST',
  headers: { 'Content-Type': 'application/json' },
  body: JSON.stringify(data)
})
.then(function(response){ return response.json();})
.then(function(data){
  bytestring = data["mask"];
  img = bytestring.split('\')[1]
```

5.3.1.8 postPickleGetMask()

```
def run_app.postPickleGetMask ( )
```

Receives path to pickle file --> returns mask as PNG to client.

Parameters

<i>patientID</i>	The ID of the patient
<i>index</i>	The index of the slice the mask refers to
<i>path</i>	The path to the mask file

Returns

JSON: {mask: byte stream} mask as transparent PNG as byte stream

Example handling of return image stream in js:

```
fetch(RadiPOP_states.FLASK_SERVER+"/labelOrgan", {
  method: 'POST',
  headers: { 'Content-Type': 'application/json' },
  body: JSON.stringify(data)
})
.then(function(response){ return response.json();})
.then(function(data){
  bytestring = data["mask"];
  img = bytestring.split('\')[1]
```

5.3.1.9 saveMasks()

```
def run_app.saveMasks ( )
```

Reveives path, saves all stored masks as pickle files to path --> returns output path.

Parameters

<i>patientID</i>	The ID of the patient
<i>index</i>	The index of the slice for which to mask should be updated

Returns

JSON: {outdir: path} path/directory to which the pickle files were written

5.3.1.10 updateMask()

```
def run_app.updateMask ( )
```

Receives index of slice + slider values --> returns updated mask as PNG to client.

Parameters

<i>patientID</i>	The ID of the patient
<i>index</i>	The index of the slice for which to mask should be updated
<i>liver-intensity-slider</i>	Slider value for liver intesity
<i>bone-intensity-slider</i>	Slider value for bone intesity
<i>blood-vessel-intensity-slider</i>	Slider value for blood-vessel intesity

Returns

JSON: {mask: byte stream} mask as transparent PNG as byte stream

Example handling of return image stream in js:

```
fetch(RadiPOP_states.FLASK_SERVER+"/labelOrgan", {
  method: 'POST',
  headers: { 'Content-Type': 'application/json' },
  body: JSON.stringify(data)
})
.then(function(response){ return response.json();})
.then(function(data){
  bytestring = data["mask"];
  img = bytestring.split('\')[1]
```

5.3.2 Variable Documentation

5.3.2.1 app

```
app = Flask(__name__)
```

5.3.2.2 FLASK_PORT

```
int FLASK_PORT = 4041
```

5.3.2.3 FLAST_HOST

```
FLAST_HOST = '0.0.0.0'
```

5.3.2.4 host

```
host
```

5.3.2.5 patients

```
dictionary patients = {}
```

Dictionary which will hold for each patientID a RadiPopGUI object.

Patients are added by the API's /initialize function

5.3.2.6 port

```
port
```

5.4 segmentation_utils Namespace Reference

Functions

- def [add_sobel_edges](#) (mask, img)
Smooth edges Steps:
- def [draw_region_outlines](#) (mask)
Color the mask light green.
- def [guess_bounds](#) (regions_map, reference_map)
Guess the bounds/labels of the region based on reference region Guess the bounds/labels of the region based on reference region (generally neighboring slice).
- def [partition_at_threshold](#) (img, thresh, square_size, min_size, title=None, show_plot=True)
After some smoothing, calculate new mask for img Steps:
- def [save_partition](#) (mask, path)

5.4.1 Function Documentation

5.4.1.1 add_sobel_edges()

```
def segmentation_utils.add_sobel_edges (
    mask,
    img )
```

Smooth edges Steps:

- Edge filter image using the Canny algorithm.
- euclidean distance transform

Parameters

<i>mask</i>	mask corresponding to image
<i>img</i>	image corresponding to mask

Returns

mask with smoothed edges

5.4.1.2 draw_region_outlines()

```
def segmentation_utils.draw_region_outlines (
    mask )
```

Color the mask light green.

Color the edges of the mask darker green.

Parameters

<i>mask</i>	mask for which to color the outlines
-------------	--------------------------------------

Returns

mask with colored outlines

5.4.1.3 guess_bounds()

```
def segmentation_utils.guess_bounds (
    regions_map,
    reference_map )
```

Guess the bounds/labels of the region based on reference region Guess the bounds/labels of the region based on reference region (generally neighboring slice).

Parameters

<i>regions_map</i>	mask to guess labels for
<i>reference_map</i>	reference mask (already labelled)

Returns

mask (labelled)

5.4.1.4 partition_at_threshold()

```
def segmentation_utils.partition_at_threshold (
    img,
    thresh,
    square_size,
    min_size,
    title = None,
    show_plot = True )
```

After some smoothing, calculate new mask for img Steps:

- gaussian filter,
- remove small objects,
- greyscale morphological closing,
- euclidean distance transform

Parameters

<i>img</i>	type numpy.ndarray
<i>thres</i>	Threshold value
<i>min_size</i>	Minimum size of an organ in the mask
<i>squaresize</i>	For greyscale morphological closing
<i>title</i>	Title of plot
<i>show_plot</i>	Show plot True/False

Returns

New binary mask (same size as img)

5.4.1.5 save_partition()


```
def segmentation_utils.save_partition (
    mask,
    path )
```


Chapter 6

Class Documentation

6.1 BaseConfig Class Reference

Inheritance diagram for BaseConfig:



Static Public Attributes

- `SECRET_KEY` = `os.getenv('SECRET_KEY', 'REPLACE ME')`

6.1.1 Member Data Documentation

6.1.1.1 SECRET_KEY


```
SECRET_KEY = os.getenv('SECRET_KEY', 'REPLACE ME') [static]
```

The documentation for this class was generated from the following file:

- `/Users/lorenz/Desktop/RadiPOP-standalone/web_app/utility/config.py`

6.2 DevelopmentConfig Class Reference

Inheritance diagram for DevelopmentConfig:



Static Public Attributes

- bool `DEBUG` = True

6.2.1 Member Data Documentation

6.2.1.1 DEBUG


```
bool DEBUG = True [static]
```

The documentation for this class was generated from the following file:

- /Users/lorenz/Desktop/RadiPOP-standalone/web_app/utility/[config.py](#)

6.3 ProductionConfig Class Reference

Inheritance diagram for ProductionConfig:



Additional Inherited Members

The documentation for this class was generated from the following file:

- /Users/lorenz/Desktop/RadiPOP-standalone/web_app/utility/[config.py](#)

6.4 RadiPopGUI Class Reference

Bridge between the flask server/API and the RadiPOP segmenter:

Public Member Functions

- def `__init__` (self, [patient_id](#))
Class constructor:
- def [extend_labels](#) (self, cur_idx, left_extend, right_extend)
Extend labels from current slice to neighbouring slices.
- def [highlightOrgan](#) (self, slice_idx, x, y)
Highlights regions of the mask (organs) that were clicked on by user.
- def [labelMask](#) (self, slice_idx, label)
Labels mask at given index at previously selected region.
- def [save_masks](#) (self, path)
Saves masks as pickle file to given path.
- def [slice_dim](#) (self)
Returns dimensions of slice images (x,y)

Static Public Member Functions

- def [correct_partition](#) (image)
Convert PNG mask to 1 channelled label mask.
- def [create_image_stream](#) (img)
Returns base64 bytestream for given input image.
- def [draw_on_image](#) (coordinates, img, correctionMode=False)
Draws a point or lines on given PNG image.
- def [find_organisms](#) (img, bones_thresh, blood_vessels_thresh, liver_thresh)
Uses three threshold values to find organs.
- def [np_label_array_to_png](#) (mask_np_array, highlight=None)
Takes an numpy label array dim(n,m,1) and returns a RGBA pillow image dim(n,m,4)
- def [read_pickle_mask_to_np_label_array](#) (path)
Opens mask pickle file and returns it as a np.array.
- def [readPNG](#) (path)
Reads an image (e.g.
- def [update_mask_upon_slider_change](#) (image, bone_intensity, blood_vessel_intensity, liver_intensity)
Sets threshold for liver intensity.

Public Attributes

- [last_clicked_x](#)
The x-coordinate of the region that was last selected/clicked on.
- [last_clicked_y](#)
The y-coordinate of the region that was last selected/clicked on.
- [masks](#)
Dictionary: key: mask index, value: mask numpy array dim(n,m,1)
- [pathToSlices](#)
List containing the path to the png slice files
- [patient_id](#)
ID of the patient.
- [selected_pixel_value_of_label_mask](#)
The label of the region that was last selected/clicked on.
- [sliceCache](#)
Dictionary: key: slice index, value: slice PNG.

Static Public Attributes

- int [LIVER_LABEL](#) = 1
Regions in mask with this label value are considered liver.
- int [SPLEEN_LABEL](#) = 2
Regions in mask with this label value are considered spleen.

6.4.1 Detailed Description

Bridge between the flask server/API and the RadiPOP segmenter:

Note:

- For each patient one object of this class should be instantiated.
- An object of this class contains all the slices and masks associated with the patient
- This class also contains static utility functions
- This class is the bridge between the flask server/API and the RadiPOP segmenter (segmentations_utils)

6.4.2 Constructor & Destructor Documentation

6.4.2.1 `__init__()`

```
def __init__ (
    self,
    patient_id )
```

Class constructor:

Parameters

<i>patient_id</i>	The ID of the patient. Must be unique!
-------------------	--

Note:

- For each patient one object of this class should be instantiated.
- An object of this class contains all the slices and masks associated with the patient

6.4.3 Member Function Documentation

6.4.3.1 `correct_partition()`

```
def correct_partition (
    image ) [static]
```

Convert PNG mask to 1 channelled label mask.

Parameters

<i>image</i>	Image (e.g.: RGBA PNG pillow)
--------------	-------------------------------

Returns

label mask

6.4.3.2 create_image_stream()

```
def create_image_stream (
    img ) [static]
```

Returns base64 bytestream for given input image.

Parameters

<i>img</i>	Image (e.g. Pillow PNG)
------------	-------------------------

Returns

img_base64 stream

6.4.3.3 draw_on_image()

```
def draw_on_image (
    coordinates,
    img,
    correctionMode = False ) [static]
```

Draws a point or lines on given PNG image.

Parameters

<i>coordinates</i>	List of the form [x0,y0,x1,y1,...,xn,yn]
<i>img</i>	Image (e.g.: RGBA PNG pillow)
<i>correctionMode</i>	True/False If true the drawn line acts as an eraser (dividing organs). If false a colored line is drawn on the image. DEFAULT: False

The modifications are made directly on the provided image. No return value

6.4.3.4 extend_labels()

```
def extend_labels (
```

```

        self,
        cur_idx,
        left_extend,
        right_extend )

```

Extend labels from current slice to neighbouring slices.

Parameters

<i>cur_idx</i>	Index of reference slice
<i>left_extend</i>	Number of slices to extend the labeling to below reference slice
<i>right_extend</i>	Number of slices to extend the labeling to above reference slice

Returns

(left_most_idx, right_most_idx) The index of the outermost slices to which the labeling was extended

Extends labels left and right from current slice How far the labels are extended is taken from left and right expansion bounds

6.4.3.5 find_organs()

```

def find_organs (
    img,
    bones_thresh,
    blood_vessels_thresh,
    liver_thresh ) [static]

```

Uses three threshold values to find organs.

Parameters

<i>image</i>	Image (e.g.: RGBA PNG pillow)
<i>bones_thresh</i>	bones threshold: [threshold, square_size , min_size]
<i>blood_vessels_thresh</i>	blood vessels threshold: [threshold, square_size , min_size]
<i>liver_thresh</i>	liver threshold: [threshold, square_size , min_size]

Returns

New labelled mask (same size as slice)

The algorithm is:

- After some smoothing, remove every pixel above bones threshold from the image.
- After some smoothing, remove every pixel above blood vessel threshold.
- Everything that then remains above liver threshold is called an organ.
- Use contiguous area divisions to roughly split into organs.

6.4.3.6 highlightOrgan()

```
def highlightOrgan (
    self,
    slice_idx,
    x,
    y )
```

Highlights regions of the mask (organs) that were clicked on by user.

Parameters

<i>slice_idx</i>	Index of mask/slice to be highlighted
<i>x</i>	x-coordinate of slice (in pixels)
<i>y</i>	y-coordinate of slice (in pixels)

Returns

Mask where the region specified by x and y is highlighted in brighther colors

6.4.3.7 labelMask()

```
def labelMask (
    self,
    slice_idx,
    label )
```

Labels mask at given index at previously selected region.

Parameters

<i>slice_idx</i>	Index of mask/slice to be labelled
<i>label</i>	Label to be assigned to previously selected region (either LIVER_LABEL or SPLEEN_LABEL)

Returns

Mask with new label

Note: It is expected that the client has before highlighted an organ with the function [self.highlightOrgan\(\)](#). This determines the region/organ that will be labelled with label.

6.4.3.8 np_label_array_to_png()

```
def np_label_array_to_png (
    mask_np_array,
    highlight = None ) [static]
```

Takes an numpy label array dim(n,m,1) and returns a RGBA pillow image dim(n,m,4)

Parameters

<i>mask_np_array</i>	numpy label array dim(n,m,1) @highlight Highlight regions where highlight==label in brighter color
----------------------	--

Returns

RGBA pillow image dim(n,m,4)

Turns a labelled mask into a transparent (RGBA) PNG.

- Default liver color is red (LIVER_LABEL)
- Default spleen color is blue (SPLEEN_LABEL)
- Default for other regions is green

6.4.3.9 read_pickle_mask_to_np_label_array()

```
def read_pickle_mask_to_np_label_array (
    path ) [static]
```

Opens mask pickle file and returns it as a np.array.

Parameters

<i>path</i>	Path to pickle file
-------------	---------------------

Returns

numpy array of mask

6.4.3.10 readPNG()

```
def readPNG (
    path ) [static]
```

Reads an image (e.g.

: PNG file) to numpy array

Parameters

<i>path</i>	Path to image
-------------	---------------

Returns

numpy array of image

6.4.3.11 save_masks()

```
def save_masks (
    self,
    path )
```

Saves masks as pickle file to given path.

Parameters

<i>path</i>	Path to which mask files should be written
-------------	--

Masks are written as .p (pickle) files

6.4.3.12 slice_dim()

```
def slice_dim (
    self )
```

Returns dimensions of slice images (x,y)

Returns

(x,y) Dimensions of slices

6.4.3.13 update_mask_upon_slider_change()

```
def update_mask_upon_slider_change (
    image,
    bone_intensity,
    blood_vessel_intensity,
    liver_intensity ) [static]
```

Sets threshold for liver intensity.

Parameters

<i>image</i>	Image (e.g.: RGBA PNG pillow)
<i>bones_thresh</i>	bones threshold
<i>blood_vessels_thresh</i>	blood vessels threshold
<i>liver_thresh</i>	liver threshold

Returns

New labelled mask

Steps:

- Sets thresholds for current slice
- Runs `self.find_organ`s on current slice with new thresholds

6.4.4 Member Data Documentation

6.4.4.1 `last_clicked_x`

```
last_clicked_x
```

The x-coordinate of the region that was last selected/clicked on.

6.4.4.2 `last_clicked_y`

```
last_clicked_y
```

The y-coordinate of the region that was last selected/clicked on.

6.4.4.3 `LIVER_LABEL`

```
int LIVER_LABEL = 1 [static]
```

Regions in mask with this label value are considered liver.

6.4.4.4 `masks`

```
masks
```

Dictionary: key: mask index, value: mask numpy array dim(n,m,1)

6.4.4.5 pathToSlices

`pathToSlices`

List containing the path to the png slice files

6.4.4.6 patient_id

`patient_id`

ID of the patient.

6.4.4.7 selected_pixel_value_of_label_mask

`selected_pixel_value_of_label_mask`

The label of the region that was last selected/clicked on.

6.4.4.8 sliceCache

`sliceCache`

Dictionary: key: slice index, value: slice PNG.

6.4.4.9 SPLEEN_LABEL

`int SPLEEN_LABEL = 2 [static]`


Regions in mask with this label value are considered spleen.

The documentation for this class was generated from the following file:

- `/Users/lorenz/Desktop/RadiPOP-standalone/web_app/utility/radipop_gui.py`

6.5 TestingConfig Class Reference

Inheritance diagram for TestingConfig:



Static Public Attributes

- bool `DEBUG` = True

6.5.1 Member Data Documentation

6.5.1.1 DEBUG

```
bool DEBUG = True [static]
```

The documentation for this class was generated from the following file:

- `/Users/lorenz/Desktop/RadiPOP-standalone/web_app/utility/config.py`

Chapter 7

File Documentation

7.1 /Users/lorenz/Desktop/RadiPOP-standalone/web_app/run_app.py File Reference

Namespaces

- namespace [run_app](#)

Functions

- def [correctPartition](#) ()
Reveives index to slice/mask + coordinates--> returns partion corrected mask as PNG to client.
- def [drawOnMask](#) ()
Reveives index to slice/mask + x,y coordinates --> returns drawn on mask as PNG to client.
- def [extendThresholds](#) ()
Reveives index to slice mask + label id --> returns highlighted mask as PNG to client.
- def [getMask](#) ()
Reveives index to slice/mask --> returns mask stored on flask server as PNG to client.
- def [highlightOrgan](#) ()
Reveives index of slice + x,y coordinates --> returns highlighted mask as PNG to client.
- def [initialize](#) ()
Receive Paths to ordered slices, caches slices.
- def [labelOrgan](#) ()
Reveives index to slice mask + label id --> returns highlighted mask as PNG to client.
- def [postPickleGetMask](#) ()
Receives path to pickle file --> returns mask as PNG to client.
- def [saveMasks](#) ()
Reveives path, saves all stored masks as pickle files to path --> returns output path.
- def [updateMask](#) ()
Receives index of slice + slider values --> returns updated mask as PNG to client.

Variables

- `app` = `Flask(__name__)`
- `int FLASK_PORT` = 4041
- `string FLASK_HOST` = '0.0.0.0'
- `host`
- `dictionary patients` = {}
Dictionary which will hold for each patientID a RadiPopGUI object.
- `port`

7.2 /Users/lorenz/Desktop/RadiPOP-standalone/web_↔ app/utility/config.py File Reference

Classes

- class `BaseConfig`
- class `DevelopmentConfig`
- class `ProductionConfig`
- class `TestingConfig`

Namespaces

- namespace `config`

7.3 /Users/lorenz/Desktop/RadiPOP-standalone/web_↔ app/utility/radipop_gui.py File Reference

Classes

- class `RadiPopGUI`
Bridge between the flask server/API and the RadiPOP segmenter:

Namespaces

- namespace `radipop_gui`

7.4 /Users/lorenz/Desktop/RadiPOP-standalone/web_↔ app/utility/segmentation_utils.py File Reference

Namespaces

- namespace `segmentation_utils`

Functions

- def `add_sobel_edges` (mask, img)
Smooth edges Steps:
- def `draw_region_outlines` (mask)
Color the mask light green.
- def `guess_bounds` (regions_map, reference_map)
Guess the bounds/labels of the region based on reference region Guess the bounds/labels of the region based on reference region (generally neighboring slice).
- def `partition_at_threshold` (img, thresh, square_size, min_size, title=None, show_plot=True)
After some smoothing, calculate new mask for img Steps:
- def `save_partition` (mask, path)

Index

`/Users/lorenz/Desktop/RadiPOP-standalone/web_app/run_app.py`, 33
`/Users/lorenz/Desktop/RadiPOP-standalone/web_app/utility/labelMask.py`, 34
`/Users/lorenz/Desktop/RadiPOP-standalone/web_app/utility/radipop_gui.py`, 34
`/Users/lorenz/Desktop/RadiPOP-standalone/web_app/utility/segmentation_utils.py`, 34
`__init__`
 RadiPopGUI, 24

`add_sobel_edges`
 segmentation_utils, 17

`app`
 run_app, 15

`BaseConfig`, 21
 SECRET_KEY, 21

`config`, 9
`correct_partition`
 RadiPopGUI, 24
`correctPartition`
 run_app, 10
`create_image_stream`
 RadiPopGUI, 25

`DEBUG`
 DevelopmentConfig, 22
 TestingConfig, 32
`DevelopmentConfig`, 21
 DEBUG, 22
`draw_on_image`
 RadiPopGUI, 25
`draw_region_outlines`
 segmentation_utils, 17
`drawOnMask`
 run_app, 11

`extend_labels`
 RadiPopGUI, 25
`extendThresholds`
 run_app, 11

`find_organs`
 RadiPopGUI, 26
`FLASK_PORT`
 run_app, 16
`FLASK_HOST`
 run_app, 16

`getMask`
 run_app, 12
`initialize`
 run_app, 13

`labelMask`
 RadiPopGUI, 27
`labelOrgan`
 run_app, 13
`last_clicked_x`
 RadiPopGUI, 30
`last_clicked_y`
 RadiPopGUI, 30
`LIVER_LABEL`
 RadiPopGUI, 30

`masks`
 RadiPopGUI, 30

`np_label_array_to_png`
 RadiPopGUI, 27

`partition_at_threshold`
 segmentation_utils, 18
`pathToSlices`
 RadiPopGUI, 30
`patient_id`
 RadiPopGUI, 31
`patients`
 run_app, 16
`port`
 run_app, 16
`postPickleGetMask`
 run_app, 14
`ProductionConfig`, 22

`radipop_gui`, 9
`RadiPopGUI`, 22
 __init__, 24
 correct_partition, 24
 create_image_stream, 25
 draw_on_image, 25

- extend_labels, 25
- find_organs, 26
- highlightOrgan, 26
- labelMask, 27
- last_clicked_x, 30
- last_clicked_y, 30
- LIVER_LABEL, 30
- masks, 30
- np_label_array_to_png, 27
- pathToSlices, 30
- patient_id, 31
- read_pickle_mask_to_np_label_array, 28
- readPNG, 28
- save_masks, 29
- selected_pixel_value_of_label_mask, 31
- slice_dim, 29
- sliceCache, 31
- SPLEEN_LABEL, 31
- update_mask_upon_slider_change, 29
- read_pickle_mask_to_np_label_array
 - RadiPopGUI, 28
- readPNG
 - RadiPopGUI, 28
- run_app, 9
 - app, 15
 - correctPartition, 10
 - drawOnMask, 11
 - extendThresholds, 11
 - FLASK_PORT, 16
 - FLAST_HOST, 16
 - getMask, 12
 - highlightOrgan, 12
 - host, 16
 - initialize, 13
 - labelOrgan, 13
 - patients, 16
 - port, 16
 - postPickleGetMask, 14
 - saveMasks, 14
 - updateMask, 15
- save_masks
 - RadiPopGUI, 29
- save_partition
 - segmentation_utils, 19
- saveMasks
 - run_app, 14
- SECRET_KEY
 - BaseConfig, 21
- segmentation_utils, 16
 - add_sobel_edges, 17
 - draw_region_outlines, 17
 - guess_bounds, 17
 - partition_at_threshold, 18
 - save_partition, 19
- selected_pixel_value_of_label_mask
 - RadiPopGUI, 31
- slice_dim
 - RadiPopGUI, 29
- sliceCache
 - RadiPopGUI, 31
- SPLEEN_LABEL
 - RadiPopGUI, 31
- TestingConfig, 32
 - DEBUG, 32
- update_mask_upon_slider_change
 - RadiPopGUI, 29
- updateMask
 - run_app, 15