

PHY 480 - Computational Physics

Project 1: Linear Algebra Methods

Thomas Bolden

February 12, 2016

Github Repository at <https://github.com/ThomasBolden/PHY-480-Spring-2016>

Abstract

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Contents

| | |
|------------------------|---|
| Introduction | 1 |
| Methods | 1 |
| Results | 2 |
| Conclusions | 2 |
| Code | 2 |

Introduction

An important skill in physics is being able to efficiently solve differential equations. There are many situations in which differential equations can be solved as a system of linear equations. Such equations are called linear second-order differential equations, of the form

$$\frac{d^2 y}{dx^2} + k^2(x)y = f(x) , \quad (1)$$

where $f(x)$ is the inhomogenous term, and k^2 is a real function.

An example of this being useful is in electromagnetism. Poisson's equation describes the electrostatic potential energy field Φ caused by a given charge density distribution ρ . The equation in three dimensions is

$$\nabla^2 \Phi = -4\pi\rho(\mathbf{r}) \quad (2)$$

where the electrostatic potential and charge density are spherically symmetric. This allows one to simplify the equation to one dimension

$$\frac{1}{r^2} \frac{d}{dr} \left(r^2 \frac{d\Phi}{dr} \right) = -4\pi\rho(r) \quad (3)$$

which can be rewritten using the substitution $\Phi(r) = \phi(r)/r$

$$\frac{d^2 \phi}{dr^2} = -4\pi r \rho(r). \quad (4)$$

Now, like equation (1), this is linear second order in r . This becomes clear when we let $k^2(r) = 0$, $f(r) = -4\pi r \rho(r)$. If we let $\phi \rightarrow u$ and $r \rightarrow x$, we get the general Poisson equation

$$-u'' = f(x). \quad (5)$$

If we apply certain boundary conditions, we can rewrite it as a set of linear equations. In this project, I explored several methods of solving systems of linear equations, including Gaussian elimination, LU decomposition, and analytically. In the section that follows, I outline the methods and algorithms used to write the C++ code, along with some examples of the output one should expect when running the code themselves. The next section contains the useful results. In it, I compare the run times and efficiency of each method used, along with the magnitude of the associated error. Finally, the source code is presented for reference.

Methods

Given a differential equation of the form

$$-\frac{d^2}{dx^2} u(x) = f(x) \quad (6)$$

where $f(x)$ is continuous on the domain $x \in (0, 1)$. We also assume the Dirichlet boundary conditions $u(0) = u(1) = 0$. We can define a discretized approximation second derivative of u as v_i with grid points $x_i = ih$ in the interval $x_0 = 0$ to $x_{n+1} = 1$, and with step lengths $h = 1/(n+1)$. The boundary conditions become $v_0 = 0 = v_{n+1}$. If the source term is $f(x) = 100e^{-10x}$, the exact

closed-form solution is $u(x) = 1 - (1 - e^{-10})x - e^{-10x}$. The second derivative of u can be approximated as

$$-u'' = -\frac{v_{i+1} + v_{i-1} - 2v_i}{h^2} = f_i \quad \text{for } i = 1, \dots, n \quad (7)$$

This equation can be written as a set of linear equations of the form

$$\mathbf{A}\mathbf{v} = \tilde{\mathbf{b}} \quad (8)$$

$$\mathbf{A} = \begin{bmatrix} 2 & -1 & 0 & \cdots & \cdots & \cdots & 0 \\ -1 & 2 & -1 & 0 & \cdots & \cdots & 0 \\ 0 & -1 & 2 & -1 & \ddots & & \vdots \\ \vdots & 0 & -1 & 2 & \ddots & \ddots & \vdots \\ \vdots & \vdots & \ddots & \ddots & \ddots & \ddots & 0 \\ \vdots & \vdots & & \ddots & \ddots & \ddots & -1 \\ 0 & 0 & \cdots & \cdots & 0 & -1 & 2 \end{bmatrix}, \quad \mathbf{v} = \begin{bmatrix} v_0 \\ v_1 \\ \vdots \\ \vdots \\ v_{n-1} \\ v_n \end{bmatrix}, \quad \tilde{b}_i = h^2 f_i$$

One way to solve tridiagonal matrices (like the one above) is Gaussian elimination. Basically, Gaussian elimination uses the first equation to eliminate the first unknown x_1 from the remaining equations, and continues this trend for the remaining equations until an upper triangular matrix is formed. An upper triangular matrix can be easily solved using back substitution. This process requires a total of $\frac{2n^3}{3} + \mathcal{O}(n^2)$ floating point operations. The general algorithm is below.

Algorithm 1 Gaussian Elimination

```

1: function GaussElim(A)
2:   for  $k = 1$  to  $n - 1$  do
3:     for  $i = k + 1$  to  $n$  do
4:        $a_{ik} = \frac{a_{ik}}{a_{kk}}$ 
5:       for  $j = k + 1$  to  $n + 1$  do
6:          $a_{ij} = a_{ij} - a_{ik} \times a_{kj}$ 
7:       end for
8:     end for
9:   end for
10: end function


```

Results

Conclusions

.

Code



../Code/Project1.cpp

```

1  /*
2
3  Project 1 a,b – Vector and Matrix Operations
4  Solving a tridiagonal matrix
5
6  */
7
8  #include <iostream>
9  #include <fstream>
10 #include <cmath>
11 #include <iomanip>
12 #include <string>
13 #include <armadillo>
14 #include "time.h"
15
16 using namespace std;
17 using namespace arma;
18
19 ofstream myfile;
20
21 // --- Functions --- \\
22
23 double f(double x){
24     return 100*exp(-10*x);
25 }
26
27 double analyze(double x){

```

```

28     return 1.0-(1-exp(-10))*x-exp(-10*x);
29 }
30
31 // --- Main --- \\
32
33 int main(){
34
35     // --- Declaration of Variables --- \\
36
37     int n;
38     string outfilename;
39
40     cout << "Dimensions of the nxn matrix: ";
41     while(!(cin >> n)){
42         cout << "Not a valid number! Try again: ";
43         cin.clear();
44         cin.ignore(numeric_limits<streamsize>::max(), '\n');
45     }
46     cout << "Enter a name for the output file: ";
47     cin >> outfilename;
48
49     // --- Body of the program --- \\
50
51     clock_t start , finish ;
52     start = clock();
53
54     double h = (1.0) / (n + 1.0);
55     double *x = new double[n+2];
56     double *tildeb = new double[n+1];
57     tildeb[0] = 0;
58
59     int *a = new int[n+1];
60     int *b = new int[n+1];
61     int *c = new int[n+1];
62
63     double *diag_temp = new double[n+1];
64
65     double *u = new double[n+2]; // Analytical solution
66     double *v = new double[n+2]; // Numerical solution
67
68     u[0] = 0;
69     v[0] = 0;
70
71     for (int i=0; i<=n+1; i++) {
72         x[i] = i*h;
73     }
74
75     for (int i=1; i<=n; i++) {
76         tildeb[i] = h*h*f(x[i]);
77         u[i] = analyze(x[i]);
78         a[i] = -1;
79         b[i] = 2;
80         c[i] = -1;
81     }

```

```

82
83     c[n] = 0;
84     a[1] = 0;
85
86     // Algorithm for finding v:
87     double b_temp = b[1];
88     v[1] = tildeb[1]/b_temp;
89     for (int i=2;i<=n;i++) {
90         diag_temp[i] = c[i-1]/b_temp;
91         b_temp = b[i] - a[i]*diag_temp[i];
92         v[i] = (tildeb[i]-v[i-1]*a[i])/b_temp;
93     }
94
95     // Row reduction; backward substitution:
96     for (int i=n-1;i>=1;i--) {
97         v[i] -= diag_temp[i+1]*v[i+1];
98     }
99
100    finish = clock() - start;
101
102    double proccesortime = ((double)finish)/CLOCKS_PER_SEC;
103
104    // --- writing results to file, to be read and graphed in python --- \\
105
106    myfile.open(outfilename);
107    //myfile << setiosflags(ios::showpoint | ios::uppercase); //sci notation
108    myfile << "Solution to tridiagonal matrix of size n=" << n << endl;
109    myfile << "Time elapsed = " << proccesortime << " seconds" << endl ;
110    myfile << "          x:                u(x):                v(x): " << endl;
111    for (int i=1;i<=n;i++) {
112        myfile << setw(15) << setprecision(8) << x[i];
113        myfile << setw(15) << setprecision(8) << u[i];
114        myfile << setw(15) << setprecision(8) << v[i] << endl;
115    }
116
117    myfile.close();
118
119    delete [] x;
120    delete [] tildeb;
121    delete [] a;
122    delete [] b;
123    delete [] c;
124    delete [] u;
125    delete [] v;
126
127    return 0;
128
129 }

```

../Code/plots.py

```

1  # -*- coding: utf-8 -*-
2  """
3  Created on Sun Feb 14 00:10:43 2016

```

```

4
5 @author: Thomas
6 """
7
8 # testing testing 123
9
10 import math
11 import matplotlib.pyplot as plt
12
13 def convert(rawdata):
14
15     x = []
16     u = []
17     v = []
18
19     file = open(rawdata , 'r')
20     valid_data = file.readlines()[3:]
21
22     for line in valid_data:
23
24         xuv = line.split()
25         x.append(float(xuv[0]))
26         u.append(float(xuv[1]))
27         v.append(float(xuv[2]))
28
29     file.close()
30
31     return x, u, v
32
33 x10 , u10 , v10 = convert('n=10')
34 x100 , u100 , v100 = convert('n=100')
35 x1000 , u1000 , v1000 = convert('n=1000')
36
37 exact = []
38
39 for value in x1000:
40
41     f = 1.0-(1-math.exp(-10))*value-math.exp(-10*value)
42
43     exact.append(f)
44
45 hfont = {'fontname':'Courier'}
46
47 fig , ax = plt.subplots(1)
48
49 ax.plot(x10,v10,'g-',label='n=10, v(x)')
50 ax.plot(x100,v100,'b-',label='n=100, v(x)')
51 ax.plot(x1000,v1000,'m-',label='n=1000, v(x)')
52 ax.plot(x1000,exact,'k—',label='Exact , u(x)')
53 ax.set_xlabel('x',**hfont)
54 ax.set_ylabel('u(x)',**hfont)
55 ax.legend(loc='lower left',fancybox='True')
56 ax.set_title('Comparing Solutions for Various Step Sizes',**hfont)
57 ax.grid()

```

58 `plt.show()`

References

- [1] M. Hjorth-Jensen, *Computational Physics*, University of Oslo (2013).
- [2] W. McLean, *Poisson Solvers*, Northwestern University (2004).