University of Portsmouth
BSc (Hons) Computer Science
Second Year

Operating Systems and Internetworking (`OSINT`)
M30233
September 2023 - January 2024
20 Credits

Thomas Boxall
up2108121@myport.ac.uk

Contents

Theme I

Operating Systems

Page 1

Lecture - Introduction

📅 2023-09-26   🕐 13:00   🎓 Tamer

1.1   Operating Systems

The *Operating System* is a special type of software which controls the hardware. It is not the desktop, as the desktop, start screen and any other GUI software is provided by a suite of *application level software* which exists at a higher level than that of the operating system. The operating system is only accessible by application programs, not directly from the user. The user cannot interact with the hardware directly.


Figure 1.1: Location of the operating system in relation to the user, applications and hardware

1.1.1   What does it do?

The operating system is a piece of systems software that manages the computer's hardware, resources and control processing. It allows multiple computational processes and users to share a processor

simultaneously, protect data from unauthorised access and keep independent input / output (I/O) devices operating correctly.

The operating system provides common services for application software, making developers lives easier as the hardware interfacing has already been done for them. Users cannot run any software application without it.

1.1.2 Characteristics of the Operating Systems

There are two key characteristics of the Operating System.

Extended Machine

The part of the Operating System which behaves as an *extended machine* deals with the Input / Output devices which involves reading and writing control registers, handling interrupts etc. If a mistake is made, it will crash the entire computer. The Operating system provides a cleaner, safer, higher level set of operations for doing these - thus making developers lives easier as they are less worried about the 'nitty gritty' of hardware handling.

Resource Manager

The part of the operating system which behaves as a *resource manager* deals with sharing the resources between the many different processes which are happening simultaneously. The OS arbitrates between the requests these processes make to make to I/O subsystems, memory, etc to ensure smooth functioning of the system.

1.2 Software Types

There are two key types of software - systems software and applications software.

1.2.1 System Software

Systems software is the software that controls the computer system and ultimately allows you to use the computer. This includes the operating system and utility programs. They allow tasks to be performed such as:

- enabling the boot process
- launching applications
- transferring files
- controlling hardware configuration
- managing files on the hard drive
- and protecting the machine from unauthorised use.

1.2.2 Application Software

Application software is software which allows the user to perform a specific task on the computer. They allow tasks to be performed such as:

- Word processing
- Playing games
- browsing the web
- listening to music

1.3   Central Processing Unit

The *Central Processing Unit* (or CPU for short), is the heart of the computer. It is sometimes also referred to as the processor, microprocessor or processing unit. The CPU's primary purpose is to interpret processes and execute instructions.

1.3.1   CPU Organisation

Modern CPUs are complex, containing many different components. All CPUs will contain a: control unit, Arithmetic Logic Unit, cache memory, and memory management unit. The inner workings of the CPU will be discussed futher in a later lecture.

The CPU processes a sequence of machine instructions. A single instruction might perform simple arithmetic on data values - typically individual words; or more data between memory and / or registers.

1.3.2   Registers

Registers are very fast storage built into the CPU. They are typically big enough to store one word of data. Nowerdays, this will usually be 64-bits however in the past, 32-bit words were common. Registers are small amounts of high-speed memory contained within the CPU which are used by the processor to store small amounts of data that is needed during processing. This could include: the address of the next instruction to be executed or the current instruction being decoded.

A CPU has many registers as they are commonly single purpose; they also play a key role in OS design because they form part of state of a computation. Most computer architecture provides a small set of General Purpose Registers (GPR). The program status word register is responsible for setting which mode the CPU is operating in.

Name	Use	Description
EAX	Accumulator	The default register for many additions and multiple instructions.
EBX	Base	Stores the base address during memory addressing.
EXC	Count	The default counter for repeat (REP) prefix instructions and LOOP instructions.
EDX	Data	Used for multiple and divide operations
ESI	Source Index	Store source index
EDI	Destination Index	Stores destination index
EBP	Base Pointer	Mainly helps in referencing the parameter variables passed to a subroutine
ESP	Stack Pointer	Provides the offset value within the program stack.

Table 1.1: GPR Registers and their purposes

1.4 Classification of Programming Languages

Higher level languages cannot interact directly with the hardware. High level language source code is *translated* into a series of low level languages - ultimately ending up with machine code that can interface with the hardware directly.

1.4.1 Assembly Language

Assembly Language is a symbolic form of machine code used by system programmers. It will generally have the same instructions as machine code but rather than the instructions being represented in binary or hexadecimal format - assembly language uses mnemonics, making it easier to read, write and understand the code.

The following two lines of code copy the contents of the `EAX` register to the `EBX` register then increases the value in the `EXB` register by 4. In a high level language, this would look something like: `b = a + 4`.

```
MOV EBX, EAX
ADD EBX, 4
```

The Intel assembler instruction set also includes the ability to access the content within a memory address. This is done by putting square brackets (`[]`) around the register containing the memory address to look in.

```
MOV ESI, 105672
MOV EAX, [ESI]
```

An I/O device, like a hard disk, will have an associated set of *ports* through which the device is controlled and data transferred. A range of ports will be associated with each device. The instruction `IN` and `OUT` are used to read or write to ports.

1.5 User and Kernel Modes

Typical CPUs support different modes of operation controlled by a register called the *Program Status Word* (recent X86 processors actually use bit 0 of the Control Register (CR0), when its set - we are in *User Mode* or *Protected Mode*).

When machine code executes while the CPU is in *user mode*, it can only use limited instructions, for example not the `IN` and `OUT` instructions.

When machine code executes while the CPU is in *kernel mode*, it can use privileged instructions - for example `IN` and `OUT`.

The Operating System will always run in Kernel Mode. Thus, enabling all I/O operations to be performed by the OS on behalf of application programs. This has multiple benefits: the OS keeps control over whats done with those I/O operations and it makes it easier for software developers as they don't have to worry about interfacing directly with hardware.

1.6 Interrupts

When an I/O controller (i.e. on a disk card) has requested data available, it must gain the attention of the CPU. This is because the CPU can't be focusing on just waiting for the disk as it has other processes it needs to service. Gaining attention of the CPU is done through asserting an electrical signal called an *interrupt*. When the CPU receives an interrupt - it must abandon the program its currently executing and instead execute specialised code to deal with the new event. Specialised

code takes form of *interrupt handlers* which are typically installed at boot time and run in kernel mode.

Interrupt handlers have a wide significance in operating systems - beyond their original role in processing data received from I/O controllers. They have a role in process scheduling and in the implementation of system calls - these two topics will be covered in later lectures. Inn some sense, the whole operating system is driven by variations on the theme of "interrupt handler".

Page 2

Lecture - Concurrency

📅 2023-10-03   🕐 13:00   🎓 Tamer

2.1   What is Concurrency

Concurrency: many things can be run at the same time.

In Computer Science, a concurrent system is a system where two or more computations are executing (literally of effectively) at the same time. This is different to a sequential system, however, as this is where a computation (or parts of a computation) are executed to completion, one after the other. A concurrent system is almost the same as a *parallel system*, where multiple computations are literally proceeding at the same time.

Concurrency is used in many different systems, including

- Multi-tasking operating systems, where many processes are runing at once;

- Individual applications like *web servers* that must be processing many "requests" at the same time;

- Multicore processors where a single application is running across more than one core;

- Parallel computers in general;

- Distributed systems in general

When discussing concurrency in operating systems, we are meaning it as multiple threads sharing the same core of the CPU by multitasking. However, in some cases where the CPU has more than one core, threads may be able to run on different cores truly in parallel.

2.2   Processes and Threads

A *thread* or *thread of control* is a specific sequence of instructions, which have been defined by a program or by a section of a program. Instruction sequences from one thread may run in parallel with, or be interleaved in an unpredictable way with, sequences from other threads.

Processes have one or more threads within them. A process will also have aomse additional structure associated with them, for example - address space. Every process has at least one control flow (thread), and may have many control flows. All control flows in the same process share the same address space.

2.3   Programming with Threads

Historically, programming languages may have come with special "parallel" constructs which can be used to write concurrent programs. Nowerdays, its more common to use *thread libraries*.

2.3.1 Occam Example

Occam, a programming language popular in the UK in the 1980s and 1990s, could be used to write parallel code with the `PAR` instruction where the subsequent `SEQ` instructions would be used define the blocks of code to run in sequence. Note that occam didn't have a `print` command however that phrase has been used for simplicity.

```
PAR
    SEQ
        x = 23
        print x
    SEQ
        y = 42
        print y
```

2.3.2 POSIX

POSIX (Portable Operating System Interface) is a low level library for thread programming, often for the C programming language - which is use in the implementation of the OS as it has good direct control over the hardware. Using POSIX, the code for a new thread is defined in a C function, where a parent thread (generally the *main programme*) calls the library function `pthread_create`, passing it a pointer to a function with the code for a new thread. A parent thread may create any number of threads, and children can create their own children etc. The following example shows creating and running a thread using POSIX in C, again there has been some simplifications to the syntax.

```
int main(int argc, char* argv[]){
    pthread_t thread;
    pthreasd_create(&thread, NULL, run, NULL);
    x = 23;
    print x;
}
void* run(void *){
    y = 42;
    print y;
}
```

2.3.3 Java

Threads in Java aren't as parallel-esque as occam or library-esque as C. Java doesn't contain explicit parallel constructs, but many features of the language have been carefully designed to support concurrency. Modifiers can be used on declarations and there are special constructs which all are carefully integrated into the Java Memory Model.

Thread creation in Java is similar to POSIX except it follows the object-oriented paradigm that Java uses. Threads can be defined in a class which extends `java.lang.Thread` in a function called `run`. To run the thread, create an object of the new class then call the `start` method on that object to being the thread.

```
public static void main(String[] args) {
    MyThread thread = new MyThread();
    thread.start();
    int x = 23;
    System.out.println (x);
    thread.join();
}
Public static class MyThread extends Thread {
```

```
    public void run() {
        int y = 42;
        System.out.println (y);
    }
}
```

The `join` method used in the main function is option. It waits until the child thread has completed before allowing execution of the main program to continue - hence synchronising between threads. POSIX has an equivalent function called `pthread_join`.

2.4   Non-Determinism

Non-Determinism is the idea that when we have multiple threads executing at exactly the same time, we don't know which will finish executing first. Therefore if these multiple threads all use the same variable then when the same code is run many times, it may result in different final values of that variable.

The number of possible orderings for a program with multiple threads to execute in grows exponentially with program size, this makes concurrent programs hard to design and debug because there are many possibilities to consider.

The following example, while a simple program, illustrates precisely why non-determinism is a bad thing. In the example there are two threads executing `A` and `B`. They are both performing operations on a shared variable `c`.

Code	Thread	c	x	y	Note
		0	-	-	initial
x = c	A	0	0	-	
c = x + 1	A	1	0	-	
y = c	B	1	0	1	
c = y + 1	B	2	0	1	final

Table 2.1: Example of non-determinism: trace 1

Code	Thread	c	x	y	Note
		0	-	-	initial
x = c	A	0	0	-	
y = c	B	0	0	0	
c = x + 1	A	1	0	0	
c = y + 1	B	1	0	0	final

Table 2.2: Example of non-determinism: trace 2

2.5   Interference

Interference is a more serious case of non-determinism. It would have been reasonable to expect that each thread increments the value of the variable `c` by 1 in the above example; therefore ending with `c` containing the value `2`. This kind of unpredictable behaviour, when concurrent threads adversely affect one anothers behaviours, is called interference. Similar, more serious, problems arise with shared access to more complex data structures.

2.5.1   Race Conditions

Interference situations may also be referred to as *race conditions*. This is because the outcome depends on which thread gets to a particular point of its programme first. In this module, *race conditions* and *interference* are essentially the same thing - even though race conditions also occur in distributed systems, without shared variables.

2.5.2   Avoiding Interference

There are a number of different ways to avoid interference in concurrent programs.

The simplest of these is to ensure that threads never have variables in common, which is essentially what happens with processes (whereby each process has a completely independent address space with no shared variables). However, in the underlying operating system, which is responsible for scheduling processes this solution is too restrictive.

Another solution is to make use of something called a *critical section*, this is where sections of the program that cannot happen at the same time are isolated from each other and a method is used to ensure they cannot update shared data structures at the same time. The methods used are called *Mutual Exclusions* which are a concept (so you can't eat or touch it) and will be covered further in the next lecture.

Theme II

Internetworking

Page 3

Lecture - Networking Services: DNS, DHCP, etc

📅 2023-09-25   🕘 09:00   🎓 **Thanos**

Follow up material for lectures will be posted on Moodle. This will commonly include LinkedIn Learning courses. Do them. Answers to Lab Sessions should be uploaded to our individual Wiki sections for each theme as pdf files. They will not be assessed but we may be asked to show them to Lab staff at some point.

3.1   Dynamic Host Configuration Protocol

Dynamic Host Configuration Protocol (DHCP) provides a set of important configuration parameters for devices which are connected to a network. These parameters include: IP address (this is required for any device to be able to talk on a network); router address (the address of the device which your communications has to go through to be passed onto the right place); subnet mask; and DNS server address.

DHCP was introduced in 1993, before DHCP - IP addresses were manually assigned to each device on the network. Whilst, this was a viable option and can still be done to this day - it makes network administrators lives much more complicated. There was also the Bootstrap Protocol (BOOTP) as DHCP supports temporary leases of IP addresses to clients with minimal human interaction. DHCP servers are compatible with BOOTP clients.

For DHCP to work on a network, you require a DHCP server. This commonly is built into modern domestic routers however in larger organisations - a separate (virtual) server will be used.

When a client is shut down or it terminates its connection to the internet - it releases it's IP address. This IP address is returned to the IP pool which means it is then available for another client to use. IP address leases are automatically renewed when 50% of the lease time is used. This works by a request to the original DHCP server. If its not available then the request is broadcast to all available DHCP servers. The IP address lease gets renewed as it prevents the need for a new IP address to be assigned.

We use DHCP for a number of reasons: it saves the network administrator from a lot of manual configuration; it allows devices to move from one network to another and gain instant connectivity (there may be conflicting devices if static IPs were used); it allows for more efficient utilisation of available IP addresses (whereby inactive clients do not obtain IP addresses).

There are, however, a number of disadvantages to using DHCP: DHCP packets are UDP packets which means they are unreliable and insecure; there is a potential for unauthorised clients obtaining IP addresses which would then make them appear legitimate (this can be avoided by using MAC address filtering); and there is potential for malicious DHCP clients and server which could lead to

incorrect configuration parameters being supplied to clients and / or the IP pool being exhausted.


Figure 3.1: DHCP Initial Message Flow

3.1.1　Terminology

DHCP Packet DHCP Message

DHCP Client Client

DHCP Server Server

Lease Length of time a DHCP client can use a specified IP address

3.2　Domain Name System

Domain Name System (DNS) is the mechanism by which Internet Software translates names to attributes such as IP addresses. Architecturally, DNS is a globally distributed, scalable and reliable database which is comprised of three components: a *namespace*, *servers* (makes the namespace available) and *resolvers* (clients - these query the servers about the namespace).

DNS exists to make users' use of the internet easier. Users generally prefer names (`thomasboxall.net`) to numbers however computers usually prefer numbers (`145.14.152.146`) to names. DNS provides the mapping between the *domain names* and *IP addresses of servers.*

DNS is distributed globally throughout many different devices. No single computer holds all the DNS data, however some remote DNS data is locally cached to improve performance. DNS lookups can be performed by any device. DNS lookups can be performed by any device. On UNIX systems, the

command `dig` provides this utility.

The DNS database is always internally consistent. This is achieved by each version of a subset of the database (a zone) having a serial number which is incremented on every database change. Changes to the master copy of the database are replicated according to timing set by the zone administrator, generally this is quite frequent. Cached data expires according to a timeout set by a zone administrator. While there is no limit to the size of the DNS database, common sense dictates that its not a good idea to store 200,000,000 domain names in the same database as there is no limit to the number of queries. This can lead to 10,000+ queries being sent each second which are handled easily. Queries are distributed among primary and secondary DNS servers as well as caches. The `nslookup` command will tell you where it has obtained the DNS information from.

Due to DNS data being replicated from the primary to multiple secondary servers, there is high levels of reliability. Clients will typically query local caches first, and if they do not contain the data requested then the queries will be passed to either the primary server or any secondary server. DNS uses both UDP and TCP (port 53) for different things: TCP is used for intra-server communications and UDP is used for communications between clients and servers.

The DNS database can be updated dynamically. This includes teh addition, deletion or modification of any record. However, it is only the primary server which can be dynamically updated. The modification of the primary database triggers replication to all the secondary databases.

3.3   Domain Names

A domain name is the sequence of labels from a node to the root, separated by dots (`.`) which is read from left to right. The namespace has a maximum depth of 127 levels and domain names are limited to 255 characters in length. A nodes domain name identifies its position in the namespace.

One domain is a subdomain of another if its domain name ends in the other's domain name.
Name servers store information about the namespace in units called *zones*. The nameservers that serve a complete zone are said to *have authority* or *be authoritative for* the zone. More than one name server can be authoritative for the same zone, ensuring redundancy and load spreading. Also, a single name server may be authoritative for many zones. There are two types of Name Servers: *authoritative* which maintains the data (has subtypes of primary and secondary) and *non-authoritative* which caches the authoritative server. No special hardware is needed for a name server.

Name resolution is the process by which local resolvers and the nameservers cooperate to find data in the namespace. Upon receiving a query from a resolver, a name server:

1. looks for the answer in its authoritative data and its cache.

2. if step 1 fails, the answer must be looked up through other servers (this can either be done recursively or iteratively).

Page 4

Lecture - IP Addresses & Subnetting

📅 2023-10-02　　　　🕘 09:00　　　　🎓 **Thanos**

NB: This page also covers this lecture and the following week's (2023-10-09) as the same slide deck & topic was split across two weeks.

4.1　Layer 3 Functionalities

Layer 3, in the OSI model, handles the routing of the data by delivering it to the correct destination. It is the layer which allows networks to communicate with each other.

The functionalities of layer 3 are spread all over the network - in ad hoc hardware (routers) and in PCs (through routing software by the operating systems)

4.1.1　Internet Protocol, a reminder

The Internet Protocol, IP, is a connectionless protocol which delivers datagrams through best effort delivery. This means it's not 100% efficient at delivering data however it will try its best to deliver the data its supposed to deliver. Naturally, this introduces a level of unreliability - as there is no guarantee of orderly delivery. However, there is an error checking algorithm used whereby if the buffer is full or the error check fails, the packet is discarded and another protocol may issue the send again command.

The Internet Protocol also has a number of functions when used in data transmission and receiving. In transmission: encapsulates data from the transport layer into datagrams and prepares headers (the source and destination addresses, etc) as well as applying routing algorithms at routers and forwarding the datagram to the Network Interface Card of the device which is transmitting the datagram. When receiving, IP: checks the validity of incoming datagrams then reads the header; it then checks if forwarding is required and if it is, then it will send to the appropriate network interface to forward the packet and if not requried then it will pass the payload to the next upper layer of the OSI model.

The Internet Protocol also provides us with IP addresses, its this which we will focus on for the majority of the lecture.

4.2　IP Addresses

An IP address is a unique identifier used to identify different devices on the network. In regular operation, there are two types - *IPv4* and the newer *IPv6*. We will primarily be focusing on IPv4.

IPv4 uses a 32-bit string which has two notations.

System Notation uses a 32-bit string of binary.
　　　　For example `10010011101000110001010000001001`

Dotted Notation (bin) uses a 32-bit string of binary, with the bits divided into bytes.
For example `10010011.10100011.00010100.00001001`

Dotted Notation (dec) uses decimal representtion of the binary numbers, this is the most common to see as it is the most human friendly. As each section of the IP address is a byte, the range of decimal values is 0 to 255 inclusive..
For example, `147.162.20.9`

4.2.1 IP Address Structure

Any IPv4 address is portioned into two fields. The first being the *network address* and the second being the *host address*. The network address is the same for every device on the network (e.g. `192.168.xxx.xxx`) and the host address is the part which uniquely identifies that device on the network (e.g. `xxx.xxx.101.236`).

4.2.2 Classful IP Addresses

There are two ways to use IP Addresses, *classful* and *classless*. Classful is the older method which is being used less however we will cover this first the conver classless later in the module.

In classful IP addressing, the network ID can either be 8, 12 or 24 bits in length (this is either 1, 2, or 3 blocks). The first bits of the NetworkID, as shown in the diagram below, indicate which class a IP address belongs to.

0 NET ID (8 bit)	HOST ID (24 bit)

Class A

1 0 NET ID (16 bit)	HOST ID (16 bit)

Class B

1 1 0 NET ID (24 bit)	HOST ID (8 bit)

Class C

Figure 4.1: Primary IP address classes and structure

There are also two additional classes, these are shown below.

| 1 | 1 | 1 | 0 | Multicast Group ID (28 bit) |

Class D: IP Multicasting

| 1 | 1 | 1 | 1 | reserved |

Class E: reserved for experimental use

Figure 4.2: Primary IP address classes and structure

The table below shows the dotted decimal ranges which are allocated for the different classes.

Address Class	Start IP range	End IP range
Class A	1.xxx.xxx.xxx	126.xxx.xxx.xxx
Class B	128.0.xxx.xxx	191.255.xxx.xxx
Class C	192.0.0.xxx	223.255.255.xxx
Class D	224.xxx.xxx.xxx	239.xxx.xxx.xxx
Class E	240.xxx.xxx.xxx	255.xxx.xxx.xxx

Table 4.1: Dotted Decimal ranges for classful IP addresses

Despite the ranges shown above, there are some reserved IP address ranges for different purposes. These are shown below.

Start IP range	End IP range	Purpose	Class
`10.0.0.0`	`10.255.255.255`	Non-Internet Routable LAN use	A
`127.0.0.0`	`127.255.255.255`	Localhost loopback address	-
`172.16.0.0`	`172.31.255.255`	Non-Internet Routable LAN use	B
`192.168.0.0`	`192.168.255.255`	Non-Internet Routable LAN use	C

Table 4.2: Dotted Decimal ranges for classful IP addresses

When referring to a network address of a given IP address, then all the HostID bits should be set to `0`. For example, the IP address `12.25.89.124` has the HostID of `12.0.0.0`.

4.3   Subnetting

IPv4 provides us a theoretical maximum of 4,294,967,296 unique IP addresses. These are broken into three classes

Class C provides 254 assignable host addresses ($2^8 - 2$)

Class B provides 65534 assignable host addresses ($2^{16} - 2$)

Class A provides 16,777,214 assignable host addresses ($2^{24} - 2$)

This is a very inflexible system, as there are only three boxes which everyone must fit into.

4.3.1   Usable Host Addresses

The number of usable host addresses for a given IP range can be calculated from the formula: total number of host addresses minus 2.

The following example will show this:

- You have been assigned a class B network address (`1928.147.0.0`)

- This gives the IP range `128.147.0.0 - 128.147.255.255`

- However! The first assignable address of it is `128.147.0.1` as `128.147.0.0` is the network address which is not assignable

- The last assignable address is `128.147.255.254` as `128.147.255.255` is the network's broadcast address - which is not assignable.

4.3.2   Introduction to Subnetting

Subnetting is the process of dividing one big network into several *subnetworks*. Each subnet behaves as a physical network however they are not physically separated, just logically separated.

We use subnetting because despite the fact, for a class B network, we can accommodate 65534 hosts - its inefficient to do this and is a pain to manage. There are also performance drawbacks to not subnetting.

When subnetting, we introduce a new component of the IP address. n-bits of the HostID now become a SubnetID. This is used to identify the subnet. Commonly, for class B IP addresses, this is the third byte.

4.3.3   Subnet Address and Mask

In this example, we use the host IP address of `148.197.9.18` (`10010100.11000101.00001001.00010010`). As this is a Class B IP address, it has the default subnet mask of `255.255.0.0` (`11111111.1111111.00000000.00000000`).

We now create a *Custom Subnet Mask*, which is decided by the network admin and will be longer than the default class mask. It tells us where the new boundary between the NetworkID and HostID is. We will set the custom subnet mask to `/21`, the subnet mask now reads as `255.255.248.0` (`11111111.11111111.11111000.00000000`).

Ultimately, this gives us a new (sub)network ID of `148.197.8.0/21` (`10010100.11000101.00001000.00000000`)

4.3.4 How Many Subnets and Hosts?

The number of subnets you can create is calculated from the formula 2^n where n is the number of bits used to create the SubnetID. For example, if the SubnetID is `255`, this uses 8-bits therefore $2^8 = 256$ subnets.

As the SubnetID is 8 bits long, this leaves the HostID with 8-bits. The number usable hosts per subnet can be calculated with the formula $2^n - 2$ where n is the number of bits in the HostID. Using the above example, where the SubnetID is 8 bits therefore the HostID is 8 bits, we get $2^8 - 2 = 254$ usable host addresses. But why do we have to subtract 2. We have to subtract 2 from the total number of Host addresses because when the HostID bits are all 1s, this is the broadcast address for that network and where the HostID bits are all 0's is reserved for *that* device on the network.