16.216: ECE Application ProgrammingSpring 2015

Lecture 17: Key Questions March 9, 2015

4	_ 1 :	1 .		- 1	1			. 1		\sim
1	Explain	what a	pointer is	and	how	we can	use	them	ın	C
- •		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	P C 1110 0 1 1	,,			•••	****		

2. Explain the use of passing function arguments by address.

3. What does the following program print?

```
#include <stdio.h>
#include <math.h>
void get r theta(double a, double b,
     double *adr r, double *adr th);
void main()
{
 double x, y, h, r, th;
 printf("Enter x, y components of vector: ");
 scanf("%lf %lf",&x,&y);
 get r theta(x,y,&r,&th);
 printf("Vector with x=%lf and y=%lf
      has r=%lf, theta=%lf\n",x,y,r,th);
}
void get r theta(double a, double b,
          double *adr r, double *adr th) {
 double sum;
 sum = pow(a,2) + pow(b,2); //or a*a+b*b;
 *adr r = sqrt(sum);
 *adr th = atan2(y, x);
}
```

4. **Example:** What does the following print?

```
int f(int *a, int *b);
int main() {
   int x = 1;
   int y = 2;
   int result1, result2, result3;
   result1 = f(&x, &y);
   result2 = f(&y, &result1);
   result3 = f(&result1, &result2);
   printf("x = %d, y = %d\n", x, y);
   printf("Result 1: %d\n", result1);
   printf("Result 2: %d\n", result2);
   printf("Result 3: %d\n", result3);
   return 0;
}
int f(int *a, int *b)
   int copyB = *b;
   while (*a > 1) {
      *b += copyB;
      (*a)--;
   }
   return *b;
}
```