

16.216: ECE Application Programming

Fall 2014

Lecture 25: Key Questions

November 7, 2014

1. Explain how `fread()` and `fwrite()` are used for unformatted I/O.
2. Explain how to check that the end of a file has been reached, or if an error has occurred.

3. Describe the functions used for character I/O.

- 3

6. **Example:** Show the output of each of the following short program.

a. Input: **Test Input** **1** **23 4 5**

```
void main() {  
    char c;  
    char buffer[50];  
    int i, n;  
    i = 0;  
    while ((c = fgetc(stdin)) != '\n') {  
        if (c != ' ') {  
            buffer[i++] = c;  
        }  
    }  
    buffer[i] = '\0';  
    fputs(buffer, stdout);  
}
```

b. Input:

Test1

Test 2

abcdefghijklmnopqrstuvwxyz

This is a test of the fgets() function

```
void main() {  
    char str[25];  
    int i;  
    for (i = 0; i < 5; i++) {  
        fgets(str, 24, stdin);  
        strcat(str, "\n");  
        fputs(str, stdout);  
    }  
}
```

c. Input:

1024Some other stuff

```
void main() {
    char c;
    char buffer[50];
    int n = 0;

    // isdigit in <ctype.h>
    while (isdigit(c = getchar())) {
        n = n * 10 + (c - 48);    // Hint: '0' = 48    }
        // (ASCII value)
    ungetc(c, stdin);
    fgets(buffer, 50, stdin);

    printf("n = %d, n * 2 = %d\n", n, n * 2);
    printf("buffer = %s\n", buffer);
}
```