

16.216: ECE Application Programming

Summer 2013

Lecture 2: Key Questions July 11, 2013

1. What are the basic binary arithmetic operators supported by C?
2. Explain the modulus operator (%).
3. What determines the type of a binary operation's result?
4. What is the difference between division of integers and floating-point types?

5. Explain the operation of the unary negation operator (e.g., $-x$).
6. **Example:** Evaluate each of the following expressions, including the type (`int` or `double`) in your answer.
- a. $19/3$
 - b. $3/19$
 - c. $19\%3$
 - d. $3\%19$
 - e. $5 + 7/2$
 - f. $5.0 + 7/2$
 - g. $5 + 7.0/2$
 - h. $5 * 3 \% 3 / 6 + 14 + 10 / 2$
 - i. $5 * (3 \% 3) / 6 + 14.0 + 10/3$

7. Describe the use of `printf()` to print numeric values and characters.

8. **Example:** Show the output of each of the following short programs:

a.

```
#include <stdio.h>
void main()
{
    int i=2, j=3, k, m;
    k = j * i;
    m = i + j;
    printf("%d %d %d %d\n", i, j, k, m);
}
```

b.

```
#include <stdio.h>
void main() {
    double f, g;
    f = 1.0 / 4.0;
    g = f * 20;
    printf("f = %lf,\ng = %lf\n", f, g);
}
```

c.

```
#include <stdio.h>
void main() {
    int a = 5, b = 2;
    printf("Output%doesn't%make%sense", a, b, a + b);
}
```

9. Describe the use of `scanf ()` for reading input values into variables.

10. How does `scanf ()` handle whitespace and other characters in format string?

a. Input: 34 5.7
scanf("%d%lf", &i, &d)

```
b. Input: 34 5.7
scanf ("%d %lf", &i, &d)
```

c. Input: 34 5.7
scanf("%lf%d", &d, &i)

d. Input: 34 5.7
scanf("%d%c", &i, &c)

e. Input: 34 5.7
scanf(" %d %c", &i, &c)

12. Describe the basic elements of a flowchart.

13. Design a flowchart to solve the following:

- Prompt a user to enter four numbers on a single line, which represent the contents of a 2x2 array
- After reading the values, your program should print the matrix represented by these values
 - For example, if the user enters “1 2 3 4”, print:
1 2
3 4
 - Assume all values have the same number of digits
- Also, calculate the matrix discriminant and print it on a separate line
 - In the example above, discriminant = $(1 \times 4) - (2 \times 3) = 4 - 6 = -2$

14. Convert the flowchart you wrote into a C program.

15. Explain the useful features of a debugger.

Note: At this point, we'll run through the use of the Visual Studio debugger; feel free to use this space to take notes on that demonstration.