## 16.317: Microprocessor Systems Design I

Spring 2013

Lecture 20: Solution to Key Questions March 22, 2013

```
a. int fact(int n)
Given a single integer argument, n, return n! = n × (n - 1) × (n - 2) × ... × 1

Solution: Here's a C version of the function, followed by the assembly code that implements it:
    int fact(int n) {
        int i;
        int fact = 1;

        for (i = n; i > 1; i--)
            fact *= i;

        return fact;
}
```

Assembly code for factorial function:

```
fact
         PROC
                                 ; Start of subroutine
  push
          ebp
                                 ; Save ebp
          ebp, esp
  mov
                                 ; Copy ebp to esp
  sub
                                 ; Create space for i, fact
         esp, 8
; CODE FOR: int fact = 1;
         DWORD PTR -8[ebp], 1
                                 ; fact = 1
  mov
; CODE FOR: i = n;
         eax, DWORD PTR 8[ebp]; eax = n
  mov
         DWORD PTR -4[ebp], eax ; i = n
  mov
; CODE FOR i > 1
L1:
         DWORD PTR -4[ebp], 1 ; Compare i to 1
  cmp
                                 ; If i <= 1, exit loop
  jle
         L2
; CODE FOR: fact *= i;
         eax, DWORD PTR -8[ebp] ; eax = fact
         eax, DWORD PTR -4[ebp] ; eax = fact * i
  imul
  mov
         DWORD PTR -8[ebp], eax ; fact = eax = fact * i
; CODE FOR: i--;
         eax, DWORD PTR -4[ebp]; eax = i
  mov
         eax, 1
  sub
                                 ; eax--
  mov
         DWORD PTR -4[ebp], eax ; i = eax = i - 1
         L1
                                 ; Return to loop start
  jmp
; CODE FOR: return fact;
L2:
         eax, DWORD PTR -8[ebp]; Copy fact to eax, which
  mov
                                 ; holds return value
; CLEANUP
                                 ; Clear space for i, fact
  mov
          esp, ebp
  pop
          ebp
                                 ; Restore ebp
                                 ; Return from subroutine
  ret
fact
         ENDP
```

Given two integer arguments, return the largest of the two values.

```
Solution: Here's a C version of the function, followed by the assembly code that implements it:
  int max(int v1, int v2) {
     if (v1 > v2)
          return v1;
     else
          return v2;
  }
max
          PROC
                                    ; Start of subroutine
                                    ; Save ebp
  push
          ebp
  mov
          ebp, esp
                                    ; Copy ebp to esp
                                    ; No local variables
; CODE FOR: if (v1 > v2)
          eax, DWORD PTR 8[ebp]
                                    ; eax = v1
  mov
  cmp
          eax, DWORD PTR 12[ebp] ; Compare v1 to v2
                                    ; Jump to L1 if v1 <= v2
  jle
          L1
                                    ; ((v1 > v2) \text{ is false})
; CODE FOR: return v1;
  jmp
          L2
                                    ; Jump to L2
                                    ; Return value (v1) is
                                        already in eax
                                    ; L2 is start of
                                        "cleanup" code
; CODE FOR: else
                return v2;
;
L1:
          eax, DWORD PTR 12[ebp] ; Copy v2 into eax
  mov
                                    ; eax always holds
                                    ; function return value
; CLEANUP
L2:
          ebp
                                    ; Restore ebp
  pop
                                    ; Return from subroutine
  ret
max
          ENDP
```

```
c. void swap(int *a, int *b)
```

Given two memory addresses, a and b, swap the contents of those addresses. You may assume a and b are offsets into the data segment.

**Solution:** Here's a C version of the function, followed by the assembly code that implements it:

```
void swap(int *a, int *b) {
     int temp;
     temp = *a;
     *a = *b;
     *b = temp;
  }
                                 ; Start of subroutine
          PROC
swap
                                 ; Save ebp
  push
          ebp
                                 ; Copy ebp to esp
  mov
          ebp, esp
          esp, 4
                                 ; Create space for temp
  sub
; CODE FOR: temp = *a
          eax, DWORD PTR 8[ebp]
                                 ; eax = address that "a"
  mov
                                     points to
          ecx, DWORD PTR [eax]
                                ; ecx = value that "a"
  mov
                                     points to = *a
          DWORD PTR -4[ebp], ecx ; temp = *a
  mov
; CODE FOR: *a = *b
          ecx, DWORD PTR 12[ebp] ; ecx = address that "b"
  mov
                                 ; points to
                                 ; edx = value that "b"
          edx, DWORD PTR [ecx]
  mov
                                     points to = *b
          DWORD PTR [eax], edx
                                 ; *a = *b
  mov
                                  ; eax still holds address
                                     "a" points to
; CODE FOR: *b = temp;
          eax, DWORD PTR -4[ebp] ; eax = temp
  mov
          DWORD PTR [ecx], eax
                                 ; *b = temp
  mov
                                 ; ecx still holds address
                                      "b" points to
; CLEANUP
  mov
          esp, ebp
                                 ; Clear space for temp
                                 ; Restore ebp
          ebp
  pop
                                  ; Return from subroutine
  ret
swap
          ENDP
```