

16.317: Microprocessor Systems Design I

Spring 2015

Homework 5

Due **Wednesday, 4/22/15**

Notes:

- While typed submissions are preferred, handwritten submissions are acceptable.
- Any electronic submission must be in a single file. Archive files will not be accepted.
- Electronic submissions should be e-mailed to Dr. Geiger at Michael_Geiger@uml.edu.
- This assignment is worth a total of 100 points.

For each of the following complex operations, write a sequence of PIC 16F1829 instructions that performs an equivalent operation. Assume that X, Y, and Z are 16-bit values split into individual bytes as shown in the following cblock directive, which defines two additional variables you can use:

```
cblock 0x70
    XH, XL    ; High and low bytes of X
    YH, YL    ; High and low bytes of Y
    ZH, ZL    ; High and low bytes of Z
    TEMP      ; Temporary byte, if needed
endc
```

- Perform the 16-bit addition: $X = Y + Z$. Do not change Y or Z when performing this operation.
- Perform the 16-bit subtraction: $X = Y - Z$. Do not change Y or Z when performing this operation.
- Perform a 16-bit arithmetic right shift: $X = Y \gg ZL$. (Note that, because the shift amount is no greater than 15, a single byte is sufficient to hold that value.) Do not change Y or ZL when performing this operation.

d. Given an 8-bit variable, YL, perform the multiplication:

$$YL = YL * 10$$

Hint: Note that multiplication by a constant amount can be broken into a series of shift and add operations. For example, in general:

- $X * 2$ can be implemented by shifting X to the left by 1 ($X \ll 1$)
- $X * 5$ can be implemented as $(X * 4) + X = (X \ll 2) + X$

e. Given two 8-bit variables stored in XL and YL, copy the value of bit position YL within variable XL into the carry flag. For example:

- If $XL = 0x03$ and $YL = 0x00$, set C to the value of bit 0 within XL.
 - Since $XL = 0x03 = 0000\ 0011_2$, $C = 1$
- If $XL = 0xC2$ and $YL = 0x04$, set C to the value of bit 4 within XL.
 - Since $XL = 0xC2 = 1100\ 0011_2$, $C = 0$

Note that:

- This operation is very similar to the bit test (BT) instruction in the x86 architecture.
- Since YL is not a constant, you cannot use the value of YL directly in any of the PIC bit test instructions (for example, `btfsc XL, YL` is not a valid instruction).
- Your code should not modify either XL or YL.