

# EECE.3220: Data Structures

Spring 2017

## Homework 1 Solution

1. (25 points) Assume each expression listed below represents the execution time of a program. Express the order of magnitude for each time using big  $O$  notation.

**Solutions:** In each case, the fastest growing term (which determines order of magnitude) is in **bold**.

a.  $T(n) = \mathbf{n^3} + 100n \cdot \log_2 n + 5000 = \mathbf{O(n^3)}$

b.  $T(n) = \mathbf{2^n} + n^{99} = \mathbf{O(2^n)}$

c.  $T(n) = \frac{n^2-1}{n+1} + 8 \log_2 n = \mathbf{O(n)}$

**Note:**  $n^2 - 1 = (n + 1) * (n - 1)$ , so that first term is simply  $(n - 1)$ .

d.  $T(n) = 1 + 2 + 4 + \dots + \mathbf{2^{n-1}} = \mathbf{O(2^n)}$

**Note:** The answer here is  $O(2^n)$  and not  $O(2^{n-1})$  because  $2^{n-1} = 2^n / 2 = 0.5 * 2^n$ .

2. (75 points) For each of the code segments below, determine an equation for the worst-case computing time  $T(n)$  (expressed as a function of  $n$ , i.e.  $2n + 4$ ) and the order of magnitude (expressed using big  $O$  notation, i.e.  $O(n)$ ).

**Solutions:** In each case, the number of times each line is executed is written to the right in red. Also, for simplicity's sake, a for loop is treated as a single statement, despite the fact that a for loop is really a collection of three statements.

```
a. // Calculate mean
   n = 0;           1
   sum = 0;         1
   cin >> x;        1
   while (x != -999) n + 1
   {
       n++;         n
       sum += x;    n
       cin >> x;    n
   }
   mean = sum / n;  1
```

$$T(n) = 1 + 1 + 1 + (n+1) + n + n + n + 1 = 4n + 5 = O(n)$$

**Note:** While the value of  $x$  controls the number of loop iterations,  $n$  counts the number of iterations, as it's incremented in every loop iteration. You can therefore express the execution time as a function of  $n$ .

```
b. // Matrix addition
   for (int i = 0; i < n; i++) {      n + 1
       for (int j = 0; j < n; j++) {  n + 1
           c[i][j] = a[i][j] + b[i][j]; n
       }                             } n
   }
```

$$T(n) = (n + 1) + n * ((n + 1) + n) = 2n^2 + 2n + 1 = O(n^2)$$

c. *// Matrix multiplication*

```
for (int i = 0; i < n; i++) {
    for (int j = 0; j < n; j++) {
        c[i][j] = 0;
        for (int k = 0; k < n; k++) {
            c[i][j] += a[i][k] * b[k][j];
        }
    }
}
```

$n + 1$   
 $n + 1$   
 $n$   
 $n + 1$   
 $n$

} n }

$$\begin{aligned} T(n) &= (n+1) + n * [(n+1) + n + n * ((n+1) + n)] \\ &= (n+1) + n * [(n+1) + n + 2n^2 + n] \\ &= (n+1) + 2n^3 + 3n^2 + n = 2n^3 + 3n^2 + 2n + 1 = O(n^3) \end{aligned}$$

d. *// Bubble sort*

```
for (int i = 0; i < n - 1; i++) {
    for (int j = 0; j < n - 1; j++) {
        if (x[j] > x[j + 1]) {
            temp = x[j];
            x[j] = x[j + 1];
            x[j + 1] = temp;
        }
    }
}
```

$n$   
 $n^2$   
 $n^2 - n$   
 $(n-1) + (n-2) + (n-3) \dots$   
 $(n-1) + (n-2) + (n-3) \dots$   
 $(n-1) + (n-2) + (n-3) \dots$

$$T(n) = n + n^2 + (n^2 - n) + n*(n-1)/2 = 2.5n^2 - 0.5n = O(n^2)$$

**Note:** The worst case for a bubble sort is that the array is initially sorted from largest to smallest value. So, the body of the if statement executes (n-1) times the first time through the inner loop, (n-2) times the second time, and so on, executing just 1 time in the last inner loop iteration. As shown in our discussion of selection sort, that sum is equal to  $n*(n-1)/2$ .

e. *while (n >= 1)*       $\log_2 n + 2$   
       *n /= 2;*             $\log_2 n + 1$

$$T(n) = (\log_2 n + 2) + (\log_2 n + 1) = 2 \log_2 n + 3 = O(\log_2 n)$$

**Note:** The analysis here is similar to the analysis of binary search, in which the loop test executes  $(\log_2 n + 2)$  times. A few examples will show this analysis to be true—for example, say  $n = 8 = 2^3$ . It takes 4 (which is  $\log_2 n + 1$ ) iterations for  $n /= 2$  to produce the value 0, and the loop condition must therefore be tested a 5<sup>th</sup> time for the loop to end.

```
f.  x = 1;
    for (int i = 1; i <= n - 1; i++) {
        for (int j = 1; j <= x; j++)
            cout << j << endl;
        x *= 2;
    }
```

1  
n  
2 + 3 + 5 + ... + (2<sup>n-2</sup>+1)  
1 + 2 + 4 + ... + 2<sup>n-2</sup>  
n-1

$$\begin{aligned} T(n) &= 1 + n + (2^{n-1} + n - 2) + (2^{n-1} - 1) + (n - 1) \\ &= 2*2^{n-1} + 3n - 3 = 2^n + 3n - 3 = O(2^n) \end{aligned}$$

**Note:** To derive the formula for T(n) shown above, I went through the following analysis:

The number of inner loop iterations is based on the value of x—the for loop condition is always tested (x + 1) times, and the body of the loop executes x times. x doubles every time you go through the outer loop, and the body of that loop executes n-1 times. So, the last time you execute the inner loop, x = 2<sup>n-2</sup>, then x is doubled one last time to 2<sup>n-1</sup>.

After about 10 minutes of Google searching (I wish that was a joke), I was able to find the following formula that helped me determine a simple value for the sum 1 + 2 + 4 + ... + 2<sup>n-2</sup>:

$$\sum_{k=0}^{N-1} r^k = \frac{1 - r^N}{1 - r}$$

Therefore, the body of the inner loop executes 2<sup>n</sup> - 1 times, as shown by evaluating that formula for r = 2 and N = (n-1):

$$\sum_{k=0}^{n-2} 2^k = \frac{1 - 2^{n-1}}{1 - 2} = 2^{n-1} - 1$$

The inner loop condition is tested 1 more time than the loop body executes. The number of terms in the sum 1 + 2 + 4 + ... + 2<sup>n-2</sup> is n-1. So, the third line executes 2<sup>n-1</sup> - 1 + (n-1) = 2<sup>n-1</sup> + n - 2 times.