

PLAN 1:5



SECTION A–A 2:1

(its part from r 120 to 160)




NOTES

1 Bonded between the spider's rim and the bridge ring's outer face.
2 G10 machined across the laminate where the drawing shows faces normal to z; seal every cut edge with low-viscosity epoxy (tracking along exposed fibres, presets/hub-locked.json shaft_coupler).
3 General tolerances ISO 2768-mK; dimensions in mm; do not scale. Views by hidden-line removal of the model's solids.

REVISIONS

Rev	Date	Description
A	2026-10-11	First issue, draft for quotation

status	PROPOSED
qty per machine	2
used in	BRG-800/-801/-802
source	sim/stack_sizing.py BEARING; sim/bridge_ring_bearings.py
mass each	0.251 kg



3-D view (axonometric, not to scale)

DCCREG turbine · the bearings

Ring adapter, G10, spider to bridge ring

Drawing no. **DCCREG-BRG-813**

Material: G10 glass-epoxy laminate, EP GC 201 (IEC 60893-3-2)

Mass: 0.251 kg	Qty per machine: 2	Rev A Sheet 65 of 79 A3
Scale: 1:5, 2:1	Tolerances: ISO 2768-mK	Date: 2026-10-11
Drawn: generated by docs/make_drawing_set.py	Checked: — Approved: —	**PROPOSED · DRAFT**