

PLAN 1:2



SECTION A–A 2:1

(its part from r 46 to 66)




NOTES

1 The two Ø6 holes pass the cross nets l1 and r1 (deck A's junctions; deck B's sit over them).
2 Bonded on the can; the parts' face is the outer (+|z|) face.
3 G10 machined across the laminate where the drawing shows faces normal to z; seal every cut edge with low-viscosity epoxy (tracking along exposed fibres, presets/hub-locked.json shaft_coupler).
4 General tolerances ISO 2768-mK; dimensions in mm; do not scale. Views by hidden-line removal of the model's solids.

REVISIONS

Rev	Date	Description
A	2026-10-11	First issue, draft for quotation

status	PROPOSED
qty per machine	2
used in	DCK-500
source	sim/multiplier_layout.py DECK_R0, DECK_R1, DECK_T
mass each	0.697 kg



3-D view (axonometric, not to scale)

DCCREG turbine · deck A / deck B

Deck plate, G10, r 50-150 × 6

Drawing no. **DCCREG-DCK-502**

Material: G10 glass-epoxy laminate, EP GC 201 (IEC 60893-3-2), plate 6 mm

Mass: 0.697 kg	Qty per machine: 2	Rev A Sheet 24 of 79 A3
Scale: 1:2, 2:1	Tolerances: ISO 2768-mK	Date: 2026-10-11
Drawn: generated by docs/make_drawing_set.py	Checked: — Approved: —	**PROPOSED · DRAFT**