FASTENERS, INSERTS, ADHESIVES AND STOCK (per machine)

item	specification	qty	used in
M4 stud (set screw) A4-70	ISO 4026, M4 × 12, A4-70: the Ca combs' posts through the tabs	24	CAP-610
M4 countersunk screw A4-70	ISO 10642, M4 × 8: r01's outer face (6), Ca_05 posts 2-3 (4), Ca_02 (6)	16	CAP-610
M4 button-head screw A4-70	ISO 7380, M4 × 8: the standoffs from inside the can (6), post 1 under Ca_05 (2)	8	CAP-610
M4 nut, brass	the tap's lug under Ca_06 (in its boot)	2	CAP-610
M4 ring lug, tinned Cu	the riser's and the tap's terminations	4	CAP-610
M5 screw A4-70	ISO 4762, M5 × 10: the cartridges to their spiders [IR]	6	BRG-802
structural epoxy	two-part, e.g. 3M DP490 class: the vane stack, the rings, the spiders, the cage	—	all
silicone, RTV-2	silicone, two-part addition cure, vacuum-degassed; ≥ 20 kV/mm [IR]: the deck's pour, the modules, the boots	≈ 2.5 kg	DCK-500
silicone gel	two-part, degassed, vacuum-cast: the hub's 0.5 mm interface	—	HUB-200
G10 stock	plate 6 / 8 / 10 / 12 / 15; tube Ø16 / 8.5, Ø41 / 64, Ø60 / 66, Ø364 / 372; rod Ø5	—	all
Al stock	EN AW-6082-T6 plate 3.0 (vanes, plates), 2.0 (can discs), tube Ø96 / 92, bar Ø8	—	all
PTFE stock	virgin: tube Ø45 / 41, sheet 2.0, rod Ø12	—	SHF-300, CAN-400

REVISIONS

Rev	Date	Description
A	2026-10-11	First issue, draft for quotation

status	BOUGHT
qty per machine	—
used in	all
source	

NOTES

1 Quantities from sim/doubler_caps.py placement and the model's counts; side A and side B together.

2 A4 stainless throughout (non-magnetic enough for the electrostatic stacks; keep it out of the utrons' gaps).

DCCREG turbine · bought parts		
Fasteners, inserts and stock		Drawing no.
Material:		**DCCREG-P-011**
Mass: —	Qty per machine: —	Rev A Sheet 79 of 79 A3
Scale: —	Tolerances: ISO 2768-mK	Date: 2026-10-11
Drawn: generated by docs/make_drawing_set.py	Checked: — Approved: —	**BOUGHT · SOURCE CONTROL**