

PLAN 1:5



SECTION A–A 2:1

(its part from r 20 to 60)




REVISIONS

Rev	Date	Description
A	2026-10-11	First issue, draft for quotation

status	PROPOSED
qty per machine	2
used in	BRG-800/-801/-802
source	sim/stack_sizing.py BEARING; sim/bridge_ring_bearings.py
mass each	1.5 kg

NOTES

1 Bore Ø52 H7 for the 6205; six Ø8.5 holes at r 173 for the tie rods; bonded in the cage's bore.
2 G10 machined across the laminate where the drawing shows faces normal to z; seal every cut edge with low-viscosity epoxy (tracking along exposed fibres, presets/hub-locked.json shaft_coupler).
3 General tolerances ISO 2768-mK; dimensions in mm; do not scale. Views by hidden-line removal of the model's solids.



3-D view (axonometric, not to scale)

DCCREG turbine · the bearings

Spider, Ca|reluctance, G10, Ø364		Drawing no.
Material: G10 glass-epoxy laminate, EP GC 201 (IEC 60893-3-2)		**DCCREG-BRG-810**
Mass: 1.5 kg	Qty per machine: 2	Rev A Sheet 65 of 103 A3
Scale: 1:5, 2:1	Tolerances: ISO 2768-mK	Date: 2026-10-11
Drawn: generated by docs/make_drawing_set.py	Checked: — Approved: —	**PROPOSED · DRAFT**