

PLAN 1:2



SECTION A–A 2:1


(its part from r 14 to 58)



REVISIONS

Rev	Date	Description
A	2026-10-11	First issue, draft for quotation

status	PROPOSED
qty per machine	2
used in	CAP-600, CAP-610
source	sim/doubler_caps.py placement (the node-1 comb's posts)
mass each	0.238 kg



3-D view (axonometric, not to scale)

NOTES

1 As CAP-601, with the node-1 comb's three posts: M4 countersunk (ISO 10642, 90°) from the outer face, at r 35.
2 Hand A (drawn): the posts at 46.3°, 166.3°, -73.7° (the blades at 0° + 60° k). Hand B: at -88.9°, 31.1°, 151.1° (side B's riser at -88.9°).
3 Every rim a full round R1.5 (t / 2), burr-free, Ra ≤ 0.8 µm: the record's rims are full rounds on a handled surface (Peek m 0.85, sim/vane-matrix-findings.md §2). Clean with IPA after the last operation; handle with gloves.
4 Flatness 0.10 over the whole plate; parallelism of the faces 0.05: the 6 mm working gaps (sim/stack_sizing.py).
5 General tolerances ISO 2768-mK; dimensions in mm; do not scale. Views by hidden-line removal of the model's solids.

DCCREG turbine · the doubler: C1 / C2

Rotor vane, the first (r01), hands A / B		Drawing no.
Material: Al EN AW-6082-T6 (the record: Al; the grade proposed [IR]), plate 3.0		**DCCREG-CAP-602**
Mass: 0.238 kg	Qty per machine: 2	Rev A Sheet 34 of 103 A3
Scale: 1:2, 2:1	Tolerances: ISO 2768-mK	Date: 2026-10-11
Drawn: generated by docs/make_drawing_set.py	Checked: — Approved: —	**PROPOSED · DRAFT**