THE DRIVE'S SMALL PARTS (per machine)

item	specification	qty	used in
spacer A	Ø25 / Ø28 × 43.0, 1.4305: the rotor gear's toe to the gear-end bearing's inner ring (through the counter-rotor's gear)	1	DRV-100
spacer B	Ø25 / Ø32 × 3, 1.4305: the rotor gear's hub to the locating bearing's inner ring; shim it to set the gear's mounting distance	1	DRV-100
spacer C	Ø25 / Ø32 × 6.6, 1.4305: the locating bearing to the pulley's bush	1	DRV-100
pinion spacer	Ø10 / Ø14 × 4, 1.4305: between the two 6000-2Z's inner rings	3	DRV-100
retaining ring	Ø44 / Ø66 × 2, 1.4305, three Ø3.4 countersunk on PCD Ø58: over the locating bearing's outer ring, three M3 × 6 (ISO 10642, A4)	1	DRV-100
shaft collar	two-piece clamp collar Ø25, ≤ Ø40 × 10, stainless: over the gear-end bearing's inner ring, it carries the rotor's weight into the stack [IR]	1	DRV-100
key	DIN 6885 A 8 × 7 × 12, stainless: the rotor gear in its hub	1	DRV-100
lock nut	SKF KM 5 (M25 × 1.5) with its tab washer MB 5: clamps the shaft's stack	1	DRV-100
circlip	DIN 471, 10 × 1, stainless: the stub shafts' outer ends	3	DRV-100
shims	Ø48 / Ø32, 0.05 / 0.1 / 0.2, stainless: under the cartridges' flanges (the backlash)	3 sets	DRV-100
screws	M4 × 10 ISO 4762 A4: 6 (the gear's flange to the hub), 9 (the cartridges); M5 × 12 ISO 10642 A4: 6 (the disc to the hub); M5 × 16 ISO 10642 A4 + 12 inserts M5: 12 (the disc to bridge ring A)	33 + 12	DRV-100
bolts	M6 × 60 ISO 4762 A4: 3 (from under the base plate through the bell into the case's flange); M5 × 16 ISO 4762: 4 (the motor's flange); M6 × 20 + washers: 4 (the motor plate to its bracket)	11	DRV-100, DRV-120
grease	POM-compatible, synthetic (PTFE-thickened class): the meshes and the closed case [IR]	—	DRV-100

REVISIONS

Rev	Date	Description
A	2026-10-11	First issue, draft for quotation

status	PROPOSED · the first cut, on the record's 940 mm stack-up: to re-cut on the layout (ledger §6, item 71)
qty per machine	—
used in	DRV-100, DRV-120
source	sim/unmodelled_parts.py reverser_sub, belt_sub

NOTES

1 Quantities from sim/unmodelled_parts.py reverser_sub and belt_sub; the drive is one per machine.

2 Status: the first cut of docs/drive-gear-belt.md on the record's 940 mm stack-up (z from the record's bottom end-bearing slot); the ledger asks for the drive to be re-cut on the layout (§6, item 71). PROPOSED.

DCCREG turbine · the drive

The drive's spacers, rings, keys and fasteners

Drawing no. **DCCREG-DRV-190**

Material:

Mass: —	Qty per machine: —	Rev A Sheet 84 of 103 A3
Scale: —	Tolerances: ISO 2768-mK	Date: 2026-10-11
Drawn: generated by docs/make_drawing_set.py	Checked: — Approved: —	**PROPOSED · DRAFT**