F-SERIES
















EFFORTLESS OPERABILITY

Power steering / adjustable columnPower steering and tilt / telescopic column adjustment are standard, helping to reduce driver fatigue. Simple operation Meters are located in the center for superior visibility, surrounding switches are designed for easy control.



Three steps and hand grips facilitate cab ingress/egress



Smooth and effortless shifting

Refinements to the master cylinder reduce the effort involved in manual shifting and ensure a smooth ride. Reliability and durability are also enhanced.



Cup holders Holds two cups or cans within easy reach of driver



Door Ashtray



Header Console



AM/FM radio Produce superior sound quality



High-visibility meters, simple operation

Meters are in the center for superior visibility, allowing drivers to confirm vehicle status at a glance. Surrounding switches are designed for easy control.



Covered overhead shelf Ideal for communications equipment or long items



Room mirror Allows driver to checkrear of cabin and through rear window

MORE VISIBILITY



Better mirror visibility for safer driving

Wide-angle mirrors on the driver's side and co-driver's side as well as front and side under mirrors on the co-driver's side expand visibility, helping to prevent "under run" and contact accidents during turns or merging.

MORE GREEN





Optimal power from Small displacement.

Isuzu engineers pushed the limits of engine technology to develop the common rail diesel engines which delivers unmatched fuel economy and reduced carbon emissions. Technologically advanced engine management features are perfectly complemented with rugged construction to reduce total cost-of-ownership and ensure reliability even in harsh operating conditions. The four-cylinder 4HK1-TCC / TCS provide optimal power required for your everyday deliveries. For long-haul transport and more demanding applications, six-cylinder 6HK1-TCN / TCS offer the ultimate output and torque.

4HK1-TCC Direct-injection OHC

- •Displacement 5,193cc
- •Max. Output 140kW (190PS) / 2,600rpm (net)
- •Max. Torque 510N•m (52kg•m) / 1,600rpm (net)

4HK1-TCS Direct-injection OHC

- •Displacement 5,193cc
- •Max. Output 154kW (210PS) / 2,600rpm (net)
- •Max. Torque 637N•m (65kg•m) / 1,600rpm (net)
- 706N•m (72kg•m) / 1,600rpm (net)

6HK1-TCN Direct-injection OHC

- Displacement 7,790cc
- •Max. Output 177kW (240PS) / 2,400rpm (net)
- •Max. Torque 706N•m (72kg•m) / 1,450rpm (net)

6HK1-TCS Direct-injection OHC

- •Displacement 7,790cc
- •Max. Output 206kW (280PS) / 2,400rpm (net)
- •Max. Torque 882N•m (90kg•m) / 1,450rpm (net)



Turbocharger

The turbocharger realizes high output from small displacement. The result is improved fuel economy and reduced emissions.

Common-rail fuel injection system

Electronic control injects fuel at extremely high pressure in 1/1000 second units and determines optimal injection amounts, reducing NOx and particulate matter.

Electronic control technologies

Proprietary ISUZU electronic control technologies are the key to precise regulation of combustion in order to deliver peak power, environmental performance and fuel economy.

Every F-Series model takes full advantage of cutting-edge ISUZU electronic control.




Designed for easy maintenance

When there is a big job, FORWARD will be ready. The quick access front panel facilitates routine replenishment of clutch and washer fluids as well as brake valve maintenance.



Cleaning the windshield is a snap

A full-length bumper step and hand grips take the hard work out of cleaning the windshield. The bumper step and grips also offer steady support for adjustment of mirrors. For remote adjustment from inside the cab, power mirrors are available.







Simplified fluid inspection and other service work


Checking fluids is simple. An engine oil inspection port is located at the back of the cab, along with brake fluid and long-life coolant reservoirs. The relay box is also conveniently placed at the back of the cab for straightforward inspection. Even fuse replacement inside the cab below the instrument panel is easy, thanks to a cartridge-type fuse box.




F-SERIES TECHNICAL SPECIFICATIONS



















MODEL	FRR90N	FTR90L LSD FTR90L non LSD		FTS34L	FVR34P	FVZ34T, Cargo truck Chassis	FVZ34T, Tipper Chassis					
ENGINE												
Model	4HK1-TCC 4HK1-TCC 4HK1-T			6HK1-TCN	6HK1-TCS	6HK1-TCS						
Туре	Diesel 4 cylinder , Co Intercooler	ommon Rail Turbo	charged with	Diesel 6 cylinder , Common Rail Turbocharged with Intercooler								
Displacement(L)	5193	5193	5193	7790	7790	7790	7790					
Max Output kW (hp) @ rpm	140(190) @ 2,600	140(190) @ 2,600	154(210) @ 2,600	177 (240)@ 2,400	177 (240)@ 2,400	206(280) @ 2,400	206(280) @ 2,400					
Max Torque Kgm (Nm) @ rpm	52(510) @ 1,600		72(705) @ 1,600	(72)706 @ 1,450	(72)706 @ 1,450	90(882)@ 1,450	90(882)@ 1,450					
Pre-air cleaner & high air intake pipe	Standard											
Fuel water sedimentors	Standard											
Heavy duty radiator	Standard											
Emission	Euro 2											
CLUTCH												
Туре	Type: Dry Single Pla	te Operation: Hyd	draulic Control, A	Air Assist								
Diameter (mm/inch)	350/14"	350/14"	350/14"	380/15"	380/15"	380/15"	380/15"					
TRANSMISSION	6 Speed over drive, 1 reverse	6 Speed over drive, 1 reverse	6 Speed direct drive, 1 reverse	6 Speed over drive, 1 reverse	9 Speed manual, direct drive, 1 reverse	9 Speed manual, direct drive, 1 reverse	9 Speed manual, direct drive, 1 reverse					
SUSPENSION	Front: Multi Leaf Spring Shock Absorbers - Double acting Rear: Multi Leaf Spring with Helper Spring											
BRAKES												
System	Air Over Hydraulic D	ual Circuit		AOH, with auto brake lining adjustment Full Air Dual Circuit, with air dryer and auto brake lining adjustment								
Park Brake	Center Drum Parking			Center Drum Parking	Rear Wheel Parking	Rear Wheel Parking	Rear Wheel Parking					
Front& Rear	Drum	Drum Drum		Drum	Drum	Drum	Drum					
Auxiliary	Exhaust Brake	Exhaust Brake	Exhaust Brake	Exhaust Brake	Exhaust Brake	Exhaust Brake	Exhaust Brake					
Speed limiter	80km/h	80km/h 80km/h		80km/h	80km/h	80km/h	80km/h					
STEERING												
Operation	Power											
САВ												
Type	Tilt Cabin Constructi	on										
Sleeper Cab	Standard											
Seat belt	3 point x 2 for driver	& Assistant, 2 Poi	nt x 1 for center	seat								
CD player w/ USB	Standard	Standard	Standard	Standard	Standard	Standard	Standard					
WHEELS & TYRES												
Tyre Size	235/75 R17.5		11R22.5- 16PR Tubeless	9.00R20-14PR	12.00R22.5 Tubeless	12.00R22.5 Tubeless	12.00R22.5 Tubeless					
Rim Size	17.5x6.00	7.5x22.5	7.5x22.5	7.0x20	8.25x22.5	8.25x22.5	8.25x22.5					
FUEL TANK												
Capacity (Litres)	200	200	200	200	200	370	370					
Final Drive Ratio (:1)	5.571	6.833	6.833	5.571	6.143	6.143	6.143					
WEIGHT (kg)												
Gross vehicle weights (GVW) (Kgs)	11000 13500		14200	13000	18000 26000		26000					
Cab chassis mass (Kgs)	3120	4560	4560	5140	5130	7155	6500					


DIMENSIONS (mm)	Overall Length	Overall Width	Overall Height	Wheel base	Front Over hang	Rear Over hang	Rear Axle Width	Front Track	Rear Track	Chassis Rear Height at Axle	Front Chassis Width	Rear Chassis Width	Rear Ground Clearance	Cab to Chassis End	Cab to Axle
FRR90N	8155	2200	2600	4860	1170	2125	2165	1790	1660	900	840	840	190	6090	3965
FTR90L LSD	7405	2400	2720	4250	1440	1715	2350	1990	1790	1015	850	850	275	5335	3620
FTR90L non LSD	7405	2400	2720	4250	1440	1715	2350	1990	1790	1015	850	850	275	5335	3620
FTS34L	7405	2400	2910	4250	1255	1900	2350	1965	1790	1120	850	850	275	5335	3435
FVR34P	8505	2400	2860	5060	1440	2015	2445	1970	1845	1250	850	870	245	6435	4420
FVZ34T, Cargo truck Chassis	9730	2400	2905	6335	1440	1940	2445	1970	1845	1220	850	870	265	7660	5070
FVZ34T, Tipper Chassis	7630	2400	2905	4250	1440	1340	2445	1970	1845	1220	850	870	265	5650	3660

A Truck for Every Application
There is a wide variety of rear bodies, application-specific models and modifications to choose from, depending on the specialised needs of your business.















Refrigerated Van Crane / Cargo



Garbage Compactor





Road Sweeper

Earth Auger Exhauster

Customized / specialized solutions and designs available.





Trucks for life

ISUZU

CONTACTS

Enterprise Road, Industrial Area Tel: 0800 724 724 Info.kenya@isuzu.co.ke www.isuzu.co.ke