



UMEÅ UNIVERSITY
DEPARTMENT OF COMPUTING SCIENCE

ARTIFICIAL INTELLIGENCE
METHODS AND APPLICATIONS

5DV181

Map maker

Thomas Ranvier

supervised by
Ola RINGDAHL
Juan CARLOS NIEVES SANCHEZ

January 10, 2019

Abstract

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

Contents

1	How to use our program	3
2	Structure of the program	4
2.1	Mapping	4
2.2	Planning	7
	Conclusion	8
	List of algorithms	9

Chapter 1

How to use our program

For this assignment we used Python 3 as programming language, to run the program you can use the following syntax:

```
> python3 main.py
```

Chapter 2

Structure of the program

Our program is divided in two main modules, the mapping module and the planning module. The role of the first one is to build the map of the environment of the robot using the echoes of the lasers. The role of the second one is to plan the path that the robot must follow in order to explore the world.

2.1 Mapping

The first point on which we worked was to find a way of building a map of the environment of the robot using the lasers echoes.

To do so we created a class 'Map' that contains a grid of values between 0 and 1. Those values represent probability that there is an obstacle on that cell.

To update this grid we created a class 'Cartographer' that uses the echoes of the lasers. For each laser echoe we compute the distance between the robot cell and the cell hit by the laser in the grid. Then we use the 'Bresenham' algorithm to update all the cells in between the two above. For all those cells we compute an increment that is added or subtracted to them using the following procedure:

1. First we compute an increment factor in regard of the value of the cell:

$$inc_factor_iro_certainty = 1 - (abs(cell_value - 0.5) * 2)$$

2. Then we compute an increment factor in regard of the distance between the robot and the cell to update:

$$inc_factor_iro_dist = 1.5 * (1 - abs(distance / max_lasers_distance))$$

3. The final increment is computed by multiplying the two factors with a defined increment value (we used 0.1):

$$final_increment = inc_factor_iro_certainty * inc_factor_iro_dist * increment$$

4. The final increment is added to the cell if the cell corresponds to the cell hit by the laser and that the distance of the echoe is below the maximum laser distance. Otherwise it is subtracted.

This is the factory map built moving the robot by hand using the cartographer described above.



Figure 1: Explored map by hand

2.2 Planning

TODO

Conclusion

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

List of Algorithms