Strength Review Package

Coil support structure of a stellarator – model, results and eight questions for structural analysts

Thomas Schmiegelt | hobby project `stellarator-design`

3 November 2026

AI-generated report. The text, program code and figures of this report were produced by AI agents. The computations were done by the solvers named. The human (Thomas Schmiegelt) set goal and direction, decided at the forks and checked images and results for plausibility.

Hobby project, non-commercial. No connection to any customer project, research institute or company, not peer-reviewed. Calculations, code and draft text were produced with the help of AI agents; the human set goal and direction. All numbers come from simplified models (linear elastic, rigid bearings, magnetic load only). That is exactly why I am asking for your critical view: the questions are in Section 9.

Audience. Structural analysts (FEM, codes and standards) without a fusion background. Everything fusion-specific is briefly explained. Reading time about 20 minutes; for the questions alone, Sections 1 and 9 are enough.

1 At a glance

- **Component:** casings of steel 1.4429 (316LN) around 24 superconducting coils, joined by steel connectors, supported on an inner and outer support ring. Load: Lorentz force during magnet operation, up to 1.1 GN per coil.
- **Criterion:** $\sigma 99$ = 99% value of the von Mises stress over the steel volume; limit 500 MPa ($\frac{2}{3}R_{p0.2}$ at 4 K, ITER grade C3).
- **Result:** of 199 evaluated designs in a study, 7 meet all limits. Recommended: design 0169 with $\sigma 99$ = 308 MPa, also on a finer mesh (319 MPa).
- **Main issue:** the peak values sit at the connector junctions and grow with every mesh refinement. For four of five candidates $\sigma 99$ rises by 34–58% on a finer mesh.
- **New (3 Nov):** in 0169 the connectors were so close that they almost formed a plate. Re-computed: separate webs are mesh-stable (+1%), a continuous plate is not (+47%).

2 What it is about

A stellarator confines a plasma hotter than 100 million degrees in a twisted magnetic field. The field comes from superconducting coils with an irregular, three-dimensional shape. The design here: 1 GW net electric power, major radius R_0 = 10.4 m, field B_0 = 6.5 T, high-temperature superconductor (REBCO), operation at about 4 K to 20 K. Each coil carries about 20 MA. In its own field and that of its neighbours it feels the Lorentz force $f = J \times B$: 50 MN/m to 140 MN/m along the coil, in total up to 1.1 GN per coil towards the machine centre. Wanted: a structure of coil casings, connectors and bearings that carries these forces without straining the superconductor by more than 0.3 %.




Figure 1: Design 0169 in a stepped cut (3D model in PicoGK).

How to read the figure: From inside out: plasma (pink), first wall and blanket (yellow), shield (green), vacuum vessel (grey), then the 24 steel coil casings (blue) with the superconducting winding pack (orange). Between the casings sit the connectors (dark blue). The inner support cylinder and the outer ring are only drawn: they show where the bearing forces go, but are neither computed nor designed.

3 Model

Geometry
Coil centre lines from the optimisation (simsopt [1]). One hexahedral mesh per coil along its path: 64 stations for 24 coils; in the cross-section 2 wall cells, 2 cm potting and 4×4 winding-pack cells. Connectors as hexahedral blocks between the casings.

Materials
Casing 1.4429 (X2CrNiMoN17-13-3, AISI 316LN), $E = 200$ GPa. Winding pack homogenised. Potting quartz-sand epoxy, $E = 10$ GPa. Connectors steel, E as a design variable 20 GPa to 200 GPa.

Load
Lorentz force density from all coils (Biot–Savart), magnet operation only.

Bearings
Patches on the casing outer surface at the smallest and largest radius, **rigidly clamped**.

Solver
Elmer [2], linear elastic, linear 8-node hexahedra (Elmer type 808), MUMPS.

Chain
Plasma → coils → package → strength → temperature, 1–3 minutes per design. A study of 200 designs varied coil count, coil–plasma distance, connector count and stiffness, wall thicknesses and bearing radius.

4 How the variants come about: computed automatically, rejected automatically

No design was drawn by hand. A chain of programs turns eleven design variables into coils, package, strength model, temperatures and a 3D model, and assesses the result against eight limits. A Latin hypercube plan spreads the variables evenly over their ranges. The AI wrote and started the chain; the 200 designs ran unattended in 8.5 hours.




Figure 2: The automatic chain of the design study and what remains of it.

How to read the figure: Top: the stations every design passes through. Bottom left, the funnel: of 200 planned designs one failed in the solver (aborted without result), in 11 the casings intersect (not buildable). Of the remaining 188, 7 meet all limits and 3 more miss one narrowly. Bottom right: why the 181 rejected designs fail, i.e. the limit with the smallest margin. Mostly it is the steel stress, but almost half fail on something else (field accuracy, superconductor strain, neutron fluence). A pure strength design would not filter them out.




Figure 3: 16 rejected designs, evenly spread over the ranking (3D models in PicoGK).

How to read the figure: Top left the design furthest from the limits, bottom right the one that fails most narrowly. Above each image: number, coil count, $\sigma 99$ and the limit it fails. "Margin" is the distance to the limit relative to the limit (-100% means twice the allowable). Red frame: clearly missed, yellow: narrowly. High stress alone does not decide: 0021 has only 558 MPa, but its superconductor would receive a multiple of the allowable neutron fluence. The catalogue in the variant report shows all 188 buildable designs like this.




Figure 4: Still from the film of all variants (second 30): the rejected designs sink.

How to read the figure: Each ring is a complete design from the study. Red: clearly missed, yellow: narrowly, blue: admissible. The inadmissible ones sink in turn, worst first; at the end the seven blue ones remain. The film is in the repository (`docs/filme/varianten.mp4`).

5 How the structure came about

The structure was not prescribed but derived from a force analysis. The first model reached 2129 MPa. Instead of varying parameters, we first examined how the force arises.

1. **Force along the coil:** 50 MN/m to 140 MN/m, net per coil up to 1.1 GN inwards.
2. **Rope or beam:** a curved segment carries transverse load as tension ($T = f_N/\kappa$); a straight one is bent. The largest load ($\approx$130 MN/m) sits on the almost straight inner leg ($\kappa < 0.08\,1/\mathrm{m}$ over about 7 m).
3. **Hand calculation:** simply supported beam, $q \approx 130$ MN/m, $l \approx 7$ m: $M = ql^2/8 \approx 800$ MNm; hollow section $H = 1.36$ m, $h = 0.755$ m, $W \approx 0.38\,\mathrm{m}^3$, hence $\sigma_B \approx 2100$ MPa. FEM gave 2129 MPa: the stress came from bending of the inner leg.
4. **Flaw in the initial model:** supported only on the outside, while the force pulls inwards.
5. **Precedents:** in a tokamak the straight leg rests against a bucking cylinder (compression instead of bending); in ARIES-CS a continuous shell passes the transverse load from coil to coil.




Figure 5: Same 16 coils, five support structures A–E.

How to read the figure: Top: four key figures per structure; bottom: the stress seen from above (blue low, red high). A: bearings outside, 6 connectors per pair. B: bearings inside (−32%, −30 to −50% was expected). C: inside and outside. D: 12 stiff connectors per pair (shorter free bending length, $M \propto l^2$). E: additionally thickest walls. The stress drops from 2129 to 481 MPa, steel grows from 15.6 to 37 kt. Since then "inside and outside" is standard; connectors, walls and bearing radius are design variables of the study.

6 Criteria and limits

Quantity	Limit	Origin
$\sigma 99$ in casing steel	500 MPa	$S_m = \frac{2}{3} R_{p0.2}$ at 4 K, ITER grade C3 ($R_{p0.2} \geq 750$ MPa) [3]
Membrane stress P_m per wall section	500 MPa	linearisation through the wall thickness
$P_m + P_b$	750 MPa	$1.5\, S_m$
Winding-pack strain	0.3 %	REBCO irreversible from 0.45 % to 0.72 %




Figure 6: Strength of 1.4429 / 316LN at room temperature and at 4 K.

How to read the figure: Blue: yield strength, green: tensile strength, yellow: resulting allowable stress. At room temperature (left, table value [4]) only about 200 MPa would be allowed. Measured at 4.2 K, the yield strength is more than three times higher (1070 MPa [5]; with high nitrogen in thick plates above 1000 MPa [6]). The dashed line is the limit used. The casing is cold in operation; no current flows during cool-down.

7 Results




Figure 7: Design study: 199 designs, $\sigma 99$ against six design variables.

How to read the figure: Each circle is a design, the colour gives the coil count. Filled circles meet all limits. The dashed line is the 500 MPa limit, the y axis is logarithmic. Only designs with 20 or 24 coils get below it. The clearest trend is the coil–plasma distance (bottom centre): coils further away are more strongly shaped.

Mesh study. The candidates were recomputed with 1.5 times as many stations along the coil and with 3 instead of 2 wall cells.




Figure 8: Mesh study: same coils and parameters, different mesh.

How to read the figure: (b) shows $\sigma 99$, (c) the peak value. A finer resolution through the wall ("cross-section fine") changes hardly anything. More stations along the coil ("1.5× stations") raise $\sigma 99$ by 34–58% for four of five candidates, for 0169 by only 4%. The peak value rises for all; it depends on the mesh.

Location of the peaks. 77–100% of the 200 most highly stressed elements lie less than 1 m from a connector junction. For 0169 the peak rises from 717 to 1262 MPa on the finer mesh, $\sigma 99$ only from 308 to 319 MPa.

Categories. The stress was linearised across each wall section into membrane (P_m) and membrane plus bending ($P_m + P_b$).




Figure 9: Stress categories of the admissible designs.

How to read the figure: (a) Peak values: they sit at the single peak at the connector end (local membrane stress P_L). (b) Value met by 99% of the wall sections: for the best designs P_m stays below 400 MPa. E (test) is the earlier support structure test E for comparison.

Connectors as webs or as a plate. In 0169 (13 connectors per pair) neighbouring connectors were exactly one connector width apart. They touched or overlapped, and steel was counted twice in the overlaps. Hypothesis before the computation: the almost continuous plate makes 0169 mesh-stable. Three variants with the same coils were computed.




Figure 10: Design 0169: three kinds of connectors, standard and fine mesh.

How to read the figure: Blue: standard mesh, orange: 1.5 times as many stations. The number above each pair is the increase due to the finer mesh. Separate webs (spacing at least one width) are higher (387 MPa) but stay stable (+1%). A continuous plate with shared nodes jumps by 47% to almost 500 MPa. The hypothesis is refuted: the mesh stability of 0169 does not come from the plate. The peaks are in well-shaped elements (scaled Jacobian 0.92–0.96), 86–96% of them in the casing. With separate webs 0169 still remains admissible.

Softer connectors. If all connectors of 0169 are made uniformly softer, $\sigma 99$ rises (+16% at 50 GPa). The connectors are the relief path.

8 Known weaknesses

1. Bearings rigidly clamped; the support cylinder is missing as a component (optimistic).
2. Connector junctions sharp-edged, hence mesh-dependent peaks. The assessment applies to the walls, not to the junctions.
3. Primary load only: no cool-down from 293 to 4 K, no dead weight, no fatigue, no fracture mechanics.
4. Winding pack homogenised, potting perfectly bonded (no debonding).
5. $\sigma 99$ is not a code quantity but a figure of merit for the design search.
6. Linear hexahedra with only 2 cells through the wall thickness.

9 Questions for you

1. **Criterion:** Is $\sigma 99$ defensible as a search criterion, or should we assess linearised categories (P_m, P_L, P_b) along selected sections from the start?
2. **Peaks at the junction:** The peak values at the connector end grow with the mesh (0169: 717 → 1262 MPa). How do you usually handle this: hot-spot structural stress, notch stress with a fillet radius, submodel?
3. **Junction shape:** Which shape would you choose for a steel connector between two casings (gap about 0.2 m to 1 m, forces in the MN range per connector): fillet, tapered thickness, longer contact face, continuous shell?
4. **Plate or webs:** In the model the continuous plate is mesh-sensitive (+47%), separate webs are not (+1%). Is this a known effect (stiffness jump at the plate edge)? Does anything speak against a continuous shell (assembly, thermal contraction during cool-down, inspectability of welds)?
5. **Load cases:** Which are missing, in which order? Proposal: cool-down, dead weight, fast discharge (quench), cyclic load for fatigue.
6. **Support:** How would you model the support cylinder, as a component with contact or as a spring boundary condition? What stiffness would be realistic?

7. **Material at 4 K:** Is $\frac{2}{3}R_{p0.2}$ (ITER magnet criteria) sufficient as a limit, or does fracture mechanics govern at 4 K (K_{IC}, crack growth)?
8. **Mesh:** How much do linear 8-node hexahedra with 2 cells through the wall underestimate bending stress (shear locking)? Are quadratic elements (20 nodes) worth it, or is a third cell enough? Our test with 3 wall cells hardly changed $\sigma 99$.

Documents

Project report (strength chapter), variant report with data sheets of all admissible designs and a catalogue of all 188 buildable designs, source code (`stellarator/kopplung.py`, `hexmodell.py`, `doe_auswertung.py`) and a film of all variants: `https://github.com/ThomasSchmiegelt/stellarator-design` (MIT licence).

References

[1] M. Landreman et al.: SIMSOPT: A flexible framework for stellarator optimization. J. Open Source Softw. 6 (2021) 3525. doi:10.21105/joss.03525.

[2] Elmer FEM, CSC – IT Center for Science, `https://www.elmerfem.org`.

[3] N. Mitchell et al.: ITER TF structure, grades C1–C3 (IAEA FEC contribution IT/1-4); year and wording not verified.

[4] Strength values of steel, after Roloff/Matek, Maschinenelemente; schweizer-fn.de, `https://www.schweizer-fn.de/festigkeit/festigkeitswerte/stahl/stahl_start.php` (accessed 3 Nov 2026).

[5] A. Fedoriková, P. Petroušek, T. Kvačkaj, R. Kočiško, M. Zemko: Development of Mechanical Properties of Stainless Steel 316LN-IG after Cryo-Plastic Deformation. Materials 16 (2023) 6473. doi:10.3390/ma16196473.

[6] T. Sakurai, O. Umezawa, Y. Ono: Strength and Fracture Toughness of Type 304 and 316 Austenitic Stainless Steels at 4.2 K. IOP Conf. Ser.: Mater. Sci. Eng. 1302 (2024) 012002. doi:10.1088/1757-899X/1302/1/012002.