

H807GPBH Board

The H807GPBH board is an 8-port GPON OLT interface board. It works together with the ONU to provide the GPON access service.



Benefits

- **High-precision clock and time synchronization** : 50-ppb frequency synchronization and 100-ns phase synchronization
- **Flexible SLA**: 4-level HQoS, improving user experience
- **High reliability**
 - Chip-level type B protection switching, shortening the switching time to less than 50 ms
 - Type C protection dual-homing, providing geography-level disaster recovery
 - Real-time rogue ONU detection and isolation, ensuring stable service running
- **Easy OAM**
 - Variable-length OMCI, improving upgrade efficiency and reducing break off time
 - A maximum distance difference of 40 km between two ONUs under the same PON port, simplifying network planning
 - 1:64 eOTDR, supporting accurate fault demarcation and quick fault locating

External Interfaces

8 GPON ports with SFP optical modules:

- Max. split ratio:
 - Class B+: 1:64
 - Class C+/C++: 1:128

Specifications

Function	
Forwarding capability	20 Gbit/s
T-CONTs per PON port	1K
Service flows per PON board	8K
Maximum frame size	2004 bytes 9216 bytes (jumbo frame enabled)
MAC addresses	32K
Maximum distance difference between two ONUs under the same PON port	40 km from V800R013
N:1/1:1 VMAC	Supported
FEC	Bidirection
CAR group	Supported
IPv6	Supported
4-level HQoS	Supported
Variable-length OMCI	Supported from V800R013
ONU-based shaping or queue-based shaping	Supported
Load sharing	Supported
High-precision clock time synchronization	Supported
Type B/Type C protection	Supported
Rogue ONU detection and isolation	Supported
Automatic shutdown at high temperature	Supported
Automatic shutdown of an idle port	Supported
1:64 eOTDR	Supported (with FBG)

Environment

Operating temperature	-40° C to +65° C
Power consumption	• Static: 25 W • Maximum: 38 W