

H80AVDPD Board

The H80AVDPD board is a 64-port VDSL2 over POTS service board. Using its VDSL2 port, the H80AVDPD board works with the VDSL transceiver unit-remote terminal end (VTU-R) to provide 64-channel VDSL2 access services.



Benefits

- High density VDSL2 board, supporting a maximum of 64 ports

External Interfaces

2x32 VDSL2 lines

- G.993.2 (VDSL2 over POTS)
- G.997.1 (Physical layer management)
- G.998.2 (Ethernet-based multi-pair bonding)
- G.998.4 (INP for DSL)
- G.994.1 (Handshake procedures)
- BF TR-165 (Vector of Profiles)
- BF TR-129 (Protocol-Independent Management Model)
- BF TR-159 (Management Framework for xDSL Bonding)

Specifications

Physical

Connector	Champ 64-pin
Built-in splitter	Not supported
Bandwidth between VDSL and control boards	6.4G (with SCUN) 1G (with SCUB)
Maximum frame size	PTM: 1518 bytes ATM: 1518 bytes

Environment

Operating temperature	-40° C to +65° C
Power consumption	With 17a profiles: • Static: 24 W • Maximum: 77 W
	With 8b profiles: • Static: 24 W • Maximum: 89 W

Functions

Category	Specification
Annex	G.992.1 Annex A G.992.3 Annex A/L/M G.992.5 Annex A/M G.993.2 Annex A/B
Profile	8a/b/c/d, 12a/b, 17a
Vectoring	Not supported
Bonding	2 pairs
SRA	Supported
RFI notch	Supported
UPBO	Supported
DPBO	Supported
G.INP	Supported
INM	Supported
Virtual noise	Supported
Built-in MELT	Not supported
Built-in SELT	Supported
IPv6	Supported
N:1 VMAC	Supported
1:1 VMAC	Supported

