


Documentation for User Interface of **NSP3CT.PRO ONE**

Portable Pipe Inspection System

Design Grid

The entire UI Layout is designed using a design grid. The specification of this grid is 90px/10px horizontally and vertically. See image as an example.



All Elements must be aligned to the design grid.

Background

Gradient-Angle: (-45) 135°

Colors: R=225 G=225 B=225 @0%
B=255 G=255 B=255 @25%
R=200 G=200 B=200 @100%

Depending on your programming you may want to add a 100x100px Tile with some in greyscale noise pattern repeatedly as a 5% opacity to add to gradient to avoid moiré effect.

Do not use large background images due to load and boot times and restricted system memory.

Buttons and Content Tiles

Regular buttons are equal in size to assure optimized touch functionality and match the physical buttons on the device in size.

All buttons have various states e.g. "inactive", "active" or "on tap/hold" (mouse down)

A sample button is placed in the design elements archive.



Buttons

Size: 90x90px

Corner radius: 5px, slanted 45°

for example:

.box

{

clip-path: polygon(0 10px,10px 0,calc(100% - 10px)

0,100% 10px,100% calc(100% - 10px),

calc(100% - 10px) 100%,10px 100%,0 calc(100% - 10px));

}

or

—mask:

conic-gradient(from 45deg at 10px 10px,#000 75%,#0000 0)-10px 0/100% 51%

repeat-x, conic-gradient(from 135deg at 10px calc(100% - 10px),#0000 25%,#000

0)-10px 100%/100% 51% repeat-x;

-webkit-mask: var(—mask);

mask: var(—mask);

INACTIVE BUTTONS

Gradient-Angle: -45°

Colors: R=225 G=225 B=225 @0%

B=225 G=225 B=225 @50%

R=200 G=200 B=200 @100%

Drop shadow: 10% R=0 G=0 B=0 (multiply)

x/y=displacement: 6px

distance: 8px

size: 4px

(-45) 135°

Inner Glow: 50% R=255 G=255 B=255

x/y=displacement: 2px

distance: 10px

size: 2px

angle: (-45) 135°



Inner Glow: 10% R=0 G=0 B=0
 size: 2px
 overflow: 20%

ACTIVE TILES/BUTTONS

Gradient-Angle: (-45) 135°
 Colors: R=255 G=205 B=0 @0%
 B=255 G=205 B=0 @50%
 R=191 G=162 B=26 @100%

Drop shadow: 10% R=0 G=0 B=0 (multiply)
 x/y=displacement: 6px
 distance: 8px
 size: 4px
 (-45) 135°

Inner Glow: 25% R=255 G=205 B=0
 x/y=displacement: 2px
 distance: 10px
 size: 2px
 angle: (-45) 135°

Inner Glow: 10% R=0 G=0 B=0
 size: 2px
 overflow: 20%



Tiles

Tiles also have two states: "inactive" or "active"

Sample tiles are placed in the design elements archive.

Tiles are placed in the middle content section - for example on System Settings - or in the sidebars.

All tiles should follow the design grid in size.

Tiles must be designed the same way as buttons, meaning corner radius and gradient as well as Drop Shadows and Glows are the same. Tiles only differ in size.

Sizes should be matching the design grid. Half steps of large design grid fields (45px) may be used. The grid then will continue within the design element after the half step regularly.

Example:

190 x 245px (1 large 90px column, 1 small 10px column. 1 large 90px column = 190px in width)
 (1 large 90px row, 1 small 10px row, 1 large 90px row, 1 small 10px row,
 ½ large 90px row [45px] = 245px in height)

Icons

All icons are available as SVG or Adobe Illustrator file format in the design elements archive.

Buttons also have an inactive and active (on Tap) state and vary in color according to their state.

Please make sure to use the correct icon for the state it should be used in.

Files are named with states as well.

Icons appear always white on active/yellow gradient buttons and tiles.

Icons appear grey (R=100 G=100 B=100) and yellow (R=255 G=205 B=0) on inactive/grey gradient buttons and tiles.

For any questions regarding the layout or further file support please contact

Sven Meyer
 Group Marketing Director
 UIP.TEAM GmbH

s.meyer@uip.team