

Deep Learning for Image Analysis - Deep Learning for object detection

Thomas Walter, PhD

Centre for Computational Biology (CBIO)
MINES Paris-Tech, PSL Research University
Institut Curie, PSL Research University
INSERM U900

Overview

1 Introduction

2 Architectures for object detection

3 Conclusion

4 References

Overview

1 Introduction

2 Architectures for object detection

3 Conclusion

4 References

Classification, segmentation and detection

- Image Classification: assign a label to each image.
- Image Segmentation: partition the image, i.e. assign a label to each pixel.
- Image understanding requires the estimation of concepts and locations of objects contained in an image.
- Problem definition: Object detection is a computer vision task that aims to detect instances of semantic objects of certain classes in images [Ren et al., 2017, Zhao et al., 2019].
- Object detection has thus two components:
 - *Object localization*: to determine where objects are located in a given image
 - *Object classification*: which category each object belongs to

Object detection: example




Figure: Object detection in action. Image taken from [Liu et al., 2016]

Object detection: example




Figure: Object detection in action. Image taken from [Liu et al., 2016]

Object detection: example




Figure: Object detection in action. Image taken from [Liu et al., 2016]

Early approaches: the sliding window approach




Figure: Mitosis detection in stained tissue sections [Cireşan et al., 2013].

- Approach was the winner of a mitosis detection challenge [Cireşan et al., 2013].
- Fixed size sliding window approach: each crop is presented to a CNN.
- The posterior probability is stored as an image value.
- Local maxima of this probability map indicate the presence of an object.
- Special case of object detection: the size of the objects was known before.

A milestone in object detection: R-CNN




Figure: R-CNN strategy [Girshick et al., 2014]

- Starting from region proposals (by any method): ~ 2000 regions).
- Warping / Cropping of the selected regions into fixed resolution and extraction of a 4096-dimensional feature vector with a pretrained CNN.
- Classification with SVM (object types and background).
- Adjustment by bounding box regression
- Filtering with greedy non-maximum suppression (NMS): removal of regions with low overlap with a single object.

Drawbacks of R-CNN

- Fixed input size for the CNN: distortion and rescaling of images is necessary.
- Multi-stage pipeline.
- Training is expensive (time and space).
- Computational expensive, sub-optimal region proposal step.

Fast R-CNN




Figure: Fast R-CNN [Girshick, 2015]

- The entire image is processed by a neural network: generation of feature maps.
- Region are proposed by some algorithm (as before).
- To each region, a ROI pooling layer is applied.

Fast R-CNN: ROI pooling layer




Figure: ROI pooling layer in Fast R-CNN

- Each region of arbitrary size $w \times h$ is divided into $W \times H$ tiles. W and H are fixed, whereas w and h are arbitrary.
- For each tile, the maximum is calculated (max-pooling operation) in the feature map.
- The output (fixed size) can then be processed by dense layers.

Fast R-CNN: Output layer

- Two outputs:
 - Classification output (with a standard softmax layer)
 - Bounding box regression: prediction of position and extension offsets with respect to the original region proposal.
- The loss has thus two components: L_{class} which is the standard cross-entropy loss and L_{loc} , the localization loss (L_1 loss of the offsets with respect to the proposed regions).
- Trick: during training, the batch is constructed from many objects drawn from very few images.
- For the prediction, each class gets its own region proposal, that is processed individually with non-maxima suppression.

Faster R-CNN: motivation

- Fast R-CNN solves nearly all problem of R-CNN, and is end-to-end given a set of region proposals.
- The problem is that we still need to make region proposals to start with (time-consuming and two-stage algorithm).
- Faster R-CNN [Ren et al., 2017] trains a network called Region Proposal Network (RPN) to overcome this issue.

Faster R-CNN: Idea




Figure: Faster R-CNN [Ren et al., 2017]

The idea is to share convolutional feature maps at test-time, i.e. to use the CNN feature maps calculated for the entire image for both region proposal and object classification [Ren et al., 2017].

Faster R-CNN: shared layers




Figure: Faster R-CNN [Ren et al., 2017]

- First, we run the image through convolutional layers of a CNN and obtain feature maps that will serve both the region proposal and the object classification.
- We now slide a small network over the common feature map, that outputs both scores (object yes/no) and regression offsets defining the bounding box.
- The size can be relatively small (in [Ren et al., 2017], it is 3×3); the receptive field is much larger.

Faster R-CNN: Region proposal network (RPN)




Figure: Faster R-CNN [Ren et al., 2017]

- A Region Proposal Network (RPN) takes an image as input and outputs a set of rectangular object proposals, each with an objectness score.
- We define k anchor regions (defined by scale and aspect ratio).
- At each sliding-window location, we simultaneously predict k region proposals from the k anchor regions, for each we predict a score (object yes/no) and the box offsets.

Faster R-CNN: Region proposal network (RPN)




Figure: Faster R-CNN [Ren et al., 2017]

- We define a combined loss (as for Fast R-CNN), as sum of the classification loss and bounding box regression loss.
- Classification loss: cross entropy for a binary classifier, indicating whether the region contains an object or not.
- Regression loss compares for each region proposal its offsets to the anchors with the offsets of the ground truth box.

Faster R-CNN: Training




Figure: Faster R-CNN [Ren et al., 2017]

- We now simply apply a Fast R-CNN to the region proposals provided by the RPN.
- The shared layers are trained in an alternating scheme.
- After this initial training, the shared layers are frozen and the separate layers are trained end-to-end.

Conclusion

- Object detection is a major challenge in Computer Vision with applications in biomedical image analysis, autonomous driving, industrial applications, etc.
- CNNs outperform most traditional methods by a large margin.
- Today, object detection is among the most stunning applications of Computer Vision.
- There are hundreds of methods, but the most important advances were achieved by R-CNN, Fast R-CNN and Faster R-CNN.
- They can be combined with segmentation (Mask R-CNN).

References I

- [Cireşan et al., 2013] Cireşan, D. C., Giusti, A., Gambardella, L. M., and Schmidhuber, J. (2013). Mitosis Detection in Breast Cancer Histology Images with Deep Neural Networks. In Hutchison, D., Kanade, T., Kittler, J., Kleinberg, J. M., Mattern, F., Mitchell, J. C., Naor, M., Nierstrasz, O., Pandu Rangan, C., Steffen, B., Sudan, M., Terzopoulos, D., Tygar, D., Vardi, M. Y., Weikum, G., Mori, K., Sakuma, I., Sato, Y., Barillot, C., and Navab, N., editors, *Medical Image Computing and Computer-Assisted Intervention – MICCAI 2013*, volume 8150, pages 411–418. Springer Berlin Heidelberg, Berlin, Heidelberg.
- [Girshick, 2015] Girshick, R. (2015). Fast R-CNN.
arXiv:1504.08083 [cs].

References II

- [Girshick et al., 2014] Girshick, R., Donahue, J., Darrell, T., and Malik, J. (2014). Rich feature hierarchies for accurate object detection and semantic segmentation. *arXiv:1311.2524 [cs]*.
- [Liu et al., 2016] Liu, W., Anguelov, D., Erhan, D., Szegedy, C., Reed, S., Fu, C.-Y., and Berg, A. C. (2016). SSD: Single Shot MultiBox Detector. *arXiv:1512.02325 [cs]*, 9905:21–37.
- [Ren et al., 2017] Ren, S., He, K., Girshick, R., and Sun, J. (2017). Faster R-CNN: Towards Real-Time Object Detection with Region Proposal Networks. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 39(6):1137–1149.
- [Zhao et al., 2019] Zhao, Z.-Q., Zheng, P., Xu, S.-t., and Wu, X. (2019). Object Detection with Deep Learning: A Review. *arXiv:1807.05511 [cs]*.