

# Fully convolutional neural networks

E. Decencière

MINES ParisTech  
PSL Research University  
Center for Mathematical Morphology




# Contents

- 1 Introduction
- 2 Binary segmentation
- 3 Semantic segmentation
- 4 Instance segmentation
- 5 Practical recommendations
- 6 Conclusion

# Contents

- 1 Introduction
- 2 Binary segmentation
- 3 Semantic segmentation
- 4 Instance segmentation
- 5 Practical recommendations
- 6 Conclusion

## Recall from yesterday: image classification with NN



Simple fully-connected neural network

Cross-entropy loss function used for classification tasks:

$$L(\theta) = - \sum_{i=1}^n y_i \ln(f(\mathbf{x}_i, \theta))$$

## Learning image transformations

- An image classification task is a function from the set of considered images into a set of labels
- In many applications, we want to transform an image into another image

# Image definition

## Definition: image

An 2-dimensional image  $I$  of size  $p \times q$  ( $p, q \in \mathbb{N}^*$ ) is a function from  $D = [0, \dots, p - 1] \times [0, \dots, q - 1]$  into  $\mathbb{R}^d$  ( $d \in \mathbb{N}^*$ ).  
The set of these images is  $\mathcal{I}^d$ .

## Examples




Figure:  $28 \times 28$  grey level image ( $d = 1$ ) from the MNIST dataset, and  $481 \times 321$  colour image ( $d = 3$ ) from the Berkeley segmentation dataset.

# Image-to-image NN

## Definition: image-to-image neural network

An image-to-image NNs  $F$  is a NN that transforms an image into an image of same size<sup>a</sup>:

$$\begin{aligned} F : \mathcal{I}^{d_1} &\longrightarrow \mathcal{I}^{d_2} \\ I &\longmapsto N(I) \end{aligned}$$


Note that the dimensions  $d_1$  and  $d_2$  of the value spaces can be different.

---

<sup>a</sup>In some applications the output size is different from the input size, but for the sake of simplicity we will not consider this case here

# Examples


## Bulge / disk decomposition



(Credits: Tuccillo, Huertas-Company, Velasco-Forero, Decencière)

# Examples

## Bulge / disk decomposition



(Credits: Tuccillo, Huertas-Company, Velasco-Forero, Decencière)

## Deblurring network [Hradiš et al., 2015]

where subscript  $j$  indicates  
ated vector, and  $L_j(z; u) =$   
 $\|e_j \odot z - u\|^2$ , where  $e_j \in \mathbb{R}^{64}$  is the vector  
all others be 0. The coordi  
marized in Algorithm I.

Note that  $g_j(z)$  is not  
we calculate the Newton di  
second-order approximation  
and solve

where subscript  $j$  indicates  
ated vector, and  $L_j(z; u) =$   
 $\|e_j \odot z - u\|^2$ , where  $e_j \in \mathbb{R}^{64}$  is the vector  
all others be 0. The coordi  
marized in Algorithm I.

Note that  $g_j(z)$  is not  
we calculate the Newton di  
second-order approximation  
and solve

# Image Segmentation with NNs

- Computer vision has been one of the main application domains of NNs
- Image segmentation often is an important step in an image processing work flow
- Image segmentation has been a very active deep learning research field

## Image segmentation example



Credit: images from the Pascal VOC database

## Other applications

- Image filtering
- High dynamic range
- Style modification
- Super-resolution (image size increases)


## Image-to-image NNs architecture

- Image-to-image NNs are based on convolutional layers
- If downsampling is used, the corresponding upsampling is needed

# Image-to-image NNs architecture

- Image-to-image NNs are based on convolutional layers
- If downsampling is used, the corresponding upsampling is needed

Example: Pang network [Pang et al., 2010]



# Receptive field

**Definition:** links between neurons

In a NN, we say that neuron  $a$  is linked to neuron  $b$  if there is an oriented path in the corresponding graph going from  $a$  to  $b$ .


**Definition**

The **receptive field** of a neuron in a NN is the set of *input neurons* that are linked to that neuron.

The size of the receptive field is an essential property when designing a fully-convolutional NN architecture.


# Receptive field of the Pang network

What is the size of the receptive field of the neurons in the last layer?



# Receptive field of the Pang network

What is the size of the receptive field of the neurons in the last layer?



Answer:  $1 + 2 \times (n + 1)$

# The specific case of image segmentation

## Definition: image segmentation

Let  $I$  be an image defined on  $D$ . A segmentation of  $I$  is a partition of  $D$ . In practice the regions of the segmentation should correspond to the objects in  $I$ , which is application dependant.

- A partition is often represented as a labelled image
- In order to make the segments symmetric, each one is represented by a different channel

## Some vocabulary on segmentation


- **Object detection / localization:** bounding box around the object(s).
- **Binary segmentation:** segmentation in 2 classes, background and object.
- **Semantic segmentation:** a label is given to each pixel, according to the object it belongs to.
- **Instance segmentation:** identify each separate object, even if they belong to the same class.

# Contents


- 1 Introduction
- 2 Binary segmentation
- 3 Semantic segmentation
- 4 Instance segmentation
- 5 Practical recommendations
- 6 Conclusion

# Neuron membrane segmentation challenge (ISBI 2012)

- Train: single stack of size  $30 \times 512 \times 512$ .
- Test: a second stack of same size.



# Neuron membrane segmentation challenge winner [Ciresan et al., 2012]




# Contents

- 1 Introduction
- 2 Binary segmentation
- 3 Semantic segmentation
- 4 Instance segmentation
- 5 Practical recommendations
- 6 Conclusion

# Pascal visual object classes segmentation challenge 2012 [Everingham et al., 2014]

- 1464 training and 1449 validation images
- automatic online test, with unknown images
- 20 image categories (cat, sofa, motorbike, person, etc.)




# Convolutional nets for semantic image segmentation


Three papers in 2015:

- Fully convolutional networks for semantic segmentation [Long et al., 2015]
- U-Net: convolutional networks for biomedical image segmentation [Ronneberger et al., 2015]
- SegNet: A Deep Convolutional Encoder-Decoder Architecture for Image Segmentation [Badrinarayanan et al., 2015]


# Example: U-Net architecture [Ronneberger et al., 2015]



# What is the size of the receptive field of U-Net




# What is the size of the receptive field of U-Net



Answer:  $185 \times 185$

# Example: SegNet architecture [Badrinarayanan et al., 2015]



## Remarks

- These architectures easily contain a number of parameters of the order of  $10^7$  (28 million for U-Net)
- Their optimization might be difficult
- For many segmentation applications, they are overkill
  - But you can reduce the number of filters or the number of layers

# Contents

- 1 Introduction
- 2 Binary segmentation
- 3 Semantic segmentation
- 4 Instance segmentation
- 5 Practical recommendations
- 6 Conclusion


## COCO: common objects in context [Lin et al., 2014]

- 2 million objects, from 80 categories, in 300 000 images




Winner 2016: Fully Convolutional Instance-aware Semantic Segmentation (Microsoft) [Li et al., 2016]





# COCO instance segmentation challenge: examples of 2016 winner results



# State of the art on the COCO database: Mask R-CNN [He et al., 2017]




# Mask R-CNN on the COCO database




# Partially supervised segmentation - [Hu et al., 2017]

- 80 segmented categories from COCO database
- 3000 visual concepts using box annotations from the Visual Genome dataset (100k images)



# Partially supervised segmentation - learning to segment every thing



[Hu et al., 2017]

## Current (?) trends for instance segmentation

- Region proposal +
- Fully convolutional (very deep) network +
- (Post-processing)




Figure: Regions with CNN features (R-CNN) (from [Girshick et al., 2014])

## Current (?) trends for instance segmentation

- Region proposal +
- Fully convolutional (very deep) network +
- (Post-processing)




Figure: Regions with CNN features (R-CNN) (from [Girshick et al., 2014])

Meanwhile, on the object detection field...

- YOLO: you look only once [Redmon and Farhadi, 2016]
- SSD: single shot detector [Liu et al., 2016]

# Contents

- 1 Introduction
- 2 Binary segmentation
- 3 Semantic segmentation
- 4 Instance segmentation
- 5 Practical recommendations
- 6 Conclusion

# Modeling your problem

## Casting your problem into the right representation

- Familiarize yourself with the training data (input and output images)
- Choose the right representation for your images
- Choose an architecture and train it
- Analyze the results on the validation data (**look** at the images!)
- Do you need preprocessing? Data augmentation?  
Post-processing?
- Iterate ...
- Only at the end: test!

# Preprocessing

- Standard statistical preprocessing: not always useful, and sometimes problematic, when applied to images
- Morphological operators

## Data augmentation

- Geometrical transformations: similarities
- Elastic transformations
- Specific methods: articulated objects, ...
- Simulated data

## Postprocessing for segmentation

- Superpixels (e.g. [Farabet et al., 2013])
- Conditional random fields
- Mathematical morphology

## What loss to use?

- Classical choice: mean squared error or cross-entropy
- My recommendation: Dice or Jaccard losses

## Practical example



(Credits: ESA/Hubble, CC BY 4.0,  
<https://commons.wikimedia.org/w/index.php?curid=34205833>)

How would you:

- segment the background?
- segment the sources?
- separate the sources?

## What precision is needed for the ground-truth?

- The ground truth boundaries do not need to be very precise
-

## Using a CNN

- A fully convolutional neural network is translation invariant
- Provided that the image size is compatible with network's subsampling process, in theory any image can be processed
- Practical limit: the memory of the system

# Contents

- 1 Introduction
- 2 Binary segmentation
- 3 Semantic segmentation
- 4 Instance segmentation
- 5 Practical recommendations
- 6 Conclusion

## A solved problem?

- Progress in image segmentation during the 5 last years has been enormous
- Several complex problems have now satisfactory solutions
- Training can be a problem (large annotated databases, difficult optimization)
- Some remaining challenges:
  - Making the training database as small as possible
  - Taking *a priori* structural information into account

# References I

- [Badrinarayanan et al., 2015] Badrinarayanan, V., Kendall, A., and Cipolla, R. (2015). SegNet: A Deep Convolutional Encoder-Decoder Architecture for Image Segmentation. *arXiv:1511.00561 [cs]*. arXiv: 1511.00561.
- [Ciresan et al., 2012] Ciresan, D., Giusti, A., Gambardella, L. M., and Schmidhuber, J. (2012). Deep Neural Networks Segment Neuronal Membranes in Electron Microscopy Images. In Pereira, F., Burges, C. J. C., Bottou, L., and Weinberger, K. Q., editors, *Advances in Neural Information Processing Systems 25*, pages 2843–2851. Curran Associates, Inc.
- [Everingham et al., 2014] Everingham, M., Eslami, S. M. A., Gool, L. V., Williams, C. K. I., Winn, J., and Zisserman, A. (2014). The Pascal Visual Object Classes Challenge: A Retrospective. *International Journal of Computer Vision*, 111(1):98–136.
- [Farabet et al., 2013] Farabet, C., Couprie, C., Najman, L., and LeCun, Y. (2013). Learning Hierarchical Features for Scene Labeling. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 35(8):1915–1929.
- [Girshick et al., 2014] Girshick, R., Donahue, J., Darrell, T., and Malik, J. (2014). Rich Feature Hierarchies for Accurate Object Detection and Semantic Segmentation. pages 580–587.
- [He et al., 2017] He, K., Gkioxari, G., Dollár, P., and Girshick, R. (2017). Mask R-CNN. *arXiv:1703.06870 [cs]*. arXiv: 1703.06870.

## References II

- [Hradiš et al., 2015] Hradiš, M., Kotera, J., Zemcík, P., and Šroubek, F. (2015). Convolutional neural networks for direct text deblurring. In *Proceedings of BMVC*, volume 10.
- [Hu et al., 2017] Hu, R., Dollár, P., He, K., Darrell, T., and Girshick, R. (2017). Learning to Segment Every Thing. *arXiv:1711.10370 [cs]*. arXiv: 1711.10370.
- [Li et al., 2016] Li, Y., Qi, H., Dai, J., Ji, X., and Wei, Y. (2016). Fully Convolutional Instance-aware Semantic Segmentation. *arXiv:1611.07709 [cs]*. arXiv: 1611.07709.
- [Lin et al., 2014] Lin, T.-Y., Maire, M., Belongie, S., Bourdev, L., Girshick, R., Hays, J., Perona, P., Ramanan, D., Zitnick, C. L., and Dollár, P. (2014). Microsoft COCO: Common Objects in Context. *arXiv:1405.0312 [cs]*. arXiv: 1405.0312.
- [Liu et al., 2016] Liu, W., Anguelov, D., Erhan, D., Szegedy, C., Reed, S., Fu, C.-Y., and Berg, A. C. (2016). SSD: Single Shot MultiBox Detector. *arXiv:1512.02325 [cs]*, 9905:21–37. arXiv: 1512.02325.
- [Long et al., 2015] Long, J., Shelhamer, E., and Darrell, T. (2015). Fully Convolutional Networks for Semantic Segmentation. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 3431–3440.

## References III

- [Pang et al., 2010] Pang, B., Zhang, Y., Chen, Q., Gao, Z., Peng, Q., and You, X. (2010). Cell Nucleus Segmentation in Color Histopathological Imagery Using Convolutional Networks. In *2010 Chinese Conference on Pattern Recognition (CCPR)*, pages 1–5.
- [Redmon and Farhadi, 2016] Redmon, J. and Farhadi, A. (2016). YOLO9000: Better, Faster, Stronger. *arXiv:1612.08242 [cs]*. arXiv: 1612.08242.
- [Ronneberger et al., 2015] Ronneberger, O., Fischer, P., and Brox, T. (2015). U-Net: Convolutional Networks for Biomedical Image Segmentation. In Navab, N., Hornegger, J., Wells, W. M., and Frangi, A. F., editors, *Medical Image Computing and Computer-Assisted Intervention – MICCAI 2015*, number 9351 in Lecture Notes in Computer Science, pages 234–241. Springer International Publishing.