Image quality assessment

E. Decencière

Mines Paris
PSL Research University
Center for Mathematical Morphology



Contents

- Introduction
- 2 Distortion: full reference image quality assessment
- 3 Perceptual quality: no reference image quality assessment
- Perception-distortion tradeoff
- Conclusion

• To improve image acquisition

- To improve image acquisition
- To compare different acquisition systems

- To improve image acquisition
- To compare different acquisition systems
- To evaluate the result of an image transformation

- To improve image acquisition
- To compare different acquisition systems
- To evaluate the result of an image transformation
- To optimize an image transformation

- To improve image acquisition
- To compare different acquisition systems
- To evaluate the result of an image transformation
- To optimize an image transformation

- To improve image acquisition
- To compare different acquisition systems
- To evaluate the result of an image transformation
- To optimize an image transformation

We will only consider here the second and third use cases.

 $\bullet \ X, x: \ {\rm ground\text{-}truth} \ {\rm image} \ {\rm set,} \ {\rm original} \ {\rm image}$

- \bullet X, x: ground-truth image set, original image
- $\bullet \ Y,y: \ {\rm degraded} \ {\rm image} \ {\rm set,} \ {\rm degraded} \ {\rm image}$

- \bullet X, x: ground-truth image set, original image
- ullet Y,y: degraded image set, degraded image
- ullet \hat{X},\hat{x} : restored image set, restored image

- \bullet X, x: ground-truth image set, original image
- ullet Y,y: degraded image set, degraded image
- \hat{X}, \hat{x} : restored image set, restored image
- ullet $f_{m{ heta}}$: image transformation parameterized by vector $m{ heta}$

Contents

- Introduction
- 2 Distortion: full reference image quality assessment
- 3 Perceptual quality: no reference image quality assessment
- Perception-distortion tradeoff
- Conclusion

Pixel-wise comparisons

- Mean squared error, PSNR
- Mean absolute error

Taking structure into account: SSIM

Idea

The measure is based on this quantity:

$$\left[1 - \frac{(\mu_x - \mu_y)^2}{\mu_x^2 + \mu_y^2}\right] \times \left[1 - \frac{(\sigma_x - \sigma_y)^2}{\sigma_x^2 + \sigma_y^2}\right] \times \frac{\sigma_{xy}}{\sigma_x \sigma_y}$$

Taking structure into account: SSIM

Idea

The measure is based on this quantity:

$$\left[1-\frac{(\mu_x-\mu_y)^2}{\mu_x^2+\mu_y^2}\right]\times \left[1-\frac{(\sigma_x-\sigma_y)^2}{\sigma_x^2+\sigma_y^2}\right]\times \frac{\sigma_{xy}}{\sigma_x\sigma_y}$$

Structure similarity index measure

$$SSIM(x,y) = \frac{2\mu_x \mu_y + c_1}{\mu_x^2 + \mu_y^2 + c_1} \times \frac{2\sigma_{xy} + c_2}{\sigma_x^2 + \sigma_y^2 + c_2}$$

where c_1 and c_2 are conveniently chosen strictly positive constants to avoid numerical problems.

Taking structure into account: SSIM

Idea

The measure is based on this quantity:

$$\left[1-\frac{(\mu_x-\mu_y)^2}{\mu_x^2+\mu_y^2}\right]\times \left[1-\frac{(\sigma_x-\sigma_y)^2}{\sigma_x^2+\sigma_y^2}\right]\times \frac{\sigma_{xy}}{\sigma_x\sigma_y}$$

Structure similarity index measure


$$SSIM(x,y) = \frac{2\mu_x \mu_y + c_1}{\mu_x^2 + \mu_y^2 + c_1} \times \frac{2\sigma_{xy} + c_2}{\sigma_x^2 + \sigma_y^2 + c_2}$$

where c_1 and c_2 are conveniently chosen strictly positive constants to avoid numerical problems.

Remarks

- Typically applied within a sliding window.
- Several variants exist, like the multi-scale SSIM.

Using artificial neural networks



Contents

- Introduction
- 2 Distortion: full reference image quality assessment
- 3 Perceptual quality: no reference image quality assessment
- Perception-distortion tradeoff
- Conclusion


Classical methods

 Many methods: CBIQ, LBIQ, BLIINDS-II, DIVINE, BRISQUE, TMIO, NIQE [Mittal et al., 2013]

Classical methods

- Many methods: CBIQ, LBIQ, BLIINDS-II, DIVINE, BRISQUE, TMIO, NIQE [Mittal et al., 2013]
- Generally based on natural image statistics

Inception score [Salimans et al., 2016]



Fréchet inception distance [Heusel et al., 2017]


Contents

- Introduction
- 2 Distortion: full reference image quality assessment
- 3 Perceptual quality: no reference image quality assessment
- Perception-distortion tradeoff
- Conclusion

Observation [Blau and Michaeli, 2018]



Perception-distortion tradeoff [Blau and Michaeli, 2018]



ullet Δ : distortion measure.

- ullet Δ : distortion measure.
- ullet d: divergence between distributions.

- ullet Δ : distortion measure.
- ullet d: divergence between distributions.

- \bullet Δ : distortion measure.
- *d* : divergence between distributions.

Distortion, perception

 \bullet Distortion between X and $\hat{X} \colon E[\Delta(X,\hat{X})]$

- \bullet Δ : distortion measure.
- *d* : divergence between distributions.

Distortion, perception

- Distortion between X and \hat{X} : $E[\Delta(X,\hat{X})]$
- ullet Perception : $d(p_X,p_{\hat{X}})$

Theorem


Perception-distortion function

$$P(D) = \min_{p_{\hat{X}|Y}} d(p_X, p_{\hat{X}}) \quad s.t. \quad E(\Delta[X, \hat{X}]) \le D$$

Theorem

Perception-distortion function


$$P(D) = \min_{p_{\hat{X}|Y}} d(p_X, p_{\hat{X}}) \quad s.t. \quad E(\Delta[X, \hat{X}]) \le D$$



Theorem

Perception-distortion function


$$P(D) = min_{p_{\hat{X}|Y}} d(p_X, p_{\hat{X}})$$
 s.t. $E(\Delta[X, \hat{X}]) \le D$



Theorem

If the divergence d is convex in its second argument (which is the case for most common divergences) then P(D) is monotonically non-increasing and convex.

Experiments



Contents

- Introduction
- 2 Distortion: full reference image quality assessment
- 3 Perceptual quality: no reference image quality assessment
- Perception-distortion tradeoff
- Conclusion

Conclusion

• The tradeoff depends on the application

Conclusion

- The tradeoff depends on the application
- In practice: choose an acceptable distortion, and try to optimize perceptual quality

References I

- [Blau and Michaeli, 2018] Blau, Y. and Michaeli, T. (2018). The Perception-Distortion Tradeoff. In 2018 IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 6228–6237. ISSN: 2575-7075.
- [Heusel et al., 2017] Heusel, M., Ramsauer, H., Unterthiner, T., Nessler, B., and Hochreiter, S. (2017). GANs Trained by a Two Time-Scale Update Rule Converge to a Local Nash Equilibrium. In Advances in Neural Information Processing Systems, volume 30. Curran Associates, Inc.
- [Mittal et al., 2013] Mittal, A., Soundararajan, R., and Bovik, A. C. (2013). Making a "Completely Blind" Image Quality Analyzer. *IEEE Signal Processing Letters*, 20(3):209–212. Conference Name: IEEE Signal Processing Letters.
- [Salimans et al., 2016] Salimans, T., Goodfellow, I., Zaremba, W., Cheung, V., Radford, A., and Chen, X. (2016). Improved techniques for training gans. Advances in neural information processing systems, 29.