



Object Oriented Architectures and Secure Development

User interfaces with JavaFX

Matthias Blomme

Mattias De Wael

Frédéric Vlummens

JavaFX: Hello world

Adding JavaFX dependencies to build.gradle

```
plugins {  
    id 'java'  
    id 'org.openjfx.javafxplugin' version '0.0.10'  
}
```

```
javafx {  
    version = "18"  
    modules = [ 'javafx.controls'  
}
```

For the latest versions:

<https://openjfx.io/openjfx-docs/#gradle>

The Application class

```
public class HelloApp extends Application {  
  
    public static void main(String[] args) {  
        launch(args);  
    }  
  
    @Override  
    public void start(Stage primaryStage) throws Exception {  
        Label lbl = new Label("Hello World!");  
        Scene scene = new Scene(lbl, 200, 100);  
        primaryStage.setScene(scene);  
        primaryStage.show();  
    }  
}
```

Do not launch your app from IntelliJ

This will cause an error:

> Task :HelloApp.main() FAILED

Error: JavaFX runtime components are missing, and are required to run this application

FAILURE: Build failed with an exception.

* What went wrong:

Execution failed for task ':HelloApp.main()'.
Execution failed for task ':HelloApp.main()'.


> Process 'command '/Users/fredericvlummens/Library/Java/JavaVirtualMachines/azul-11.0.8/Contents/Home/bin/java'' finished with non-zero exit value 1

Instead, configure your build.gradle

```
plugins {  
    id 'java'  
    id 'application'  
    id 'org.openjfx.javafxplugin' version '0.0.10'  
}
```

```
application {  
    mainClass = 'be.howest.ti.HelloApp'  
}
```

Adding the application plugin, allows you specify a main class,
And it creates a run task. (double click it to start the app)



JavaFX: building an actual UI

Building an actual UI

- Not required to add all controls manually as in previous example
- We will be using FXML, an XML-based format to describe our UI
- Make sure to add the necessary dependency to **build.gradle**:

```
javafx {  
    version = "18"  
    modules = [ 'javafx.controls', 'javafx.fxml' ]  
}
```


The FXML file

- Stored in **/resources/fxml** (=convention followed in this course):

```
<?xml version="1.0" encoding="UTF-8"?>
```

```
<?import javafx.scene.control.Button?>
```

```
<?import javafx.scene.control.Label?>
```

```
<?import javafx.scene.layout.VBox?>
```

```
<VBox maxHeight="-Infinity" maxWidth="-Infinity"
```

```
  minHeight="-Infinity" minWidth="-Infinity"
```

```
  prefHeight="100.0" prefWidth="200.0"
```


```
  xmlns="http://javafx.com/javafx/18">
```

```
  <Label>Hello</Label>
```

```
  <Label>World</Label>
```

```
  <Button>Do nothing</Button>
```

```
</VBox>
```



Load the FXML file in Application class

```
public class FxApplication extends Application {  
  
    public static void main(String[] args) {  
        launch(args);  
    }  
  
    @Override  
    public void start(Stage primaryStage) throws IOException {  
        Parent root = FXMLLoader.load(getClass().getResource("/fxml/demo.fxml"));  
        Scene scene = new Scene(root);  
        primaryStage.setScene(scene);  
        primaryStage.show();  
    }  
}
```

The FXML file, with controller

```
<?xml version="1.0" encoding="UTF-8"?>
```

```
<?import javafx.scene.control.Button?>
```

```
<?import javafx.scene.control.Label?>
```

```
<?import javafx.scene.layout.VBox?>
```

```
<VBox maxHeight="-Infinity" maxWidth="-Infinity" minHeight="-Infinity" minWidth="-Infinity"
```

```
  prefHeight="100.0" prefWidth="200.0"
```

```
  xmlns="http://javafx.com/javafx/18"
```

```
  xmlns:fx="http://javafx.com/fxml/1"
```



```
  fx:controller="be.howest.ti.shop.ui.fx.DemoController">
```

```
    <Label>Hello</Label>
```

```
    <Label fx:id="lblWord">World</Label>
```

```
    <Button onAction="#doSomething">Do something</Button>
```

```
</VBox>
```



The Controller

```
public class DemoController {  
    @FXML private Label lblWord;  
  
    public void doSomething(ActionEvent actionEvent) {  
        lblWord.setText("user interaction");  
    }  
}
```

The controls in the the fxml-file need an `fx:id` , if you want to access them as a `field` in the controller. Use the `@FXML` annotation, to make your fields private in the controller.

Some controls allow you to specify a handler `method` in the controller, using the #-symbol. Buttons, for instance, have the `onAction`-property.

Usually, you do not need to access the button itself, then you should not provide it with an `fx:id` . In case you do want to access the button, then you need the `fx:id` of course, but only add it if needed.

Project structure

```
@FXML private ListView<String> someLinesOfText;
```

```
public void doSomething(ActionEvent actionEvent) {  
    lblWord.setText("user interaction");
```


```
    List<String> myClassicList = new ArrayList<>();  
    myClassicList.add("a");  
    myClassicList.add("b");  
    myClassicList.add("c");
```

```
    someLinesOfText.setItems(FXCollections.observableList(  
        myClassicList  
    ));
```

SceneBuilder


Introducing SceneBuilder

- JavaFX application that can be used to design FX GUIs
- No longer required to write FXML manually
- Free download:
<https://gluonhq.com/products/scene-builder/>




Creating an FXML file with SceneBuilder

1. Create a new file (or open existing one)
2. Add a **container** (Containers)
3. Add **controls** (Controls)
4. Provide controls (and containers) with an **fx:id** (Code)
5. Provide controls with **action handlers** (Code)
6. Define the **controller class** (Controller)



Creating an FXML file with SceneBuilder

1. Generate Controller class
(View > Show Sample Controller Skeleton)
2. Copy-Paste in Java file




Alert dialog

Showing an Alert dialog

@FXML

```
void doAdd(ActionEvent event) {  
    try {  
        String name = txtName.getText();  
        double price = Double.parseDouble(txtPrice.getText());  
        int vat = cboVAT.getSelectionModel().getSelectedItem();  
  
        Product product = new Product(name, price, vat);  
  
        Repositories.getProductsRepository().addProduct(product);  
        products.add(product);  
        stage.close();  
    } catch (NumberFormatException ex) {  
        Alert al = new Alert(Alert.AlertType.ERROR, "Invalid price specified.", ButtonType.CLOSE);  
        al.showAndWait();  
    } catch (ProductsException ex) {  
        Alert al = new Alert(Alert.AlertType.ERROR, ex.getMessage(), ButtonType.CLOSE);  
        al.showAndWait();  
    }  
}
```



Common errors/mistakes

javafx.fxml.LoadException

- javafx.fxml.LoadException: Root hasn't been set. Use method setRoot() before load.
- Cause: sometimes SceneBuilder creates the following FXML:
 <fx:root type="VBox" ...>
 </fx:root>
- Solution: replace by:
 <VBox ... >
 </VBox>

java.lang.NullPointerException: Location is required.

- Wrong path/name of your fxml:

```
FXMLLoader.load(  
    FXApp.class.getResource(  
        "fxml/ShowProducts.fxml"  
    ));
```

```
FXMLLoader.load(  
    FXApp.class.getResource(  
        "/fxml/ShowProdukts.fxml"  
    ));
```

- FXML file not where it should be:

```
FXMLLoader.load(  
    FXApp.class.getResource(  
        "/fxml/ShowProducts.fxml"  
    ));
```



Wrong or missing Controller definition in FXML file

- `java.lang.ClassNotFoundException`
 - Typo or non-existing controller class specified
- `javafx.fxml.LoadException: No controller specified`
 - No controller specified
- Initialize method is not executed
 - No controller specified

java.lang.UnsupportedOperationException

```
List<Products> getAllProducts() {  
    return Collections.unmodifiableList(allProducts);  
}
```

FXCollections.observableList(getAllProducts());

FXCollections.observableList(new ArrayList<>(getAllProducts()));

FXCollections.observableArrayList(getAllProducts());

FX:ids on Buttons

- For most buttons you will implement an "onAction" in the FXML and the corresponding method in the controller.
- If this is the use-case, you should not add an fx:id for this button, it is not needed!