

```

1 import time #used for the sleep function
2 from pypot.dynamixel import autodetect_robot #used to get the robot object
3 import pypot.dynamixel #used to get the motors, legs etc.
4 import math #quite obvious
5 import json #to use a json file
6 from contextlib import closing #to close properly the robot at the end
7 import pypot.robot
8
9 asterix = None
10 legs = []
11 xCorrection = [80,0,0,80,0,0]
12 yCorrection = [0,0,0,0,0,0]
13
14
15
16 def leg_ik(x3,y3,z3,alpha = 20.69, beta = 5.06,l1=51,l2=63.7,l3=93):
17     d13 = math.sqrt(x3*x3 + y3*y3) - l1
18     d = math.sqrt(d13*d13 + z3*z3)
19     tmp = (l2**2 + d**2 - l3**2)/(2*l2*d)
20     a1 = z3 / d13
21     a2 = (l2**2 + l3**2 - d**2)/(2*l2*l3)
22
23     angles = (None,None,None)
24     theta1 = math.degrees(math.atan2(y3,x3)) # OK
25
26     theta2 = math.degrees(math.atan(a1) + math.acos(tmp))
27     theta3 = 180 - math.degrees(math.acos(a2))
28 # Corrections to the angles theta2 and theta3
29     theta2 = -(theta2 + alpha)
30     theta3 = -(theta3 - 90 + alpha + beta)
31     angles = (theta1,theta2,theta3)
32     return angles
33
34 def get_legs(obj):
35     return [obj.leg1,obj.leg2,obj.leg3,obj.leg4,obj.leg5,obj.leg6]
36
37 def get_xCorrection(leg):
38     i = int(leg[0].id*0.1)
39     return xCorrection[i-1]
40
41 def get_yCorrection(leg):
42     i = int(leg[0].id*0.1)
43     return yCorrection[i-1]
44
45 """----- Rotation Functions -----"""
46 """ Written by Thor the 24/03/15 """
47 """ Tested by Corentin the 24/03/15 """
48
49
50 """ -----Mathematics to correct the rotation -----"""

```

```

51 """ Written by Thor the 26/04/15"""
52 # This needs to be done so that we can define a common circle of rotation
53 # for all the legs. To communicate this common information to all the legs
54 # we need to express the radius of this common circle of rotation as a function of theta and
    the legs
55 """ I added the attributes needed to obtain this information to the json file
56 Currently these attributes are set to zero"""
57 def R_leg(theta, leg, R):
58     xCorrection = get_xCorrection(leg)
59     yCorrection = get_yCorrection(leg)
60     cos = math.cos(math.radians(theta))
61     sin = math.sin(math.radians(theta))
62     tmp = (xCorrection**2)*((cos**2)-1)
63     tmp += (yCorrection**2)*((sin**2)-1)
64     tmp += xCorrection*yCorrection*math.sin(math.radians(2*theta))
65     tmp += R**2
66     return (-xCorrection*cos - yCorrection*sin + math.sqrt(tmp))
67
68
69 # This function takes care of 1 leg at a time
70 # This moves the leg given polar coordinates. Important because we when we need to do a
    rotation the legs should not move
71 # outside the circle of rotation. We want a perfect rotation!
72 # TEST : Working perfectly
73 def move_leg(theta, z, leg, R = 150):
74
75     i=0
76     # Tupl is a vector that carries the angles that represent the final position of the tip of
        the leg
77     # The angles are calculated from the arguments of the function using inverse kinematics
78     # R is the radius of the circle of rotation. Theta is given in degrees.
79     # Lets transform our polar coordinates onto the Cartesian plane
80     # print R_leg(theta, leg, R), " - ", leg[0].id
81     x = R_leg(theta, leg, R)*math.cos(math.radians(theta))+get_xCorrection(leg)
82     y = R_leg(theta, leg, R)*math.sin(math.radians(theta))+get_yCorrection(leg)
83     motor_angles = leg_ik(x, y, z)
84     for m in leg:
85         m.goal_position = motor_angles[i]
86         i+=1
87     return (x, y, z)
88
89 # This should just give us our initial spider position
90 # We also use this function when rotating to refix the legs' frames of reference
91 """SOLVED?"""
92 #TEST : We SHOULD NOT put negative value in this function (otehrwise the legs (except legs 1-4)
    will 'meet each other')
93 def initial_pos(asterix, theta, z):
94     # Experiments have shown that using the values 100 and 30 for changing x and y respectively
        is working okay
95     initial_position = []
96     initial_position.append(move_leg(0, z, legs[0]))

```

```

97     initial_position.append(move_leg(-abs(theta),z,legs[1]))
98     initial_position.append(move_leg(abs(theta),z,legs[2]))
99     initial_position.append(move_leg(0,z,legs[3]))
100    initial_position.append(move_leg(-abs(theta),z,legs[4]))
101    initial_position.append(move_leg(abs(theta),z,legs[5]))
102
103    time.sleep(0.1)
104
105    return initial_position
106
107    """
108    TODO: make sure that this works. If it works than we can easily do experiments to find the
109           highest value on alpha
110    If we know the highest value of alpha we can determine the number of turns needed to do an
111           arbitrary amount of rotation by using Euclidean division
112    See the draft implementation for arbitrary_rotation above.
113    """
114    # theta is the value we need to set the initial position
115    # alpha determines the amount of rotation (made by each call to the function) from this initial
116           position
117    # alpha is physically limited because of the legs. We should define this limit as max_angle -
118           see above.
119    # TEST : A value of 45 will make the legs (2-3 and 4-5) touch for a little while (actually
120           until the next leg move)
121    def rotation_angle(asterix,alpha,theta,z):
122        #clockwise 2 and 5 are limited
123        breaklength = 0.1
124        # Position 1: The 'spider' position. This position has a low center of gravity.
125        # Here we define the initial position. i.e. the spider position
126        # It is important to observe the x and y values of each leg in its own frame of reference
127
128        # Position 2: Put legs 1, 3, 5 in the air and rotate at the same time
129        move_leg(-abs(theta)+alpha,z+20,legs[1])
130        move_leg(alpha,z+20,legs[3])
131        move_leg(abs(theta)+alpha,z+20,legs[5])
132        time.sleep(breaklength)
133
134        # Position 3: Put legs 1,3 and 5 down
135        move_leg(-abs(theta)+alpha,z,legs[1])
136        move_leg(alpha,z,legs[3])
137        move_leg(abs(theta)+alpha,z,legs[5])
138        time.sleep(breaklength)
139
140        # Position 4: Rotate legs 0, 2, 4
141        move_leg(alpha,z+20,legs[0])
142        move_leg(abs(theta)+alpha,z+20,legs[2])
143        move_leg(-abs(theta)+alpha,z+20,legs[4])
144        time.sleep(breaklength)
145
146        # Position 5: Put legs 0, 2 and 4 down.
147        move_leg(alpha,z,legs[0])

```

```

143     move_leg(abs(theta)+alpha,z,legs[2])
144     move_leg(-abs(theta)+alpha,z,legs[4])
145     time.sleep(breaklength)
146
147     # max_angle = 20 is just a guess.
148     # TEST : Working not too bad. beta = 180 are doing a rotation of 90deg. It seems that we have
149             to multiply the wanted value by 2 to have a proper rotation
150     """SOLVED?"""
151     #TEST : If we put negative value fot the beta angle, this is just not working.
152     # TEST : If the value of max_angle is not 20, the rotation does not work proprely
153     # theta and z are simply values that determine the initial position
154     # Other parameters are to define the rotation
155     def arbitrary_rotation(asterix,beta,max_angle=20,theta=45,z=-60):
156     # Here we do euclidean division. We determine how often max_angle divides beta and the
157             remainder of this division.
158     # This gives us the number of rotations we need to make by a predefined max_angle
159     # The remainder gives us the amount we need to rotate by to be able to finish the full rotation
160             by an angle of beta
161     # i.e. beta = q*max_angle + r
162     initial_pos(asterix,theta,z)
163     if beta < 0:
164         max_angle = -max_angle
165
166     q = beta//max_angle
167     r = beta%max_angle
168     print q
169     print r
170     # rotate by max_angle q times
171     for i in range(1,q):
172         rotation_angle(asterix,max_angle,theta,z)
173         initial_pos(asterix,theta,z)
174     # finally rotate by r
175     rotation_angle(asterix,r,theta,z)
176     initial_pos(asterix,theta,z)
177
178     """ _____ """

```

rotation.py

```

1 import time #used for the sleep function
2 from pypot.dynamixel import autodetect_robot #used to get the robot object
3 import pypot.dynamixel #used to get the motors,legs etc.
4 import math #quite obvious
5 import json #to use a json file
6 from contextlib import closing #to close properly the robot at the end
7 import pypot.robot
8 import rotation
9
10 import Tkinter as tk # to get the a graphic interface for the control function
11
12

```

```

13 asterix = None
14 legs = []
15 initial = []
16
17 def leg_ik(x3,y3,z3,alpha = 20.69, beta = 5.06,l1=51,l2=63.7,l3=93):
18     d13 = math.sqrt(x3*x3 + y3*y3) - l1
19     d = math.sqrt(d13*d13 + z3*z3)
20     tmp = (l2**2 + d**2 - l3**2)/(2*l2*d)
21     a1 = z3 / d13
22     a2 = (l2**2 + l3**2 - d**2)/(2*l2*l3)
23
24     angles = (0,0,0)
25     theta1 = angles[0]
26     theta2 = angles[1]
27     theta3 = angles[2]
28
29     try:
30         theta1 = math.degrees(math.atan2(y3,x3)) # OK
31         theta2 = math.degrees(math.atan(a1) + math.acos(tmp))
32         theta3 = 180 - math.degrees(math.acos(a2))
33         # Corrections to the angles theta2 and theta3
34         theta2 = -(theta2 + alpha)
35         theta3 = -(theta3 - 90 + alpha + beta)
36         angles = (theta1,theta2,theta3)
37     except ValueError:
38         print "The legs of the robot cannot go that far!!"
39
40     return angles
41
42 """
43 Get the legs of the given robot object (from the json file).
44 """
45 def get_legs(obj):
46     return [obj.leg1,obj.leg2,obj.leg3,obj.leg4,obj.leg5,obj.leg6]
47
48 """
49 Makes one leg move.
50 parameters:
51     L — The length between the start point and the end point (in a right line)
52     leg — The leg we want to move
53     initial — a tuple with three values wich correspond to the intial coordonnate of the end
54               of the leg
55 """
56 def move_leg(L,z,leg):
57     num = int(leg[0].id*0.1)-1
58     theta = math.atan(initial[num][1]/initial[num][0])
59     hypo = math.sqrt(initial[num][0]**2 + initial[num][1]**2)
60     x = math.cos(theta)*(hypo+L)
61     y = math.sin(theta)*(hypo+L)
62     z = z
63     angles = leg_ik(x,y,z)

```

```

63     i=0
64     for motors in leg:
65         motors.goal_position = angles[i]
66         i+=1
67     """
68     Make the robot move along his two separate legs
69     """
70     def move_center_forward(L,z):
71         break_length = 1
72         theta = 20 #more than 20 would make the legs touch for a sec (because of the speed)
73         order = [1,5,2,4]
74         if L<0:
75             order = [4,2,5,1]
76
77         move_leg(L,z+40,legs[0])
78         move_leg(-L,z+40,legs[3])
79         time.sleep(break_length)
80
81         move_leg(L,z,legs[0])
82         move_leg(-L,z,legs[3])
83         time.sleep(break_length)
84         for i in order:
85             if i==order[0] or i==order[2]:
86                 rotation.move_leg(-theta,z+40,legs[i])
87             else:
88                 rotation.move_leg(theta,z+40,legs[i])
89                 time.sleep(break_length)
90         for i in order:
91             if i==order[0] or i==order[2]:
92                 rotation.move_leg(-theta,z,legs[i])
93             else:
94                 rotation.move_leg(theta,z,legs[i])
95                 time.sleep(break_length)
96         time.sleep(break_length)
97
98     """
99     THEORICAL WORK: The order of the leg or the direction could be wrong...TO TEST
100     Make the robot move along its two legged side.
101     """
102     def move_center_aside(L,z):
103
104         break_length = 1
105         theta = 20
106         if L<0:
107             theta = -theta
108
109         initial = rotation.initial_pos(0,-60)
110         time.sleep(break_length)
111         move_leg(L,z+40,legs[1])
112         move_leg(L,z+40,legs[2])
113         time.sleep(break_length)

```

```

114     move_leg(L, z, legs [1])
115     move_leg(L, z, legs [2])
116
117
118     move_leg(-L, z+40, legs [4])
119     move_leg(-L, z+40, legs [5])
120     time.sleep(break_length)
121     move_leg(-L, z, legs [4])
122     move_leg(-L, z, legs [5])
123     time.sleep(break_length)
124
125     rotation.move_leg(theta, z+40, legs [0])
126     rotation.move_leg(theta, z+40, legs [3])
127     time.sleep(break_length)
128     rotation.move_leg(theta, z, legs [0])
129     rotation.move_leg(theta, z, legs [3])
130     time.sleep(break_length)
131
132 def moving_all_legs(L, z):
133     move_leg(L, z, legs [0])
134     move_leg(L, z, legs [1])
135     move_leg(L, z, legs [2])
136     move_leg(-L, z, legs [3])
137     move_leg(L, z, legs [4])
138     move_leg(L, z, legs [5])

```

walk.py

```

1 import walk as walk
2 import rotation as rotation
3
4 import itertools
5 import time
6 import numpy
7 from pypot.dynamixel import autodetect_robot
8 import pypot.dynamixel
9 import math
10 import json
11 import time
12 from contextlib import closing
13 import Tkinter as tk
14
15 import pypot.robot
16
17 asterix = None
18 legs = []
19
20
21 def get_object():
22     asterix = pypot.robot.from_json('my_robot.json')
23     legs = get_legs(asterix)
24     rotation.legs = get_legs(asterix)

```

```

25     walk.legs = get_legs(asterix)
26
27     return asterix
28
29 def detection():
30
31     my_robot = autodetect_robot() #detect al the legs of the robot. Might take a while to operate
32     .
33
34     #write the configuration found into a json file. We shouldn't use the complete detection
35     #whith this json file.
36     config = my_robot.to_config()
37     with open('my_robot.json', 'wb') as f:
38         json.dump(config, f)
39
40     with closing(pypot.robot.from_json('my_robot.json')) as my_robot:
41         # do stuff without having to make sure not to forget to close my_robot!
42         pass
43
44 def initialize():
45
46     asterix = pypot.robot.from_json('my_robot.json')
47     # print asterix
48     # Note that all these calls will return immediately,
49     # and the orders will not be directly sent
50     # (they will be sent during the next write loop iteration).
51     for m in asterix.motors:
52         print m.present_position
53         m.compliant = False # <=> enable_torque.
54         m.goal_position = 0
55         # with closing(pypot.robot.from_json('my_robot.json')) as my_robot:
56         # # do stuff without having to make sure not to forget to close my_robot!
57         # pass
58
59     time.sleep(2)
60     return asterix
61
62 def get_legs(obj):
63     return [obj.leg1, obj.leg2, obj.leg3, obj.leg4, obj.leg5, obj.leg6]
64
65 if __name__ == '__main__':
66
67     asterix = get_object()
68     initialize()
69     walk.initial = rotation.initial_pos(asterix, 0, -60)
70     # time.sleep(2)
71     # walk.move_leg(30, 0, rotation.legs[0])
72     # time.sleep(1)
73     # walk.move_leg(30, -60, rotation.legs[0])
74     # time.sleep(1)
75     while 1:

```



```
74     walk.initial = rotation.initial_pos(asterix,0,-60)
75     time.sleep(0.2)
76     walk.move_center_forward(30,-60)
77     walk.initial = rotation.initial_pos(asterix,0,-60)
78     time.sleep(0.2)
79
80     # print rotation.legs[0][0].id
81     # rotation.move_leg(0,-60,rotation.legs[0])
82     # rotation.arbitrary_rotation(asterix,720)
```

main.py