Here is the Markdown table mapping the Attack/Decay/Release 8-bit register values (P) to the actual segment time durations (T), alongside their pre-calculated **22-bit Phase Increment ROM values** in both decimal and hexadecimal formats (clock frequency = 24 MHz, 32-bit accumulator).

Register Value (P)	Time Duration (T)	Phase Increment (inc - Decimal)	Phase Increment (inc - Hex)
0	**0.50 ms** (`0.00050` s)	**357,914**	`0x05761A` (Max speed)
8	**0.71 ms** (`0.00071` s)	**253,440**	`0x03DE00`
16	**1.00 ms** (`0.00100` s)	**179,462**	`0x02BD06`
24	**1.41 ms** (`0.00141` s)	**127,078**	`0x01F066`
32	**1.99 ms** (`0.00199` s)	**89,984**	`0x015F80`
40	**2.81 ms** (`0.00281` s)	**63,718**	`0x00F8E6`
48	**3.97 ms** (`0.00397` s)	**45,119**	`0x00B03F`
56	**5.60 ms** (`0.00560` s)	**31,949**	`0x007CCD`
64	**7.91 ms** (`0.00791` s)	**22,623**	`0x00585F`
72	**11.17 ms** (`0.01117` s)	**16,020**	`0x003E94`
80	**15.78 ms** (`0.01578` s)	**11,344**	`0x002C50`
88	**22.28 ms** (`0.02228` s)	**8,032**	`0x001F60`
96	**31.46 ms** (`0.03146` s)	**5,688**	`0x001638`
104	**44.43 ms** (`0.04443` s)	**4,028**	`0x000FBC`
112	**62.75 ms** (`0.06275` s)	**2,852**	`0x000B24`
120	**88.62 ms** (`0.08862` s)	**2,019**	`0x0007E3`
128	**125.15 ms** (`0.12515` s)	**1,430**	`0x000596`
136	**176.73 ms** (`0.17673` s)	**1,013**	`0x0003F5`
144	**249.59 ms** (`0.24959` s)	**717**	`0x0002CD`
152	**352.47 ms** (`0.35247` s)	**508**	`0x0001FC`

Register Value (P)	Time Duration (T)	Phase Increment (inc - Decimal)	Phase Increment (inc - Hex)
160	**497.77 ms** (`0.49777` s)	**360**	`0x000168`
168	**702.96 ms** (`0.70296` s)	**255**	`0x0000FF`
176	**992.73 ms** (`0.99273` s)	**180**	`0x0000B4`
184	**1.40 s** (`1.40196` s)	**128**	`0x000080`
192	**1.98 s** (`1.97987` s)	**90**	`0x00005A`
200	**2.80 s** (`2.79602` s)	**64**	`0x000040`
208	**3.95 s** (`3.94859` s)	**45**	`0x00002D`
216	**5.58 s** (`5.57629` s)	**32**	`0x000020`
224	**7.87 s** (`7.87495` s)	**23**	`0x000017`
232	**11.12 s** (`11.12118` s)	**16**	`0x000010`
240	**15.71 s** (`15.70556` s)	**11**	`0x00000B`
248	**22.18 s** (`22.17973` s)	**8**	`0x000008`
255	**30.00 s** (`30.00000` s)	**6**	`0x000006` (Min speed)