

Input and Interaction

Sorin Babii

sorin.babii@cs.upt.ro

Objectives

- Introduce the basic input devices
 - Physical Devices
 - Logical Devices
 - Input Modes
- Event-driven input
- Introduce double buffering for smooth animations
- Programming event input with WebGL


Project Sketchpad

- Ivan Sutherland (MIT 1963) established the basic interactive paradigm that characterizes interactive computer graphics:
 - User sees an *object* on the display
 - User points to (*picks*) the object with an input device (light pen, mouse, trackball)
 - Object changes (moves, rotates, morphs)
 - Repeat


Graphical Input

- Devices can be described either by
 - Physical properties
 - Mouse
 - Keyboard
 - Trackball
 - Logical Properties
 - What is returned to program via API
 - A position
 - An object identifier
- Modes
 - How and when input is obtained
 - Request or event


Physical Devices




mouse




trackball




light pen



data tablet



joystick



space ball

Incremental (Relative) Devices

- Devices such as the data tablet return a position directly to the operating system
- Devices such as the mouse, trackball, and joystick return incremental inputs (or velocities) to the operating system

Must integrate these inputs to obtain an absolute position

- Rotation of cylinders in mouse
- Roll of trackball
- Difficult to obtain absolute position
- Can get variable sensitivity

Logical Devices

- Consider the C and C++ code

- C++: `cin >> x;`

- C: `scanf ("%d", &x);`

- What is the input device?

- Can't tell from the code

- Could be keyboard, file, output from another program

- The code provides *logical input*


- A number (an `int`) is returned to the program regardless of the physical device

Graphical Logical Devices

- Graphical input is more varied than input to standard programs which is usually numbers, characters, or bits
- Two older APIs (GKS, PHIGS) defined six types of logical input
 - **Locator**: return a position
 - **Pick**: return ID of an object
 - **Keyboard**: return strings of characters
 - **Stroke**: return array of positions
 - **Valuator**: return floating point number
 - **Choice**: return one of n items

X Window Input

- The X Window System introduced a client-server model for a network of workstations
 - Client:** OpenGL program
 - Graphics Server:** bitmap display with a pointing device and a keyboard




Input Modes

- Input devices contain a *trigger* which can be used to send a signal to the operating system
 - Button on mouse
 - Pressing or releasing a key
- When triggered, input devices return information (their *measure*) to the system
 - Mouse returns position information
 - Keyboard returns ASCII code


Request Mode

- Input provided to program only when user triggers the device
- Typical of keyboard input
 - Can erase (backspace), edit, correct until enter (return) key (the trigger) is depressed



Event Mode

- Most systems have more than one input device, each of which can be triggered at an arbitrary time by a user
- Each trigger generates an *event* whose measure is put in an *event queue* which can be examined by the user program



Event Types

- Window: resize, expose, iconify
- Mouse: click one or more buttons
- Motion: move mouse
- Keyboard: press or release a key
- Idle: nonevent


Define what should be done if no other event is in queue

Animation

Callbacks

- Programming interface for event-driven input uses ***callback functions*** or ***event listeners***
 - Define a callback for each event the graphics system recognizes
 - Browsers enters an event loop and responds to those events for which it has callbacks registered
 - The callback function is executed when the event occurs

Execution in a Browser



Execution in a Browser


- Start with HTML file
 - Describes the page
 - May contain the shaders
 - Loads files
- Files are loaded asynchronously and JS code is executed
- Then what?
- Browser is in an *event loop* and *waits* for an event

onload Event

- What happens with our JS file containing the graphics part of our application?
 - All the “action” is within functions such as `init()` and `render()`
 - Consequently these functions are never executed and we see nothing
 - Solution: use the `onload` window event to initiate execution of the init function
 - `onload` event occurs when all files read
- `-window.onload = init();`

Rotating Square

- Consider the four points on the unit circle



Animate display by re-rendering with different values of θ

Simple but Slow Method

```
for(var theta = 0.0; theta<thetaMax; theta += dtheta;) {  
  
    vertices[0] = vec2(Math.sin(theta), Math.cos.(theta));  
    vertices[1] = vec2(Math.sin(theta), -Math.cos.(theta));  
    vertices[2] = vec2(-Math.sin(theta), -Math.cos.(theta));  
    vertices[3] = vec2(-Math.sin(theta), Math.cos.(theta));  
  
    gl.bufferSubData (.....  
  
    render();  
}
```

Better Way

- Send original vertices to vertex shader
- Send θ to shader as a uniform variable
- Compute vertices in vertex shader
- Render recursively

Render Function

```
var thetaLoc = gl.getUniformLocation(program, "theta");
```

```
function render()
```

```
{
```

```
    gl.clear(gl.COLOR_BUFFER_BIT);
```

```
    theta += 0.1;
```

```
    gl.uniform1f(thetaLoc, theta);
```

```
    gl.drawArrays(gl.TRIANGLE_STRIP, 0, 4);
```

```
    render();
```

```
}
```

Vertex Shader

```
attribute vec4 vPosition;  
uniform float theta;  
  
void main()  
{  
    gl_Position.x = -sin(theta) * vPosition.x + cos(theta) * vPosition.y;  
    gl_Position.y = sin(theta) * vPosition.y + cos(theta) * vPosition.x;  
    gl_Position.z = 0.0;  
    gl_Position.w = 1.0;  
}
```

Double Buffering

- Although we are rendering the square, it goes always into a buffer that is not displayed
- Browser uses double buffering
 - Always display front buffer
 - Rendering into back buffer
 - Need a buffer swap
- Prevents display of a partial rendering

Triggering a Buffer Swap

- Browsers refresh the display at ~60 Hz
 - redisplay of front buffer
 - not a buffer swap
- Trigger a buffer swap through an event
- Two options for rotating square
 - Interval timer
 - requestAnimationFrame

Interval Timer

- Executes a function after a specified number of milliseconds
 - Also generates a buffer swap

```
setInterval(render, interval);
```

- Note an interval of 0 generates buffer swaps *as fast as possible*

requestAnimationFrame

```
function render {  
    gl.clear(gl.COLOR_BUFFER_BIT) ;  
    theta += 0.1 ;  
    gl.uniform1f(thetaLoc, theta) ;  
    gl.drawArrays(gl.TRIANGLE_STRIP, 0, 4) ;  
    requestAnimationFrame(render) ;  
}
```

Add an Interval

```
function render()  
{  
    setTimeout( function() {  
        requestAnimationFrame(render) ;  
        gl.clear(gl.COLOR_BUFFER_BIT) ;  
        theta += 0.1 ;  
        gl.uniform1f(thetaLoc, theta) ;  
        gl.drawArrays(gl.TRIANGLE_STRIP, 0, 4) ;  
    }, 100) ;  
}
```

Working with Callbacks

Objectives

- Learn to build interactive programs using event listeners
 - Buttons
 - Menus
 - Mouse
 - Keyboard
 - Reshape

Adding a Button

- Let's add a button to control the rotation direction for our rotating cube
- In the render function we can use a var **direction** which is true or false to add or subtract a constant to the angle

```
var direction = true; // global initialization
```

```
// in render()
```

```
if(direction) theta += 0.1;  
else theta -= 0.1;
```

The Button

- In the HTML file

```
<button id="DirectionButton">Change Rotation Direction</button>
```

- Uses HTML **button** tag
- **id** gives an identifier we can use in JS file
- Text “Change Rotation Direction” displayed in button
- Clicking on button generates a **click** event
- Note we are using default style and could use CSS or jQuery to get a prettier button

Button Event Listener

- We still need to define the listener
 - no listener and the event occurs but is ignored
- Two forms for event listener in JS file

```
var myButton =  
document.getElementById("DirectionButton");  
  
myButton.addEventListener("click", function() {  
    direction = !direction;  
});
```

```
document.getElementById("DirectionButton").onclick =  
function() { direction = !direction; };
```

onclick Variants

```
myButton.addEventListener("click", function() {  
  if (event.button == 0) { direction = !direction; }  
});
```

```
myButton.addEventListener("click", function() {  
  if (event.shiftKey == 0) { direction = !direction; }  
});
```

```
<button onclick="direction = !direction"></button>
```

Controlling Rotation Speed

```
var delay = 100;

function render()
{
    setTimeout(function() {
        requestAnimationFrame(render);
        gl.clear(gl.COLOR_BUFFER_BIT);
        theta += (direction ? 0.1 : -0.1);
        gl.uniform1f(thetaLoc, theta);
        gl.drawArrays(gl.TRIANGLE_STRIP, 0, 4);
    }, delay);
}
```

Video

rotatingSquare1

rotatingSquare2

Menus

- Use the HTML `select` element
- Each entry in the menu is an `option` element with an integer `value` returned by click event

```
<select id="mymenu" size="3">
<option value="0">Toggle Rotation Direction</option>
<option value="1">Spin Faster</option>
<option value="2">Spin Slower</option>
</select>
```

Menu Listener

```
var m = document.getElementById("mymenu");  
m.addEventListener("click", function() {  
    switch (m.selectedIndex) {  
        case 0:  
            direction = !direction;  
            break;  
        case 1:  
            delay /= 2.0;  
            break;  
        case 2:  
            delay *= 2.0;  
            break;  
    }  
});
```

Using keydown Event

```
window.addEventListener("keydown", function() {  
    switch (event.keyCode) {  
        case 49: // '1' key  
            direction = !direction;  
            break;  
        case 50: // '2' key  
            delay /= 2.0;  
            break;  
        case 51: // '3' key  
            delay *= 2.0;  
            break;  
    }  
});
```

Don't Know Unicode

```
window.onkeydown = function(event) {  
    var key = String.fromCharCode(event.keyCode);  
    switch (key) {  
        case '1':  
            direction = !direction;  
            break;  
        case '2':  
            delay /= 2.0;  
            break;  
        case '3':  
            delay *= 2.0;  
            break;  
    }  
};
```


Slider Element

- Puts slider on page
 - Give it an **id**entifier
 - Give it **minimum** and **maximum** values
 - Give it a step **size** needed to generate an event
 - Give it an initial **value**
- Use **div** tag to put below canvas

```
<div>  
speed 0 <input id="slide" type="range"  
    min="0" max="100" step="10" value="50" />  
100 </div>
```

onchange Event Listener

```
document.getElementById("slide").onchange =  
    function() { delay = event.srcElement.value; };
```

Video

rotatingSquare3

Position Input


Objectives

- Learn to use the mouse to give locations

Must convert from position on canvas to position in application

- Respond to window events such as reshapes triggered by the mouse

Window Coordinates



Window to Clip Coordinates

$$(0, h) \rightarrow (-1, -1)$$

$$(w, 0) \rightarrow (1, 1)$$

$$x = -1 + \frac{2 * x_w}{w}$$

$$y = -1 + \frac{2 * (h - y_w)}{h}$$

Returning Position from Click Event

Canvas specified in HTML file of size `canvas.width` x `canvas.height`

Returned window coordinates are `event.clientX` and `event.clientY`

```
// add a vertex to GPU for each click
canvas.addEventListener("click", function() {
    gl.bindBuffer(gl.ARRAY_BUFFER, vBuffer);
    var t = vec2(-1 + 2*event.clientX/canvas.width,
        -1 + 2*(canvas.height-event.clientY)/canvas.height);
    gl.bufferSubData(gl.ARRAY_BUFFER,
        sizeof['vec2']*index, t);
    index++;
});
```


CAD-like Examples

`www.cs.upt.ro/~sorin/webgl/Code/w04/`

`square.html`: puts a colored square at location of each mouse click

`triangle.html`: first three mouse clicks define first triangle of triangle strip. Each succeeding mouse clicks adds a new triangle at end of strip

`cad1.html`: draw a rectangle for each two successive mouse clicks

`cad2.html`: draws arbitrary polygons

Video

www.cs.upt.ro/~sorin/webgl/Code/w04/

square

triangle

cad1

cad2

Window Events

- Events can be generated by actions that affect the canvas window
 - moving or exposing a window
 - resizing a window
 - opening a window
 - iconifying/deiconifying a window a window
- Note that events generated by other application that use the canvas can affect the WebGL canvas
 - There are default callbacks for some of these events

Reshape Events

- Suppose we use the mouse to change the size of our canvas
- Must redraw the contents
- Options
 - Display the same objects but change size
 - Display more or fewer objects at the same size
- Almost always want to keep proportions

onresize Event

- Returns size of new canvas is available through `window.innerHeight` and `window.innerWidth`
- Use `innerHeight` and `innerWidth` to change `canvas.height` and `canvas.width`
- Example: maintaining a square display

Keeping Square Proportions

```
window.onresize = function() {  
    var min = innerWidth;  
    if (innerHeight < min) {  
        min = innerHeight;  
    }  
    if (min < canvas.width || min < canvas.height) {  
        gl.viewport(0, canvas.height-min, min, min);  
    }  
};
```

Picking

Objectives

- How do we identify objects on the display
- Overview three methods
 - selection
 - using an off-screen buffer and color
 - bounding boxes

Why is Picking Difficult?

- Given a point in the canvas how do map this point back to an object?
- Lack of uniqueness
- Forward nature of pipeline
- Take into account difficulty of getting an exact position with a pointing device

Selection

- Supported by fixed function OpenGL pipeline
- Each primitive is given an id by the application indicating to which object it belongs
- As the scene is rendered, the id's of primitives that render near the mouse are put in a hit list
- Examine the hit list after the rendering

Selection


- Implement by creating a window that corresponds to small area around mouse
 - We can track whether or not a primitive renders to this window
 - Do not want to display this rendering
 - Render off-screen to an extra color buffer or user back buffer and don't do a swap
- Requires a rendering which puts depths into hit record
- Possible to implement with WebGL

Picking with Color

- We can use `gl.readPixels` to get the color at any location in window
- Idea is to use color to identify object but
 - Multiple objects can have the same color
 - A shaded object will display many colors
- Solution: assign a unique color to each object and render off-screen
 - Use `gl.readPixels` to get color at mouse location
 - Use a table to map this color to an object

Picking with Bounding Boxes

- Both previous methods require an extra rendering each time we do a pick
- Alternative is to use a table of (axis-aligned) bounding boxes
- Map mouse location to object through table



Geometry

Objectives

- Introduce the elements of geometry
 - Scalars
 - Vectors
 - Points
- Develop mathematical operations among them in a coordinate-free manner
- Define basic primitives
 - Line segments
 - Polygons

Basic Elements

- Geometry is the study of the relationships among objects in an n-dimensional space
 - In computer graphics, we are interested in objects that exist in three dimensions
- Want a minimum set of primitives from which we can build more sophisticated objects
- We will need three basic elements
 - Scalars
 - Vectors
 - Points

Coordinate-Free Geometry


- When we learned simple geometry, most of us started with a Cartesian approach
 - Points were at locations in space $\mathbf{p}=(x,y,z)$
 - We derived results by algebraic manipulations involving these coordinates
- This approach was nonphysical
 - Physically, points exist regardless of the location of an arbitrary coordinate system
 - Most geometric results are independent of the coordinate system
 - Example: Euclidean geometry: two triangles are identical if two corresponding sides and the angle between them are identical

Scalars

- Need three basic elements in geometry
 - Scalars, Vectors, Points
- Scalars can be defined as members of sets which can be combined by two operations (addition and multiplication) obeying some fundamental axioms (associativity, commutativity, inverses)
- Examples include the real and complex number systems under the ordinary rules with which we are familiar
- Scalars alone have no geometric properties


Vectors

- Physical definition: a vector is a quantity with two attributes
 - Direction
 - Magnitude
- Examples include
 - Force
 - Velocity
 - Directed line segments
 - Most important example for graphics
 - Can map to other types



Vector Operations

- Every vector has an inverse
 - Same magnitude but points in opposite direction
- Every vector can be multiplied by a scalar
- There is a zero vector
 - Zero magnitude, undefined orientation
- The sum of any two vectors is a vector
 - Use head-to-tail axiom




Linear Vector Spaces

- Mathematical system for manipulating vectors
- Operations
 - Scalar-vector multiplication $U = \alpha V$
 - Vector-vector addition: $W = U + V$
- Expressions such as
$$v = u + 2w - 3r$$

Make sense in a vector space


Vectors Lack Position

- These vectors are identical
 - Same length and magnitude
- Vectors spaces insufficient for geometry
 - Need points



Points

- Location in space
- Operations allowed between points and vectors
 - Point-point subtraction yields a vector
 - Equivalent to point-vector addition



$$v = P - Q$$

$$P = v + Q$$

Affine Spaces


- Point + a vector space
- Operations
 - Vector-vector addition
 - Scalar-vector multiplication
 - Point-vector addition
 - Scalar-scalar operations
- For any point define
 - 1 • P = P
 - 0 • P = **0**(zero vector)

Lines

- Consider all points of the form

- $P(\alpha) = P_0 + \alpha \mathbf{d}$

- Set of all points that pass through P_0 in the direction of the vector \mathbf{d}



Parametric Form

- This form is known as the parametric form of the line
 - More robust and general than other forms
 - Extends to curves and surfaces
- Two-dimensional forms
 - Explicit: $y = mx + h$
 - Implicit: $ax + by + c = 0$
 - Parametric:
$$x(\alpha) = \alpha x_0 + (1-\alpha)x_1$$
$$y(\alpha) = \alpha y_0 + (1-\alpha)y_1$$

Rays and Line Segments


- If $\alpha \geq 0$, then $P(\alpha)$ is the *ray* leaving P_0 in the direction \mathbf{d}

If we use two points to define \mathbf{v} , then

$$P(\alpha) = Q + \alpha (R - Q) = Q + \alpha \mathbf{v}$$


$$= \alpha R + (1 - \alpha)Q$$

For $0 \leq \alpha \leq 1$ we get all the points on the *line segment* joining R and Q




Convexity

- An object is *convex* iff for any two points in the object all points on the line segment between these points are also in the object



convex



not convex

Affine Sums

- Consider the “sum”

$$P = \alpha_1 P_1 + \alpha_2 P_2 + \dots + \alpha_n P_n$$

Can show by induction that this sum makes sense iff


$$\alpha_1 + \alpha_2 + \dots + \alpha_n = 1$$

in which case we have the *affine sum* of the points P_1, P_2, \dots, P_n

- If, in addition, $\alpha_i \geq 0$, we have the *convex hull* of P_1, P_2, \dots, P_n


Convex Hull

- Smallest convex object containing P_1, P_2, \dots, P_n
- Formed by “shrink wrapping” points




Curves and Surfaces

- Curves are one parameter entities of the form $P(\alpha)$ where the function is nonlinear
- Surfaces are formed from two-parameter functions $P(\alpha, \beta)$
 - Linear functions give planes and polygons




$P(\alpha)$




$P(\alpha, \beta)$

Planes

- A plane can be defined by a point and two vectors or by three points




$$P(\alpha, \beta) = R + \alpha u + \beta v$$



$$P(\alpha, \beta) = R + \alpha(Q - R) + \beta(P - R)$$

Triangles



for $0 \leq \alpha, \beta \leq 1$, we get all points in triangle

Barycentric Coordinates

Triangle is convex so any point inside can be represented as an affine sum

$$P(\alpha_1, \alpha_2, \alpha_3) = \alpha_1 P + \alpha_2 Q + \alpha_3 R$$

where

$$\alpha_1 + \alpha_2 + \alpha_3 = 1$$

$$\alpha_i \geq 0$$

The representation is called the **barycentric coordinate** representation of P

Normals

- In three dimensional spaces, every plane has a vector \mathbf{n} perpendicular or orthogonal to it called the **normal vector**
- From the two-point vector form $P(\alpha, \beta) = P + \alpha\mathbf{u} + \beta\mathbf{v}$, we know we can use the cross product to find $\mathbf{n} = \mathbf{u} \times \mathbf{v}$ and the equivalent form

$$(\mathbf{P}(\alpha, \beta) - \mathbf{P}) \cdot \mathbf{n} = 0$$

