

Exp No: 5

DESIGN A DESK CALCULATOR USING LEX TOOL

AIM:

To check whether the arithmetic expression using lex and yacc tool.


ALGORITHM:

- Using the flex tool, create lex and yacc files.
- In the C include section define the header files required.
- In the rules section define the REGEX expressions along with proper definitions.
- In the user defined section define yywrap() function.
- Declare the yacc file inside it in the C definitions section declare the header files required along with an integer variable valid with value assigned as 1.
- In the Yacc declarations declare the format token num id op.
- In the grammar rules section if the starting string is followed by assigning operator or identifier or number or operator followed by a number or open parenthesis followed by an identifier. The x could be an operator followed by an identifier or operator or no operator then declare that as valid expressions by making the valid stay in 1 itself.
- In the user definition section if the valid is 0 print as Invalid expression in yyerror() and define the main function.

LEX AND YACC WORKING:

Parser generator:

- Takes a specification for a context-free grammar.
- Produces code for a parser.



PROGRAM:

cdlab5.l:

```
%{  
    #include "y.tab.h"  
}%  
  
%%
```

```
[a-zA-Z_][a-zA-Z_0-9]* return id;
```

```
[0-9]+(\\. [0-9]*)?    return num;  
[+/*]                return op;  
                    return yytext[0];
```

```
.  
\\n                    return 0;
```

```
%%
```

```
int yywrap(){ return  
1; } cdlab5.y:  
%{
```

```
    #include<stdio.h  
    > int yylex()); int  
    yyerror();    int  
    valid=1;
```

```
%}
```

```
%token num id op
```

```
%%  
start : id '=' s ';' ;
```

```
s :    id x  
      | num x  
      | '-' num x  
      | '(' s ')' x
```

```

| '-' s
|
;
%%
int yyerror(){ valid=0; printf("\nInvalid
expression!\n"); return 0;
} int main(){ printf("\nEnter the
expression:\n"); yyparse(); if(valid){
printf("\nValid expression!\n");
}}

```

OUTPUT:

```

(kali㉿kali)-[~/Documents/cdlab]
$ vi cdlab5.y

(kali㉿kali)-[~/Documents/cdlab]
$ yacc -d cdlab5.y

(kali㉿kali)-[~/Documents/cdlab]
$ vi cdlab5.l

(kali㉿kali)-[~/Documents/cdlab]
$ lex cdlab5.l

(kali㉿kali)-[~/Documents/cdlab]
$ gcc lex.yy.c y.tab.c

(kali㉿kali)-[~/Documents/cdlab]
$ ./a.out

Enter the expression:
a=b

Invalid expression!

(kali㉿kali)-[~/Documents/cdlab]
$ ./a.out

Enter the expression:
a=b;

Valid expression!

```

RESULT:

Thus, a program to check whether the arithmetic expression using lex and yacc tool is implemented.