

VISVESVARAYA TECHNOLOGICAL UNIVERSITY

“JnanaSangama”, Belgaum -590014, Karnataka.



LAB RECORD

Computer Network Lab (23CS5PCCON)

Submitted by

Thrisha D (1BM24CS426)

in partial fulfillment for the award of the degree of

BACHELOR OF ENGINEERING

in

COMPUTER SCIENCE AND ENGINEERING



B.M.S. COLLEGE OF ENGINEERING

(Autonomous Institution under VTU)

BENGALURU-560019


Academic Year 2024-25 (odd)

B.M.S. College of Engineering

Bull Temple Road, Bangalore 560019

(Affiliated To Visvesvaraya Technological University, Belgaum)

Department of Computer Science and Engineering



CERTIFICATE

This is to certify that the Lab work entitled “ Computer Network (23CS5PCCON)” carried out by **Thrisha D (1BM24CS426)**, who is bonafide student of **B.M.S. College of Engineering**. It is in partial fulfilment for the award of **Bachelor of Engineering in Computer Science and Engineering** of the Visvesvaraya Technological University, Belgaum. The Lab report has been approved as it satisfies the academic requirements of the above-mentioned subject and the work prescribed for the said degree.

Surabhi S Assistant Professor Department of CSE, BMSCE	Dr. Kavitha Sooda Professor & HOD Department of CSE, BMSCE
--	--

Index

Sl. No.	Date	Experiment Title	Page No.
1	03/09/25	Simple PDU from source to destination using hub and switch as connecting devices.	4
2	10/09/25	Default route and static route to the Router	9
3	17/09/25	DHCP within a LAN and outside LAN	14
4	17/09/25	Web Server, DNS within a LAN	17
5	08/10/25	Operation of TELNET to access the router in server room from a PC in IT office	19
6	08/10/25	RIP routing Protocol in Routers	23
7	15/10/25	VLAN to make the PCs communicate among a VLAN	26
8	29/10/25	WLAN to make the nodes communicate wirelessly	29
9	12/11/25	Simple LAN to understand the concept and operation of ARP	33
10	12/11/25	OSPF routing protocol	36
11	08/10/25	TTL/ Life of a Packet	41
12	03/09/25	Ping responses, destination unreachable, request timed out, reply	43
13	29/10/25	Congestion control using Leaky bucket algorithm	45
14	29/10/25	Error detecting code using CRC-CCITT	49
15	03/11/25	TCP File Request–Response Using Client–Server Socket Program	54
16	03/11/25	UDP File Request–Response Using Client–Server Socket Program	57

Github Link:

https://github.com/ThrishaD2/Computer_Networks.git


CYCLE 1:

Program 1

Aim of the program:

Create a topology and simulate sending a simple PDU from source to destination using hub and switch as connecting devices and demonstrate ping message.

Procedure and topology:




Lab -1

3/09/25


create a topology and simulate sending a simple PDU from source to destination using hub and switch as connecting devices and demonstrate ping message

Topology

Hub



Switch



Aim: To understand Simple PC-PDU Configuration

Procedure

1. Select PC from end devices select generic PC and drop it in workspace similarly, select generic server
2. Choose copper - cross-over in the connections and choose fast ethernet
3. click on server and choose fast ethernet ()
4. click on PC and go to config tab. set IP address to 10.0.0.1 and click on Subnet Mask
5. Repeat same step and set IP address for server
6. In simulation mode, in edit filters click only ICMP
7. Add a simple PDU from PC to server

8. Click on autocapture / play

Hub

Procedure

- 1) select the end devices and change their IP address suitably
- 2) select hub as the connecting device
- 3) select copper straight-through as the connecting wire between end devices and hub
- 4) connect the fast ethernet to hub ports
- 5) select the message and first check on source device and destination device
- 6) observe the packet transmission and acknowledgement receiving procedure





Switch

Procedure


1. select the end devices and change their IP address suitably
2. select switch as the connecting device
3. select copper straight through as the connecting wire b/w end devices and hub
4. connect the fast ethernet to hub ports
5. select the message and first click on source device and then destination device
6. observe the packet transmission and acknowledgement receiving procedure.


Doalor

Screenshots/ Output:



Updated topology





Observation:


- In the hub-based topology, the PDU was broadcast to all ports, while the switch forwarded the PDU only to the destination MAC after learning addresses from incoming frames.
- Successful ICMP echo and echo-reply messages confirm that both devices enabled connectivity, with the switch demonstrating selective unicast forwarding and reduced unnecessary traffic.

Program 2

Aim of the program:

Configure default route, static route to the Router

Procedure and topology:



6) we need to set ip address for all routers via routers
For router - 1 & router - 2 we do default routing and
for router - 0, static routing is done.

For router - 1

```
# config t
```

```
# ip route 0.0.0.0 0.0.0.0 20.0.0.2
```

```
# no shut
```

```
# exit
```

```
show ip rout
```


C 10.0.0.0/8 is directly connected, FastEthernet 0/0

C 20.0.0.0/8 is directly connected, Serial 2/0


S * 0.0.0.0/0 [1/0] via 20.0.0.2

Similarly for router - 2


Screenshots/ Output:



Static routing CLI commands:



Default routing CLI commands:



Observation:


- The configured static and default routes correctly updated the router's routing table, enabling deterministic next-hop selection for remote networks.
- Successful ping tests verified that traffic was forwarded according to the static/default route entries, ensuring end-to-end reachability across different network segments.

Program 3

Aim of the program:

Configure DHCP within a LAN and outside LAN.

Procedure and topology:






```
#interface fastEthernet 0/0  
#ip address 20.0.0.1 255.0.0.0  
# no shutdown  
# exit
```

9) Now go to **network < services < DHCP < add new IP address**

10) To check the connection go to the IP configuration of PC outside the network and click on DHCP and IP gateway will be visible

Screenshots/ Output:



Observation:

- The DHCP server successfully allocated IP addresses to clients within the LAN, confirming proper scope configuration and automatic distribution of network parameters.
- DHCP relay (IP Helper) enabled clients outside the LAN to obtain leases from the central DHCP server, demonstrating correct inter-network forwarding of DHCP Discover and Offer messages.


Program 4

Aim of the program:

Configure Web Server, DNS within a LAN.

Procedure and topology:

2. Configure Web server DNS within a LAN



```
graph LR; PC[PC 10.0.0.1] --- Switch[Switch]; Switch --- Server[Server 10.0.0.2]
```

Procedure

- 1) the topology consists of a PC, server and switch
- 2) connect them using copper - straight through wires
- 3) set ip address of PC as 10.0.0.1 and that of server as 10.0.0.2
- 4) click on PC
Desktop < web browser < 10.0.0.2
It displays the index.html page of the server
- 5) click on server
services < index.html < edit <
change the subject to BMS college of engineering CSE < save
- 6) click on PC
Desktop < web browser < 10.0.0.2
It changes the content of index.html, page as It changes the content of 1

1) click on server
services < DNS < ON <
give domain name as bmscscse <
set address as 10.0.0.2
< add


8) click on PC

Desktop < webbrowser < bmscscse

It displays the same index.html of page of the server (with
ip address 10.0.0.2)

17.09

Screenshots/ Output:



Observation:

- The DNS server successfully resolved domain names to the corresponding web server's IP address, confirming proper hostname-to-IP mapping within the LAN.
- HTTP requests reached the web server using the DNS-resolved address, validating correct server configuration and internal LAN communication.

Program 5

Aim of the program:

To understand the operation of TELNET by accessing the router in server room from a PC in IT office

Procedure and topology:

8/10/25

Lab - 4

To understand the operation of TELNET

Topology:-

```
graph LR
    PC[PC - 0  
192.168.1.3] --- Switch[Switch 2]
```

Procedure

- 1) Configure topology as above. Use copper cross over wire to connect both. Configure IP address and gateway and the ~~router~~ switch generally
- 2) In switch CLI

```
> enable
> configure terminal
> hostname Switch2
> enable secret pass
> interface vlan1
> ip address 192.168.1.3 255.255.255.0
> no shutdown
> #exit
> #line vty 0 4
> #password cisco
> #login
> #exit
```

Open command prompt in PC

PC > telnet 192.168.1.2 = (default gateway)

Trying - - - open

> user verification

> Password: cisco

observation:

→ Telnet connection was successfully established b/w PC and switch

→ LAN access the switch command line

→ can manage the switch directly, connected through console

→ prompt to configure the password (Cisco)

8110

router
↓
gate way = 192.168.1.1

Fast ethernet 0 = 192.168.1.2

PC₀

PC₁ = 192.168.1.3

gateway = 192.168.20.1

PC₂ = 192.168.20.2

PC₃ = 192.168.20.3

VLAN num
VLAN name


```

CLI router 1
> enable
> conf t
> interface gigabitethernet 0/24
> ip address 192.168.1.1 255.255.255.0
> no shutdown
> exit
> interface gigabitethernet 0/24
> ip address 192.168.20.1 255.255.255.0
> no shutdown
> exit
  
```

```

CLI router 0
> enable
> conf t
> interface gigabitethernet 0/24
> ip address 192.168.1.2 255.255.255.0
> no shutdown
> exit
> interface gigabitethernet 0/24
> ip address 192.168.20.2 255.255.255.0
> no shutdown
> exit
> interface gigabitethernet 0/24
> ip address 192.168.20.3 255.255.255.0
> no shutdown
> exit
  
```

Screenshots/ Output:



A screenshot of a Packet Tracer PC Command Line window for PC1. The window has tabs for Physical, Config, Desktop, and Custom Interface. The Command Prompt shows the following text:

```
Packet Tracer PC Command Line 1.0
PC>telnet 192.168.1.2
Trying 192.168.1.2 ...Open

User Access Verification

Password:
Router1>ping 192.168.1.1

Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 192.168.1.1, timeout
is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip
min/avg/max = 0/1/3 ms

Router1>exit

[Connection to 192.168.1.2 closed by foreign host]
PC>
```

A screenshot of a Packet Tracer Router CLI window for Router2. The window has tabs for Physical, Config, and CLI. The CLI shows the following text:

```
Router2
Router(config-if)#npno shutdown

Router(config-if)#
%LINK-5-CHANGED: Interface FastEthernet0/0, changed state
to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface
FastEthernet0/0, changed state to up

Router(config-if)#exit
Router(config)#hostname Router1
Router1(config)#enable secret p1
Router1(config)#line vty 0 4
Router1(config-line)#login
% Login disabled on line 132, until 'password' is set
% Login disabled on line 133, until 'password' is set
% Login disabled on line 134, until 'password' is set
% Login disabled on line 135, until 'password' is set
% Login disabled on line 136, until 'password' is set
Router1(config-line)#password cisco
Router1(config-line)#exit
```

At the bottom of the window are 'Copy' and 'Paste' buttons.

Observation:


- The Telnet session successfully established a remote CLI connection to the router, confirming proper VTY line configuration and IP reachability between the IT office PC and the server room router.
- Command execution over the Telnet session demonstrated reliable remote device management.

Program 6

Aim of the program:

Configure RIP routing Protocol in Routers


Procedure and topology:





>end
 >show ip interface brief
 >show ip route

CLI routers

>enable
 >config t
 >interface se 2/0
 >ip address 30.0.0.2 255.0.0.0
 >encapsulation PPP
 >no shutdown
 >exit
 >interface fa 0/0
 >ip address 40.0.0.1 255.0.0.0
 >no shutdown
 >exit
 >router rip
 >version 2
 >network 30.0.0.0
 >network 40.0.0.0
 >exit
 >end



Screenshots/ Output:



Observation:


- RIP routing updates were successfully exchanged between routers, allowing each router to dynamically learn remote network routes through hop-count-based distance vector advertisements.
- The routing tables converged correctly, and successful ping tests confirmed end-to-end connectivity maintained by periodic RIP updates and route propagation.

Program 7

Aim of the program:

To construct a VLAN and make the PCs communicate among a VLAN

Procedure and topology:



7. In Router, select VLAN DATABASE, enter the number and name of the VLAN created.

In CLI of router

Router(VLAN)# exit

APPLY completed.

Exiting...

Router# config t

Router(config)# int f 0/0.1

Router(config-subif)# ip address 192.168.1.1 255.255.255.0

Router(config-subif)# no shut

Router(config)# interface fastethernet 0/0.1

Router(config-subif)# encapsulation dot1q 10

Router(config-subif)# ip address 192.168.2.1 255.255.255.0

Router(config-subif)# no shut

Router(config-subif)# exit

Result

in PC

PC > ping 192.168.20.3

Pinging 192.168.20.3 with 32 bytes of data:

Reply from 192.168.20.3: bytes=32 time=1ms TTL=128

Reply from 192.168.20.3: bytes=32 time=1ms TTL=128

Reply from 192.168.20.3: bytes=32 time=0ms TTL=128

Reply from 192.168.20.3: bytes=32 time=0ms TTL=128

Ping: statistics for 192.168.20.3

Packets: sent=4, Received=4, Lost=0

Approximate round trip time in milliseconds.


Minimum=0ms, Minimum=1ms, Average=0ms

Observation:

- 1) VLAN - virtual local area network is any broadcast domain that is partitioned and isolated in a completed network at the data link layer.
- 2) It is a virtualized connection that converts multiple devices and network nodes from different LANs into one locally logical network.

Q. 15.10

Screenshots/ Output:



Observation:


- VLAN segmentation successfully separated broadcast domains, and switch ports were correctly assigned to their respective VLAN IDs using access mode configuration.
- Inter-VLAN communication was achieved through the Layer-3 device, and successful ping tests confirmed proper VLAN membership, tagging, and routing functionality.

Program 8


Aim of the program:

To construct a WLAN and make the nodes communicate wirelessly

Procedure and topology:



Topology



observation :

1. wireless local area network WLAN is a group of allocated computers or other devices that form a n/w based on radio transmission rather than wired connections
2. After the WLAN is setup linear connection appears in topology from access point.

Result :

In PC0

PC > Ping 10.0.0.3

pinging 10.0.0.3 with 32 bytes of data

Reply from 10.0.0.3 : bytes = 32 time = 21ms TTL = 125

Reply from 10.0.0.3 : bytes = 32 time = 21ms TTL = 12

1


Ping statistics for 10.0.0.3

Packets : sent = 4 Received = 4 lost = 0

Approximate roundtrip time in ms

minimum = 6ms maximum = 21ms Average = 12ms

Screenshots/ Output:



Observation:

- The WLAN configuration enabled wireless nodes to associate with the access point using the configured SSID and security settings, confirming proper authentication and signal coverage.
- Successful ping communication between wireless devices verified stable wireless Connectivity.

Program 9


Aim of the program:

To construct simple LAN and understand the concept and operation of Address Resolution Protocol (ARP)

Procedure and topology:

Aim : To construct simple LAN and understand the concept and operation of Address Resolution Protocol (ARP)

Topology :



Procedure :

1. select a switch server and 3 PC's and connect them to the switch as shown the topology above
2. Connect them with copper - straight through
3. set the IP address of switch and PC as shown
4. select the inject tool from the tool base and open the ARP tables of all devices
5. then , ping the device from the command prompt of other devices from the command prompt of other devices and click on capture in the simulation mode to know the packet routing
6. with every ping the arp tables of devices get filled with MAC address of the corresponding devices
7. Even the switch learns about the MAC address of all devices during pinging process
8. once you have pinged all devices , you can check the arp table of each device in command prompt of PC's

>arp -a

Internet address	Physical address	Type
10.0.0.1	006.0.49043	Dynamic
10.0.0.2	006.0475.143	Dynamic

9) In the switch → CLI you can check the MAC address of the devices as follows

Switch > show MAC address-table
MAC address table


VLAN	MAC address	Type	Ports
1	0005.50060b46	Dynamic	Fa2/1
1	000C.8546.6a9c	Dynamic	Fa3/1
1	0060.47a4.a043	Dynamic	Fa0/1

observation

ARP protocol is communication protocol used for discovering the link layer address, such as a MAC address. After pinging, every device learns about the MAC address of the pinged devices and the switch store these MAC address in the ARP table for future pinging.

19-11

Screenshots/ Output:



Observation:


- ARP successfully resolved the destination IP address to its corresponding MAC address, as seen from ARP request and reply exchanges between LAN hosts.
- The populated ARP tables and successful ping communication confirmed correct layer-2 addressing, frame forwarding, and basic LAN operation.

Program 10

Aim of the program:

Configure OSPF routing protocol

Procedure and topology:




```
R1 (config-r)# network 20.0.0.0 0.255.255.255 area 1 3  
R1 (config-r)# exit
```

Router 0

```
>config t  
R0 (config)# router ospf 1  
R0 (config)# router-id 2.2.2.2  
R0 (config-r)# network 20.0.0.0 0.255.255.255 area 1 3  
R0 (config-r)# network 30.0.0.0 0.255.255.255 area 0  
R0 (config-r)# exit
```

Router 2

```
>config t  
R2 (config)# router ospf 1  
R2 (config)# router-id 3.3.3.3  
R2 (config-r)# network 30.0.0.0 0.255.255.255 area 0  
R2 (config-r)# network 40.0.0.0 0.255.255.255 area 2
```

7. configuring the interface

```
R1 (config-if)# interface loopback 0  
R1 (config-if)# ip add 172.16.1.252 255.255.0.0  
R1 (config-if)# no shutdown
```

```
R2 (config-if)# interface loopback 0  
R2 (config-if)# ip address 172.16.1.253 255.255.255.0  
# no shutdown
```

```
R3 (config-if)# interface loopback 0  
# ip address 172.16.1.254 255.255.0.0  
# no shutdown
```

```
R3 #show ip route
```

C to 40.0.0.0/8 is directly connected

30.0.0.0/8 is directly connected, serial 3/0
30.0.0.1/32 is directly connected serial 3/0
40.0.0.1/32 is directly connected

8) In Router R1

R1 (config) # router ospf 1

area 1 virtual link 2.2.2.2



In Router R2

R2 (config) # router ospf 1

area 1 virtual link 2.2.2.2

12.11

Screenshots/ Output:



Observation:


- OSPF successfully established neighbour adjacencies and exchanged LSAs, allowing routers to build a synchronized link-state database across the OSPF area.
- The routing tables converged using SPF calculations, and successful pings confirmed efficient path selection and dynamic route learning through OSPF.

Program 11


Aim of the program:

Demonstrate the TTL/ Life of a Packet

Procedure and topology:



Screenshots/ Output:



PDU Information at Device: Router0

OSI Model Inbound PDU Details Outbound PDU Details

PDU Formats

Ethernet II


0	4	8	14	19 bytes
PREAMBLE:		DEST MAC:		SRC MAC:
101010...				
TYP	DATA (VARIABLE LENGTH)			FCS
E:				:

IP

0	4	8	16	19	31 bits
4	IHL	DSCP:	TL: 28		
ID: 0x3		0x		0x0	
TTL: 255		PRO: 0x1		CHKSUM	
SRC IP: 10.0.0.10					
DST IP: 20.0.0.10					
OPT: 0x0					0x0
DATA (VARIABLE LENGTH)					

ICMP

0	8	16	31 bits
TYPE:	CODE:	CHECKSUM	
ID: 0x4	SEQ NUMBER: 3		



PDU Information at Device: Router0

OSI Model Inbound PDU Details Outbound PDU Details

PDU Formats

HDLC

0	8	16	32	2+x	8+x	6+x bits
FL	AD	CONTR	DATA:	FCS:	FL	
G:	R:	OL:	(VARIABLE)	0x0	G:	

IP

0	4	8	16	19	31 bits
4	IHL	DSCP:	TL: 28		
ID: 0x3		0x		0x0	
TTL: 254		PRO: 0x1		CHKSUM	
SRC IP: 10.0.0.10					
DST IP: 20.0.0.10					
OPT: 0x0					0x0
DATA (VARIABLE LENGTH)					

ICMP

0	8	16	31 bits
TYPE:	CODE:	CHECKSUM	
ID: 0x4	SEQ NUMBER: 3		

Observation:


- The TTL field in the IP header decreased by one at each router hop, demonstrating its role in preventing packets from looping indefinitely in the network.

Program 12


Aim of the program:

Configure IP address to routers in packet tracer. Explore the following messages: ping responses, destination unreachable, request timed out, reply

Procedure and topology:



Screenshots/ Output:



Observation:

- Proper IP addressing on router interfaces enabled successful ICMP echo and echo-reply communication, confirming correct Layer-3 configuration and reachability.
- “Destination Unreachable” and “Request Timed Out” responses occurred when routes or interfaces were misconfigured, demonstrating how routers handle missing paths and non-responsive hosts.


CYCLE 2:

Program 13

Aim of the program:

Write a program for congestion control using Leaky bucket algorithm

Procedure and topology:



LEAKY BUCKET

```
#include <stdio.h>
```

```
int main(){
```

```
    int n, rate, capacity;
```

```
    printf("Enter the number of units: ");
```

```
    scanf("%d", &n);
```

```
    printf("Enter constant output rate: ");
```

```
    scanf("%d", &capacity);
```

```
    int arrival[n];
```

```
    for (int i = 0; i < n; i++) {
```

```
        printf("Enter number of packets arriving at time %d:",
```

```
            i + 1);
```

```
        scanf("%d", &arrival[i]);
```

```
    }
    int buffer = 0;
```

```
    printf("n ----- \n");
```

```
    printf("time | buffer-before | arrival | buffer-arrival-captured  
drops | departure | buffer-end \n");
```

```
    printf("n ----- \n");
```

```
    for (int t = 0; t < n; t++) {
```

```
        int buffer-before = buffer;
```

```
        int drops = 0;
```

```
        int departure = 0;
```

```
        buffer += arrival[t];
```

```
        if (buffer > capacity) {
```

```
            drops = buffer - capacity;
```



```

    buffer = capacity;
}
int buffer-arrival-capture = buffer;
if (buffer >= rate)
    departure = rate;
else
    departure = buffer;
printf ("%2d | %4d | %3d | %4d | %3d | %3d | %4d \n",
t+1, buffer-before, arrival[t], buffer-arrival-capture, drops,
3
printf (" - - - - - \n");
int t = n;
while (buffer > 0) {
    int buffer-before = buffer;
    int departure = (buffer >= rate) ? rate : buffer;
    buffer -= departure;
    printf ("%2d | %4d | %3d | %4d | %3d | %3d | %4d \n",
t+1, buffer-before, 0, buffer-before, 0, departure, buffer);
3
printf (" - - - - - \n");
printf ("simulation complete \n");
return 0;
}

```

OUTPUT

Enter number of time units : 7
Enter constant output rate : 1
Enter bucket capacity : 10
~~Enter number of packets arriving at time~~ 1 : 3
2 : 2
3 : 1
4 : 4
5 : 0
6 : 0
7 : 0

time	buffer-before	arrival	buffer-arrival capture	drops	departure	buffer-end
1	0	3	3	0	1	2
2	2	2	4	0	1	3
3	3	1	4	0	1	3
4	3	4	7	0	1	6
5	6	0	6	0	1	5
6	5	0	5	0	1	4
7	4	0	4	0	1	3
8	3	0	3	0	1	2
9	2	0	2	0	1	1
10	1	0	1	0	1	0

Simulation Complete.

Screenshots/ Output:

Output

```
Enter bucket size: 4
Enter outgoing size: 1
Enter number of inputs: 7
Enter the incoming packet size: 3
Bucket buffer size 3 out of 4
After outgoing 2 packets left out of 4 in buffer
Enter the incoming packet size: 2
Bucket buffer size 4 out of 4
After outgoing 3 packets left out of 4 in buffer
Enter the incoming packet size: 1
Bucket buffer size 4 out of 4
After outgoing 3 packets left out of 4 in buffer
Enter the incoming packet size: 4
Dropped 3 packets
Bucket buffer size 4 out of 4
After outgoing 3 packets left out of 4 in buffer
Enter the incoming packet size: 0
Bucket buffer size 3 out of 4
After outgoing 2 packets left out of 4 in buffer
Enter the incoming packet size: 0
Bucket buffer size 2 out of 4
After outgoing 1 packets left out of 4 in buffer
Enter the incoming packet size: 0
Bucket buffer size 1 out of 4
After outgoing 0 packets left out of 4 in buffer
```

Observation:

- The leaky bucket mechanism regulated the outgoing packet flow at a constant rate, preventing sudden traffic bursts from overwhelming the network.
- Packets exceeding the bucket capacity were dropped, demonstrating effective congestion control by smoothing traffic and enforcing rate-limiting.

Program 14

Aim of the program:

Write a program for error detecting code using CRC-CCITT (16-bits).

Procedure and topology:

Lab - 7 29/10/25

CRC - cyclic Redundancy check

→ Data Link Layer → Error Detection Technique

→ Gen Data bits - Message → $M(x)$

→ Generator polynomial → $g(x)$ → Divisor

→ CRC bits → $r(x)$ → remainder

$M(x) = 101101 + \text{CRC bits}$
 $g(x) = \frac{1101}{4}$

Sender

$$\begin{array}{r} 1101 \overline{) 1011010000} \\ \underline{1101} \\ \times 1100 \\ \underline{1101} \\ \times 0011 \\ \underline{0000} \\ 0110 \\ \underline{0000} \\ 1100 \\ \underline{1101} \\ 0010 \\ \underline{0000} \\ 0010 \end{array}$$

$$\begin{array}{l} M(x) + R(x) \\ 101101 + 010 \\ \hline \end{array}$$

Receiver

$$\begin{array}{r} 1101 \overline{) 1011010100} \\ \underline{1101} \\ \times 1100 \\ \underline{1101} \\ 0011 \\ \underline{0000} \\ \times 0110 \\ \underline{0000} \\ 1101 \\ \underline{1101} \\ \times 0000 \rightarrow 000 \end{array}$$

Transmitted message Don't contains an error

∴ if it is 001 = it is error

CRC - cyclic Redundancy and check

```
#include <stdio.h>
```

```
int main() {
    int n, rate, capacity;
    printf("Enter number of time units :");
    scanf("%d", &rate);
    printf("Enter constant output rate :");
    scanf("%d", &rate);
    printf("Enter bucket capacity :");
    scanf("%d", &capacity);

    int arrival[n];
    for (int i = 0; i < n; i++) {
        printf("Enter number of packets arriving at time %d:",
            i + 1);
        scanf("%d", &arrival[i]);
    }

    int buffer = 0;
    printf("\n _____ \n");
    printf("time | buffer-before | arrival | buffer-arrival-  

    capture | drops | departure | buffer-end \n");
    printf("\n _____ \n");
    for (int t = 0; t < n; t++) {
        int buffer-before = buffer;
        int drops = 0;
        int departure = 0;
        buffer += arrival[t];
        if (buffer > capacity) {
            drops = buffer - capacity;
            buffer = capacity;
        }
        int buffer-arrival-capture = buffer;
    }
}
```



```

if (buffer >= rate)
    departure = rate;
else
    departure = buffer;
buffer -= departure;
int buffer_end = buffer;
printf("%d | %d | %d | %d | %d | %d | %d\n",
t+1, buffer-before, arrival[t], buffer-arrival-capture,
drops, departure, buffer_end);
}
printf(" - - - \n");
int t = n;
while (buffer > 0) {
    int buffer-before = buffer;
    int departure = (buffer >= rate) ? rate : buffer;
    buffer -= departure;
    printf("%d | %d | %d | %d | %d | %d | %d\n",
t+1, buffer-before, 0, departure, buffer);
}
printf(" - - - \n");
printf("Simulation complete.\n");
return 0;
}

```

OUTPUT

Enter data to be transmitted : 101010

Enter the divisor polynomial : 1011

Data padded with n-1 zeroes : 101010000

CRC value is : 001

Final codeword to be sent : 101010001

Enter the received data : 101010001

Screenshots/ Output:

Output

```
Enter message bits: 101100
Enter polynomial g(x): 1001

Padded data (Message + zeros): 101100000
CRC bits (remainder): 001
Transmitted message: 101100001

Enter received bits: 101100001

No Error detected. Message OK.

=== Code Execution Successful ===
```

Observation:

- The CRC-CCITT (16-bit) algorithm correctly generated a checksum for the transmitted data, ensuring reliable detection of single-bit and burst errors.
- Intentional error tests produced mismatched CRC values at the receiver, confirming accurate error detection through polynomial division.

Program 15

Aim of the program:

Using TCP/IP sockets, write a client-server program to make client sending the file name and the server to send back the contents of the requested file if present.

Procedure and topology:

TCP, UDP

Server Program (TCP)

```
import socket
server_socket = socket.socket(socket.AF_INET, socket.SOCK_STREAM)
server_socket.bind(('localhost', 8080))
server_socket.listen(1)
print("server is listening on port 8080. . .")
conn, addr = server_socket.accept()
print("connected by:", addr)
filename = conn.recv(1024).decode()
try:
    with open(filename, 'r') as f:
        data = f.read()
        conn.send(data.encode())
except FileNotFoundError:
    conn.send(b"File not found on server.")
conn.close()
server_socket.close()
```

Client Program (TCP)

```
import socket
client_socket = socket.socket(socket.AF_INET, socket.SOCK_STREAM)
client_socket.connect(('localhost', 8080))
filename = input("Enter filename to request: ")
client_socket.send(filename.encode())
data = client_socket.recv(4096).decode()
print("\n -- File Content -- \n")
print(data)
client_socket.close()
```


Screenshots/ Output:

```
● PS D:\CN stuff\TCP> python client.py
Enter filename to request: test.txt

--- File Content ---

Hello from server side
○ PS D:\CN stuff\TCP> 
```

```
PS D:\CN stuff\TCP> python --version
● Python 3.12.6
● PS D:\CN stuff\TCP> python server.py
Server is listening on port 8080 ...
Connected by: ('127.0.0.1', 65258)
○ PS D:\CN stuff\TCP> 
```

Observation:


- The TCP client successfully established a reliable connection with the server and transmitted the requested filename using stream-oriented communication.
- The server correctly retrieved and returned the file contents over the same TCP session, demonstrating reliable data transfer, acknowledgment handling, and error-free delivery.

Program 16

Aim of the program:

Using UDP sockets, write a client-server program to make client sending the file name and the server to send back the contents of the requested file if present.

Procedure and topology:



```
server Program (UDP)
import socket
server_socket = socket.socket(socket.AF_INET, socket.SOCK_DGRAM)
server_socket.bind(('localhost', 8081))
print("UDP server is ready - - -")
while True:
    filename, addr = server_socket.recvfrom(1024)
    filename = filename.decode()
    print(f"Requested file: {filename}")
    try:
        with open(filename, 'r') as f:
            data = f.read()
            server_socket.sendto(data.encode(), addr)
    except FileNotFoundError:
        server_socket.sendto(b"File not found on server", addr)

client Program (UDP)
import socket
client_socket = socket.socket(socket.AF_INET, socket.SOCK_DGRAM)
server_address = ('localhost', 8081)
filename = input("Enter filename to request: ")
client_socket.sendto(filename.encode(), server_address)
data, _ = client_socket.recvfrom(4096)
print("\n - - File content - - \n")
print(data.decode())
client_socket.close()
```

Screenshots/ Output:

```
● PS D:\CN stuff\UDP> python server.py
UDP Server is ready ...
Requested file: test.txt
○ PS D:\CN stuff\UDP> █
```

```
● PS D:\CN stuff\UDP> python client.py
Enter filename to request: test.txt

--- File Content ---

Welcome to UDP file server
○ PS D:\CN stuff\UDP> █
```

Observation:

- The UDP client successfully sent the filename as a connectionless datagram, demonstrating non-reliable, low-overhead message transfer without session establishment.
- The server responded with the file contents using UDP packets, and correct reception validated functional data exchange despite the absence of acknowledgment and retransmission mechanisms.