Chapter 1 Deep Learning Foundations and Agent Systems
This is page 1. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 1. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 1. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 1. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 1. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 1. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 2. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 2. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 2. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 2. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 2. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 2. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 3. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 3. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 3. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 3. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 3. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 3. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 4. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 4. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 4. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 4. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 4. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 4. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 5. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 5. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 5. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 5. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 5. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 5. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 6. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 6. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 6. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 6. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 6. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 6. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 7. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 7. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 7. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 7. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 7. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 7. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 8. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 8. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 8. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 8. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 8. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 8. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 9. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 9. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 9. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 9. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 9. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 9. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling, c
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 10. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 10. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 10. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 10. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 10. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 10. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 11. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 11. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 11. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 11. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 11. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 11. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 12. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 12. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 12. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 12. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 12. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 12. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 13. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 13. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 13. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 13. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 13. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 13. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 14. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 14. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 14. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 14. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 14. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 14. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 15. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 15. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 15. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 15. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 15. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 15. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 16. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 16. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 16. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 16. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 16. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 16. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 17. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 17. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 17. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 17. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 17. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 17. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 18. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 18. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 18. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 18. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 18. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 18. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 19. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 19. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 19. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 19. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 19. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 19. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 20. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 20. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 20. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 20. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 20. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 20. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 21. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 21. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 21. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 21. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 21. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 21. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 22. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 22. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 22. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 22. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 22. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 22. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 23. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 23. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 23. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 23. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 23. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 23. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 24. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 24. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 24. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 24. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 24. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 24. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 25. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 25. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 25. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 25. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 25. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 25. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 26. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 26. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 26. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 26. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 26. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 26. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 27. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 27. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 27. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 27. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 27. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 27. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 28. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 28. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 28. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 28. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 28. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 28. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 29. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 29. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 29. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 29. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 29. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 29. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 30. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 30. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 30. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 30. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 30. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 1 Deep Learning Foundations and Agent Systems
This is page 30. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 31. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 31. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 31. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 31. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 31. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 31. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 32. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 32. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 32. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 32. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 32. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 32. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 33. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 33. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 33. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 33. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 33. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 33. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 34. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 34. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 34. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 34. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 34. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 34. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 35. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 35. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 35. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 35. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 35. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 35. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 36. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 36. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 36. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 36. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 36. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 36. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 37. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 37. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 37. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 37. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 37. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 37. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 38. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 38. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 38. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 38. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 38. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 38. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 39. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 39. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 39. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 39. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 39. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 39. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 40. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 40. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 40. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 40. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 40. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 40. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 41. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 41. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 41. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 41. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 41. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 41. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 42. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 42. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 42. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 42. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 42. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 42. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 43. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 43. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 43. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 43. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 43. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 43. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 44. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 44. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 44. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 44. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 44. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 44. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 45. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 45. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 45. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 45. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 45. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 45. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 46. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 46. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 46. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 46. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 46. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 46. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 47. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 47. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 47. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 47. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 47. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 47. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 48. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 48. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 48. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 48. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 48. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 48. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 49. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 49. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 49. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 49. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 49. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 49. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 50. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 50. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 50. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 50. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 50. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 50. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 51. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 51. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 51. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 51. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 51. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 51. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 52. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 52. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 52. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 52. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 52. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 52. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 53. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 53. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 53. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 53. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 53. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 53. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 54. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 54. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 54. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 54. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 54. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 54. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 55. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 55. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 55. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 55. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 55. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 55. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 56. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 56. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 56. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 56. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 56. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 56. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 57. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 57. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 57. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 57. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 57. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 57. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 58. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 58. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 58. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 58. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 58. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 58. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 59. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 59. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 59. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 59. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 59. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 59. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 60. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 60. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 60. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 60. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 60. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 2 Deep Learning Foundations and Agent Systems
This is page 60. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 61. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 61. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 61. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 61. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 61. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 61. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 62. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 62. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 62. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 62. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 62. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 62. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 63. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 63. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 63. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 63. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 63. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 63. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 64. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 64. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 64. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 64. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 64. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 64. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 65. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 65. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 65. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 65. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 65. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 65. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 66. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 66. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 66. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 66. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 66. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 66. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 67. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 67. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 67. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 67. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 67. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 67. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 68. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 68. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 68. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 68. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 68. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 68. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 69. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 69. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 69. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 69. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 69. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 69. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 70. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 70. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 70. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 70. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 70. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 70. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 71. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 71. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 71. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 71. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 71. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 71. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 72. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 72. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 72. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 72. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 72. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 72. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 73. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 73. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 73. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 73. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 73. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 73. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 74. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 74. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 74. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 74. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 74. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 74. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 75. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 75. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 75. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 75. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 75. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 75. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 76. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 76. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 76. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 76. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 76. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 76. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 77. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 77. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 77. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 77. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 77. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 77. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 78. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 78. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 78. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 78. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 78. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 78. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 79. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 79. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 79. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 79. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 79. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 79. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 80. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 80. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 80. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 80. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 80. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 80. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 81. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 81. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 81. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 81. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 81. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 81. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 82. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 82. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 82. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 82. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 82. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 82. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 83. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 83. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 83. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 83. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 83. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 83. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 84. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 84. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 84. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 84. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 84. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 84. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 85. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 85. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 85. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 85. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 85. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 85. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 86. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 86. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 86. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 86. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 86. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 86. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 87. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 87. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 87. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 87. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 87. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 87. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 88. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 88. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 88. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 88. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 88. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 88. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 89. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 89. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 89. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 89. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 89. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 89. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 90. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 90. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 90. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 90. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 90. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 3 Deep Learning Foundations and Agent Systems
This is page 90. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 91. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 91. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 91. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 91. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 91. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 91. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 92. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 92. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 92. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 92. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 92. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 92. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 93. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 93. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 93. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 93. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 93. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 93. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 94. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 94. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 94. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 94. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 94. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 94. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 95. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 95. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 95. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 95. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 95. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 95. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 96. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 96. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 96. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 96. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 96. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 96. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 97. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 97. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 97. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 97. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 97. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 97. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 98. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 98. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 98. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 98. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 98. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 98. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 99. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 99. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 99. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 99. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 99. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 99. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling,
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 100. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 100. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 100. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 100. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 100. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 100. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 101. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 101. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 101. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 101. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 101. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 101. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 102. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 102. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 102. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 102. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 102. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 102. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 103. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 103. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 103. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 103. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 103. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 103. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 104. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 104. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 104. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 104. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 104. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 104. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 105. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 105. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 105. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 105. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 105. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 105. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 106. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 106. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 106. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 106. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 106. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 106. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 107. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 107. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 107. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 107. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 107. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 107. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 108. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 108. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 108. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 108. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 108. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 108. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 109. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 109. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 109. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 109. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 109. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 109. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 110. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 110. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 110. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 110. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 110. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 110. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 111. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 111. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 111. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 111. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 111. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 111. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 112. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 112. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 112. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 112. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 112. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 112. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 113. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 113. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 113. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 113. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 113. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 113. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 114. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 114. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 114. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 114. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 114. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 114. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 115. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 115. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 115. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 115. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 115. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 115. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 116. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 116. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 116. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 116. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 116. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 116. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 117. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 117. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 117. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 117. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 117. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 117. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 118. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 118. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 118. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 118. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 118. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 118. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 119. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 119. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 119. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 119. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 119. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 119. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 120. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 120. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 120. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 120. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 120. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 4 Deep Learning Foundations and Agent Systems
This is page 120. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 121. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 121. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 121. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 121. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 121. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 121. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 122. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 122. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 122. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 122. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 122. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 122. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 123. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 123. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 123. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 123. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 123. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 123. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 124. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 124. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 124. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 124. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 124. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 124. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 125. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 125. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 125. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 125. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 125. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 125. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 126. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 126. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 126. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 126. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 126. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 126. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 127. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 127. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 127. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 127. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 127. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 127. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 128. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 128. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 128. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 128. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 128. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 128. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 129. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 129. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 129. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 129. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 129. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 129. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 130. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 130. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 130. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 130. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 130. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 130. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 131. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 131. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 131. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 131. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 131. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 131. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 132. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 132. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 132. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 132. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 132. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 132. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 133. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 133. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 133. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 133. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 133. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 133. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 134. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 134. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 134. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 134. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 134. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 134. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 135. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 135. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 135. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 135. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 135. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 135. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 136. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 136. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 136. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 136. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 136. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 136. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 137. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 137. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 137. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 137. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 137. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 137. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 138. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 138. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 138. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 138. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 138. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 138. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 139. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 139. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 139. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 139. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 139. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 139. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 140. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 140. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 140. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 140. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 140. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 140. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 141. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 141. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 141. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 141. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 141. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 141. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 142. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 142. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 142. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 142. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 142. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 142. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 143. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 143. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 143. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 143. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 143. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 143. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 144. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 144. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 144. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 144. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 144. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 144. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 145. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 145. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 145. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 145. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 145. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 145. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 146. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 146. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 146. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 146. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 146. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 146. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 147. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 147. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 147. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 147. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 147. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 147. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 148. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 148. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 148. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 148. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 148. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 148. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 149. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 149. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 149. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 149. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 149. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 149. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 150. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 150. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 150. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 150. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 150. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 5 Deep Learning Foundations and Agent Systems
This is page 150. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 151. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 151. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 151. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 151. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 151. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 151. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 152. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 152. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 152. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 152. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 152. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 152. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 153. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 153. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 153. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 153. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 153. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 153. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 154. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 154. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 154. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 154. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 154. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 154. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 155. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 155. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 155. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 155. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 155. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 155. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 156. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 156. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 156. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 156. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 156. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 156. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 157. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 157. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 157. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 157. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 157. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 157. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 158. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 158. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 158. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 158. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 158. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 158. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 159. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 159. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 159. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 159. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 159. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 159. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 160. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 160. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 160. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 160. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 160. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 160. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 161. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 161. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 161. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 161. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 161. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 161. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 162. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 162. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 162. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 162. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 162. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 162. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 163. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 163. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 163. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 163. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 163. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 163. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 164. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 164. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 164. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 164. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 164. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 164. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 165. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 165. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 165. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 165. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 165. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 165. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 166. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 166. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 166. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 166. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 166. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 166. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 167. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 167. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 167. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 167. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 167. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 167. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 168. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 168. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 168. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 168. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 168. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 168. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 169. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 169. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 169. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 169. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 169. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 169. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 170. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 170. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 170. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 170. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 170. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 170. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 171. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 171. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 171. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 171. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 171. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 171. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 172. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 172. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 172. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 172. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 172. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 172. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 173. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 173. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 173. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 173. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 173. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 173. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 174. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 174. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 174. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 174. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 174. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 174. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 175. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 175. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 175. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 175. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 175. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 175. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 176. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 176. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 176. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 176. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 176. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 176. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 177. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 177. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 177. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 177. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 177. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 177. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 178. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 178. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 178. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 178. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 178. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 178. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 179. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 179. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 179. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 179. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 179. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 179. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 180. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 180. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 180. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 180. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 180. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 6 Deep Learning Foundations and Agent Systems
This is page 180. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 181. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 181. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 181. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 181. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 181. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 181. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 182. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 182. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 182. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 182. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 182. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 182. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 183. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 183. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 183. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 183. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 183. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 183. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 184. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 184. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 184. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 184. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 184. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 184. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 185. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 185. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 185. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 185. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 185. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 185. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 186. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 186. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 186. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 186. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 186. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 186. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 187. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 187. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 187. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 187. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 187. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 187. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 188. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 188. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 188. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 188. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 188. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 188. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 189. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 189. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 189. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 189. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 189. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 189. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 190. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 190. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 190. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 190. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 190. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 190. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 191. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 191. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 191. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 191. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 191. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 191. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 192. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 192. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 192. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 192. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 192. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 192. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 193. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 193. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 193. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 193. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 193. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 193. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 194. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 194. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 194. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 194. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 194. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 194. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 195. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 195. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 195. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 195. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 195. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 195. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 196. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 196. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 196. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 196. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 196. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 196. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 197. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 197. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 197. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 197. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 197. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 197. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 198. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 198. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 198. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 198. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 198. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 198. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 199. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 199. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 199. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 199. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 199. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 199. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 200. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 200. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 200. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 200. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 200. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 200. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 201. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 201. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 201. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 201. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 201. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 201. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 202. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 202. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 202. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 202. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 202. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 202. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 203. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 203. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 203. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 203. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 203. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 203. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 204. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 204. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 204. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 204. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 204. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 204. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 205. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 205. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 205. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 205. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 205. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 205. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 206. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 206. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 206. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 206. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 206. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 206. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 207. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 207. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 207. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 207. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 207. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 207. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 208. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 208. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 208. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 208. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 208. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 208. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 209. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 209. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 209. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 209. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 209. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 209. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 210. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 210. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 210. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 210. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 210. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 7 Deep Learning Foundations and Agent Systems
This is page 210. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 211. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 211. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 211. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 211. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 211. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 211. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 212. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 212. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 212. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 212. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 212. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 212. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 213. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 213. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 213. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 213. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 213. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 213. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 214. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 214. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 214. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 214. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 214. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 214. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 215. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 215. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 215. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 215. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 215. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 215. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 216. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 216. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 216. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 216. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 216. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 216. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 217. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 217. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 217. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 217. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 217. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 217. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 218. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 218. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 218. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 218. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 218. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 218. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 219. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 219. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 219. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 219. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 219. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 219. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 220. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 220. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 220. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 220. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 220. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 220. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 221. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 221. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 221. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 221. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 221. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 221. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 222. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 222. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 222. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 222. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 222. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 222. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 223. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 223. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 223. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 223. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 223. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 223. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 224. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 224. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 224. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 224. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 224. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 224. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 225. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 225. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 225. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 225. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 225. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 225. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 226. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 226. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 226. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 226. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 226. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 226. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 227. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 227. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 227. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 227. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 227. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 227. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 228. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 228. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 228. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 228. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 228. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 228. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 229. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 229. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 229. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 229. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 229. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 229. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 230. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 230. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 230. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 230. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 230. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 230. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 231. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 231. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 231. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 231. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 231. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 231. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 232. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 232. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 232. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 232. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 232. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 232. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 233. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 233. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 233. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 233. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 233. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 233. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 234. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 234. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 234. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 234. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 234. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 234. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 235. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 235. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 235. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 235. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 235. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 235. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 236. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 236. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 236. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 236. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 236. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 236. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 237. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 237. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 237. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 237. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 237. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 237. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 238. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 238. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 238. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 238. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 238. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 238. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 239. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 239. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 239. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 239. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 239. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 239. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 240. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 240. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 240. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 240. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 240. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 8 Deep Learning Foundations and Agent Systems
This is page 240. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 241. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 241. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 241. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 241. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 241. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 241. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 242. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 242. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 242. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 242. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 242. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 242. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 243. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 243. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 243. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 243. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 243. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 243. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 244. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 244. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 244. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 244. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 244. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 244. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 245. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 245. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 245. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 245. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 245. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 245. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 246. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 246. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 246. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 246. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 246. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 246. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 247. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 247. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 247. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 247. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 247. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 247. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 248. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 248. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 248. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 248. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 248. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 248. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 249. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 249. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 249. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 249. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 249. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 249. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 250. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 250. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 250. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 250. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 250. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 250. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 251. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 251. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 251. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 251. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 251. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 251. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 252. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 252. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 252. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 252. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 252. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 252. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 253. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 253. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 253. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 253. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 253. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 253. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 254. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 254. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 254. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 254. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 254. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 254. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 255. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 255. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 255. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 255. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 255. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 255. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 256. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 256. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 256. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 256. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 256. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 256. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 257. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 257. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 257. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 257. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 257. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 257. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 258. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 258. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 258. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 258. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 258. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 258. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 259. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 259. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 259. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 259. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 259. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 259. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 260. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 260. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 260. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 260. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 260. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 260. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 261. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 261. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 261. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 261. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 261. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 261. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 262. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 262. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 262. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 262. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 262. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 262. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 263. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 263. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 263. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 263. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 263. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 263. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 264. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 264. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 264. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 264. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 264. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 264. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 265. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 265. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 265. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 265. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 265. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 265. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 266. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 266. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 266. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 266. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 266. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 266. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 267. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 267. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 267. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 267. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 267. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 267. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 268. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 268. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 268. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 268. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 268. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 268. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 269. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 269. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 269. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 269. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 269. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 269. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 270. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 270. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 270. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 270. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 270. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 9 Deep Learning Foundations and Agent Systems
This is page 270. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 271. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 271. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 271. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 271. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 271. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 271. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 272. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 272. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 272. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 272. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 272. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 272. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 273. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 273. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 273. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 273. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 273. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 273. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 274. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 274. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 274. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 274. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 274. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 274. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 275. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 275. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 275. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 275. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 275. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 275. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 276. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 276. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 276. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 276. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 276. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 276. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 277. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 277. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 277. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 277. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 277. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 277. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 278. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 278. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 278. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 278. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 278. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 278. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 279. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 279. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 279. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 279. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 279. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 279. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 280. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 280. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 280. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 280. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 280. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 280. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 281. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 281. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 281. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 281. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 281. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 281. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 282. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 282. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 282. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 282. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 282. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 282. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 283. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 283. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 283. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 283. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 283. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 283. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 284. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 284. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 284. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 284. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 284. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 284. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 285. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 285. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 285. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 285. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 285. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 285. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 286. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 286. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 286. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 286. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 286. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 286. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 287. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 287. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 287. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 287. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 287. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 287. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 288. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 288. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 288. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 288. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 288. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 288. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 289. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 289. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 289. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 289. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 289. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 289. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 290. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 290. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 290. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 290. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 290. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 290. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 291. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 291. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 291. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 291. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 291. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 291. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 292. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 292. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 292. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 292. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 292. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 292. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 293. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 293. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 293. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 293. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 293. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 293. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 294. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 294. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 294. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 294. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 294. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 294. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 295. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 295. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 295. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 295. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 295. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 295. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 296. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 296. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 296. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 296. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 296. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 296. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 297. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 297. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 297. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 297. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 297. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 297. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 298. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 298. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 298. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 298. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 298. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 298. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 299. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 299. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 299. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 299. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 299. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 299. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 300. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 300. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 300. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 300. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 300. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 10 Deep Learning Foundations and Agent Systems
This is page 300. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 301. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 301. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 301. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 301. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 301. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 301. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 302. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 302. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 302. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 302. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 302. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 302. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 303. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 303. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 303. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 303. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 303. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 303. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 304. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 304. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 304. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 304. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 304. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 304. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 305. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 305. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 305. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 305. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 305. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 305. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 306. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 306. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 306. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 306. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 306. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 306. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 307. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 307. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 307. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 307. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 307. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 307. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 308. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 308. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 308. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 308. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 308. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 308. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 309. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 309. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 309. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 309. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 309. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 309. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 310. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 310. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 310. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 310. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 310. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 310. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 311. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 311. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 311. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 311. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 311. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 311. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 312. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 312. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 312. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 312. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 312. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 312. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 313. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 313. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 313. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 313. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 313. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 313. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 314. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 314. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 314. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 314. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 314. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 314. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 315. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 315. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 315. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 315. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 315. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 315. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 316. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 316. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 316. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 316. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 316. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 316. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 317. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 317. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 317. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 317. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 317. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 317. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 318. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 318. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 318. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 318. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 318. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 318. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 319. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 319. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 319. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 319. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 319. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 319. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 320. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 320. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 320. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 320. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 320. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 320. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 321. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 321. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 321. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 321. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 321. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 321. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 322. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 322. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 322. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 322. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 322. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 322. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 323. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 323. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 323. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 323. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 323. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 323. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 324. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 324. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 324. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 324. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 324. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 324. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 325. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 325. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 325. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 325. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 325. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 325. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 326. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 326. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 326. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 326. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 326. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 326. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 327. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 327. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 327. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 327. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 327. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 327. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 328. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 328. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 328. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 328. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 328. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 328. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 329. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 329. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 329. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 329. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 329. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 329. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 330. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 330. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 330. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 330. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 330. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 11 Deep Learning Foundations and Agent Systems
This is page 330. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 331. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 331. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 331. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 331. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 331. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 331. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 332. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 332. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 332. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 332. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 332. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 332. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 333. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 333. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 333. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 333. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 333. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 333. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 334. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 334. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 334. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 334. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 334. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 334. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 335. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 335. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 335. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 335. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 335. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 335. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 336. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 336. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 336. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 336. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 336. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 336. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 337. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 337. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 337. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 337. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 337. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 337. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 338. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 338. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 338. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 338. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 338. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 338. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 339. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 339. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 339. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 339. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 339. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 339. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 340. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 340. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 340. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 340. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 340. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 340. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 341. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 341. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 341. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 341. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 341. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 341. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 342. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 342. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 342. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 342. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 342. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 342. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 343. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 343. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 343. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 343. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 343. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 343. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 344. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 344. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 344. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 344. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 344. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 344. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 345. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 345. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 345. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 345. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 345. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 345. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 346. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 346. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 346. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 346. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 346. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 346. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 347. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 347. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 347. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 347. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 347. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 347. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 348. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 348. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 348. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 348. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 348. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 348. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 349. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 349. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 349. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 349. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 349. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 349. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 350. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 350. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 350. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 350. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 350. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 350. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 351. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 351. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 351. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 351. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 351. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 351. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 352. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 352. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 352. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 352. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 352. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 352. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 353. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 353. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 353. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 353. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 353. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 353. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 354. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 354. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 354. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 354. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 354. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 354. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 355. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 355. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 355. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 355. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 355. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 355. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 356. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 356. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 356. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 356. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 356. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 356. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 357. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 357. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 357. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 357. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 357. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 357. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 358. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 358. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 358. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 358. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 358. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 358. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 359. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 359. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 359. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 359. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 359. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 359. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 360. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 360. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 360. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 360. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 360. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 12 Deep Learning Foundations and Agent Systems
This is page 360. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 361. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 361. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 361. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 361. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 361. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 361. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 362. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 362. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 362. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 362. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 362. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 362. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 363. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 363. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 363. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 363. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 363. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 363. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 364. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 364. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 364. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 364. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 364. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 364. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 365. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 365. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 365. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 365. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 365. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 365. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 366. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 366. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 366. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 366. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 366. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 366. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 367. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 367. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 367. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 367. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 367. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 367. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 368. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 368. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 368. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 368. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 368. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 368. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 369. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 369. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 369. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 369. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 369. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 369. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 370. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 370. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 370. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 370. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 370. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 370. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 371. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 371. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 371. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 371. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 371. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 371. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 372. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 372. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 372. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 372. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 372. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 372. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 373. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 373. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 373. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 373. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 373. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 373. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 374. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 374. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 374. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 374. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 374. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 374. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 375. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 375. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 375. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 375. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 375. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 375. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 376. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 376. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 376. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 376. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 376. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 376. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 377. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 377. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 377. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 377. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 377. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 377. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 378. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 378. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 378. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 378. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 378. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 378. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 379. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 379. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 379. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 379. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 379. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 379. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 380. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 380. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 380. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 380. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 380. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 380. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 381. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 381. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 381. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 381. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 381. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 381. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 382. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 382. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 382. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 382. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 382. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 382. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 383. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 383. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 383. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 383. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 383. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 383. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 384. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 384. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 384. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 384. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 384. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 384. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 385. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 385. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 385. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 385. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 385. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 385. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 386. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 386. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 386. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 386. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 386. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 386. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 387. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 387. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 387. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 387. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 387. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 387. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 388. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 388. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 388. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 388. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 388. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 388. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 389. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 389. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 389. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 389. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 389. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 389. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 390. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 390. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 390. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 390. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 390. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 13 Deep Learning Foundations and Agent Systems
This is page 390. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 391. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 391. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 391. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 391. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 391. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 391. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 392. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 392. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 392. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 392. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 392. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 392. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 393. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 393. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 393. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 393. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 393. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 393. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 394. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 394. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 394. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 394. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 394. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 394. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 395. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 395. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 395. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 395. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 395. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 395. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 396. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 396. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 396. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 396. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 396. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 396. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 397. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 397. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 397. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 397. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 397. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 397. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 398. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 398. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 398. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 398. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 398. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 398. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 399. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 399. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 399. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 399. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 399. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 399. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 400. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 400. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 400. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 400. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 400. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 400. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 401. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 401. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 401. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 401. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 401. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 401. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 402. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 402. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 402. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 402. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 402. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 402. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 403. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 403. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 403. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 403. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 403. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 403. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 404. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 404. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 404. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 404. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 404. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 404. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 405. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 405. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 405. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 405. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 405. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 405. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 406. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 406. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 406. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 406. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 406. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 406. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 407. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 407. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 407. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 407. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 407. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 407. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 408. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 408. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 408. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 408. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 408. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 408. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 409. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 409. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 409. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 409. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 409. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 409. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 410. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 410. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 410. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 410. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 410. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 410. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 411. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 411. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 411. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 411. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 411. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 411. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 412. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 412. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 412. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 412. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 412. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 412. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 413. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 413. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 413. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 413. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 413. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 413. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 414. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 414. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 414. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 414. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 414. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 414. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 415. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 415. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 415. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 415. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 415. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 415. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 416. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 416. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 416. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 416. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 416. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 416. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 417. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 417. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 417. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 417. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 417. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 417. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 418. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 418. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 418. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 418. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 418. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 418. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 419. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 419. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 419. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 419. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 419. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 419. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 420. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 420. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 420. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 420. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 420. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 14 Deep Learning Foundations and Agent Systems
This is page 420. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 421. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 421. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 421. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 421. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 421. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 421. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 422. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 422. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 422. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 422. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 422. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 422. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 423. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 423. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 423. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 423. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 423. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 423. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 424. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 424. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 424. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 424. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 424. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 424. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 425. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 425. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 425. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 425. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 425. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 425. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 426. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 426. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 426. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 426. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 426. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 426. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 427. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 427. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 427. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 427. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 427. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 427. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 428. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 428. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 428. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 428. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 428. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 428. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 429. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 429. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 429. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 429. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 429. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 429. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 430. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 430. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 430. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 430. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 430. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 430. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 431. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 431. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 431. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 431. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 431. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 431. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 432. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 432. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 432. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 432. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 432. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 432. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 433. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 433. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 433. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 433. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 433. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 433. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 434. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 434. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 434. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 434. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 434. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 434. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 435. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 435. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 435. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 435. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 435. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 435. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 436. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 436. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 436. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 436. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 436. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 436. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 437. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 437. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 437. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 437. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 437. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 437. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 438. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 438. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 438. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 438. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 438. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 438. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 439. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 439. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 439. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 439. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 439. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 439. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 440. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 440. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 440. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 440. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 440. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 440. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 441. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 441. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 441. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 441. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 441. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 441. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 442. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 442. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 442. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 442. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 442. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 442. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 443. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 443. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 443. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 443. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 443. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 443. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 444. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 444. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 444. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 444. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 444. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 444. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 445. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 445. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 445. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 445. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 445. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 445. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 446. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 446. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 446. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 446. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 446. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 446. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 447. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 447. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 447. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 447. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 447. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 447. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 448. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 448. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 448. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 448. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 448. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 448. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 449. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 449. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 449. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 449. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 449. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 449. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 450. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 450. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 450. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 450. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 450. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 15 Deep Learning Foundations and Agent Systems
This is page 450. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 451. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 451. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 451. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 451. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 451. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 451. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 452. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 452. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 452. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 452. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 452. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 452. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 453. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 453. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 453. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 453. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 453. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 453. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 454. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 454. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 454. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 454. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 454. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 454. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 455. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 455. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 455. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 455. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 455. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 455. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 456. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 456. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 456. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 456. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 456. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 456. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 457. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 457. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 457. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 457. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 457. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 457. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 458. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 458. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 458. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 458. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 458. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 458. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 459. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 459. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 459. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 459. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 459. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 459. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 460. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 460. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 460. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 460. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 460. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 460. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 461. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 461. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 461. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 461. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 461. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 461. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 462. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 462. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 462. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 462. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 462. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 462. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 463. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 463. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 463. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 463. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 463. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 463. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 464. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 464. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 464. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 464. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 464. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 464. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 465. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 465. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 465. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 465. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 465. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 465. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 466. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 466. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 466. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 466. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 466. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 466. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 467. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 467. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 467. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 467. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 467. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 467. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 468. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 468. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 468. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 468. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 468. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 468. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 469. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 469. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 469. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 469. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 469. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 469. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 470. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 470. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 470. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 470. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 470. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 470. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 471. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 471. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 471. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 471. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 471. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 471. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 472. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 472. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 472. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 472. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 472. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 472. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 473. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 473. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 473. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 473. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 473. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 473. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 474. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 474. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 474. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 474. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 474. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 474. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 475. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 475. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 475. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 475. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 475. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 475. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 476. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 476. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 476. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 476. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 476. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 476. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 477. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 477. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 477. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 477. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 477. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 477. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 478. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 478. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 478. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 478. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 478. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 478. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 479. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 479. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 479. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 479. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 479. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 479. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 480. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 480. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 480. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 480. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 480. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 16 Deep Learning Foundations and Agent Systems
This is page 480. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 481. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 481. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 481. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 481. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 481. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 481. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 482. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 482. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 482. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 482. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 482. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 482. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 483. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 483. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 483. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 483. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 483. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 483. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 484. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 484. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 484. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 484. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 484. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 484. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 485. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 485. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 485. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 485. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 485. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 485. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 486. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 486. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 486. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 486. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 486. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 486. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 487. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 487. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 487. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 487. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 487. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 487. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 488. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 488. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 488. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 488. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 488. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 488. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 489. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 489. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 489. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 489. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 489. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 489. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 490. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 490. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 490. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 490. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 490. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 490. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 491. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 491. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 491. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 491. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 491. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 491. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 492. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 492. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 492. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 492. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 492. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 492. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 493. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 493. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 493. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 493. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 493. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 493. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 494. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 494. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 494. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 494. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 494. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 494. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 495. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 495. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 495. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 495. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 495. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 495. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 496. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 496. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 496. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 496. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 496. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 496. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 497. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 497. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 497. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 497. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 497. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 497. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 498. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 498. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 498. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 498. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 498. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 498. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 499. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 499. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 499. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 499. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 499. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 499. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 500. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 500. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 500. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 500. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 500. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 500. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 501. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 501. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 501. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 501. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 501. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 501. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 502. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 502. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 502. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 502. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 502. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 502. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 503. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 503. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 503. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 503. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 503. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 503. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 504. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 504. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 504. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 504. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 504. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 504. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 505. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 505. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 505. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 505. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 505. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 505. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 506. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 506. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 506. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 506. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 506. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 506. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 507. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 507. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 507. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 507. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 507. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 507. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 508. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 508. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 508. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 508. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 508. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 508. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 509. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 509. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 509. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 509. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 509. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 509. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 510. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 510. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 510. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 510. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 510. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 17 Deep Learning Foundations and Agent Systems
This is page 510. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 511. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 511. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 511. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 511. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 511. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 511. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 512. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 512. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 512. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 512. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 512. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 512. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 513. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 513. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 513. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 513. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 513. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 513. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 514. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 514. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 514. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 514. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 514. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 514. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 515. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 515. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 515. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 515. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 515. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 515. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 516. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 516. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 516. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 516. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 516. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 516. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 517. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 517. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 517. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 517. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 517. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 517. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 518. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 518. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 518. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 518. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 518. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 518. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 519. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 519. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 519. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 519. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 519. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 519. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 520. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 520. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 520. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 520. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 520. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 520. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 521. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 521. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 521. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 521. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 521. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 521. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 522. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 522. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 522. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 522. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 522. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 522. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 523. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 523. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 523. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 523. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 523. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 523. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 524. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 524. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 524. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 524. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 524. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 524. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 525. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 525. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 525. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 525. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 525. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 525. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 526. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 526. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 526. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 526. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 526. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 526. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 527. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 527. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 527. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 527. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 527. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 527. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 528. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 528. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 528. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 528. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 528. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 528. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 529. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 529. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 529. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 529. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 529. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 529. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 530. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 530. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 530. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 530. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 530. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 530. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 531. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 531. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 531. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 531. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 531. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 531. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 532. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 532. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 532. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 532. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 532. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 532. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 533. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 533. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 533. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 533. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 533. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 533. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 534. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 534. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 534. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 534. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 534. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 534. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 535. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 535. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 535. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 535. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 535. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 535. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 536. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 536. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 536. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 536. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 536. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 536. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 537. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 537. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 537. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 537. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 537. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 537. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 538. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 538. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 538. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 538. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 538. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 538. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 539. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 539. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 539. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 539. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 539. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 539. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 540. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 540. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 540. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 540. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 540. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V

Chapter 18 Deep Learning Foundations and Agent Systems
This is page 540. We consider attention mechanisms, retrieval augmented generation, multi-agent orchestration, function calling
Equation: y = W x + b ; L = -sum y log p ; Attention(Q,K,V)=softmax(QK^T/sqrt(d_k))V