
Identity Authentication

Van Nguyen – HUT

Hanoi – 2009

(with material from Bishop's text "Introduction to Computer Science")

Authentication

- Basics
- Passwords
- Challenge-Response
- Biometrics
- Location
- Multiple Methods

Basics

- Authentication: binding of identity to subject
 - Identity is that of external entity (my identity, Van, *etc.*)
 - Subject is computer entity (process, *etc.*)
- Note:
 - message authentication is a different topic and already mentioned in the applications of hash functions

Establishing Identity

- One or more of the following
 - ❑ What entity knows (*eg.* password)
 - ❑ What entity has (*eg.* Identity card, smart card)
 - ❑ What entity is (*eg.* fingerprints, retinal characteristics)
 - ❑ Where entity is (*eg.* In front of a particular terminal)

Authentication System

- We need a formal definition, rather abstract view, of an AS
- A 5-tuple (A, C, F, L, S)
 - A – a set: information that proves identity
 - C – a set: information stored on computer and used to validate authentication information
 - F : a set of complementation functions; $f: A \rightarrow C$
 - *To compute complement information from identity information*
 - L : authentication functions that prove identity
 - S : functions enabling entity to create, alter information in A or C

Example

- Password system, with passwords stored on line in clear text
 - A set of strings making up passwords
 - $C = A$
 - F singleton set of identity function $\{ I \}$
 - L single equality test function $\{ eq \}$
 - S function to set/change password

Passwords

- Sequence of characters
 - Examples: 10 digits, a string of letters, *etc.*
 - Generated randomly, by user, by computer with user input
- Sequence of words
 - Examples: pass-phrases
- Algorithms
 - Examples: challenge-response, one-time passwords

Storage

- Store as cleartext
 - If password file compromised, *all* passwords revealed
- Encipher file
 - Need to have decipherment, encipherment keys in memory
 - Reduces to previous problem → need something else
- Solution: Instead store one-way hash of password
 - Got the file, attacker must still guess passwords or invert the hash values

Example: Unix

- By definition, a 5-tuple (A, C, F, L, S)
 - A – a set: information that proves identity
 -
 - C – a set: information stored on computer and used to validate authentication information
 -
 - F : a set of complementation functions; $f: A \rightarrow C$
 -
 - L : authentication functions that prove identity
 -
 - S : functions enabling entity to create, alter information in A or C
 -

Example: Unix

- By definition, a 5-tuple (A, C, F, L, S)
 - A – a set: information that proves identity
 - $A = \{ \text{strings of 8 chars or less} \}$
 - C – a set: information stored on computer and used to validate authentication information
 - $C = \{ \text{hash values of password} \}$
 - F : a set of complementation functions; $f: A \rightarrow C$
 - $F = \{ \text{versions of modified DES} \}$
 - L : authentication functions that prove identity
 - $L = \{ \text{login, su, ...} \}$
 - S : functions enabling entity to create, alter information in A or C
 - $S = \{ \text{passwd, nispasswd, passwd+, ...} \}$

Attacking passwords

- Goal: find $a \in A$ such that:
 - For some $f \in F$, $f(a) = c \in C$
 - c is associated with entity
- Two ways to determine whether a meets these requirements:
 - By trying computing $f(a)$ for a set of a values until succeed
 - By trying calling $I(a)$ until succeed ($I(a)$ returns true)

Preventing Attacks

- How to prevent this:
 - Hide one of a , f , or c
 - Prevents obvious attack from above
 - Example: UNIX/Linux shadow password files
 - Hides the c 's
 - Block access to all $l \in L$ or result of $l(a)$
 - Prevents attacker from knowing if guess succeeded
 - Example: preventing *any* logins to an account from a network
 - Prevents knowing results of l (or accessing l)

Dictionary Attacks

- Trial-and-error from a list of potential passwords
 - *Off-line*: know f and c 's, and repeatedly try different guesses $g \in A$ until the list is done or passwords guessed
 - Examples: *crack*, *john-the-ripper*
 - *On-line*: have access to functions in L and try guesses g until some $l(g)$ succeeds
 - Examples: trying to log in by guessing a password

Success probability over a time period

Anderson's formula:

- P probability of guessing a password in specified period of time
- G number of guesses tested in 1 time unit
- T number of time units
- N number of possible passwords ($|A|$)
- Then $P \geq TG/N$

Example

■ Goal

- ❑ Passwords drawn from a 96-char alphabet
- ❑ Can test 10^4 guesses per second
- ❑ Probability of a success to be 0.5 over a 365 day period
- ❑ What is minimum password length?

■ Solution

- ❑ $N \geq TG/P = (365 \times 24 \times 60 \times 60) \times 10^4 / 0.5 = 6.31 \times 10^{11}$
- ❑ Choose s such that $\sum_{j=0}^s 96^j \geq N$
- ❑ So $s \geq 6$, meaning passwords must be at least 6 chars long

On password selection

- Random selection
 - Any password from A equally likely to be selected
- Pronounceable passwords
- User selection of passwords

Pronounceable Passwords

- Generate phonemes randomly
 - Phoneme is unit of sound, eg. *cv*, *vc*, *cvc*, *vcv*
 - Examples: *helgoret*, *juttelon* are; *przbqxdf*, *zxrptglfn* are not
- Problem: too few
- Solution: key crunching
 - Run long key through hash function and convert to printable sequence
 - Use this sequence as password

User Selection

- Problem: people pick easy to guess passwords
 - ❑ Based on account names, user names, computer names, place names
 - ❑ Dictionary words (also reversed, odd capitalizations, control characters, “elite-speak”, conjugations or declensions, swear words, Torah/Bible/Koran/... words)
 - ❑ Too short, digits only, letters only
 - ❑ License plates, acronyms, social security numbers
 - ❑ Personal characteristics or foibles (pet names, nicknames, job characteristics, *etc.*)

Picking Good Passwords

- “LIMm*2^Ap”
 - Names of members of 2 families
- “OoHeO/FSK”
 - Second letter of each word of length 4 or more in third line of third verse of Star-Spangled Banner, followed by “/”, followed by author’s initials
- What’s good here may be bad there
 - “DMC/MHmh” bad at Dartmouth (“Dartmouth Medical Center/Mary Hitchcock memorial hospital”), ok here
- Why are these now bad passwords? ☹

Proactive Password Checking

- Analyze proposed password for “goodness”
 - ❑ Always invoked
 - ❑ Can detect, reject bad passwords for an appropriate definition of “bad”
 - ❑ Discriminate on per-user, per-site basis
 - ❑ Needs to do pattern matching on words
 - ❑ Needs to execute subprograms and use results
 - Spell checker, for example
 - ❑ Easy to set up and integrate into password selection system

Salting

- Goal: slow dictionary attacks
- Method: perturb hash function so that:
 - Parameter controls *which* hash function is used
 - Parameter differs for each password
 - So given n password hashes, and therefore n salts, need to hash guess n

Examples

- Vanilla UNIX method
 - Use DES to encipher 0 message with password as key; iterate 25 times
 - Perturb E table in DES in one of 4096 ways
 - 12 bit salt flips entries 1–11 with entries 25–36
- Alternate methods
 - Use salt as first part of input to hash function

Unix actually is ...

- UNIX system standard hash function
 - Hashes password into 11 char string using one of 4096 hash functions
- As authentication system:
 - $A = \{ \text{strings of 8 chars or less} \}$
 - $C = \{ 2 \text{ char hash id} \parallel 11 \text{ char hash} \}$
 - $F = \{ 4096 \text{ versions of modified DES} \}$
 - $L = \{ \textit{login}, \textit{su}, \dots \}$
 - $S = \{ \textit{passwd}, \textit{nispasswd}, \textit{passwd+}, \dots \}$

Guessing Through L


- Cannot prevent these
 - Otherwise, legitimate users cannot log in
- Make them slow
 - Backoff
 - Disconnection
 - Disabling
 - Be very careful with administrative accounts!
 - Jailing
 - Allow in, but restrict activities

Password Aging

- Force users to change passwords after some time has expired
 - How do you force users not to re-use passwords?
 - Record previous passwords
 - Block changes for a period of time
 - Give users time to think of good passwords
 - Don't force them to change before they can log in
 - Warn them of expiration days in advance

Challenge-Response

- User, system share a secret function f (in practice, f is a known function with unknown parameters, such as a cryptographic key)



Pass Algorithms

- Challenge-response with the function f itself a secret
 - Challenge is a random string of characters
 - Response is some function of that string
 - Usually used in conjunction with fixed, reusable password

The image shows a web login interface. At the top is a blue header bar with the word "login" in white. Below the header, there are two input fields: "username:" and "password:". Below these is a CAPTCHA section. The CAPTCHA displays two words, "asbury" and "law", in a stylized font. Below the words is a text input field with the placeholder text "Type the two words:". To the right of the input field are three small icons: a refresh button, a volume icon, and a help icon. Below the CAPTCHA section is a "login" button.

One-Time Passwords

- Password that can be used exactly *once*
 - After use, it is immediately invalidated
- Challenge-response mechanism
 - Challenge is number of authentications; response is password for that particular number
- Problems
 - Synchronization of user, system
 - Generation of good random passwords
 - Password distribution problem

S/Key

- One-time password scheme based on idea of Lamport
- h one-way hash function (MD5 or SHA-1, for example)
- User chooses initial seed k
- System calculates:


$$h(k) = k_1, h(k_1) = k_2, \dots, h(k_{n-1}) = k_n$$

- Passwords are reverse order:

$$p_1 = k_n, p_2 = k_{n-1}, \dots, p_{n-1} = k_2, p_n = k_1$$

S/Key Protocol

System stores maximum number of authentications n , number of next authentication i , last correctly supplied password p_{i-1} .



System computes $h(p_i) = h(k_{n-i+1}) = k_{n-i} = p_{i-1}$. If match with what is stored, system replaces p_{i-1} with p_i and increments i .

Hardware Support

- Token-based

- Used to compute response to challenge
 - May encipher or hash challenge
 - May require PIN from user

- Temporally-based

- Every minute (or so) different number shown
 - Computer knows what number to expect when
- User enters number and fixed password

C-R and Dictionary Attacks

- Same as for fixed passwords
 - Attacker knows challenge r and response $f(r)$; if f encryption function, can try different keys
 - May only need to know *form* of response; attacker can tell if guess correct by looking to see if deciphered object is of right form
 - Example: Kerberos Version 4 used DES, but keys had 20 bits of randomness; Purdue attackers guessed keys quickly because deciphered tickets had a fixed set of bits in some locations

Encrypted Key Exchange

- Defeats off-line dictionary attacks
- Idea: random challenges enciphered, so attacker cannot verify correct decipherment of challenge
- Assume Alice, Bob share secret password s
- In what follows, Alice needs to generate a random public key p and a corresponding private key q
- Also, k is a randomly generated session key, and R_A and R_B are random challenges

EKE Protocol

Alice $\xrightarrow{\text{Alice} \parallel E_s(p)}$ Bob

Alice $\xleftarrow{E_s(E_p(k))}$ Bob

Now Alice, Bob share a randomly generated
secret session key k

Alice $\xrightarrow{E_k(R_A)}$ Bob

Alice $\xleftarrow{E_k(R_A R_B)}$ Bob

Alice $\xrightarrow{E_k(R_B)}$ Bob

Biometrics

- Automated measurement of biological, behavioral features that identify a person
 - Fingerprints: optical or electrical techniques
 - Maps fingerprint into a graph, then compares with database
 - Measurements imprecise, so approximate matching algorithms used
 - Voices: speaker verification or recognition
 - Verification: uses statistical techniques to test hypothesis that speaker is who is claimed (speaker dependent)
 - Recognition: checks content of answers (speaker independent)

Other Characteristics

- Can use several other characteristics
 - Eyes: patterns in irises unique
 - Measure patterns, determine if differences are random; or correlate images using statistical tests
 - Faces: image, or specific characteristics like distance from nose to chin
 - Lighting, view of face, other noise can hinder this
 - Keystroke dynamics: believed to be unique
 - Keystroke intervals, pressure, duration of stroke, where key is struck
 - Statistical tests used

Cautions

- These can be fooled!
 - ❑ Assumes biometric device accurate *in the environment it is being used in!*
 - ❑ Transmission of data to validator is tamperproof, correct

Location

- If you know where user is, validate identity by seeing if person is where the user is
 - Requires special-purpose hardware to locate user
 - GPS (global positioning system) device gives location signature of entity
 - Host uses LSS (location signature sensor) to get signature for entity

Multiple Methods

- Example: “where you are” also requires entity to have LSS and GPS, so also “what you have”
- Can assign different methods to different tasks
 - As users perform more and more sensitive tasks, must authenticate in more and more ways (presumably, more stringently) File describes authentication required
 - Also includes controls on access (time of day, *etc.*), resources, and requests to change passwords
 - Pluggable Authentication Modules

PAM

- Idea: when program needs to authenticate, it checks central repository for methods to use
- Library call: *pam_authenticate*
 - Accesses file with name of program in */etc/pam_d*
- Modules do authentication checking
 - *sufficient*: succeed if module succeeds
 - *required*: fail if module fails, but all required modules executed before reporting failure
 - *requisite*: like *required*, but don't check all modules
 - *optional*: invoke only if all previous modules fail

Example PAM File

```
auth    sufficient    /usr/lib/pam_ftp.so
auth    required      /usr/lib/pam_unix_auth.so use_first_pass
auth    required      /usr/lib/pam_listfile.so onerr=succeed \
        item=user sense=deny file=/etc/ftpusers
```

For ftp:

1. If user “anonymous”, return okay; if not, set PAM_AUTHTOK to password, PAM_RUSER to name, and fail
2. Now check that password in PAM_AUTHTOK belongs to that of user in PAM_RUSER; if not, fail
3. Now see if user in PAM_RUSER named in /etc/ftpusers; if so, fail; if error or not found, succeed

Key Points

- Authentication is not cryptography
 - You have to consider system components
- Passwords are here to stay
 - They provide a basis for most forms of authentication
- Protocols are important
 - They can make masquerading harder
- Authentication methods can be combined
 - Example: PAM

Kerberos

- A computer network authentication protocol
 - which allows nodes communicating over a non-secure network to prove their identity to one another in a secure manner.
- Details:
 - Self-study materials from Internet