Selected files

18 printable files

Swin-Adventure/IdentifiableObjectClass.cs
Swin-Adventure/GameObject.cs
Swin-Adventure/Item.cs
Swin-Adventure/Inventory.cs
Swin-Adventure/Player.cs
Swin-Adventure/Bag.cs
Swin-Adventure/Command.cs
Swin-Adventure/IHaveInventory.cs
Swin-Adventure/Location.cs
Swin-Adventure/LookCommand.cs
Swin-Adventure/Program.cs
IdentifiableObjectTest/BagTest.cs
IdentifiableObjectTest/IdentifiableObjectTest.cs
IdentifiableObjectTest/ItemTest.cs
IdentifiableObjectTest/InventoryTest.cs
IdentifiableObjectTest/LocationTest.cs
IdentifiableObjectTest/LookCommandTest.cs
IdentifiableObjectTest/PlayerTest.cs

Swin-Adventure/IdentifiableObjectClass.cs

```
1  using System;
2  namespace Swin_Adventure
3  {
4       public class IdentifiableObject
5       {
6            private List<string> _identifiers;
7
8            public IdentifiableObject(string[] idents)
9            {
10                _identifiers = new List<string>(idents);
11                _identifiers.AddRange(idents);
12           }
13
14           public bool AreYou(string id)
15           {
16                return _identifiers.Contains(id.ToLower());
17           }
18
19           public string FirstId
20           {
21                get
22                {
23                     if (_identifiers.Count == 0)
24                     {
25                          return "";
26                     }
27                     return _identifiers[0];
28                }
29           }
30
31           public void AddIdentifier(string id)
32           {
33                _identifiers.Add(id.ToLower());
34           }
35      }
36 }
```

```
37
38
```

Swin-Adventure/GameObject.cs

```
1  using System;
2  using System.Xml.Linq;
3
4  namespace Swin_Adventure
5  {
6       public class GameObject : IdentifiableObject
7       {
8          private string _description;
9          private string _name;
10
11         public GameObject(string[] ids, string name, string description) : base(ids)
12         {
13             _description = description;
14             _name = name;
15         }
16
17         public string Name
18           {
19                get { return _name.ToLower(); }
20           }
21
22           public string ShortDescription
23           {
24             get { return $"a {_name.ToLower()} ({FirstId.ToLower()})"; }
25         }
26
27         public virtual string FullDescription
28           {
29                get { return _description; }
30           }
31      }
32 }
33
34
```

Swin-Adventure/Item.cs

```
1  using System;
2
3  namespace Swin_Adventure
4  {
5      public class Item : GameObject
6      {
7          public Item(string[] idents, string name, string description) : base(idents,
   name, description)
8          {
9
10         }
11     }
12 }
13
14
```

Swin-Adventure/Inventory.cs

```
1  using System;
2  namespace Swin_Adventure
```

```
{
     public class Inventory
     {
          private List<Item> _items;
          public Inventory()
          {
               _items = new List<Item>();
          }

          public bool HasItem(string id)
          {
               foreach (Item itm in _items)
               {
                    if (itm.AreYou(id))
                    {
                         return true;
                    }
               }
               return false;
          }

          public void Put(Item itm)
          {
               _items.Add(itm);
          }

        public Item Take(string id)
        {
            Item itm = Fetch(id);

            if (itm != null)
            {
                _items.Remove(itm);
            }

            return itm;
        }

        public Item Fetch(string id)
          {
               foreach (Item itm in _items)
               {
                    if (itm.AreYou(id))
                    {
                         return itm;
                    }
               }
               return null;
          }

          public string ItemList
          {
               get
               {
                    string list = "";
                foreach (Item item in _items)
                {
                    list += "\t" + "a " + item.Name + " (" + item.FirstId + ")\n";
                }
                return list;
```

```
            }
        }
    }
}


```

Swin-Adventure/Player.cs

```
using System;
using Swin_Adventure;

namespace Swin_Adventure
{
    public class Player : GameObject, IHaveInventory
    {
        private Inventory _inventory;
        private Location _location;

        public Player(string name, string desc, Location location)
            : base(new string[] { "player", "me", "inventory", name }, name, desc)
        {
            _inventory = new Inventory();
            _location = location;
        }

        public GameObject Locate(string id)
        {
            if (AreYou(id))
            {
                return this;
            }
            GameObject item = _inventory.Fetch(id);
            if (item != null)
            {
                return item;
            }
            if (_location != null)
            {
                item = _location.Locate(id);
                if (item != null)
                {
                    return item;
                }
            }
            return null;
        }

        public override string FullDescription
        {
            get { return "You are " + Name + ", " + base.FullDescription + ".\n" +
                        "You are carrying:\n" + Inventory.ItemList; ; }
        }

        public Inventory Inventory
        {
            get { return _inventory; }
        }

        public Location Location
```

```
52          {
53              get { return _location; }
54              set { _location = value; }
55          }
56      }
57  }
58
```

Swin-Adventure/Bag.cs

```
1   using System;
2   namespace Swin_Adventure
3   {
4       public class Bag : Item, IHaveInventory
5       {
6           private Inventory _inventory;
7
8           public Bag(string[] ids, string name, string description) : base(ids, name,
    description)
9           {
10              _inventory = new Inventory();
11          }
12
13          public GameObject Locate(string id)
14          {
15              if (this.AreYou(id))
16              {
17                  return this;
18              }
19              return _inventory.Fetch(id);
20          }
21
22          public override string FullDescription
23          {
24              get { return $"In the {Name} you can see:\n" + _inventory.ItemList; }
25          }
26
27          public Inventory Inventory
28          {
29              get { return _inventory; }
30          }
31      }
32  }
33
34
```

Swin-Adventure/Command.cs

```
1   using System;
2   namespace Swin_Adventure
3   {
4       public abstract class Command : IdentifiableObject
5       {
6           public Command(string[] ids) : base(ids)
7           {
8           }
9            public abstract string Execute(Player player, string[] text);
10      }
11  }
12
13
```

Swin-Adventure/IHaveInventory.cs

```
using System;
namespace Swin_Adventure
{
    public interface IHaveInventory
    {
        GameObject Locate(string id);
        string Name { get; }
    }
}


```

Swin-Adventure/Location.cs

```
using System;
using System.Collections.Generic;

namespace Swin_Adventure
{
    public class Location : GameObject, IHaveInventory
    {
        private Inventory _inventory;

        public Location(string [] idents,string name, string description) :
base(idents, name, description)
        {
            _inventory = new Inventory();
        }

        public Inventory Inventory
        {
            get { return _inventory; }
        }

        public GameObject Locate(string id)
        {
            if (AreYou(id))
            {
                return this;
            }

            return _inventory.Fetch(id);
        }

        public override string FullDescription
        {
            get
            {
                return "You are at the " + Name + ". " + base.FullDescription + "\n"
+
                       "You can see:\n" + Inventory.ItemList;
            }
        }
    }
}


```

Swin-Adventure/LookCommand.cs

```
using System;

namespace Swin_Adventure
{
    public class LookCommand : Command
    {
        public LookCommand() : base(new string[] { "look" }) { }

        public override string Execute(Player player, string[] text)
        {

            if (text.Length == 1 && text[0].ToLower() == "look")
            {
                return player.Location != null ? player.Location.FullDescription : "
There is no location to look at.";
            }


            if (text.Length != 3 && text.Length != 5)
            {
                return "I don't know how to look like that";
            }

            if (text[0].ToLower() != "look")
            {
                return "Error in look input";
            }

            if (text[1].ToLower() != "at")
            {
                return "What do you want to look at?";
            }

            IHaveInventory container;


            if (text.Length == 3)
            {
                container = player;
            }
            else if (text.Length == 5 && text[3].ToLower() == "in")
            {
                GameObject found = player.Locate(text[4].ToLower());
                if (found == null)
                {
                    return $"I can't find the {text[4]}";
                }

                container = found as IHaveInventory;

                if (container == null)
                {
                    return $"The {text[4]} does not contain items";
                }
            }
            else
            {
                return "What do you want to look in?";
            }

```

```
            string itemId = text[2].ToLower();
            GameObject item = container.Locate(itemId);


            if (item == null)
            {
                return $"I can't find the {itemId}";
            }


            return item.FullDescription;
        }
    }
}


```

Swin-Adventure/Program.cs

```
using System;
using Swin_Adventure;

namespace Swin_Adventure;

class Program
{
    static void Main(string[] args)
    {
        Console.WriteLine("Welcome to SwinAdventure, designed by Thuan!");

        Console.WriteLine("Enter Player Name: ");
        string playerName = Console.ReadLine();

        Console.WriteLine("Enter your description: ");
        string playerDescription = Console.ReadLine();


        Location startingLocation = new Location(new string[] { "jungle" }, "Jungle", "Big wood jungle");


        Player player = new Player(playerName, playerDescription, startingLocation);

        Item item1 = new Item(new string[] { "weapon" }, "sword", "this is an Excalibur");
        Item item2 = new Item(new string[] { "armor" }, "shield", "this is a shield");
        player.Inventory.Put(item1);
        player.Inventory.Put(item2);

        Bag bag = new Bag(new string[] { "bag" }, "bag", "This is a bag.");
        player.Inventory.Put(bag);

        Item itemInBag = new Item(new string[] { "gem" }, "ruby", "This is a beautiful gem");
        bag.Inventory.Put(itemInBag);

        bool exitRequested = false;

        while (!exitRequested)
        {
```

```
            Console.WriteLine("Enter a command (or type 'exit' to quit):");
            string input = Console.ReadLine();
            string[] inputArray = input.Split(' ');

            if (inputArray.Length > 0)
            {
                string command = inputArray[0].ToLower();

                if (command == "exit" || command == "quit")
                {
                    exitRequested = true;
                }
                else
                {
                    LookCommand lookCommand = new LookCommand();
                    string result = lookCommand.Execute(player, inputArray);
                    Console.WriteLine(result);
                }
            }
        }
    }
}


```

IdentifiableObjectTest/BagTest.cs

```
using System;
namespace Swin_Adventure
{
     [TestFixture]
     public class BagTest
     {
          private Bag _bagTest1;
        private Bag _bagTest2;
        private Item _weaponTest;
        private Item _armorTest;

        [SetUp]
        public void SetUp()
          {
               _bagTest1 = new Bag(new string[] { "bag1" }, "backpack", "It's spacious");
            _bagTest2 = new Bag(new string[] { "bag2" }, "suitcase", "It's compact");
            _weaponTest = new Item(new string[] { "weapon" }, "sword", "this is an Excalibur");
            _armorTest = new Item(new string[] { "armor" }, "shield", "this is a shield");

            _bagTest1.Inventory.Put(_bagTest2);
            _bagTest1.Inventory.Put(_weaponTest);
            _bagTest2.Inventory.Put(_armorTest);
        }

        [Test]
        public void TestBagLocatesItems()
        {
           Assert.AreSame(_weaponTest, _bagTest1.Locate("weapon"));
        }

        [Test]
```

```
32          public void TestBagLocatesitself()
33          {
34              Assert.AreSame(_bagTest1, _bagTest1.Locate("bag1"));
35          }
36
37          [Test]
38          public void TestBagLocatesnothing()
39          {
40              Assert.IsNull(_bagTest1.Locate("bag3"));
41          }
42
43          [Test]
44          public void TestBagFullDescription()
45          {
46              Assert.AreEqual("In the backpack you can see:\n\ta suitcase (bag2)\n\ta
    sword (weapon)\n", _bagTest1.FullDescription);
47          }
48
49          [Test]
50          public void TestBaginBag()
51          {
52              Assert.AreSame(_bagTest2, _bagTest1.Locate("bag2"));
53              Assert.AreSame(_weaponTest, _bagTest1.Locate("weapon"));
54              Assert.IsNull(_bagTest1.Locate("armor"));
55          }
56      }
57  }
58
59
```

IdentifiableObjectTest/IdentifiableObjectTest.cs

```
1   using NUnit.Framework;
2   using Swin_Adventure;
3
4   namespace IdentifiableObjectTest
5   {
6
7       internal class Tests
8       {
9           private IdentifiableObject _test1;
10          private IdentifiableObject _test2;
11          private IdentifiableObject _test3;
12          private IdentifiableObject _test4;
13          private IdentifiableObject _test5;
14          private IdentifiableObject _test6;
15
16          [SetUp]
17          public void Setup()
18          {
19              _test1 = new IdentifiableObject(new string[] { "fred", "bob" });
20              _test2 = new IdentifiableObject(new string[] { "fred", "bob" });
21              _test3 = new IdentifiableObject(new string[] { "fred", "bob" });
22              _test4 = new IdentifiableObject(new string[] { "fred", "bob" });
23              _test5 = new IdentifiableObject(new string[] { });
24              _test6 = new IdentifiableObject(new string[] { "fred", "bob" });
25          }
26
27          [Test]
28          public void TestAreYou()
29          {
```

```
            Assert.IsTrue(_test1.AreYou("fred"));
            Assert.IsTrue(_test1.AreYou("bob"));
        }

        [Test]
        public void TestNotAreYou()
        {
            Assert.IsFalse(_test2.AreYou("wilma"));
            Assert.IsFalse(_test2.AreYou("boby"));
        }

        [Test]
        public void TestCaseSensitive()
        {
            Assert.IsTrue(_test3.AreYou("FRED"));
            Assert.IsTrue(_test3.AreYou("bOB"));
        }

        [Test]
        public void TestFirstID()
        {
            Assert.AreEqual("fred", _test4.FirstId);
        }

        [Test]
        public void TestFirstIdWithNoIDs()
        {
            Assert.AreEqual("", _test5.FirstId);
        }

        [Test]
        public void TestAddID()
        {
            _test6.AddIdentifier("wilma");
            Assert.IsTrue(_test6.AreYou("fred"));
            Assert.IsTrue(_test6.AreYou("bob"));
            Assert.IsTrue(_test6.AreYou("wilma"));
        }
    }
}


```

IdentifiableObjectTest/ItemTest.cs

```
using System;
using Swin_Adventure;

namespace SwinAdventureTest
{
    [TestFixture]
    public class ItemTest
     {
          private Item _itemTest;


        [SetUp]
        public void Setup()
        {
            _itemTest = new Item(new string[] { "weapon" }, "sword", "This is an
Excalibur");
```

```
16
17          }
18
19          [Test]
20          public void TestItemIsIdentifiable()
21          {
22              Assert.IsTrue(_itemTest.AreYou("weapon"));
23          }
24
25          [Test]
26          public void TestShortDescription()
27          {
28              Assert.IsTrue(_itemTest.ShortDescription == "a sword (weapon)");
29          }
30
31          [Test]
32          public void TestFullDescription()
33          {
34              Assert.IsTrue(_itemTest.FullDescription == "This is an Excalibur");
35          }
36      }
37  }
38
39
```

IdentifiableObjectTest/InventoryTest.cs

```
1   using System;
2   using Swin_Adventure;
3
4   namespace SwinAdventureTest
5   {
6       [TestFixture]
7       public class InventoryTest
8        {
9             private Inventory _inventoryTest;
10            private Item _weaponTest;
11            private Item _armorTest;
12
13            [SetUp]
14            public void SetUp()
15            {
16                _inventoryTest = new Inventory();
17                _weaponTest = new Item(new string[] { "weapon" }, "sword", "this is an
    Excalibur");
18              _armorTest = new Item(new string[] { "armor" }, "shield", "this is a
    shield");
19
20              _inventoryTest.Put(_weaponTest);
21              _inventoryTest.Put(_armorTest);
22          }
23
24          [Test]
25          public void TestFindItem()
26          {
27              Assert.IsTrue(_inventoryTest.HasItem("weapon"));
28              Assert.IsTrue(_inventoryTest.HasItem("armor"));
29          }
30
31          [Test]
32          public void TestNoItemFind()
```

```
33          {
34              Assert.IsFalse(_inventoryTest.HasItem("axe"));
35              Assert.IsFalse(_inventoryTest.HasItem("helmet"));
36          }
37
38          [Test]
39          public void TestFetchItem()
40          {
41              Assert.IsTrue(_weaponTest == _inventoryTest.Fetch("weapon"));
42              Assert.IsTrue(_inventoryTest.HasItem("weapon"));
43
44              Assert.IsTrue(_armorTest == _inventoryTest.Fetch("armor"));
45              Assert.IsTrue(_inventoryTest.HasItem("armor"));
46          }
47
48          [Test]
49          public void TestTakeItem()
50          {
51              Assert.IsTrue(_weaponTest == _inventoryTest.Take("weapon"));
52              Assert.IsFalse(_inventoryTest.HasItem("weapon"));
53
54              Assert.IsTrue(_armorTest == _inventoryTest.Take("armor"));
55              Assert.IsFalse(_inventoryTest.HasItem("armor"));
56          }
57
58          [Test]
59          public void TestItemList()
60          {
61              Assert.IsTrue(_inventoryTest.ItemList.Replace("\t", "") == "a sword
    (weapon)\na shield (armor)\n");
62          }
63      }
64  }
65
66
```

IdentifiableObjectTest/LocationTest.cs

```
1   using NUnit.Framework;
2   using Swin_Adventure;
3   using System;
4   namespace SwinAdventureTest
5   {
6       public class LocationTest
7       {
8           public Player _playerTest;
9           public Location _locationTest;
10          public Item _itemTest;
11
12          [SetUp]
13          public void Setup()
14          {
15              _locationTest = new Location(new string[] { "jungle" }, "Jungle", "Big
    wood jungle");
16              _playerTest = new Player("thuan", "dan choi", _locationTest);
17              _itemTest = new Item(new string[] { "sword" }, "a sword", "This is a
    sword");
18              _playerTest.Location = _locationTest;
19              _locationTest.Inventory.Put(_itemTest);
20          }
21
```

```
22          [Test]
23          public void TestLocationItSelf()
24          {
25
26              Assert.IsTrue(_locationTest.AreYou("location"));
27          }
28
29          [Test]
30          public void TestLocationNotItSelf()
31          {
32
33              Assert.IsFalse(_locationTest.AreYou("NotForest"));
34          }
35
36          [Test]
37          public void TestPlayerHasLocation()
38          {
39
40              Assert.AreEqual(_playerTest.Locate("location"), _locationTest);
41          }
42
43          [Test]
44          public void TestLocationLocateItem()
45          {
46
47              Assert.AreEqual(_itemTest, _locationTest.Locate("sword"));
48          }
49
50          [Test]
51          public void TestLocationLocateNoItem()
52          {
53
54              Assert.AreNotEqual(_itemTest, _locationTest.Locate("spear"));
55          }
56
57      }
58  }
```

IdentifiableObjectTest/LookCommandTest.cs

```
1   using NUnit.Framework;
2   using System.Numerics;
3   using Swin_Adventure;
4
5   namespace SwinAdventureTest
6   {
7       [TestFixture]
8       public class TestLookCommand
9       {
10          private LookCommand _lookCommandTest;
11          private Player _playerTest;
12          private Bag _bagTest;
13          private Item _gemTest;
14          private Location _locationTest;
15
16          [SetUp]
17          public void Setup()
18          {
19              _locationTest = new Location(new string[] { "jungle" }, "Jungle", "Big
    wood jungle");
20              _lookCommandTest = new LookCommand();
```

```
21              _playerTest = new Player("thuan", "dan choi", _locationTest);
22              _bagTest = new Bag(new string[] { "duffelbag" }, "duffelbag", "it's
    small-sized");
23              _gemTest = new Item(new string[] { "gem" }, "gem", "a beautiful gem");
24          }
25
26          [Test]
27          public void TestLookAtMe()
28          {
29              Assert.That(_lookCommandTest.Execute(_playerTest, new string[] { "look",
    "at", "inventory" }), Is.EqualTo("You are thuan, dan choi.\nYou are carrying:\n"));
30          }
31
32          [Test]
33          public void TestLookAtGem()
34          {
35              _playerTest.Inventory.Put(_gemTest);
36
37              Assert.That(_lookCommandTest.Execute(_playerTest, new string[] { "look",
    "at", "gem" }), Is.EqualTo("a beautiful gem"));
38          }
39
40          [Test]
41          public void TestLookAtUnk()
42          {
43              Assert.That(_lookCommandTest.Execute(_playerTest, new string[] { "look",
    "at", "unknown" }), Is.EqualTo("I can't find the unknown"));
44          }
45
46          [Test]
47          public void TestLookAtGemInMe()
48          {
49              _playerTest.Inventory.Put(_gemTest);
50
51              Assert.That(_lookCommandTest.Execute(_playerTest, new string[] { "look",
    "at", "gem", "in", "inventory" }), Is.EqualTo("a beautiful gem"));
52          }
53
54          [Test]
55          public void TestLookAtGemInBag()
56          {
57              _bagTest.Inventory.Put(_gemTest);
58              _playerTest.Inventory.Put(_bagTest);
59
60              Assert.That(_lookCommandTest.Execute(_playerTest, new string[] { "look",
    "at", "gem", "in", "duffelbag" }), Is.EqualTo("a beautiful gem"));
61          }
62
63          [Test]
64          public void TestLookAtGemInNoBag()
65          {
66              Assert.That(_lookCommandTest.Execute(_playerTest, new string[] { "look",
    "at", "gem", "in", "duffelbag" }), Is.EqualTo("I can't find the duffelbag"));
67          }
68
69          [Test]
70          public void TestLookAtNoGemInBag()
71          {
72              _playerTest.Inventory.Put(_bagTest);
73
74              Assert.That(_lookCommandTest.Execute(_playerTest, new string[] { "look",
    "at", "gem", "in", "duffelbag" }), Is.EqualTo("I can't find the gem"));
```

```
75          }
76
77          [Test]
78          public void TestInvalidLook()
79          {
80              Assert.That(_lookCommandTest.Execute(_playerTest, new string[] { "look", "around" }), Is.EqualTo("I don't know how to look like that"));
81              Assert.That(_lookCommandTest.Execute(_playerTest, new string[] { "hello" }), Is.EqualTo("I don't know how to look like that"));
82              Assert.That(_lookCommandTest.Execute(_playerTest, new string[] { "look", "at", "a", "at", "b" }), Is.EqualTo("What do you want to look in?"));
83              Assert.That(_lookCommandTest.Execute(_playerTest, new string[] { "hello", "at", "a" }), Is.EqualTo("Error in look input"));
84              Assert.That(_lookCommandTest.Execute(_playerTest, new string[] { "look", "by", "a" }), Is.EqualTo("What do you want to look at?"));
85          }
86      }
87  }
88
```

IdentifiableObjectTest/PlayerTest.cs

```
1   using System;
2   using System.Numerics;
3   using Swin_Adventure;
4
5   namespace SwinAdventureTest
6   {
7       [TestFixture]
8       public class PlayerTest
9       {
10          public Player _playerTest;
11          public Item _weaponTest;
12          public Item _armorTest;
13          public Location _locationTest;
14
15          [SetUp]
16          public void Setup()
17          {
18
19              _locationTest = new Location(new string[] { "jungle" }, "Jungle", "Big wood jungle");
20              _playerTest = new Player("thuan", "dan choi", _locationTest);
21              _weaponTest = new Item(new string[] { "weapon" }, "sword", "this is an Excalibur");
22              _armorTest = new Item(new string[] { "armor" }, "shield", "this is a shield");
23
24
25
26
27              _playerTest.Inventory.Put(_weaponTest);
28              _playerTest.Inventory.Put(_armorTest);
29          }
30
31          [Test]
32          public void TestPlayerIsIdentifiable()
33          {
34              Assert.IsTrue(_playerTest.AreYou("me"));
35              Assert.IsTrue(_playerTest.AreYou("inventory"));
36          }
37
```

```
        [Test]
        public void TestPlayerLocateItems()
        {
            Assert.IsTrue(_playerTest.Locate("weapon") == _weaponTest);
            Assert.IsTrue(_playerTest.Locate("armor") == _armorTest);

            Assert.IsTrue(_playerTest.Inventory.HasItem("weapon"));
            Assert.IsTrue(_playerTest.Inventory.HasItem("armor"));
        }

        [Test]
        public void TestPlayerLocateItself()
        {
            Assert.IsTrue(_playerTest == _playerTest.Locate("me"));
            Assert.IsTrue(_playerTest == _playerTest.Locate("inventory"));
        }

        [Test]
        public void TestPlayerLocateNothing()
        {
            Assert.IsTrue(_playerTest.Locate("helmet") == null);
        }

        [Test]
        public void TestPlayerFullDescription()
        {
            Assert.IsTrue(_playerTest.FullDescription == "You are thuan, dan choi.\nYou are carrying:\n\ta sword (weapon)\n\ta shield (armor)\n");
        }

        [Test]
        public void TestPlayerLocateItemInLocation()
        {

            Assert.AreSame(_weaponTest, _playerTest.Locate("sword"));
        }

        [Test]
        public void TestPlayerLocateNoItemInLocation()
        {

            Assert.IsNull(_playerTest.Locate("helmet"));
        }
    }
}
```